Meter Configuration Report for MZ-2208A680-01

Report created on miércoles, 27 de septiembre de 2023 13:06:13
Report generated by bfigueri

Metering Setup - Basic

PM1 Volts Mode	4W-WYE
PM1 PT Prim	115000.0
PM1 PT Sec	115.0
PM1 CT Prim	200.0
PM1 CT Sec	1.0
Nominal Voltage	115000.0
Nominal Current	200.0
Nominal Frequency	50Hz

Metering Setup - Advanced

PM1 PhaseOrder	ABC
PM1 V4 PT Prim	120.0
PM1 V4 PT Sec	120.0
PM1 I4 CT Prim	5.0
PM1 I4 CT Sec	5.0
PM1 I5 CT Prim	5.0
PM1 I5 CT Sec	5.0
PM1 kVA tot Method	Vector Sum
UseFundkVAR	ON
Scale Rev Param	ON

Metering Setup - Phasor

kW Total	0.000
kvar Total	0.000
kVA Total	0.000
PF Total	-100.000
Frequency (Hz)	"Not Available"
Firmware	003.001.000
V1 Magnitude	0.000
V1 Angle°	0.000
V2 Magnitude	0.000
V2 Angle°	-9.139
V3 Magnitude	0.000
V3 Angle°	0.477
I1 Magnitude	0.000
I1 Angle°	-165.678
I2 Magnitude	0.000
I2 Angle°	-160.857
I3 Magnitude	0.000
I3 Angle°	22.578
V1 Polarity	Normal
V2 Polarity	Normal
V3 Polarity	Normal
I1 Polarity	Normal
I2 Polarity	Normal
I3 Polarity	Normal

Metering Setup - Nameplate Info	
FAC1 DeviceType	9000
FAC1 Revision	003.001.000
FAC1 Feature Set	Standard
FAC1 SerialNum	MZ-2208A680-01
FAC1 Regulation Tag 1	
FAC1 Template	9000_V3.1.0.0.0
FAC1 Options	
FAC1 Owner	BCEI
FAC1 Tag1	SE LAS CANTERAS
FAC1 Tag2	HT3
Metering Setup - Rollover	
Energy Rollover	1000000000
I^2h/V^2h Rollover	1000000000
Security - Security	
Security Mode	Advanced
Hardware Lock	Disabled
Front Panel Password	Yes
Web Server	Yes
Allow Web Server Programming	Yes
Secure Web Page Viewing	Yes
Allow Modbus Programming	Yes
Allow Front Panel Programming	Yes
Allow Broadcasting Time Synchronization	Yes
SSH Lock Attempts	8
Telnet Lock Attempts	N/A
FTP Lock Attempts	N/A
Factory Lock Attempts	8
Front Panel Lock Attempts	8
ION Lock Attempts	8
HTTPS Lock Attempts	8
Lockout Duration Minutes	1440
ION Silence Minutes	30
HTTP Silence Minutes	N/A
Valid Auth Priority	0
Invalid Auth Priority	128
Lockout Auth Priority	255
Legacy User Support	Yes
USER1 Rights:	
Time Sync Access	Yes
Read Access	Yes
Peak Demand Reset Access	Yes
Test Mode Access	Yes
Full Meter Config Access	Yes
Security Config Access	Yes
Comm Config Access	Yes
FACTORY Rights:	
Time Sync Access	Yes
Read Access	Yes

Peak Demand Reset Access	Yes
Test Mode Access	Yes
Full Meter Config Access	Yes
Security Config Access	Yes
Comm Config Access	Yes

Serial Settings - Com1	
CM1 Protocol	ION
CM1 Unit ID	100
CM1 Baud Rate	19200
CM1 Rx Timeout	3.0
CM1 Serial Port	8N1
CM1 RS485 Bias	OFF

Serial Settings - Com4	
CM4 Protocol	ION
CM4 Unit ID	103
CM4 Baud Rate	19200
CM4 Rx Timeout	3.0
CM4 Serial Port	8N1
CM4 RS485 Bias	OFF

Basic Ethernet - IPv4	
IP Method	Stored
IPv4 Address	172.30.100.139
Subnet Mask	255.255.255.192
Gateway	172.30.100.129

Basic Ethernet - IPv6	
IPv6 Enabled	Yes
IPv6 Link Local	fe80::260:78ff:fe13:b1e1
IP Method	Stored
Global IPv6 Address	::
Global Gateway	::

Basic Ethernet - TCP/IP	
Ethernet Device Name	ION9000-13b1e1
ETH1 Rx Timeout	3.0
Modbus TCP Timeout	0
Modbus Gateway	Disabled
MAC Address	00-60-78-13-B1-E1

Advanced Ethernet - DNS	
ETH1 Primary DNS	None
ETH1 Secondary DNS	None

Advanced Ethernet - SMTP	
ETH1 SMTP Server	None
ETH1 SMTP Connection Timeout	1 minute

Advanced Ethernet - NTP	
CL1 Enable NTP Time Sync	No

CL1 NTP Time Sync Interval	10 minutes
CL1 Event Logging Threshold	0.02
ETH1 NTP Server	None
CL1 Time Sync Type	UTC
CL1 Time Sync Source	ETHERNET
Time Sync Count	0
Time Since Sync/Reset	11733

Advanced Ethernet - PTP

CL1 Time Sync Source	ETHERNET
CL1 Clock Source	COMM
CL1 Event Logging Threshold	0.02
CL1 Time Sync Type	UTC
CL1 PTP Domain Number	0
Time Sync Count	0
Time Since Sync/Reset	11733

Advanced Ethernet - SNMP

ETH1 Enable SNMP	No
SMO1 Enable Traps	Disabled
SMO1 Trap Rcvr1 Addr	None
SMO1 Trap Rcvr2 Addr	None
SMO1 Trap Rcvr3 Addr	None
SMO1 Trap Rcvr4 Addr	None
SMO1 Read Only Community	public
SMO1 Read Write Community	private
SMO1 System Contact	Contact
SMO1 System Name	ION9000
SMO1 System Location	Schneider

Advanced Ethernet - SysLog

EL1 Enable Syslog	No
ETH1 Syslog Server	None

Advanced Ethernet - Protocols

SSH Enabled	No
SSH Port #	22
Web Protocol	HTTPS With HTTP Redirect
Web Port #	80 & 443
SNMP Enabled	No
SNMP Port #	161
Modbus TCP Enabled	Yes
Modbus TCP Port #	502
DPWS Enabled	Yes
DPWS Port #	5357
ION Enabled	Yes
ION Port #	7700
Modbus RTU Enabled	Yes
Modbus RTU Port #	7701
Ethergate Com1 Enabled	See serial settings
Ethergate Com1 Port #	7801
Ethergate Com4 Enabled	See serial settings

Ethergate Com4 Port #	7802
DNP Enabled	Yes
DNP Port #	20000
DLMS Enabled	No
DLMS Port #	4059
IEC61850 Enabled	See CID settings
IEC61850 Port #	102

Clock - Timezone	
Timezone	+0 Hours
CL1 Time Sync Type	UTC
CL1 Time Sync Source	ETHERNET
CL1 Clock Source	COMM
CL1 DST Offset	0
CL1 LocalTime	mi. sep. 27, 2023 15:03:43
Time Sync Count	0
Time Since Sync/Reset	11734
Start of the week	Monday

Demand - Rolling Block	
Number of Sub-intervals	1
Sub-interval Length	15 minutes
Demand Lockout	25 days

Demand - Test Mode	
Test Sub-intervals	1
Test Sub-interval Length	15 minutes

LED Pulsing - WATT LED	
Source	kW del+rec
Enable	CAP Enable
CAP2 Int Mode	Net
W Kt	0.05
W Pulse Width	0.05
Pulser Mode	Always
Wh pulse ovrld	Pulsing normally

LED Pulsing - VAR LED	
Source	kVAR del+rec
Enable	CAP Enable
CAP3 Int Mode	Net
CAP3 Kt	0.05
CAP3 Pulse Width	0.05
Pulser Mode	Always
VARh plse ovrld	Pulsing normally

Energy Pulsing - Wh Del	
CAP7 Kt	1.8
CAP7 Pulse Width	0.1
CAP7 OutputMode	Pulse
CAP7 Port	Not Used
Wh del ovrld	"Not Available"

Energy Pulsing - Wh Rec	
CAP4 Kt	1.8
CAP4 Pulse Width	0.1
CAP4 OutputMode	Pulse
CAP4 Port	Not Used
Wh rec ovrld	"Not Available"
Energy Pulsing - VARh Del	
CAP5 Kt	1.8
CAP5 Pulse Width	0.1
CAP5 OutputMode	Pulse
CAP5 Port	Not Used
VARh del ovrld	"Not Available"
Energy Pulsing - VARh Rec	
CAP6 Kt	1.8
CAP6 Pulse Width	0.1
CAP6 OutputMode	Pulse
CAP6 Port	Not Used
VARh rec ovrld	"Not Available"
Energy Pulsing - End of Interval	
PU1 PulseWidth	0.1
PU1 OutputMode	Pulse
PU1 Port	Not Used
Energy Applications - Digital Input Based	
Conditional Energy	Disabled
Input Metering CH 1	Disabled
Standard quantity	Yes
Pulse Weight	1
Units	No units
Demand Period	15 minutes
Rate	No units
Source ID	
Input Metering CH 2	Disabled
Standard quantity	Yes
Pulse Weight	1
Units	No units
Demand Period	15 minutes
Rate	No units
Source ID	
Input Metering CH 3	Disabled
Standard quantity	Yes
Pulse Weight	1
Units	No units
Demand Period	15 minutes
Rate	No units
Source ID	
Input Metering CH 4	Disabled
Standard quantity	Yes

Pulse Weight	1
Units	No units
Demand Period	15 minutes
Rate	No units
Source ID	
Input Metering CH 5	Disabled
Standard quantity	Yes
Pulse Weight	1
Units	No units
Demand Period	15 minutes
Rate	No units
Source ID	

Energy Applications - Incremental Energy

Status	Disabled

Digital Inputs - S1

Input Mode	Pulse
Polarity	Non-Inverting
Debounce	0.001
Assigned Port	Port S1
EventLog Mode	Log Off
S1 State	OFF

Digital Inputs - S2

Input Mode	Pulse
Polarity	Non-Inverting
Debounce	0.001
Assigned Port	Port S2
EventLog Mode	Log Off
S2 State	OFF

Digital Inputs - S3

Input Mode	Pulse
Polarity	Non-Inverting
Debounce	0.001
Assigned Port	Port S3
EventLog Mode	Log Off
S3 State	OFF

Digital Inputs - S4

Input Mode	Pulse
Polarity	Non-Inverting
Debounce	0.001
Assigned Port	Port S4
EventLog Mode	Log Off
S4 State	OFF

Digital Inputs - S5

Input Mode	Pulse
Polarity	Non-Inverting
Debounce	0.001

Assigned Port	Port S5
EventLog Mode	Log Off
S5 State	OFF
Digital Inputs - S6	
Input Mode	Pulse
Polarity	Non-Inverting
Debounce	0.001
Assigned Port	Port S6
EventLog Mode	Log Off
S6 State	OFF
Digital Inputs - S7	
Input Mode	Pulse
Polarity	Non-Inverting
Debounce	0.001
Assigned Port	Port S7
EventLog Mode	Log Off
S7 State	OFF
Digital Inputs - S8	
Input Mode	Pulse
Polarity	Non-Inverting
Debounce	0.001
Assigned Port	Port S8
EventLog Mode	Log Off
S8 State	OFF
Digital Outputs - R1	
Source	NotUsed
Force ON	NotUsed
Force OFF	NotUsed
Normal	NotUsed
Polarity	Non-Inverting
PulseWidth	0.0
Assigned Port	Not Used
R1 State	"Not Available"
Digital Outputs - R2	
Source	NotUsed
Force ON	NotUsed
Force OFF	NotUsed
Normal	NotUsed
Polarity	Non-Inverting
PulseWidth	0.0
Assigned Port	Not Used
R2 State	"Not Available"
Digital Outputs - D1	
Source	NotUsed
Force ON	NotUsed
Force OFF	NotUsed

Normal	NotUsed
Polarity	Non-Inverting
PulseWidth	0.0
Assigned Port	Not Used
D1 State	"Not Available"

Digital Outputs - D2

Source	NotUsed
Force ON	NotUsed
Force OFF	NotUsed
Normal	NotUsed
Polarity	Non-Inverting
PulseWidth	0.0
Assigned Port	Not Used
D2 State	"Not Available"

Digital Outputs - D3

Source	NotUsed
Force ON	NotUsed
Force OFF	NotUsed
Normal	NotUsed
Polarity	Non-Inverting
PulseWidth	0.0
Assigned Port	Not Used
D3 State	"Not Available"

Digital Outputs - D4

Source	NotUsed
Force ON	NotUsed
Force OFF	NotUsed
Normal	NotUsed
Polarity	Non-Inverting
PulseWidth	0.0
Assigned Port	Not Used
D4 State	"Not Available"

Option Modules - Module A

Card Type	None
Card Status	None

Option Modules - Module B

Card Type	None
Card Status	None

Option Modules - Module C

Card Type	None
Card Status	None

Option Modules - Module D

Card Type	None
Card Status	None

Memory - Status	
Log Memory	1644 MB
In Use	1.5%
Available	98.5%
Load Profile	
Allocated	0.05%
Duration	90.0 days
Records	8640
Event Log	
Allocated	0.01%
Duration	N/A
Records	5000
Sag/Swell Waveforms	
Allocated	0.09%
Duration	N/A
Records	30
Sag/Swell COMTRADE	
Allocated	0.03%
Duration	N/A
Records	10
Transient Waveforms	
Allocated	0.09%
Duration	N/A
Records	30
Transient COMTRADE	
Allocated	0.03%
Duration	N/A
Records	10
EgyDmd Log	
Allocated	0.02%
Duration	35.0 days
Records	3360
Harm high Log	
Allocated	0.00%
Duration	35.0 days
Records	840
Harm mean Log	
Allocated	0.00%
Duration	35.0 days
Records	840
Hist high Log	
Allocated	0.02%
Duration	35.0 days
Records	3360
Hist low Log	
Allocated	0.02%
Duration	35.0 days
Records	3360
Hist mean Log	
Allocated	0.02%
Duration	35.0 days
Records	3360

Loss Log	
Allocated	0.01%
Duration	35.0 days
Records	3360
Sag/Swell Log	
Allocated	0.00%
Duration	N/A
Records	100
Sg/Sw HS Log	
Allocated	0.09%
Duration	N/A
Records	18010
Transient Log	
Allocated	0.00%
Duration	N/A
Records	100
DailyNom Log	
Allocated	0.00%
Duration	N/A
Records	450
RVC Log	
Allocated	0.00%
Duration	N/A
Records	100
EN50160 Logs	
Allocated	0.17%
Duration	N/A
Records	N/A
IEC 4-30 Logs	
Allocated	0.06%
Duration	N/A
Records	N/A
IEEE 519 Logs	
Allocated	0.62%
Duration	N/A
Records	N/A
System Resources	
Allocated	0.17%
Duration	N/A
Records	N/A

Revenue Log - Channels	
Source 1	kWh del int
Source 2	kVARh del int
Source 3	kWh rec int
Source 4	kVARh rec int
Source 5	Vll ab mean
Source 6	Vll bc mean
Source 7	Vll ca mean
Source 8	I a mean
Source 9	I b mean
Source 10	I c mean

Source 11	Vll avg mean
Source 12	I avg mean
Source 13	NotUsed
Source 14	NotUsed
Source 15	NotUsed
Source 16	NotUsed
Enable	NotUsed
Record	Revnue Log Trg
Rearm	NotUsed

Revenue Log - Interval/Depth

Interval length	15 minutes
RE1 Depth	8640
RE1 Insert Outage Records	Yes - Zero Fill Disabled

EnergyDemand Log - Channels

Source 1	kWh del
Source 2	kWh rec
Source 3	kWh del-rec
Source 4	kVARh del
Source 5	kVARh rec
Source 6	kVARh del-rec
Source 7	kVAh del+rec
Source 8	kW sd del-rec
Source 9	kVAR sd del-rec
Source 10	kVA sd del+rec
Source 11	NotUsed
Source 12	NotUsed
Source 13	NotUsed
Source 14	NotUsed
Source 15	NotUsed
Source 16	NotUsed
Enable	EgyDmd Log Enbl
Record	EgyDmd Log Trg
Rearm	NotUsed

EnergyDemand Log - Interval/Depth

PT6 Period	15 minutes
RE10 Depth	3360

PT/CT Correction - ITC Correction

Active Correction	None

Transformer Loss - Method Selection

Loss Comp Enble	Comp Disabled
Comp Mthod Slct	Method 1

Transformer Loss - Test Sheet

MP Definition 1	Load-side
MP Definition 2	Not Xfrmer-side
kVA rated	0
Vll rated	0

LWFe test	0
LWCu test	0
% Excitation	0
% Impedance	0
PT Ratio	1
CT Ratio	1
Xformer ratio	1
Line Length-SY	0
r/l - SY	0
x/l - SY	0
Line Length-LD	0
r/l - LD	0
x/l - LD	0

Transformer Loss - %Loss Constants	
Rated Mtr Volts	120
1/2 Mtr Current	5
# Stator Elmnts	3
PT Ratio	1
CT Ratio	1
Cu Comp Enable	ON
%LWCu	0
%LVCu	0
Fe Comp Enable	ON
%LWFe	0
%LVFe	0

Time of Use - Time of Use	
Sample TOU	
TOU1 Season 1	Oct 1 - May 31
TOU1 Season 1 Weekday Rates	A 0:00
TOU1 Season 1 Weekend Rates	A 0:00
TOU1 Season 1 Alt 1 Rates	
TOU1 Season 1 Alt 2 Rates	
TOU1 Season 1 Holiday Rates	A 0:00
TOU1 Season 2	Jun 1 - Sep 30
TOU1 Season 2 Weekday Rates	A 0:00, B 10:00, A 18:00
TOU1 Season 2 Weekend Rates	A 0:00
TOU1 Season 2 Alt 1 Rates	
TOU1 Season 2 Alt 2 Rates	
TOU1 Season 2 Holiday Rates	A 0:00
TOU1 Season 3	
TOU1 Season 3 Weekday Rates	
TOU1 Season 3 Weekend Rates	
TOU1 Season 3 Alt 1 Rates	
TOU1 Season 3 Alt 2 Rates	
TOU1 Season 3 Holiday Rates	
TOU1 Season 4	
TOU1 Season 4 Weekday Rates	
TOU1 Season 4 Weekend Rates	
TOU1 Season 4 Alt 1 Rates	
TOU1 Season 4 Alt 2 Rates	

TOU1 Season 4 Holiday Rates

TOU1 Weekdays	Mon - Fri
TOU1 Weekends	Sat, Sun
TOU1 Alt 1 Days	
TOU1 Alt 2 Days	
TOU1 Holidays	Jan 1, Jun 14, Jul 4, Dec 25, Feb 21 2000, May 29 2000, Sep 4 2000, Nov 23 2000
TOU1 Self Read Dates	Jan 1, Apr 1, Jul 1, Oct 1

Alarming - Standard

Over kW sd

High Limit	Not set
Low Limit	Not set
Priority	Forced Off

Over I a

High Limit	Not set
Low Limit	Not set
Priority	Forced Off

Over I b

High Limit	Not set
Low Limit	Not set
Priority	Forced Off

Over I c

High Limit	Not set
Low Limit	Not set
Priority	Forced Off

Over I 4

High Limit	Not set
Low Limit	Not set
Priority	Forced Off

Over V unbal

High Limit	5
Low Limit	5
Priority	Forced Off

Over I unbal

High Limit	10
Low Limit	10
Priority	Forced Off

Over THD V1

High Limit	5
Low Limit	5
Priority	Medium

Over THD V2

High Limit	5
Low Limit	5
Priority	Medium
Over THD V3	
High Limit	5
Low Limit	5
Priority	Medium
Freq Setpoint	
High Limit	5.0
Low Limit	5.0
Priority	Medium
V1 Setpoint	
High Limit	5.0
Low Limit	5.0
Priority	Forced Off
V2 Setpoint	
High Limit	5.0
Low Limit	5.0
Priority	Forced Off
V3 Setpoint	
High Limit	5.0
Low Limit	5.0
Priority	Forced Off
Alarming - Sag/Swell	
Voltage	
Swell Limit	110%
Sag Limit	90%
Hysteresis	2%
Priority	Forced Off
Current Swell	
Pickup	155%
Dropout	145%
Priority	Forced Off
Current Sag	
Pickup	45%
Dropout	55%
Priority	Forced Off
Alarming - Transient	
Transient/Waveshape	
Nominal	115000.0 V
Threshold	150%

Priority	High (200)

Alarming - Digital Input

Port S1	
Active when	Port S1 ON
Priority	Info Only
Port S2	
Active when	Port S2 ON
Priority	Info Only
Port S3	
Active when	Port S3 ON
Priority	Info Only
Port S4	
Active when	Port S4 ON
Priority	Info Only
Port S5	
Active when	Port S5 ON
Priority	Info Only
Port S6	
Active when	Port S6 ON
Priority	Info Only
Port S7	
Active when	Port S7 ON
Priority	Info Only
Port S8	
Active when	Port S8 ON
Priority	Info Only

Power Quality - Sag/Swell Logging	
Sag/Swell depth	100
Waveform depth	30
Waveform format	32x54
Post Event Cycles	7
COMTRADE Status	Enabled
COMTRADE Depth	10
Pre-Trigger Burst	6.00 seconds
Post-Trigger Burst	12.00 seconds
Burst Log Depth	10

Power Quality - Transient Logging	
Transient depth	100
Waveform depth	30
Waveform format	512x4
Post Event Cycles	2

COMTRADE Status	Enabled
COMTRADE Depth	10
Power Quality - Advanced PQ	
4-30 Enable	ON
V Intrp Pickup	5
V Intrp Dropout	7
4-30 3s Enable	OFF
4-30 10s Enable	OFF
EN50160 Enable	OFF
FAC1 Vnominal	115000
PM1 Nominal Frequency	50Hz
PQ Prm Rc Enbl	ON
519 Enable	OFF
519 Volt enum	Below 1.0 kV
519 I_SC	10000
519 I_L	100
RVC Enable	Disabled
SS1 RVC Threshold	5
SS1 RVC Hysteresis	3
Displays - Front Panel	
kWh	
Line 1	kWh del
Line 2	kWh rec
DIS1 Screen Title	Active Energy
DIS1 Screen Resolution	Default
DIS1 Last Digit Mode	Round
DIS1 Screen Number	Normal Screen 1
kVARh	
Line 1	kVARh del
Line 2	kVARh rec
DIS2 Screen Title	Reactive Energy
DIS2 Screen Resolution	Default
DIS2 Last Digit Mode	Round
DIS2 Screen Number	Normal Screen 2
kVAh	
Line 1	kVAh del
Line 2	kVAh rec
DIS3 Screen Title	Apparent Energy
DIS3 Screen Resolution	Default
DIS3 Last Digit Mode	Round
DIS3 Screen Number	Normal Screen 3
Peak Demand Del	
Line 1	kW sd mx del
Line 2	kVAR sd mx del
Line 3	kVA sd mx del
DIS4 Screen Title	Peak Demand Delivered
DIS4 Screen Resolution	Default

DIS4 Last Digit Mode	Round
DIS4 Screen Number	Normal Screen 4
Pk Dmd Rst Cnt	
Line 1	Pk Dmd Rset Cnt
DIS5 Screen Title	Peak Demand Reset Count
DIS5 Screen Resolution	Default
DIS5 Last Digit Mode	Round
DIS5 Screen Number	Normal Screen 5
kWh Test	
Line 1	kWh del T
Line 2	kWh rec T
Line 3	kWh del+rec T
DIS6 Screen Title	Active Energy Test
DIS6 Screen Resolution	Default
DIS6 Last Digit Mode	Round
DIS6 Screen Number	Test Screen 1
kVARh Test	
Line 1	kVARh del T
Line 2	kVARh rec T
Line 3	kVARh del+rec T
DIS7 Screen Title	Reactive Energy Test
DIS7 Screen Resolution	Default
DIS7 Last Digit Mode	Round
DIS7 Screen Number	Test Screen 2
kW Block Test	
Line 1	kW sd del T
Line 2	kW sd rec T
Line 3	kW sd mx del T
Line 4	kW sd mx rec T
DIS8 Screen Title	Demand Test
DIS8 Screen Resolution	Default
DIS8 Last Digit Mode	Round
DIS8 Screen Number	Test Screen 3

Displays - Localization	
DOP1 Language	English
DOP1 Digit Grouping	1000.0
DOP1 Date Format	MM/DD/YYYY
DOP1 Time Format	24 H
PM1 PF Sign Convention	IEEE
DOP1 Measurement Symbols	IEEE
PM1 Phase Lbls	ABC