BaseContract
BaseContract()
getPackedSelector(bytes4) internal pure returns (bytes)
getSelector(bytes4) internal pure returns (bytes4)
getSelector(function) internal pure returns (bytes4)
getSelector(string) internal pure returns (bytes4)
Ownable
Ownable()
owner() public view returns (address)
renounceOwnership() public onlyOwner
transferOwnership(address) public onlyOwner
_transferOwnership(address) internal
modifier onlyOwner()
ERC20
ERC20(string, string)
name() public view returns (string)
symbol() public view returns (string)
decimals() public view returns (uint8)
totalSupply() public view returns (uint256)
balanceOf(address) public view returns (uint256)
transfer(address, uint256) public returns (bool)
allowance(address, address) public view returns (uint256)
approve(address, uint256) public returns (bool)
transferFrom(address, address, uint256) public returns (bool)
_transfer(address, address, uint256) internal
_mint(address, uint256) internal
_burn(address, uint256) internal
_approve(address, address, uint256) internal
_spendAllowance(address, address, uint256) internal
_beforeTokenTransfer(address, address, uint256) internal
_afterTokenTransfer(address, address, uint256) internal
ERC20Burnable
burn(uint256) public
burnFrom(address, uint256) public
ERC20Capped
ERC20Capped(uint256)
cap() public view returns (uint256)
_mint(address, uint256) internal
ERC20Pausable
_beforeTokenTransfer(address, address, uint256) internal
paused() public view returns (bool)
_pause() internal
_unpause() internal
modifier whenNotPaused()
modifier whenPaused()
ERC20Snapshot
_snapshot() internal returns (uint256)
balanceOfAt(address, uint256) public view returns (uint256)
totalSupplyAt(uint256) public view returns (uint256)
_beforeTokenTransfer(address, address, uint256) internal
_getCurrentSnapshotId() internal view returns (uint256)
_valueAt(uint256, Snapshots) private view returns (bool, uint256)
_updateAccountSnapshot(address) private
_updateTotalSupplySnapshot() private
_updateSnapshot(Snapshots, uint256) private
_lastSnapshotId(uint256[]) private view returns (uint256)
Snapshots
uint256[] ids
uint256[] values
ERC20Votes
_afterTokenTransfer(address, address, uint256) internal
_mint(address, uint256) internal
_burn(address, uint256) internal
_maxSupply() internal view returns (uint224)
getVotes(address) public view returns (uint256)
getPastVotes(address, uint256) public view returns (uint256)
getPastTotalSupply(uint256) public view returns (uint256)
delegates(address) public view returns (address)
delegate(address) public
delegateBySig(address, uint256, uint256, uint8, bytes32, bytes32) public
_delegate(address, address) internal
_moveVotingPower(address, address, uint256) private
_writeCheckpoint(Checkpoint[], function(uint256,uint256) pure returns (uint256), uint256) private returns (uint256, uint256)
_add(uint256, uint256) private pure returns (uint256)
_subtract(uint256, uint256) private pure returns (uint256)
_checkpointsLookup(Checkpoint[], uint256) private view returns (uint256)
Checkpoint
uint32 fromBlock
uint224 votes
ERC20VotesComp
_maxSupply() internal view returns (uint224)
getCurrentVotes(address) public view returns (uint96)
getPriorVotes(address, uint256) public view returns (uint96)
ERC20Wrapper
ERC20Wrapper(IERC20)
underlying() public view returns (IERC20)
depositFor(address, uint256) public returns (bool)
withdrawTo(address, uint256) public returns (bool)
_recover(address) internal returns (uint256)
IERC20
totalSupply() external view returns (uint256)
balanceOf(address) external view returns (uint256)
transfer(address, uint256) external returns (bool)
allowance(address, address) external view returns (uint256)
approve(address, uint256) external returns (bool)
transferFrom(address, address, uint256) external returns (bool)
IERC20Metadata
name() external view returns (string)
symbol() external view returns (string)
decimals() external view returns (uint8)
IERC20Permit
permit(address, address, uint256, uint256, uint8, bytes32, bytes32) external
nonces(address) external view returns (uint256)
DOMAIN_SEPARATOR() external view returns (bytes32)
IERC20Votes
getVotes(address) external view returns (uint256)
getPastVotes(address, uint256) external view returns (uint256)
getPastTotalSupply(uint256) external view returns (uint256)
delegates(address) external view returns (address)
delegate(address) external
delegateBySig(address, uint256, uint256, uint8, bytes32, bytes32) external
IERC20VotesComp
getCurrentVotes(address) external view returns (uint96)
getPriorVotes(address, uint256) external view returns (uint96)
SafeERC20
safeTransfer(IERC20, address, uint256) internal
safeTransferFrom(IERC20, address, address, uint256) internal
safeApprove(IERC20, address, uint256) internal
safeIncreaseAllowance(IERC20, address, uint256) internal
safeDecreaseAllowance(IERC20, address, uint256) internal
_callOptionalReturn(IERC20, bytes) private
Address
isContract(address) internal view returns (bool)
sendValue(address payable, uint256) internal
functionCall(address, bytes) internal returns (bytes)
functionCall(address, bytes, string) internal returns (bytes)
functionCallWithValue(address, bytes, uint256) internal returns (bytes)
functionCallWithValue(address, bytes, uint256, string) internal returns (bytes)
functionStaticCall(address, bytes) internal view returns (bytes)
functionStaticCall(address, bytes, string) internal view returns (bytes)
functionDelegateCall(address, bytes) internal returns (bytes)
functionDelegateCall(address, bytes, string) internal returns (bytes)
verifyCallResult(bool, bytes, string) internal pure returns (bytes)
Context
_msgSender() internal view returns (address)
_msgData() internal view returns (bytes)
Counters
current(Counter) internal view returns (uint256)
increment(Counter) internal
decrement(Counter) internal
reset(Counter) internal
Counter
uint256 _value
ECDSA
recover(bytes32, bytes) internal pure returns (address)
recover(bytes32, bytes32, bytes32) internal pure returns (address)
recover(bytes32, uint8, bytes32, bytes32) internal pure returns (address)
toEthSignedMessageHash(bytes32) internal pure returns (bytes32)
toEthSignedMessageHash(bytes) internal pure returns (bytes32)
toTypedDataHash(bytes32, bytes32) internal pure returns (bytes32)
EIP712
EIP712(string, string)
_domainSeparatorV4() internal view returns (bytes32)
_hashTypedDataV4(bytes32) internal view returns (bytes32)
_buildDomainSeparator(bytes32, bytes32, address) private view returns (bytes32)
_getChainId() private view returns (uint256)
_getChainIdToType() private view returns (bytes32)
_getHashedName() private view returns (bytes32)
_getHashedVersion() private view returns (bytes32)
_getName() private view returns (string)
_getVersion() private view returns (string)
_getType() private view returns (string)
Strings
toString(uint256) internal pure returns (string)
toHexString(uint256) internal pure returns (string)
toHexString(uint256, uint256) internal pure returns (string)
toHexString(address) internal pure returns (string)
Timers
getDeadline(Timestamp) internal pure returns (uint64)
setDeadline(Timestamp, uint64) internal
reset(Timestamp) internal
isUnset(Timestamp) internal pure returns (bool)
isStarted(Timestamp) internal pure returns (bool)
isPending(Timestamp) internal view returns (bool)
isExpired(Timestamp) internal view returns (bool)
Timestamp
uint64 _deadline
IGovernor
name() public view returns (string)
version() public view returns (string)
COUNTING_MODE() public pure returns (string)
hashProposal(address[], uint256[], bytes[], bytes32) public pure returns (uint256)
state(uint256) public view returns (ProposalState)
proposalSnapshot(uint256) public view returns (uint256)
proposalDeadline(uint256) public view returns (uint256)
votingDelay() public view returns (uint256)
votingPeriod() public view returns (uint256)
quorum(uint256) public view returns (uint256)
getVotes(address, uint256) public view returns (uint256)
hasVoted(uint256, address) public view returns (bool)
propose(address[], uint256[], bytes[], string) public returns (uint256)
execute(address[], uint256[], bytes[], bytes32) public payable returns (uint256)
castVote(uint256, uint8) public returns (uint256)
castVoteWithReason(uint256, uint8, string) public returns (uint256)
castVoteBySig(uint256, uint8, uint8, bytes32, bytes32) public returns (uint256)
ProposalState
Pending
Active
Canceled
Defeated
Succeeded
Queued
Expired
Executed
GovernorCompatibilityBravo
propose(address[], uint256[], string[], bytes[], string) public returns (uint256)
queue(uint256) public
execute(uint256) public payable
cancel(uint256) public
getActions(uint256) public view returns (address[], uint256[], string[], bytes[])
getReceipt(uint256, address) public view returns (Receipt)
proposals(uint256) public view returns (uint256, address, uint256, uint256, uint256, uint256, uint256, bool, bool)
Receipt
bool hasVoted
uint8 support
uint96 votes
GovernorCountingSimple
COUNTING_MODE() public pure returns (string)
hasVoted(uint256, address) public view returns (bool)
proposalVotes(uint256) public view returns (uint256, uint256, uint256)
_quorumReached(uint256) internal view returns (bool)
_voteSucceeded(uint256) internal view returns (bool)
_countVote(uint256, address, uint8, uint256) internal
ProposalVote
uint256 againstVotes
uint256 forVotes
uint256 abstainVotes
mapping(address => bool) hasVoted
GovernorProposalThreshold
propose(address[], uint256[], bytes[], string) public returns (uint256)
GovernorTimelockCompound
supportsInterface(bytes4) public view returns (bool)
timelock() public view returns (address)
proposalEta(uint256) public view returns (uint256)
queue(uint256, address[], uint256[], bytes[], bytes32) public returns (uint256)
execute(uint256, address[], uint256[], bytes[], bytes32) public payable returns (uint256)
cancel(uint256, address[], uint256[], bytes[], bytes32) public returns (uint256)
_execute(uint256, address[], uint256[], bytes[], bytes32) internal
_cancel(address[], uint256[], bytes[], bytes32) internal returns (uint256)
_executor() internal view returns (address)
ICompoundTimelock
receive() external payable
GRACE_PERIOD() public view returns (uint256)
MINIMUM_DELAY() public view returns (uint256)
MAXIMUM_DELAY() public view returns (uint256)
admin() public view returns (address)
pendingAdmin() public view returns (address)
delay() public view returns (uint256)
queuedTransactions(bytes32) public view returns (bool)
setDelay(uint256) public
acceptAdmin() public
setPendingAdmin(address) public
queueTransaction(address, uint256, string, bytes, uint256) public returns (bytes32)
cancelTransaction(address, uint256, string, bytes, uint256) public
executeTransaction(address, uint256, string, bytes, uint256) public payable returns (bytes)
GovernorTimelockControl
supportsInterface(bytes4) public view returns (bool)
timelock() public view returns (address)
proposalEta(uint256) public view returns (uint256)
queue(uint256, address[], uint256[], bytes[], bytes32) public returns (uint256)
execute(uint256, address[], uint256[], bytes[], bytes32) public payable returns (uint256)
cancel(uint256, address[], uint256[], bytes[], bytes32) public returns (uint256)
_execute(uint256, address[], uint256[], bytes[], bytes32) internal
_cancel(address[], uint256[], bytes[], bytes32) internal returns (uint256)
_executor() internal view returns (address)
TimelockController
receive() external payable
isOperation(bytes32) public view returns (bool)
isOperationPending(bytes32) public view returns (bool)
isOperationReady(bytes32) public view returns (bool)
isOperationDone(bytes32) public view returns (bool)
getTimestamp(bytes32) public view returns (uint256)
getMinDelay() public view returns (uint256)
hashOperation(address, uint256, bytes, bytes32, bytes32) public pure returns (bytes32)
hashOperationBatch(address[], uint256[], bytes[], bytes32, bytes32) public pure returns (bytes32)
schedule(address, uint256, bytes, bytes32, bytes32, uint256) public
scheduleBatch(address[], uint256[], bytes[], bytes32, bytes32, uint256) public
cancel(bytes32) public
execute(address, uint256, bytes, bytes32, bytes32) public payable
executeBatch(address[], uint256[], bytes[], bytes32, bytes32) public payable
updateDelay(uint256) external
_schedule(bytes32, uint256) private
_beforeCall(bytes32, bytes32) private view
_afterCall(bytes32) private
_call(bytes32, uint256, address, uint256, bytes) private
modifier onlyRoleOrOpenRole(bytes32)
modifier onlyRole(bytes32)
modifier onlyRoleOrOpenRole(bytes32)
modifier onlyRole(bytes32)
GovernorVotes
token() public view returns (IERC20Votes)
_getVotes(address, uint256, bytes) internal view returns (uint256)
GovernorVotesComp
token() public view returns (IERC20VotesComp)
_getVotes(address, uint256, bytes) internal view returns (uint256)
GovernorVotesQuorumFraction
quorumNumerator() public view returns (uint256)
quorumDenominator() public view returns (uint256)
quorum(uint256) public view returns (uint256)
updateQuorumNumerator(uint256) external
_updateQuorumNumerator(uint256) internal
GovernorSettings
votingDelay() public view returns (uint256)
votingPeriod() public view returns (uint256)
proposalThreshold() public view returns (uint256)
_setVotingDelay(uint256) internal
_setVotingPeriod(uint256) internal
_setProposalThreshold(uint256) internal
GovernorPreventLateQuorum
proposalDeadline(uint256) public view returns (uint256)
_castVote(uint256, address, uint8, string, bytes) internal returns (uint256)
_extendDeadline(uint256, uint64) internal
GovernorMock
_quorumReached(uint256) internal view returns (bool)
_voteSucceeded(uint256) internal view returns (bool)
_countVote(uint256, address, uint8, uint256) internal
_getVotes(address, uint256, bytes) internal view returns (uint256)
_executor() internal view returns (address)
_execute(uint256, address[], uint256[], bytes[], bytes32) internal
_cancel(address[], uint256[], bytes[], bytes32) internal returns (uint256)
votingDelay() public view returns (uint256)
votingPeriod() public view returns (uint256)
quorum(uint256) public view returns (uint256)
proposalThreshold() public view returns (uint256)
proposalDeadline(uint256) public view returns (uint256)
_castVote(uint256, address, uint8, string, bytes) internal returns (uint256)
_extendDeadline(uint256, uint64) internal
GovernorTimelockCompoundMock
receive() external payable
GRACE_PERIOD() public view returns (uint256)
MINIMUM_DELAY() public view returns (uint256)
MAXIMUM_DELAY() public view returns (uint256)
admin() public view returns (address)
pendingAdmin() public view returns (address)
delay() public view returns (uint256)
queuedTransactions(bytes32) public view returns (bool)
setDelay(uint256) public
acceptAdmin() public
setPendingAdmin(address) public
queueTransaction(address, uint256, string, bytes, uint256) public returns (bytes32)
cancelTransaction(address, uint256, string, bytes, uint256) public
executeTransaction(address, uint256, string, bytes, uint256) public payable returns (bytes)
GovernorTimelockControlMock
receive() external payable
isOperation(bytes32) public view returns (bool)
isOperationPending(bytes32) public view returns (bool)
isOperationReady(bytes32) public view returns (bool)
isOperationDone(bytes32) public view returns (bool)
getTimestamp(bytes32) public view returns (uint256)
getMinDelay() public view returns (uint256)
hashOperation(address, uint256, bytes, bytes32, bytes32) public pure returns (bytes32)
hashOperationBatch(address[], uint256[], bytes[], bytes32, bytes32) public pure returns (bytes32)
schedule(address, uint256, bytes, bytes32, bytes32, uint256) public
scheduleBatch(address[], uint256[], bytes[], bytes32, bytes32, uint256) public
cancel(bytes32) public
execute(address, uint256, bytes, bytes32, bytes32) public payable
executeBatch(address[], uint256[], bytes[], bytes32, bytes32) public payable
updateDelay(uint256) external
modifier onlyRoleOrOpenRole(bytes32)
modifier onlyRole(bytes32)
modifier onlyRoleOrOpenRole(bytes32)
modifier onlyRole(bytes32)
GovernorVotesMock
_getVotes(address, uint256, bytes) internal view returns (uint256)
GovernorVotesQuorumFractionMock
_getVotes(address, uint256, bytes) internal view returns (uint256)
quorumNumerator() public view returns (uint256)
quorumDenominator() public view returns (uint256)
quorum(uint256) public view returns (uint256)
updateQuorumNumerator(uint256) external
_updateQuorumNumerator(uint256) internal
GovernorSettingsMock
votingDelay() public view returns (uint256)
votingPeriod() public view returns (uint256)
proposalThreshold() public view returns (uint256)
_setVotingDelay(uint256) internal
_setVotingPeriod(uint256) internal
_setProposalThreshold(uint256) internal
GovernorPreventLateQuorumMock
votingDelay() public view returns (uint256)
votingPeriod() public view returns (uint256)
quorum(uint256) public view returns (uint256)
proposalDeadline(uint256) public view returns (uint256)
_castVote(uint256, address, uint8, string, bytes) internal returns (uint256)
_extendDeadline(uint256, uint64) internal
GovernorWithParamsMock
_countVote(uint256, address, uint8, uint256) internal
_getVotes(address, uint256, bytes) internal view returns (uint256)
votingDelay() public view returns (uint256)
votingPeriod() public view returns (uint256)
quorum(uint256) public view returns (uint256)
ERC20Mock
ERC20Mock(string, string, address, uint256)
ERC20PausableMock
ERC20PausableMock(string, string, address, uint256)
pause() public
unpause() public
ERC20SnapshotMock
ERC20SnapshotMock(string, string, address, uint256)
snapshot() public returns (uint256)
ERC20VotesCompMock
ERC20VotesCompMock(string, string, address)
mint(address, uint256) public
ERC20VotesMock
ERC20VotesMock(string, string, address)
mint(address, uint256) public
ERC20WrapperMock
ERC20WrapperMock(IERC20, string, string)
recover(address) public returns (uint256)
CallReceiverMock
mockFunction() public payable returns (string)
mockFunctionRevertsNoReason() public payable
mockFunctionRevertsReason() public payable
mockFunctionThrows() public payable
mockFunctionOutOfGas() public payable
mockFunctionWritesStorage() public returns (string)
mockStaticFunction() public view returns (string)
mockReentrantFunction(address) public returns (string)
mockReentrantStaticFunction(address) public view returns (string)
mockFunctionNonExistent() public returns (string)
mockFunctionWithArgs(uint256, uint256) public payable returns (string)
event MockFunctionCalled()
event MockFunctionCalledWithArgs(uint256, uint256)
ContextMock
msgSender() public returns (address)
msgData(uint256, uint256) public returns (bytes)
event Sender(address)
event Data(bytes, uint256, uint256)
ContextMock2
msgSender() public returns (address)
ERC1155ReceiverMock
ERC1155ReceiverMock(bytes4, bytes4, bool, bool)
onERC1155Received(address, address, uint256, uint256, bytes) public returns (bytes4)
onERC1155BatchReceived(address, address, uint256[], uint256[], bytes) public returns (bytes4)
supportsInterface(bytes4) public view returns (bool)
event Received(address, address, uint256, uint256, bytes, uint256)
event BatchReceived(address, address, uint256[], uint256[], bytes, uint256)
ERC165CheckerMock
supportsERC165(address) public view returns (bool)
supportsInterface(address, bytes4) public view returns (bool)
supportsAllInterfaces(address, bytes4[]) public view returns (bool)
ERC165InterfacesSupported
ERC165InterfacesSupported(bytes4[])
supportsInterface(bytes4) public view returns (bool)
ERC165MissingData
supportsInterface(bytes4) public view returns (bool)
ERC165NotSupported
ERC165MaliciousData
supportsInterface(bytes4) public view returns (bool)
ERC165NotSupported
ERC165Mock
supportsInterface(bytes4) public view returns (bool)
ERC165NotSupported
InitializableMock
initialize() public initializer
initializeNested() public initializer
initializeWithX(uint256) public initializer
nonInitializable(uint256) public
fail() public
initializerModifier() public initializer
onlyInitializingModifier() public onlyInitializing
initializeUnchained() public initializer
initializeNestedUnchained() public initializer
ReentrancyAttack
callSender(bytes4) public
ReentrancyMock
ReentrancyMock()
callback() external
countLocalRecursive(uint256) public
countThisRecursive(uint256) public
countAndCall(ReentrancyAttack) public
modifier nonReentrant()
SafeERC20Helper
safeTransfer(IERC20, address, uint256) internal
safeTransferFrom(IERC20, address, address, uint256) internal
safeApprove(IERC20, address, uint256) internal
safeIncreaseAllowance(IERC20, address, uint256) internal
safeDecreaseAllowance(IERC20, address, uint256) internal
SafeMathMock
add(uint256, uint256) public pure returns (uint256)
sub(uint256, uint256) public pure returns (uint256)
mul(uint256, uint256) public pure returns (uint256)
div(uint256, uint256) public pure returns (uint256)
mod(uint256, uint256) public pure returns (uint256)
addMemory(uint256, uint256) public pure returns (uint256)
subMemory(uint256, uint256) public pure returns (uint256)
mulMemory(uint256, uint256) public pure returns (uint256)
divMemory(uint256, uint256) public pure returns (uint256)
modMemory(uint256, uint256) public pure returns (uint256)
SignatureCheckerMock
isValidSignature(address, bytes32, bytes) public view returns (bool)
StorageSlotMock
setBoolean(bytes32, bool) public
getBoolean(bytes32) public view returns (bool)
setAddress(bytes32, address) public
getAddress(bytes32) public view returns (address)
setUint256(bytes32, uint256) public
getUint256(bytes32) public view returns (uint256)
setString(bytes32, string) public
getString(bytes32) public view returns (string)
setBytes(bytes32, bytes) public
getBytes(bytes32) public view returns (bytes)
TimersBlockNumberImpl
getDeadline(Timestamp) internal pure returns (uint64)
setDeadline(Timestamp, uint64) internal
reset(Timestamp) internal
isUnset(Timestamp) internal pure returns (bool)
isStarted(Timestamp) internal pure returns (bool)
isPending(Timestamp) internal view returns (bool)
isExpired(Timestamp) internal view returns (bool)
Timestamp
uint64 _deadline
TimersTimestampImpl
getDeadline(Timestamp) internal pure returns (uint64)
setDeadline(Timestamp, uint64) internal
reset(Timestamp) internal
isUnset(Timestamp) internal pure returns (bool)
isStarted(Timestamp) internal pure returns (bool)
isPending(Timestamp) internal view returns (bool)
isExpired(Timestamp) internal view returns (bool)
Timestamp
uint64 _deadline