PA 6 E PŁYTY



MATERIAŁ		PA 6 E nat.	PA 6 E czarny		
TOLERANCJA	GRUBOŚĆ	gęstość 1,14g/m³	gęstość 1,14g/m³	SZEROKOŚĆ	DŁUGOŚĆ
[mm]	[mm]	waga: kg/m	waga: kg/m	[mm]	[mm]
-0,1/+0,1	0,3*	0,356	0,356	1000	1000 2000
	0,5*	0,593	0,593	1000	1000 2000
	0,8*	0,949	0,949	1000	1000 2000
	1	1,186	1,186	1000	1000 2000
0.15/-0.15	1,5	1,779	1,779	1000	1000 2000
-0,15/+0,15	2	2,372	2,372	1000	1000 2000
-0,2/+0,2	2,5	2,965	2,965	1000	1000 2000
	3	3,558	3,558	1000	1000 2000
	4	4,744	4,744	1000	1000 2000
-0,25/+0,25	5	5,93	5,93	1000	1000 2000
	6	7,116	7,116	1000	1000 2000
+0,2/+1,1	8	10,259	10,259	1000	1000 2000
	10	6,316	6,316	500	1000 3000
	10	7,705	7,705	610	1000 3000
+0,3/+1,5	12	7,65	7,65	500	1000 3000
	12	9,333	9,333	610	1000 3000
	15	9,429	9,429	500	1000 3000
	15	11,503	11,503	610	1000 3000
	20	12,394	12,394	500	1000 3000
	20	15,121	15,121	610	1000 3000
	25	15,359	15,359	500	1000 3000
	25	18,738	18,738	610	1000 3000
+0,5/+2,5	30	18,68	18,68	500	1000 3000
	30	22,79	22,79	610	1000 3000
	35	21,645	21,645	500	1000 3000
	35	26,407	26,407	610	1000 3000
	40	24,61	24,61	500	1000 3000
	40	30,024	30,024	610	1000 3000
	45	27,575	27,575	500	1000 3000
	45	33,642	33,642	610	1000 3000
	50	30,54	30,54	500	1000 3000
	50	37,259	37,259	610	1000 3000
+0,5/+3,5	60	36,767	36,767	500	1000 3000
	60	44,856	44,856	610	1000 3000
	70	42,697	42,697	500	1000 3000
	70	52,09	52,09	610	1000 3000
+0,5/+5,0	80	59,868	59,868	610	1000 3000
	90	67,102	67,102	610	1000 3000
	100	74,337	74,337	610	1000 3000

Inne rozmiary dostępne na zapytanie. Tolerancja długości: 0% do +3% Tolerancja szerokości: +0,5% do +4%

pozycje standardowe zwykle dostępne z magazynu

^{*} materiał w zwojach