SPACELOFT®

FOR BUILDINGS AND HOMES

INSULATION

DATA SHEET

Spaceloft[®] is a flexible, nanoporous aerogel blanket insulation that reduces energy loss while conserving interior space in residential and commercial building applications.

Spaceloft*'s unique properties – extremely low thermal conductivity, superior flexibility, compression resistance, hydrophobicity, and ease of use – make it essential for those seeking the ultimate in thermal protection.

Using patented nanotechnology, Spaceloft® insulation combines a silica aerogel with reinforcing fibers to deliver industry-leading thermal performance in an easy-to-handle and environmentally safe product.


Spaceloft* Is a proven, effective insulator in building applications, providing the highest R-value of any insulation material for maximum energy efficiency in walls, floors, roofs, framing, and windows.


Physical Properties

Thicknesses*	0.20 in (5 mm), 0.40 in (10 mm)		
Max. Use Temp.	390°F (200°C)		
Color	White		
Density*	9.4 lb/ft² (0.15 g/cc)		
Hydrophobic	Yes		
Material Form*	57 in (1,450 mm) wide		

* Nominal Value


R-Value Per Inch





Thermal Conductivity

ASTM C 177 Results



Mean Temp.	~	0	25	59	75	100	125	150	175	200
	ng.	32	-77	122	167	212	257	302	347	392
k mw)	m-K	13.1	13.6	14.3	15.3	16.4	17.7	19.3	21.0	23.0
BTU-mmr-ft	LAF	0.091	0.094	0.099	0.106	0.114	0.123	0.134	0.146	0,160

aspen aerogels Spaceloft® Revision Date

SAFETY DATA SHEET

Revision Date: 02/09/2011

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Product Name:

Spaceloft®

Synonyms:

Silica aerogel materials

Use of the

Address:

High performance insulation materials

Substance/Preparation:

Manufacturer:

Aspen Aerogeis, Inc.

30 Forbes Road

Northborough, MA 01532

Telephone: Email:

(508) 691-1111

EHS@aerogel.com

Emergency Telephone Number:

800-535-5053

US (INFOTRAC)

352-323-3500

INTERNATIONAL.

2. HAZARDS IDENTIFICATION

Classification:

Product is not classified as a dangerous material or preparation as defined in EC Directives

67/548/EEC or 1999/45/EC.

Emergency Overview:

Inhalation of excessive amounts of dust from the product may cause mechanical irritation to

the respiratory tract. Dermal contact may cause mechanical irritation.

POTENTIAL HEALTH EFFECTS

Inhalation:

Inhalation of airborne dusts may cause mechanical irritation of the upper respiratory tract.

Eve Contact:

Exposure to dust from this product can produce a drying sensation and mechanical irritation

of the eyes.

Skin Contact:

Skin contact with dust from this product can produce a drying sensation and mechanical

irritation of the skin and mucous membranes.

Ingestion:

This material is not intended to be ingested (eaten). If ingested in large quantity, the

material may produce mechanical irritation and blockage

Acute Health Hazards:

Dust from this product is a physical irritant, and may cause temporary irritation or

scratchiness of the throat and / or itching and redness of the eyes and skin.

Chronic Health

Hazards:

Per the fiberglass manufacturer, the fiberglass is considered textile grade and is not classified as a human carcinogenic by IARC (Group 3), ACGIH (Group A4), NTP, or

OSHA.

Medical Conditions

Excessive inhalation of dust may aggravate pre-existing chronic lung conditions including, but not limited to, bronchitis, emphysema, and asthma. Dermal contact may aggravate existing dermatitis.

Aggravated by Exposure:

CARCINOGENICITY

Component	ACGIH	NTP	IARC
Continuous Filament Glass Fibers	A4	Not Listed	3
Amorphous Silica	NA	Not Listed	None
Calcium Silicate	NA	Not Listed	3
Synthetic Graphite	NA	Note Listed	None



SAFETY DATA SHEET

SECTION 2 NOTES: This product is composed of synthetic amorphous silica dioxide. Amorphous silica should not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects from exposure to synthetic amorphous silica.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Percent	EINECS Number	EU Classification
Methylsilylated Silica	68909-20-6	40-50	272-697-1	None
Polyethylene terephthalate (PET or polyester)	25038-59-9	10-20	Not Assigned	None
Fibrous glass (textile grade)	NA	10-20	Not Assigned	None
Calcium Silicate	13983-17-0	5-10	237-772-5	None
Synthetic Graphite	7782-42-5	0-5	231-995-3	None

4. FIRST AID MEASURES

Immediately wash with large amounts of water for at least 15 minutes, occasionally lifting lids. Eye Contact:

If irritation occurs and persists, get medical treatment.

Wash skin thoroughly with soap and plenty of water. Remove contaminated clothing and shoes. Skin Contact:

Wash clothing before reuse. Obtain medical attention if symptoms occur.

Material will pass through the body normally. Ingestion:

Remove to fresh air. Drink water to clear throat and blow nose to remove dust. Obtain medical Inhalation:

attention if ill effects persist.

5. FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY PROPERTIES

Auto ignition Temperature	Not Applicable
Flash Point	Not Applicable
Flammability Limits: (Lower Explosive Limit)	Not Applicable
Flammability Limits: (Upper Explosive Limit)	Not Applicable

5.2 EXTINGUISHING MEDIA:

Use media suitable for surrounding fire and that are appropriate to the surrounding environment; normal fog nozzle water application and/or exclusion of air is typically suitable for extinguishing this product in blanket form.

5.3 PROTECTION FOR FIRE FIGHTERS

Special Fire Fighting Procedures:

Normal fire fighting procedures should be followed to avoid inhalation of smoke and

gases produced by a fire.

Unusual Fire and Explosion Hazards: Product is a super-insulation material. Rolls of material can retain heat within internal

layers causing re-ignition in the presence of oxygen if heat is not removed.

Hazardous Decomposition

Primary combustion products are carbon monoxide and carbon dioxide.

Products:



SAFETY DATA SHEET

Spaceloft®

Revision Date: 02/09/2011

6. ACCIDENTAL RELEASE MEASURES

Minimize dust generation. Ensure adequate ventilation. Use personal protective Personal Precautions:

equipment as necessary.

Material is not soluble. Do not flush into surface water or sanitary sewer system. **Environmental Precautions:**

Contain and collect released material for proper disposal. Dry vacuuming is the Methods for Cleaning Up:

preferred method of cleaning up.

7. HANDLING AND STORAGE

Aerogel blankets will generate dust when handled. Workplace exposure to all dusts should be Handling controlled with standard industrial hygiene practices. Dry vacuuming is the preferred method for

cleaning up dust. Because aerogel dust is hydrophobic, water is not effective as a dust control agent,

Aerogel blankets should be kept in their packaging until they are ready to be used. Unpack the material Storage

in the work area. This will help to minimize the area where dust exposure may occur. Trimmed material and scrap should be promptly packed in disposal bags.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Limit Values

There are no exposure limits identified for the main product component, classified as synthetic amorphous silica.

CAS Number 7631-86-9	Component Name Silica, Amorphous	Exposure Limits Germany TRGS 900 UK WEL	4 mg/m ³ (inhalable fraction) 6 mg/m ³ (total inhalable fraction) 2.4 mg/m ³ (respirable fraction)
		US OSHA PEL (TWA)a	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
		US ACGIH ^b	10 mg/m ³ (inhalable) 3 mg/m ³ (respirable)
NA	Continuous filament glass	US ACGIH	1.0 fibers/ce ^c 5 mg/m ³ (inhalable)
	fibers	US OSHA	10 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
13983-17-0	Calcium Silicate	US OSHA PEL (TWA)a	15 mg/m ³ (total dust)
		US ACGIH ^b	5 mg/m ³ (respirable fraction) 10 mg/m ³ (inhalable) 3 mg/m ³ (respirable)
7782-42-5	Synthetic Graphite	US OSHA PEL (TWA)2	15 mg/m3 (total dust)
		US ACGIH ^b	5 mg/m ³ (respirable fraction) 2 mg/m ³

The US OSHA standard for amorphous silica is: (80 mg/m²)/(%SiO2). The NIOSH Sampling Method 7501 for Amorphous Silica calculates the %SiO2 based on the percentage of crystalline silica in the sample. Because the percentage of crystalline silica in aerogel is 0%, the particulate limit applies.

US ACGH based on Particles Not Otherwise Specified (PNOS)

^a Respirable fibers: length >5 µm; aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective). using phase-contrast illumination. US NIOSlengthum, width <3 µm diameter and length: width ratios ≥3.

aspen aerogels

SAFETY DATA SHEET

Spaceloft®

Revision Date: 02/09/2011

8.2 Exposure Control

Ventilation:

Local exhaust in accordance with general industrial hygiene practices is recommended to

control dust.

Respiratory Protection:

A properly fitted, NIOSH or CE approved respirator should be worn when ventilation is unavailable or inadequate to maintain airborne concentrations below applicable occupational

exposure limits. A respiratory protection program that meets applicable local regulations should be implemented whenever workplace conditions warrant use of a respirator.

Hand Protection

Silica acrogels are hydrophobic (repel water) and may cause drying and irritation of the skin,

eyes, and mucous membranes. For this reason, nitrile, latex, or other impermeable gloves

should be worn when handling aerogel blankets.

Eve Protection:

Safety glasses, or chemical goggles as needed to provide greater protection from dust.

Skin Protection:

Long-sleeved, long-legged work clothes are also advised. Disposable coveralls should be considered to minimize skin exposure and track out of acrogel dusts into adjacent areas.

Work Hygienic Practices

Keep materials packaged until just prior to use. Die cut in preserence to rotary or other

cutting methods. Dry vacuum with proper filtration preferred to sweeping. Wash thoroughly after using the product. Wash clothing if dusty conditions present. Wash hands before eating

or drinking.

9. PHYSICAL AND CHEMICAL PROPERTIES

White or gray fabric blanket; material is hydrophobic (repels water). Gray material Appearance:

contains an opacifier. White material does not.

Odor: No characteristic odor. Under certain conditions, product may have faint ammonia-

like odor.

pH:

Boling Point/Range:

Flash Point:

Flammability (solid, gas):

Explosive Properties: Oxidizing Properties:

Vapor Pressure: Solubility:

Viscosity: **Evaporation Rate:**

Not applicable.

Not applicable. Not applicable.

Not applicable. Not applicable. Not applicable.

Not applicable. Insoluble. Not applicable. Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability:

Conditions to Avoid: Materials to Avoid:

Prolonged exposure to temperatures above the recommended use temperatures.

None known

Hazardous

Under recommended usage conditions, hazardous decomposition products are not

Decomposition Products

expected.



SAFETY DATA SHEET

Spaceloft®

Revision Date: 02/09/2011

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Dust may cause mechanical irritation and dryness to eyes and skin.

Synthetic Amorphous Silica

Oral LD50:

>5,000 mg/kg

Inhalation LC50: >2,000 mg/m3

Dermal LD50:

>3,000 mg/kg

Eve Irritation:

Synthetic amorphous silica and silicates are not irritating to skin and eyes under

experimental conditions, but may produce dryness following prolonged and repeated

exposure.

Skin Irritation:

Synthetic amorphous silica and silicates are not irritating to skin and eyes under

experimental conditions, but may produce dryness following prolonged and repeated

exposure.

CARCINOGENICITY

The International Agency for Research on Cancer (IARC) considers synthetic amorphous silica to be not classifiable as to its carcinogenicity to humans (Group 3). According to the manufacturer, the fiberglass in this product is considered textile grade fibrous glass and it is not classified as a carcinogen by ACGIH, IARC, NTP or OSHA.

NOTE TO SECTION 11: Toxicological information is based on literature review for synthetic amorphous silica.

12. ECOLOGICAL INFORMATION

Synthetic Amorphous Silica

Aquatic Toxicity	Fish: LC50 > 10,000 mg/L (Brachydanio rerio: 96 hour), Method OECD 203 Daphnia magna: EC50 > 10,000 mg/l (24 hours), Method OECD 202
Mobility	None expected due to insoluble nature of product.
Persistence and Biodegradability	Not applicable for inorganic material.
Bioaccumulative Potential	None expected due to insoluble nature of product.
Other Adverse Effects	None expected.

13. DISPOSAL CONSIDERATIONS

Dispose in an approved landfill in accordance with federal, state / provincial, and local regulation. Cover promptly to avoid dust generation. This product is not regulated as a hazardous waste under US RCRA regulations.

14. TRANSPORT INFORMATION

Shipping Name:

Not regulated for transport

Hazard Class UN Number

None None None

Packing Group Required Label(s) Marine Pollutant

None No

Additional Information

None

aspen aerogels

SAFETY DATA SHEET

Spaceloft®

Revision Date: 02/09/2011

15. REGULATORY INFORMATION

EC REGULATORY INFORMATION

Product is not classified as a dangerous material or preparation as defined in EC Directives 67/548/EEC or 1999/45/EC. Aerogel insulation blankets are considered an article, not a substance or preparation, under the REACH directive.

CANADIAN REGULATIONS

All chemical substances in this product are included on or exempted from the Canadian Domestic Substance List (DSL). Amorphous silica (CAS No. 7631-86-9) is listed on the WHMIS Ingredient Disclosure List at a concentration threshold of 1 %.

U.S. FEDERAL REGULATIONS

CERCLA (Comprehensive Response Compensation and Liability Act): Product is not classified as hazardous or reportable under this requirement.

SARA TITLE III (Superfund Amendments and Reauthorization Act): Product is not classified as hazardous or reportable under this requirement.

311/312 HAZARD CATEGORIES: Materials in this product are classified as hazardous or reportable under this requirement.

313 REPORTABLE INGREDIENTS: Materials in this product are not classified as hazardous or reportable under this requirement.

STATE REGULATIONS: Materials in this product appear on the following state hazardous substance lists: CA, IN, KY, MA, MN, NC, NJ, OR, PA. Check individual state requirements

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

16. OTHER INFORMATION

NFPA HAZARD CLASSIFICATION		HMIS HAZARD CLASSIFICATION		
Health	1	Health	1	
Flammability	1	Flammability	1	
Reactivity	0	Reactivity	0	
Other	N/A	Protection	Please refer to Section 8.	

Section 11 Synthetic Amorphous Silica Toxicity Information Reference: United Nations Environmental Programme (UNEP), Organization for Economic Co-operation and Development (OECD) Screening Information Data Set (SIDS) Initial Assessment Report, Synthetic Amorphous Silica, July 23, 2004.

Revision Summary: New for reformulated product.

DISCLAIMER: The information herein is presented in good faith and believed to be accurate as of the effective data given. However, no warranty, expressed or implied, is given. It is the user's responsibility to ensure that its activities comply with Federal, State or Provincial, and local laws.