

رگرسیون لجستیک

Logistic Regression

رگرسیون لجستیک دوتایی (Binary Logistic Regression)

مجموعه ای از d پیش‌بینی کننده یا متغیر مستقل x_1, x_2, \dots, x_d و یک متغیر پاسخ دوتایی یا برنولی Y که فقط دو مقدار می‌گیرد.

$$\tilde{\mathbf{x}}_i = (1, x_1, x_2, \dots, x_d)^T \in \mathbb{R}^{d+1}$$

$$P(Y = 1 | \tilde{\mathbf{X}} = \tilde{\mathbf{x}}) = \pi(\tilde{\mathbf{x}})$$

$$P(Y = 0 | \tilde{\mathbf{X}} = \tilde{\mathbf{x}}) = 1 - \pi(\tilde{\mathbf{x}})$$

که در آن $\pi(\tilde{\mathbf{x}})$ مقدار واقعی پارامتر و برای ما ناشناخته است.




Figure 24.1. Logistic function.

تابع منطقی یا هلالی (Logistic or Sigmoid)

$$\theta(z) = \frac{1}{1 + \exp\{-z\}} = \frac{\exp\{z\}}{1 + \exp\{z\}}$$

$$f(\tilde{\mathbf{x}}) = \omega_0 \cdot x_0 + \omega_1 \cdot x_1 + \omega_2 \cdot x_2 + \dots + \omega_d \cdot x_d = \tilde{\omega}^T \tilde{\mathbf{x}}$$

رگرسیون لجستیک دوتایی (Binary Logistic Regression)

$$P(Y=1|\tilde{\mathbf{X}}=\tilde{\mathbf{x}}) = \pi(\tilde{\mathbf{x}}) = \theta(f(\tilde{\mathbf{x}})) = \theta(\tilde{\omega}^T \tilde{\mathbf{x}}) = \frac{\exp\{\tilde{\omega}^T \tilde{\mathbf{x}}\}}{1 + \exp\{\tilde{\omega}^T \tilde{\mathbf{x}}\}}$$

$$P(Y=0|\tilde{\mathbf{X}}=\tilde{\mathbf{x}}) = 1 - P(Y=1|\tilde{\mathbf{X}}=\tilde{\mathbf{x}}) = \theta(-\tilde{\omega}^T \tilde{\mathbf{x}}) = \frac{1}{1 + \exp\{\tilde{\omega}^T \tilde{\mathbf{x}}\}}$$

$$P(Y|\tilde{\mathbf{X}}=\tilde{\mathbf{x}}) = \theta(\tilde{\omega}^T \tilde{\mathbf{x}})^Y \cdot \theta(-\tilde{\omega}^T \tilde{\mathbf{x}})^{1-Y}$$

Log-Odds Ratio

$$\begin{aligned} \ln(\text{odds}(Y=1|\tilde{\mathbf{X}}=\tilde{\mathbf{x}})) &= \ln\left(\frac{P(Y=1|\tilde{\mathbf{X}}=\tilde{\mathbf{x}})}{1 - P(Y=1|\tilde{\mathbf{X}}=\tilde{\mathbf{x}})}\right) = \ln\left(\exp\{\tilde{\omega}^T \tilde{\mathbf{x}}\}\right) = \tilde{\omega}^T \tilde{\mathbf{x}} \\ &= \omega_0 \cdot x_0 + \omega_1 \cdot x_1 + \cdots + \omega_d \cdot x_d \end{aligned}$$

$$\text{logit}(z) = \ln\left(\frac{z}{1-z}\right)$$

$$\ln(\text{odds}(Y=1|\tilde{\mathbf{X}}=\tilde{\mathbf{x}})) = \text{logit}(P(Y=1|\tilde{\mathbf{X}}=\tilde{\mathbf{x}}))$$

رگرسیون لجستیک دوتایی (Binary Logistic Regression)

برآوردگر بیشینه درستنمایی (Maximum Likelihood Estimation)

$$L(\tilde{\mathbf{w}}) = P(Y|\tilde{\mathbf{w}}) = \prod_{i=1}^n P(y_i | \tilde{\mathbf{x}}_i) = \prod_{i=1}^n \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i)^{y_i} \cdot \theta(-\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i)^{1-y_i}$$

The cross-entropy error function

$$\ln(L(\tilde{\mathbf{w}})) = \sum_{i=1}^n y_i \cdot \ln(\theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i)) + (1 - y_i) \cdot \ln(\theta(-\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i))$$

$$E(\tilde{\mathbf{w}}) = -\ln(L(\tilde{\mathbf{w}})) = \sum_{i=1}^n y_i \cdot \ln\left(\frac{1}{\theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i)}\right) + (1 - y_i) \cdot \ln\left(\frac{1}{1 - \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i)}\right)$$

$$\nabla(\tilde{\mathbf{w}}) = \frac{\partial}{\partial \tilde{\mathbf{w}}} \left\{ \ln(L(\tilde{\mathbf{w}})) \right\} = \frac{\partial}{\partial \tilde{\mathbf{w}}} \left\{ \sum_{i=1}^n y_i \cdot \ln(\theta(z_i)) + (1 - y_i) \cdot \ln(\theta(-z_i)) \right\}$$

$$\begin{aligned} \nabla(\tilde{\mathbf{w}}) &= \sum_{i=1}^n y_i \cdot \theta(-z_i) \cdot \tilde{\mathbf{x}}_i - (1 - y_i) \cdot \theta(z_i) \cdot \tilde{\mathbf{x}}_i & z_i &= \tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i \\ &= \sum_{i=1}^n (y_i - \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i)) \cdot \tilde{\mathbf{x}}_i \end{aligned}$$

رگرسیون لجستیک دوتایی (Binary Logistic Regression)

Algorithm 24.1: Logistic Regression: Stochastic Gradient Ascent

LOGISTICREGRESSION-SGA ($\mathbf{D}, \eta, \epsilon$):

```
1 foreach  $\mathbf{x}_i \in \mathbf{D}$  do  $\tilde{\mathbf{x}}_i^T \leftarrow (1 \quad \mathbf{x}_i^T)$  // map to  $\mathbb{R}^{d+1}$ 
2  $t \leftarrow 0$  // step/iteration counter
3  $\tilde{\mathbf{w}}^0 \leftarrow (0, \dots, 0)^T \in \mathbb{R}^{d+1}$  // initial weight vector
4 repeat
5    $\tilde{\mathbf{w}} \leftarrow \tilde{\mathbf{w}}^t$  // make a copy of  $\tilde{\mathbf{w}}^t$ 
6   foreach  $\tilde{\mathbf{x}}_i \in \tilde{\mathbf{D}}$  in random order do
7      $\nabla(\tilde{\mathbf{w}}, \tilde{\mathbf{x}}_i) \leftarrow (y_i - \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i)) \cdot \tilde{\mathbf{x}}_i$  // compute gradient at  $\tilde{\mathbf{x}}_i$ 
8      $\tilde{\mathbf{w}} \leftarrow \tilde{\mathbf{w}} + \eta \cdot \nabla(\tilde{\mathbf{w}}, \tilde{\mathbf{x}}_i)$  // update estimate for  $\tilde{\mathbf{w}}$ 
9    $\tilde{\mathbf{w}}^{t+1} \leftarrow \tilde{\mathbf{w}}$  // update  $\tilde{\mathbf{w}}^{t+1}$ 
10   $t \leftarrow t + 1$ 
11 until  $\|\tilde{\mathbf{w}}^t - \tilde{\mathbf{w}}^{t-1}\| \leq \epsilon$ 
```

Stochastic Gradient Ascent

$$\nabla(\tilde{\mathbf{w}}, \tilde{\mathbf{x}}_i) = (y_i - \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}_i)) \cdot \tilde{\mathbf{x}}_i$$

$$\tilde{\mathbf{w}}^{t+1} = \tilde{\mathbf{w}}^t + \eta \cdot \nabla(\tilde{\mathbf{w}}^t)$$

رگرسیون لجستیک دوتایی (Binary Logistic Regression)

Example 24.2 (Logistic Regression). Figure 24.2(a) shows the output of logistic regression modeling on the Iris principal components data, where the independent attributes X_1 and X_2 represent the first two principal components, and the binary response variable Y represents the type of Iris flower; $Y = 1$ corresponds to Iris-virginica, whereas $Y = 0$ corresponds to the two other Iris types, namely Iris-setosa and Iris-versicolor.


The fitted logistic model is given as

$$\tilde{\mathbf{w}} = (w_0, w_1, w_2)^T = (-6.79, -5.07, -3.29)^T$$

$$P(Y = 1|\tilde{\mathbf{x}}) = \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}) = \frac{1}{1 + \exp\{6.79 + 5.07 \cdot x_1 + 3.29 \cdot x_2\}}$$

Figure 24.2(a) plots $P(Y = 1|\tilde{\mathbf{x}})$ for various values of $\tilde{\mathbf{x}}$.

$$\hat{y} = \begin{cases} 1 & \text{if } \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{z}}) \geq 0.5 \\ 0 & \text{if } \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{z}}) < 0.5 \end{cases}$$



(a) Logistic Regression

رگرسیون لجستیک دوتایی (Binary Logistic Regression)

Given $\tilde{\mathbf{x}}$, if $P(Y = 1|\tilde{\mathbf{x}}) \geq 0.5$, then we predict $\hat{y} = 1$, otherwise we predict $\hat{y} = 0$. Figure 24.2(a) shows that five points (shown in dark gray) are misclassified. For example, for $\tilde{\mathbf{x}} = (1, -0.52, -1.19)^T$ we have:

$$P(Y = 1|\tilde{\mathbf{x}}) = \theta(\tilde{\mathbf{w}}^T \tilde{\mathbf{x}}) = \theta(-0.24) = 0.44$$

$$P(Y = 0|\tilde{\mathbf{x}}) = 1 - P(Y = 1|\tilde{\mathbf{x}}) = 0.54$$

Thus, the predicted response for $\tilde{\mathbf{x}}$ is $\hat{y} = 0$, whereas the true class is $y = 1$.

Figure 24.2 also contrasts logistic versus linear regression. The plane of best fit in linear regression is shown in Figure 24.2(b), with the weight vector:

$$\tilde{\mathbf{w}} = (0.333, -0.167, 0.074)^T$$

$$\hat{y} = f(\tilde{\mathbf{x}}) = 0.333 - 0.167 \cdot x_1 + 0.074 \cdot x_2$$

Since the response vector Y is binary, we predict the response class as $y = 1$ if $f(\tilde{\mathbf{x}}) \geq 0.5$, and $y = 0$ otherwise. The linear regression model results in 17 points being misclassified (dark gray points), as shown in Figure 24.2(b).

Since there are $n = 150$ points in total, this results in a training set or in-sample accuracy of 88.7% for linear regression. On the other hand, logistic regression misclassifies only 5 points, for an in-sample accuracy of 96.7%, which is a much better fit, as is also apparent in Figure 24.2.

رگرسیون لجستیک چندکلاسی (Multiclass Logistic Regression)

Y را با یک متغیر تصادفی برنولی چند متغیره‌ی k بعدی مدل می‌کنیم. $Y \in \{c_1, c_2, \dots, c_K\}$.

از آنجایی که Y فقط یکی از k مقدار را می‌گیرد می‌توانیم از One-hot encoding استفاده کنیم.

$$\mathbf{Y} \in \{\mathbf{e}_1, \mathbf{e}_2, \dots, \mathbf{e}_K\}, \quad \mathbf{e}_i = (\underbrace{0, \dots, 0}_{i-1}, 1, \underbrace{0, \dots, 0}_{K-i})^T$$

$$P(\mathbf{Y} = \mathbf{e}_i | \tilde{\mathbf{X}} = \tilde{\mathbf{x}}) = \pi_i(\tilde{\mathbf{x}}), \text{ for } i = 1, 2, \dots, K$$

$$\sum_{i=1}^K \pi_i(\tilde{\mathbf{x}}) = \sum_{i=1}^K P(\mathbf{Y} = \mathbf{e}_i | \tilde{\mathbf{X}} = \tilde{\mathbf{x}}) = 1$$

اگر $\mathbf{Y} = \mathbf{e}_i$ باشد آنگاه فقط $Y_i = 1$ و الباقی Y_j ها صفر است.

$$P(\mathbf{Y} | \tilde{\mathbf{X}} = \tilde{\mathbf{x}}) = \prod_{j=1}^K (\pi_j(\tilde{\mathbf{x}}))^{Y_j}$$

رگرسیون لجستیک چندکلاسی (Multiclass Logistic Regression)

در حالت چندکلاس باید یک کلاس را به عنوان مبنا انتخاب کنیم.

$$\pi_i(\tilde{\mathbf{x}}) = \exp\{\tilde{\omega}_i^T \tilde{\mathbf{x}}\} \cdot \pi_K(\tilde{\mathbf{x}})$$

$$\ln(\text{odds}(\mathbf{Y} = \mathbf{e}_i | \tilde{\mathbf{X}} = \tilde{\mathbf{x}})) = \ln \left(\frac{P(\mathbf{Y} = \mathbf{e}_i | \tilde{\mathbf{X}} = \tilde{\mathbf{x}})}{P(\mathbf{Y} = \mathbf{e}_K | \tilde{\mathbf{X}} = \tilde{\mathbf{x}})} \right) = \ln \left(\frac{\pi_i(\tilde{\mathbf{x}})}{\pi_K(\tilde{\mathbf{x}})} \right) = \tilde{\omega}_i^T \tilde{\mathbf{x}}$$

$$= \omega_{i0} \cdot x_0 + \omega_{i1} \cdot x_1 + \cdots + \omega_{id} \cdot x_d$$

$$\sum_{j=1}^K \pi_j(\tilde{\mathbf{x}}) = 1 \implies \left(\sum_{j \neq K} \exp\{\tilde{\omega}_j^T \tilde{\mathbf{x}}\} \cdot \pi_K(\tilde{\mathbf{x}}) \right) + \pi_K(\tilde{\mathbf{x}}) = 1$$

$$\implies \pi_K(\tilde{\mathbf{x}}) = \frac{1}{1 + \sum_{j \neq K} \exp\{\tilde{\omega}_j^T \tilde{\mathbf{x}}\}}$$

The Softmax function

$$\pi_i(\tilde{\mathbf{x}}) = \exp\{\tilde{\omega}_i^T \tilde{\mathbf{x}}\} \cdot \pi_K(\tilde{\mathbf{x}}) = \frac{\exp\{\tilde{\omega}_i^T \tilde{\mathbf{x}}\}}{1 + \sum_{j \neq K} \exp\{\tilde{\omega}_j^T \tilde{\mathbf{x}}\}}$$

$$\pi_i(\tilde{\mathbf{x}}) = \frac{\exp\{\tilde{\omega}_i^T \tilde{\mathbf{x}}\}}{\sum_{j=1}^K \exp\{\tilde{\omega}_j^T \tilde{\mathbf{x}}\}}, \quad \text{for all } i = 1, 2, \dots, K$$

رگرسیون لجستیک چندکلاسی (Multiclass Logistic Regression)

برآورد بیشینه‌ی درست‌نمایی (Maximum Likelihood Estimation)

$$L(\tilde{\mathbf{W}}) = P(\mathbf{Y}|\tilde{\mathbf{W}}) = \prod_{i=1}^n P(\mathbf{y}_i|\tilde{\mathbf{X}} = \tilde{\mathbf{x}}_i) = \prod_{i=1}^n \prod_{j=1}^K (\pi_j(\tilde{\mathbf{x}}_i))^{y_{ij}}$$

مجموعه‌ی K بردار وزن و K بردار پاسخ که One-hot encoding مدل شده است.

$$\mathbf{Y} \in \{\mathbf{e}_1, \mathbf{e}_2, \dots, \mathbf{e}_K\}, \quad \tilde{\mathbf{W}} = \{\tilde{\mathbf{w}}_1, \tilde{\mathbf{w}}_2, \dots, \tilde{\mathbf{w}}_K\}$$

$$\ln(L(\tilde{\mathbf{W}})) = \sum_{i=1}^n \sum_{j=1}^K y_{ij} \cdot \ln(\pi_j(\tilde{\mathbf{x}}_i)) = \sum_{i=1}^n \sum_{j=1}^K y_{ij} \cdot \ln\left(\frac{\exp\{\tilde{\mathbf{w}}_j^T \tilde{\mathbf{x}}_i\}}{\sum_{a=1}^K \exp\{\tilde{\mathbf{w}}_a^T \tilde{\mathbf{x}}_i\}}\right)$$

$$\frac{\partial}{\partial \pi_j(\tilde{\mathbf{x}}_i)} \ln(\pi_j(\tilde{\mathbf{x}}_i)) = \frac{1}{\pi_j(\tilde{\mathbf{x}}_i)}$$

$$\frac{\partial}{\partial \tilde{\mathbf{w}}_a} \pi_j(\tilde{\mathbf{x}}_i) = \begin{cases} \pi_a(\tilde{\mathbf{x}}_i) \cdot (1 - \pi_a(\tilde{\mathbf{x}}_i)) \cdot \tilde{\mathbf{x}}_i & \text{if } j = a \\ -\pi_a(\tilde{\mathbf{x}}_i) \cdot \pi_j(\tilde{\mathbf{x}}_i) \cdot \tilde{\mathbf{x}}_i & \text{if } j \neq a \end{cases}$$

رگرسیون لجستیک چندکلاسی (Multiclass Logistic Regression)

$$\nabla(\tilde{\mathbf{w}}_a) = \frac{\partial}{\partial \tilde{\mathbf{w}}_a} \left\{ \ln(L(\tilde{\mathbf{W}})) \right\} = \sum_{i=1}^n (y_{ia} - \pi_a(\tilde{\mathbf{x}}_i)) \cdot \tilde{\mathbf{x}}_i$$

$$\nabla(\tilde{\mathbf{w}}_j, \tilde{\mathbf{x}}_i) = (y_{ij} - \pi_j(\tilde{\mathbf{x}}_i)) \cdot \tilde{\mathbf{x}}_i$$

برای SGA وزن‌ها را در هر مرحله برای یک نقطه به روز می‌کنیم.

$$\tilde{\mathbf{w}}_j^{t+1} = \tilde{\mathbf{w}}_j^t + \eta \cdot \nabla(\tilde{\mathbf{w}}_j^t, \tilde{\mathbf{x}}_i)$$

$$\hat{y} = \arg \max_{c_i} \{ \pi_i(\tilde{\mathbf{z}}) \} = \arg \max_{c_i} \left\{ \frac{\exp\{\tilde{\mathbf{w}}_i^T \tilde{\mathbf{z}}\}}{\sum_{j=1}^K \exp\{\tilde{\mathbf{w}}_j^T \tilde{\mathbf{z}}\}} \right\}$$

رگرسیون لجستیک چندکلاسی (Multiclass Logistic Regression)

Algorithm 24.2: Multiclass Logistic Regression Algorithm

LOGISTICREGRESSION-MULTICLASS ($\mathbf{D}, \eta, \epsilon$):

```
1 foreach  $(\mathbf{x}_i^T, y_i) \in \mathbf{D}$  do
2    $\tilde{\mathbf{x}}_i^T \leftarrow (1 \quad \mathbf{x}_i^T)$  // map to  $\mathbb{R}^{d+1}$ 
3    $\mathbf{y}_i \leftarrow \mathbf{e}_j$  if  $y_i = c_j$  // map  $y_i$  to  $K$ -dimensional Bernoulli vector
4  $t \leftarrow 0$  // step/iteration counter
5 foreach  $j = 1, 2, \dots, K$  do
6    $\tilde{\mathbf{w}}_j^t \leftarrow (0, \dots, 0)^T \in \mathbb{R}^{d+1}$  // initial weight vector
7 repeat
8   foreach  $j = 1, 2, \dots, K-1$  do
9      $\tilde{\mathbf{w}}_j \leftarrow \tilde{\mathbf{w}}_j^t$  // make a copy of  $\tilde{\mathbf{w}}_j^t$ 
10    foreach  $\tilde{\mathbf{x}}_i \in \tilde{\mathbf{D}}$  in random order do
11      foreach  $j = 1, 2, \dots, K-1$  do
12         $\pi_j(\tilde{\mathbf{x}}_i) \leftarrow \frac{\exp\{\tilde{\mathbf{w}}_j^T \tilde{\mathbf{x}}_i\}}{\sum_{a=1}^K \exp\{\tilde{\mathbf{w}}_a^T \tilde{\mathbf{x}}_i\}}$ 
13         $\nabla(\tilde{\mathbf{w}}_j, \tilde{\mathbf{x}}_i) \leftarrow (y_{ij} - \pi_j(\tilde{\mathbf{x}}_i)) \cdot \tilde{\mathbf{x}}_i$  // compute gradient at  $\tilde{\mathbf{w}}_j$ 
14         $\tilde{\mathbf{w}}_j \leftarrow \tilde{\mathbf{w}}_j + \eta \cdot \nabla(\tilde{\mathbf{w}}_j, \tilde{\mathbf{x}}_i)$  // update estimate for  $\tilde{\mathbf{w}}_j$ 
15    foreach  $j = 1, 2, \dots, K-1$  do
16       $\tilde{\mathbf{w}}_j^{t+1} \leftarrow \tilde{\mathbf{w}}_j$  // update  $\tilde{\mathbf{w}}_j^{t+1}$ 
17     $t \leftarrow t + 1$ 
18 until  $\sum_{j=1}^{K-1} \|\tilde{\mathbf{w}}_j^t - \tilde{\mathbf{w}}_j^{t-1}\| \leq \epsilon$ 
```

Example 24.3. Consider the Iris dataset, with $n = 150$ points in a 2D space spanned by the first two principal components, as shown in Figure 24.3. Here, the response variable takes on three values: $Y = c_1$ corresponds to Iris-setosa (shown as

رگرسیون لجستیک چندکلاسی (Multiclass Logistic Regression)

squares), $Y = c_2$ corresponds to Iris-versicolor (as circles) and $Y = c_3$ corresponds to Iris-virginica (as triangles). Thus, we map $Y = c_1$ to $\mathbf{e}_1 = (1, 0, 0)^T$, $Y = c_2$ to $\mathbf{e}_2 = (0, 1, 0)^T$ and $Y = c_3$ to $\mathbf{e}_3 = (0, 0, 1)^T$.

The multiclass logistic model uses $Y = c_3$ (Iris-virginica; triangles) as the reference or base class. The fitted model is given as:

$$\tilde{\mathbf{w}}_1 = (-3.52, 3.62, 2.61)^T$$

$$\tilde{\mathbf{w}}_2 = (-6.95, -5.18, -3.40)^T$$

$$\tilde{\mathbf{w}}_3 = (0, 0, 0)^T$$

Figure 24.3 plots the decision surfaces corresponding to the softmax functions:

$$\pi_1(\tilde{\mathbf{x}}) = \frac{\exp\{\tilde{\mathbf{w}}_1^T \tilde{\mathbf{x}}\}}{1 + \exp\{\tilde{\mathbf{w}}_1^T \tilde{\mathbf{x}}\} + \exp\{\tilde{\mathbf{w}}_2^T \tilde{\mathbf{x}}\}}$$

$$\pi_2(\tilde{\mathbf{x}}) = \frac{\exp\{\tilde{\mathbf{w}}_2^T \tilde{\mathbf{x}}\}}{1 + \exp\{\tilde{\mathbf{w}}_1^T \tilde{\mathbf{x}}\} + \exp\{\tilde{\mathbf{w}}_2^T \tilde{\mathbf{x}}\}}$$

$$\pi_3(\tilde{\mathbf{x}}) = \frac{1}{1 + \exp\{\tilde{\mathbf{w}}_1^T \tilde{\mathbf{x}}\} + \exp\{\tilde{\mathbf{w}}_2^T \tilde{\mathbf{x}}\}}$$

The surfaces indicate regions where one class dominates over the others. It is important to note that the points for c_1 and c_2 are shown displaced along Y to emphasize the contrast with c_3 , which is the reference class.

Overall, the training set accuracy for the multiclass logistic classifier is 96.7%, since it misclassifies only five points (shown in dark gray). For example, for the point $\tilde{\mathbf{x}} = (1, -0.52, -1.19)^T$, we have:

$$\pi_1(\tilde{\mathbf{x}}) = 0$$

$$\pi_2(\tilde{\mathbf{x}}) = 0.448$$

$$\pi_3(\tilde{\mathbf{x}}) = 0.552$$

Thus, the predicted class is $\hat{y} = \arg \max_{c_i} \{\pi_i(\tilde{\mathbf{x}})\} = c_3$, whereas the true class is $y = c_2$.




Figure 24.3. Multiclass logistic regression: Iris principal components data. Misclassified points are shown in dark gray color. All the points actually lie in the (X_1, X_2) plane, but c_1 and c_2 are shown displaced along Y with respect to the base class c_3 purely for illustration purposes.