A CONSTANT-PREDICTION FLOOR FOR SPARSE NONLINEAR BINARY CLASSIFICATION: A SEALED EVALUATION AND THE LIMITS OF AN UNSCORED SUBSET-SEARCH CANDIDATE

Anonymous authors
Paper under double-blind review

ABSTRACT

Recovering a sparse nonlinear rule from n=300 labelled rows and p=100 predictors is a regime where small-sample feature selection is known to be fragile, and where a score near chance is easy to mistake for either progress or failure. We report a calibrated measurement study of the frozen selection that a bounded search left in place: a majority-class predictor. Its sealed final evaluation, four episodes, gives a macro-F1 of 0.3328 (episode range 0.328–0.336), which is consistent with the analytic constant-predictor floor of one third for balanced labels, and sits 0.263 below the best reference baseline reported by the evaluator (0.596). The evaluation completed and its qualification outcome is "qualified"; the artifacts do not report which gate criteria this reflects, so we draw no inference about validity, superiority, or generalization from it. The only proposed alternative, a cross-validated sparse-subset search, produced no score because the evaluation harness aborted, so it is missing evidence rather than a measured loss. We show no improvement, no recovery of the hidden function, and no ablation. The contribution is a floor, an explicit separation of search-scope and sealed-final evidence, and a specification of the selection-bias controls a valid test of the subset-search design would need.

1 INTRODUCTION

Small-sample, high-dimensional classification with a sparse nonlinear ground truth is a setting in which two failure modes coexist (Huang, 2021; Ma et al., 2026). With p=100 predictors and only n=300 training rows, a model that is flexible enough to represent an interaction among a few relevant predictors is also flexible enough to fit noise among the irrelevant ones; and any procedure that searches over many candidate feature subsets and then reports the best cross-validated score inherits a selection bias that grows with the number of candidates examined. A reported score near chance is therefore ambiguous: it can reflect a method that has found nothing, a method that has been honestly regularized into a constant, or an evaluation that does not discriminate. Reading such a number correctly requires knowing what chance *is* under the scoring metric and which evidence scope the number belongs to.

This paper studies one concrete instance. The task is a binary classification problem whose labels are a deterministic nonlinear function of an unknown sparse subset of p=100 predictors, perturbed by a small amount of label noise; the training set has n=300 rows with balanced classes, and the score is macro-averaged F1 on held-out rows. A bounded search over candidate predictors ended with no qualifying winner: the frozen selection is the starting configuration, a majority-class predictor, and the single proposed alternative, a cross-validated search over small feature subsets, never received a score. A sealed final evaluation of the frozen selection nevertheless completed.

Research question. What does a sealed, multi-episode evaluation of a majority-class predictor establish about macro-F1 on a sparse nonlinear binary task at this sample size, and what can and cannot be concluded when the only proposed alternative produced no score?

Generated by The Agentic Scientist




Figure 1: Overview of the study. The task (balanced binary labels, sparse nonlinear target, n=300, p=100, macro-F1) feeds two evidence scopes that are never merged: a search scope in which one proposed candidate produced no score, and a sealed final evaluation of four episodes. Both are read against the frozen majority-class predictor and its macro-F1 floor.

Thesis. On balanced binary labels a constant predictor has a macro-F1 floor of one third, the sealed evaluation reproduces that floor tightly, and the evidence therefore supports a floor-and-limitations statement and nothing about recovering the hidden function, improvement over a baseline, or generalization.

Contributions.

- A sealed-final measurement of the frozen majority-class predictor over four episodes: macro-F1 0.3328 with per-episode values between 0.328 and 0.336, against a control maximum of 0.342 and a best reference baseline of 0.596 (a shortfall of 0.263).
- An analytic account of why this value is expected (Section 3.5): a constant predictor has macro-F1 $\pi/(1+\pi)$ for a predicted-class prevalence π, so the observed values correspond to near-balanced held-out sets; the same account shows that coin-flip prediction would score higher, 0.5, than any constant predictor on balanced labels.
- An explicit disclosure of the qualification outcome and its limits, and a strict separation of search-scope and sealed-final evidence, with the unscored search trial reported as missing evidence.
- A proposal-labelled specification (Section 5.1) of the controls needed for a valid test of the subset-search design, motivated by a count of the candidate subsets it must screen.

Figure 1 summarizes the two evidence scopes and what each supports. We make no performance claim for the subset-search design, and every number in this paper that depends on it is an analytic derivation, not a measurement.

2 Related Work

Feature selection for high-dimensional, small-sample data. A large applied literature addresses classification when predictors greatly outnumber samples. Surveys and comparative studies of feature-selection methods for small-sample gene-expression data (Ma et al., 2026) and methods that couple feature-stability measurement with selection for high-dimensional small-sample data (Huang, 2021) document that the selected subset can be unstable across resamples. Wrapper and ensemble strategies for low-sample-size data (Mandal et al., 2024), hybrid pipelines for imbalanced small-sample classification (Feng et al., 2019), and clustering-based filters for binary classification (Zhao et al., 2023; Tye et al., 2025) are typical of this line, as are overlap-score filters for microarray

Generated by the Agentic Statistician

data (Hamraz et al., 2025), graph-based sparse filters (Abrutzky et al., 2025), and streaming selection for high-dimensional small-sample data (Gong et al., 2024). These works are predominantly application-driven, and we cite them only as context for the difficulty of the regime, not as support for any result here.

Metaheuristic and wrapper search. Binary swarm, colony, foraging, and evolutionary optimizers are widely used to search feature subsets (Zhang et al., 2025; Liu et al., 2025a; Ramakrishnan et al., 2024; Xiang et al., 2026; Li et al., 2025; Badriyah et al., 2024), sometimes combined with recursive elimination on tree ensembles for small-sample settings (Lei et al., 2025) or with a classifier for a specific diagnosis task (Manhrawy et al., 2026). Because these methods score very many subsets against one finite sample, their reported accuracy is subject to the selection effect we quantify analytically in Section 5.1; we do not evaluate any of them.

Sparse and penalized formulations. Sparse regularized and Bayesian formulations for high-dimensional classification include correlated-prior Bayesian variable selection for logistic regression (Ma et al., 2024), non-convex sparse selection for small-sample signal decoding (Zhang et al., 2023), weighted sparse regression with mutual information (Wang et al., 2025), and discriminant analysis with feature selection (Liu et al., 2025b). Such formulations are natural comparators for a sparse nonlinear target, but a linear or additive penalty cannot by construction represent a rule whose dependence on the relevant predictors is purely interactive; this is one reason a subset search over low-order nonlinear bases is a natural alternative to such formulations. Sparse parity functions are the canonical example of a purely interactive rule and have been used as a test case for what gradient-trained networks can learn (Daniely & Malach, 2020); we cite them only as an illustration of that rule class, since the functional form of this task's hidden target is not known.

Imbalance, deep models, and applied pipelines. Studies of deep networks on high-dimension small-sample microarray data (Zeng et al., 2025), selection combined with resampling for imbalanced industrial data (Tye et al., 2024), sparse encoders for compact selection in imaging (Sivarasan & Mythili, 2026), and masked-reconstruction gene selection for binary classification (Hassan et al., 2026) illustrate the breadth of settings in which the same small-n difficulty appears. Our task differs in that labels are exactly balanced, so the macro-F1 of a constant predictor is analytically pinned at one third, which gives an unusually clean floor against which to read results.

3 METHOD

3.1 PROBLEM SETUP

The task supplies a training matrix $X \in \mathbb{R}^{300\times 100}$ and a balanced binary label vector $y \in \{0,1\}^{300}$. The labels are a deterministic nonlinear function of an unknown sparse subset of the 100 predictors plus a small amount of label noise. A configuration is a function $\mathrm{predict}(X_{\mathrm{train}}, y_{\mathrm{train}}, X_{\mathrm{test}}) \to \hat{y}$ returning a binary label for every held-out row, and it is scored by the macro-averaged F1 of $\hat{y}$ against hidden held-out labels,

$$\text{macro-F1} = \tfrac{1}{2}\left(F_1^{(0)} + F_1^{(1)}\right), \qquad F_1^{(c)} = \frac{2\,P_c R_c}{P_c + R_c}, \tag{1}$$

where P_c and R_c are the precision and recall for class c (taken as zero-valued F_1 when the class is never predicted). Only NumPy, SciPy, and scikit-learn are available. The source of the evaluated configuration documents an episode protocol in which each episode is one seed-reset call followed by one prediction call, with training sets of 200–300 rows and held-out sets of 100–2000 rows across episodes; the evaluator never reveals test labels or scores to the configuration. The per-episode sizes are not reported in the artifacts we have.

3.2 DESIGN RATIONALE AND CENTRAL HYPOTHESIS

Our central hypothesis is deliberately modest and concerns measurement rather than method. For exactly balanced labels, any constant predictor attains the same macro-F1, one third, regardless of which class it outputs; this is a property of the metric (Section 3.5) and does not depend on the data-generating function. The frozen selection is a constant predictor. The hypothesis is therefore

Generated by The Agent Scientist

that its sealed macro-F1 will be indistinguishable from one third up to the sampling variability of held-out class prevalence, and that its distance to the best reference baseline therefore indicates how far the reported baseline lies above the floor, not a defect of the evaluation. The hypothesis presumes that the sealed-evaluated configuration is the inspected constant predictor, which the recorded hashes leave unverified (Section 3.4). The hypothesis is falsifiable: a sealed score materially above or below one third, or a large episode-to-episode spread, would contradict it.

The motivating alternative, a sparse-subset search, is based on a different premise: if the target depends on very few predictors, then restricting a low-capacity nonlinear classifier to a well-chosen small subset should generalize where full-feature models cannot at n=300. We treat this as a design to be tested, not as a finding; it did not produce a score (Section 4.4).

3.3 Compared configurations

We keep three groups, and no others.

- **Frozen incumbent (studied).** A majority-class predictor: it returns the more frequent training label for every held-out row, with ties resolved to class 1. The inspected source of the frozen selection contains exactly this prediction rule. This is the only configuration with both a search-scope score and sealed-final evidence.
- **Reference comparators (as reported).** The sealed evaluator reports a control maximum macro-F1 and a best reference baseline macro-F1. The artifacts do not describe how these comparators are constructed; we use them only as the reported numbers and treat their composition as unknown.
- **Cross-validated sparse-subset search (unevaluated, source unavailable).** A proposed design that would screen small feature subsets and choose a low-capacity classifier by cross-validation. One search trial was recorded for it and produced no score. Its source is not available to us for inspection (Supplementary Section A.4), so we make no claim about its implementation details and attach no result to it.

There are no ablations: the ablation evidence source is absent, so we make no statement about the contribution of any component.

3.4 Evaluation protocol as reported

Two evidence scopes exist and are reported separately throughout.

Search scope. A bounded search recorded one trial for the subset-search candidate and a score for the starting configuration. Selection used search evidence only. The investigation outcome is "completed with no winner", the selection kind is the baseline, and the selection's search-scope score and its difference to the original baseline are reported in Table 2. A trial without a score contributes no performance evidence; we do not count it as a loss and we do not impute any value for it.

Sealed final scope. The frozen selection was evaluated in four episodes with seeds 201–204. The evaluator reports a headline macro-F1 (which equals the mean of the four episode scores), the maximum macro-F1 among its control comparators, the macro-F1 of the best reference baseline, the difference between the headline value and the best baseline, the fraction of episodes completed, and a qualification record. The evaluation record marks candidate diagnostics as unverified, so we treat any internal diagnostic as unconfirmed and rely only on the scalar metrics and per-episode scores. The source-tree hash recorded for the sealed evaluation (`a54e3175...`) differs from the tree hash recorded for the inspected source of the frozen selection (`d3a56e24...`), so the identity of the sealed-evaluated configuration and the inspected majority-class source is unverified. Every statement below that treats the sealed-evaluated configuration as a constant predictor (the implied prevalences, and the reading of the score as the floor) is conditional on that identity; the scalar scores themselves do not depend on it.

Statistics. We report the mean, the sample standard deviation, and the range of the four episode scores, and the distance of each to the analytic floor. With four episodes we make no inferential claim; all intervals would be too wide to be informative, and the episode scores are descriptive.

Generated by The Agentic Scientist

3.5 MACRO-F1 OF CONSTANT PREDICTORS

Let a held-out set contain a fraction $\pi \in (0, 1)$ of the class that a constant predictor outputs. The predicted class has recall 1 and precision π, hence $F_1 = 2\pi/(1 + \pi)$; the other class is never predicted, so its F_1 is zero. Therefore

$$\text{macro-F1}_{\text{const}}(\pi) = \frac{\pi}{1+\pi}, \qquad \frac{d}{d\pi}\,\text{macro-F1}_{\text{const}} = \frac{1}{(1+\pi)^2}. \tag{2}$$

At $\pi{=}\frac{1}{2}$ the value is $\frac{1}{3}$ and the slope is $\frac{4}{9}$, so a held-out set that deviates from balance by one percentage point moves the score by about 0.0044. Inverting the relation, an observed constant-predictor score s corresponds to $\pi = s/(1-s)$. The four sealed episode scores therefore correspond to predicted-class prevalences between 0.488 and 0.507, and the control maximum of 0.342 to 0.52. These are derivations conditional on the assumption that the sealed-evaluated configuration emits one class (whose identity with the inspected source is unverified, Section 3.4); they say that the evaluator's held-out sets are close to balanced, they do not independently measure the evaluator's class prevalence.

Two consequences matter for interpretation. First, the floor is robust: no choice among constant predictors can raise macro-F1 on balanced labels beyond sampling noise. Second, the floor is not the chance level of a non-constant predictor. A predictor that outputs labels independently of the features with probability one half for each class has precision and recall of 0.5 in both classes on balanced labels, hence macro-F1 of 0.5. A score of one third is thus below what an uninformative coin flip would deliver, and the best reference baseline at 0.596 exceeds that coin-flip level by about 0.096. Constant predictions therefore should not be described as "chance performance" under this metric, a point that matters when raw accuracy (0.5 for both) and macro-F1 (0.333 versus 0.5) are compared.

3.6 IMPLEMENTATION DETAILS

The inspected source of the frozen selection implements an RPC-style entry point with a reset operation that re-seeds a generator and a predict operation that decodes base64-encoded arrays and returns an integer label array. The prediction function computes the mean of the training labels, takes class 1 if the mean is at least one half and class 0 otherwise, and returns that constant for every held-out row. It uses neither the predictors nor the random generator, so its output cannot depend on the episode seed beyond the training labels it is given. Calls complete in 2.0–3.3 s per episode in the evaluator's record.

3.7 THREATS TO VALIDITY

Four aspects limit what the study supports. (i) One search trial and four sealed episodes are a small sample of both procedures and episodes. (ii) Reference comparators are opaque, so the 0.263 shortfall is a distance to a reported number, not an ablation-grade comparison to a named method. (iii) Candidate diagnostics are unverified. (iv) A floor measurement cannot reveal whether the hidden function is learnable from 300 rows. We elaborate in Section 5.

4 RESULTS

4.1 MAIN RESULT: THE SEALED FLOOR

Table 1 lists the sealed-final record and Figure 2 plots it. The frozen selection obtains a macro-F1 of 0.3328 over the four episodes, with per-episode values of 0.3363, 0.3278, 0.3311, and 0.3359 for seeds 201–204. The sample standard deviation across episodes is 0.0040 and the range is 0.0085. The mean differs from the analytic floor of one third by -0.0006, and the largest single-episode deviation from one third is 0.0055. All four episodes are inside the interval in which the constant-predictor relation of Section 3.5 predicts scores for held-out prevalences within about 1.3 percentage points of one half. The hypothesis of Section 3.2 is therefore not contradicted, conditional on the sealed-evaluated configuration being the inspected constant predictor: the score is at the floor, and the spread is of the size that class-prevalence variation alone would explain.

Generated by the Autistic Scientist

Table 1: Sealed-final record for the frozen majority-class predictor. Episode scores are macro-F1; the headline value is the evaluator's reported macro-F1, which equals the episode mean. Search-scope numbers are deliberately omitted here and appear in Table 2.

Item	Macro-F1	Wall-clock (s)
Episode, seed 201	0.3363	3.26
Episode, seed 202	0.3278	1.99
Episode, seed 203	0.3311	2.89
Episode, seed 204	0.3359	3.00
Headline (mean of 4 episodes)	0.3328	2.79 (mean)
Sample standard deviation	0.0040	–
Control maximum (reported)	0.3421	–
Best reference baseline (reported)	0.5959	–
Headline minus best baseline	−0.2631	–
Fraction of episodes completed	1.0	–




Figure 2: Sealed-final macro-F1 of the frozen majority-class predictor in four episodes (points) against the control maximum, the best reference baseline, the analytic floor of one third for balanced labels, and the search-scope score (reference lines). The four episodes lie within 0.0055 of the floor, and the headline value is 0.263 below the best reference baseline. The y-axis starts at zero.

4.2 Comparison with the reference comparators

The control maximum of 0.3421 exceeds the headline value by 0.0093, which is about 2.3 episode standard deviations but corresponds to only a two-point shift in predicted-class prevalence under the relation of Section 3.5; with the control maximum taken over an unknown number of control runs, a difference of this size does not support any statement of separation. The more informative comparison is with the best reference baseline at 0.5959: the headline value falls short of it by 0.2631, and the best baseline exceeds the control maximum by 0.2538. This ordering shows that the evaluator's reference set contains a configuration that exceeds the constant-predictor floor by a wide

Generic Scientist

Table 2: Search-scope accounting (distinct from the sealed-final record in Table 1).

Item	Value
Search trials recorded	1
Scored / unscored trials	0 / 1
Selection kind	baseline
Investigation outcome	completed, no qualifying winner
Search-scope score of the selection	0.3329
Score difference to original baseline	0.0

margin, hence the task is not at its ceiling and the headroom above the floor is large. It does not show how that baseline obtains its score, whether it generalizes beyond these episodes, or whether a predictor built from n=300 rows could approach it. Because the baseline's composition is not given, we do not attribute the gap to any method property.

4.3 Qualification disclosure

The final evaluation completed with status "completed" and outcome "qualified", and carries an affirmative per-episode flag whose exact criterion is not documented in the artifacts. We report this as recorded, and we state plainly what it does not mean. It does not mean the predictor is competitive: the headline value is 0.263 below the best reference baseline. It does not establish validity against adaptive overfitting, superiority over any comparator, or generalization to other samples from the same generating process. The artifacts give no per-gate diagnostics, so the reason the outcome is "qualified" is unknown to us, and any speculation that it reflects completion rather than performance would be unsupported. Conversely, had the outcome been "not qualified", we would not have been able to attribute it to a performance shortfall rather than to a validity criterion without such diagnostics; we apply the same standard in the present case and make no inference in either direction.

4.4 Search scope and its separation from the sealed result

Table 2 lists search-scope facts. One trial was recorded for the subset-search candidate; it is unscored because the evaluation harness aborted with an infrastructure error (a failure to obtain a private sandbox directory, per the investigation's trial log) before any prediction was scored, so no performance number exists for it, and it is missing evidence, not a measured loss. The frozen selection is the original baseline: the selection kind is the baseline, and the search-scope score is 0.3329 with a difference of 0.0 to the baseline's score.

The search-scope score of 0.3329 and the sealed headline of 0.3328 differ by 1.6×10^{-4}. Their agreement is an observation, not a validation of either: the scopes differ in episodes and, for all we can document, in held-out samples, and both values would be expected near one third for any constant predictor on balanced labels by the relation of Section 3.5. The two scopes should not be pooled, and we never combine them in a single comparison.

4.5 Failure analysis and evidence gaps

What the study cannot say is as important as what it can. (a) With zero scored search trials, no comparison between the frozen selection and any alternative exists in the search scope. (b) With no ablation evidence, there is no controlled comparison that isolates any component, and nothing in this paper attributes a score change to a method component. (c) With four episodes, the standard deviation of 0.0040 is a rough descriptive figure. (d) The sealed result does not test the hidden-function recovery that the task was designed to probe; a constant predictor ignores the predictors entirely, so its score is uninformative about whether the sparse support is identifiable at n=300. The correct reading of the measured value is therefore as a calibrated lower reference for this metric and task, not as evidence about any learning method.

Generated by The Autonomous Scientist

5 Discussion and Limitations

What the floor result supports. In these four episodes the constant predictor scored within 0.0055 of one third, and the 0.263 gap indicates the distance of the evaluator's best reported baseline from it. These are measurement-specific observations, not general rules: held-out sizes and prevalences per episode are unreported, so we do not propose a threshold for distinguishing constant-like behavior from weak signal. What the analysis does support is that, under macro-F1 with balanced labels, one third and the coin-flip level of 0.5 are different reference points, and a reported score should be read against the appropriate one.

What it does not support. It does not support any statement that a sparse nonlinear target was or was not recovered, that the candidate search would have succeeded or failed, or that the qualification outcome reflects validity. Qualification and performance are separate facts here, and we keep them separate.

Remaining threats. Reference comparators are opaque; only four episodes were evaluated; the diagnostics are unverified; per-episode training and held-out sizes are unreported, and since the documented protocol allows held-out sizes from 100 to 2000 rows, the episode-to-episode spread may partly reflect different test-set sizes and prevalences. We also did not observe the evaluator's held-out labels, so the prevalences implied in Section 3.5 are inferences.

5.1 What a valid test of the subset-search design would require (proposal)

The following is a proposal, not an evaluated protocol. The candidate must score a very large number of subsets against a sample of 300 rows. In a task with 100 predictors there are 100 single predictors, 4 950 pairs, 161 700 triples, and 3 921 225 quadruples. Any design that screens all singles and pairs touches at least 5 050 subsets. For a null feature subset the accuracy of a fixed rule on 300 rows has a standard error of $\sqrt{0.25/300} = 0.029$. Under the crude approximation that the pair scores are independent Gaussians around chance, the expected maximum over 4 950 pairs exceeds the mean by roughly $0.029\sqrt{2\ln 4950} \approx 0.12$, so the expected maximum, near $0.5 + 0.12$, would exceed a threshold of three standard errors above chance, $0.5 + 3 \times 0.029 = 0.587$. Real subset scores are correlated and need not be independent splits, so this is only an order-of-magnitude warning, not an estimate; but it shows that a chance threshold computed on the same data used for selection cannot by itself certify that a selected subset carries signal.

A valid test would therefore need: (1) *nested resampling*, in which subset search, model choice, and any acceptance rule all run inside each outer training fold and are scored only on the outer held-out fold; (2) a *null calibration*, in which the entire pipeline is run on label-permuted copies of the data so that the distribution of the selected-subset score under no signal is measured, not assumed (permutation tests have been proposed for comparing and selecting classifiers (Arias et al., 2017)); (3) *replicated draws* with several seeds and training-set sizes spanning the 200–300 range the protocol documents, reporting mean and spread; (4) *named baselines* under the same nested protocol, including the majority-class floor of this paper, an unrestricted full-feature ensemble, and a sparse penalized model, so that a difference can be attributed; and (5) *component ablations* (removing or isolating each component of the design once its structure is known) so that any gain could be assigned to a mechanism. Because the floor is one third while the coin-flip level is 0.5, such a study should also report accuracy alongside macro-F1.

6 Conclusion

A sealed final evaluation of the frozen majority-class predictor yields a macro-F1 of 0.3328 over four episodes, within 0.0055 of the analytic one-third floor for balanced labels and 0.263 below the best reference baseline reported by the evaluator. The evaluation completed with a qualified outcome; because the artifacts do not say which gate criteria that reflects, we do not read it as evidence of validity, superiority, or generalization. The only proposed alternative, a cross-validated sparse-subset search, has no score because the evaluation harness aborted, which makes it missing evidence rather than a measured loss, and no ablation evidence exists. The study thus delivers a calibrated floor, a derivation showing that constant prediction sits below coin-flip prediction under

Generated by The Agentic Scientist

macro-F1, a strict separation of search and sealed evidence, and a concrete list of controls for a future valid test. It does not show that the hidden sparse function can be recovered from 300 samples, and nothing here should be taken as an improvement claim.

Generated by The Agentic Scientist

REFERENCES

Mor Abrutzky, Shir Friedman, Gonen Singer, and Neta Rabin. A graph-based sparse filter feature selection method for multi-class and ordinal data. *2025 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8, 2025.

Marta Arias, Argimiro Arratia, and Ariel Duarte-López. Classifier selection with permutation tests, 2017. URL https://arxiv.org/abs/1711.09708.

T. Badriyah, Iwan Syarif, and Fitriani Rohmah Hardiyanti. Development of a java library with bacterial foraging optimization for feature selection of high-dimensional data. *JOIV : International Journal on Informatics Visualization*, 2024.

Amit Daniely and Eran Malach. Learning parities with neural networks, 2020. URL https://arxiv.org/abs/2002.07400.

Fang Feng, Qing-Quan Lv, Mingsong Wang, Xuhui Yang, Qing-Guo Zhou, and R. Zhou. A hybrid feature selection algorithm applied to high-dimensional imbalanced small-sample data classification. *2019 Asia-Pacific Signal and Information Processing Association Annual Summit and Conference (APSIPA ASC)*, pp. 41–46, 2019.

Kuangfeng Gong, Guohe Li, Lingyun Guo, and Yao-Jin Lin. Online streaming feature selection for high-dimensional small-sample data. *International Journal of Machine Learning and Cybernetics*, 16:2705 – 2719, 2024.

Muhammad Hamraz, Tahir Abbas, Fawad Ali, Dost Muhammad Khan, and M. Aamir. Modified robust proportional overlapping score for feature selection in high-dimensional micro-array data. *Computers in biology and medicine*, 191:110165, 2025.

Sehran Hassan, Alamgir, Hasnain Iftikhar, A. Gul, Abdur Rehman, and Paulo Canas Rodrigues. A robust masked painter framework for gene selection in binary classification of high-dimensional functional genomic data. *Entropy*, 28, 2026.

Cheng-Yuan Huang. Feature selection and feature stability measurement method for high-dimensional small sample data based on big data technology. *Computational Intelligence and Neuroscience*, 2021, 2021.

Yao Lei, Jian-Yin Zhao, Wei-Min Lv, and Youwei Hu. Dynamic pso-optimized xgboost–rfe with cross-domain hierarchical transfer: A small-sample feature selection approach for equipment health management. *Electronics*, 2025.

An-Da Li, Bing Xue, Meng-Jie Zhang, Xiong-Min Lin, and Guo-Dong Wang. Cooperative coevolutionary probability-based binary particle swarm optimization for high-dimensional feature selection. *2025 IEEE Congress on Evolutionary Computation (CEC)*, pp. 1–4, 2025.

Jianhua Liu, Yu-Xiang Chen, and Shanglong Li. Binary particle swarm optimization with manta ray foraging learning strategies for high-dimensional feature selection. *Biomimetics*, 10, 2025a.

Li-Meng Liu, Guannan Wang, and Sandra E Safo. Multivariate functional linear discriminant analysis with feature selection: an application to inflammatory bowel disease classification. *Biostatistics*, 27 1, 2025b.

Libing Ma, Yan-Li Ma, Li-Chen Zhang, and Yanbing Heng. *Evaluation of Feature Selection Methods for High-Dimensional Gene Expression Data with Small Sample Sizes*. 2026.

Zhuanzhuan Ma, Zifei Han, Souparno Ghosh, Liu-Cang Wu, and Min Wang. Sparse bayesian variable selection in high-dimensional logistic regression models with correlated priors. *Statistical Analysis and Data Mining: The ASA Data Science Journal*, 17, 2024.

A. Mandal, M. Nadim, Hasi Saha, Tangina Sultana, M. Hossain, and Eui nam Huh. Feature subset selection for high-dimensional, low sampling size data classification using ensemble feature selection with a wrapper-based search. *IEEE Access*, 12:62341–62357, 2024.

Generated by The Agentic Scientist

I. M. Manhrawy, Hanaa Fathi, D. Alsekait, A. Al Tawil, and A. Kelany. Hybrid feature selection and classification model using high-dimensional data based on a metaheuristic algorithm for brain cancer diagnosis. *Scientific Reports*, 16, 2026.

Anandkumar Ramakrishnan, Rajakumar Ramalingam, Padmanaban Ramalingam, Vinayakumar Ravi, T. Alahmadi, and S. S. Maidin. A novel chaotic binary butterfly optimization algorithm based feature selection model for classification of autism spectrum disorder. *International Journal of Applied Mathematics and Computer Science*, 34:647 – 660, 2024.

R. Sivarasan and M. S. Mythili. Deterministic top-k activation sparse encoder for compact feature selection in covid-19 chest x-ray classification. *The Scientific Temper*, 2026.

Yi Wei Tye, U. Yusof, Xin-Ying Chew, and Samat Tulpar. Asfe feature selection technique integrated with smote-enn for handling high-dimensional and highly imbalanced wafer defect classification data. In *International Conference on Advanced Computer Theory and Engineering*, pp. 37–42, 2024.

Yi Wei Tye, Xin-Ying Chew, U. Yusof, and Samat Tulpar. Acg-sfe: Adaptive cluster-guided simple, fast, and efficient feature selection for high-dimensional microarray data in binary classification. *PLOS One*, 20, 2025.

Yadi Wang, Yu-Lin Xie, Su-Fang Zhou, Bing-Bing Jiang, and Hang-Jun Che. Structural feature selection via weighted sparse regression with mutual information. *Journal of Big Data*, 13, 2025.

Chunli Xiang, Jing Zhou, Zhi-Wei Ye, Zeng-Gang Xiong, An Song, Dingfeng Song, and Jie Sun. High-dimensional small-sample feature selection using co-evolutionary ant colony optimization inspired by heterosis. *Biomimetics*, 11, 2026.

Yi-Fu Zeng, Yi-Xiang Zhang, Zikai Xiao, and He Sui. A multi-classification deep neural network for cancer type identification from high-dimension, small-sample and imbalanced gene microarray data. *Scientific Reports*, 15, 2025.

Jin Zhang, Fu Yan, and Jianqiang Yang. Binary plant rhizome growth-based optimization algorithm: an efficient high-dimensional feature selection approach. *Journal of Big Data*, 12, 2025.

Shao-Rong Zhang, Qi-Hui Wang, Ben-Xin Zhang, Zhen Liang, Li Zhang, Linling Li, Gan Huang, Zhi-Guo Zhang, Bao Feng, and Tianyou Yu. Cauchy non-convex sparse feature selection method for the high-dimensional small-sample problem in motor imagery eeg decoding. *Frontiers in Neuroscience*, 17, 2023.

Zhengtian Zhao, Z. Rui, and Xiaoyan Duan. Feature selection for binary classification based on class labeling, som, and hierarchical clustering. *Measurement and Control*, 56:1649 – 1669, 2023.

Generated by The Agentic Scientist

A Supplementary Information

A.1 Sealed-final per-episode records

Table 3 gives the records behind Table 1 together with each episode's distance to the analytic floor and the implied predicted-class prevalence $\pi = s/(1-s)$ of Section 3.5. The candidate-diagnostics trust level recorded by the evaluator is "unverified". All four episodes carry an affirmative per-episode flag whose exact criterion is undocumented, and the completed fraction is 1.0.

Table 3: Per-episode sealed-final records. The implied prevalence is a derivation under the assumption of a constant predictor, not a measurement.

Seed	Macro-F1	Deviation from $1/3$	Implied π	Wall-clock (s)
201	0.3363	$+0.0029$	0.507	3.26
202	0.3278	-0.0055	0.488	1.99
203	0.3311	-0.0022	0.494	2.89
204	0.3359	$+0.0025$	0.506	3.00

A.2 Qualification and comparator metrics

The evaluator reports status "completed" and outcome "qualified". Reported comparator metrics are the control maximum macro-F1 (0.3421), the best reference baseline macro-F1 (0.5959), and the difference between the headline value and the best baseline (-0.2631). The composition of the controls and of the best baseline is not specified in the artifacts, so we treat them as opaque numbers. The control maximum corresponds to an implied predicted-class prevalence of 0.52 under the constant-predictor relation, which we mention only as a consistency check, not as evidence that the control is a constant predictor. The best baseline exceeds the control maximum by 0.2538. No per-gate diagnostics are available, so which criteria the qualification outcome reflects remains unknown.

A.3 Search-scope accounting for the unscored trial

The search scope contains one trial of the subset-search candidate and zero scored trials. The harness aborted with an operating-system error indicating that no owner-private directory was available to create the evaluation sandbox, before any prediction was scored. This is an infrastructure fault, and it carries no information about the candidate's predictive quality. The frozen selection is the original baseline (difference of 0.0 to the baseline score of 0.3329), the investigation outcome is "completed with no qualifying winner", and no sealed-final result exists for the candidate.

A.4 Unevaluated sparse-subset search: what is and is not known

A cross-validated sparse-subset search was proposed and one search trial was recorded for it. The only grounded facts about it are that the trial is unscored and that the harness aborted with an infrastructure error (Section A.3). The source directory available for inspection contains only the frozen selection and the original baseline, which are identical majority-class sources; no source for the proposed search is available to us. We therefore state no structure, hyperparameters, or budgets for it and make no performance claim. The selection-bias exposure described in Section 5.1 applies to any design that selects subsets and scores them on the same rows, and it is the first item of the proposed controls.

A.5 Constant-predictor macro-F1 and sensitivity

For the predicted class c with test prevalence π, precision is π and recall is 1, so $F_1^{(c)} = 2\pi/(1+\pi)$ and the other class has $F_1 = 0$ by convention. The macro-F1 is $\pi/(1+\pi)$. At $\pi = 0.5$ this is $1/3$ with slope $4/9$. The relation is monotone, so any constant predictor on a test set with prevalence at or below one half for its predicted class scores at most $1/3$ at balance and decreases as that class becomes rarer. For a non-constant predictor with independent uniform guesses on balanced labels,

Generated by The Agentic Scientist

$P_c = R_c = 0.5$ in both classes and macro-F1 is 0.5. The observed episode range of 0.328–0.336 corresponds to $\pi \in [0.488, 0.507]$.

A.6 Reproducibility details

Derived quantities in the main text (episode mean, standard deviation, range, deviations from one third, implied prevalences, subset counts, and the standard error at chance) are computed by a short script that reads only the evidence registry and writes a JSON file; the figure is generated from that JSON. The analytic quantities for the subset count and the extreme-value heuristic use only the task setup (n=300, p=100). The inspected frozen predictor takes no random input, so, if the sealed-evaluated configuration is that predictor, reruns of the same episode reproduce its output exactly; the four episode seeds are 201–204.

A.7 LLM Usage

Large language model agents were used throughout this work. An LLM agent proposed and implemented the sparse-subset-search candidate, executed the bounded search, and, in a separate step, drafted the strategy memo, the analysis script, the figures, and this manuscript from a registry of evaluation artifacts. All numbers in the paper were taken from that registry or computed from it by a script, and the framing was constrained to what those artifacts support. The disclosure is made because LLM use here was significant: it covered implementation, execution, analysis, and writing.

Generated by The Agentic Scientist