

spec_tools

Generated by Doxygen 1.8.13

Contents

1	Todo List	2
2	Class Documentation	2
2.1	_csv<_T> Class Template Reference	2
2.1.1	Detailed Description	4
2.1.2	Constructor & Destructor Documentation	5
2.1.3	Member Function Documentation	6
2.2	_io<_T> Class Template Reference	19
2.2.1	Detailed Description	20
2.2.2	Member Function Documentation	20
2.3	_log Class Reference	21
2.4	_marker<_T> Class Template Reference	22
2.4.1	Detailed Description	24
2.4.2	Member Function Documentation	25
2.4.3	Member Data Documentation	26
2.5	_msg Class Reference	26
2.5.1	Detailed Description	27
2.5.2	Member Function Documentation	27
2.6	_marker<_T>::Line Struct Reference	28
2.6.1	Detailed Description	29
2.7	_io<_T>::vec Struct Reference	29
2.7.1	Detailed Description	29

3	File Documentation	30
3.1	csv.h File Reference	30
3.1.1	Detailed Description	31
3.2	der_snr.cpp File Reference	31
3.2.1	Detailed Description	32
3.3	elemlist.cpp File Reference	32
3.3.1	Detailed Description	33
3.3.2	Macro Definition Documentation	33
3.4	findncopy.cpp File Reference	34
3.4.1	Detailed Description	35
3.4.2	Macro Definition Documentation	35
3.5	genrandspec.cpp File Reference	35
3.5.1	Detailed Description	36
3.5.2	Macro Definition Documentation	37
3.6	log.h File Reference	37
3.6.1	Detailed Description	38
3.7	marker.cpp File Reference	38
3.7.1	Detailed Description	39
3.7.2	Macro Definition Documentation	39
3.8	msg.h File Reference	40
3.8.1	Detailed Description	41
3.9	shift.cpp File Reference	41
3.9.1	Detailed Description	42
3.9.2	Macro Definition Documentation	42
3.10	waverage.cpp File Reference	43
3.10.1	Detailed Description	43
	Index	45

1 Todo List

Member `_csv<_T>::set_separator` (const std::string &sSep)

Class `_io<_T>`

bool `write`(std::string sFilename)

Class `_marker<_T>`

marker(const _marker<_T>&)

2 Class Documentation

2.1 `_csv<_T>` Class Template Reference

This is the templated `_csv` class, initialized with double by default. STL parallel execution policy does not provide enhancements for simple operations.

```
#include <csv.h>
```

Public Types

- enum `eVerbose` { **QUIET**, **DEBUG** }
- Define verbosity values.

Public Member Functions

- `_csv` ()
Default constructor without parameters. These parameters must be set after by methods. It will rise lot of errors if something is missing.
- `_csv` (const std::string &sFilename, const char &cSep)
Constructor with two parameters such as the name of the working file and the separator character as usual with csv.
- `_csv` (const std::string &sFilename, const std::string &sSep)
- `_csv` (const std::vector< std::vector<_T> > &vvData)
Constructor fed with external data.
- `_csv` (const std::vector< std::string > &vsHeader, const std::vector< std::vector<_T> > &vvData)
Constructor fed with external header and data.
- `_csv` (const std::vector< std::string > &vsHeader, const std::vector< std::vector<_T> > &vvData, const char &cSep)
Constructor fed with external header and data.
- bool `read` ()
Read the content of the file given to the constructor using boost. It detects the header and data consistency with digit sequence: {0123456789e+-, tab std::endl} and basic regex and dimension matching between header and data line. It is able to recover basic errors such as 'tab'==' '. The method put NaN in the grid if an unrecoverable error appends. Data will be store in private variables.
- bool `show` () const

Show whole data, i.e. the header and data with no restriction on length or terminal size. It uses `boost::format` in order to correct spacing of number and strings.

- `bool show (int iLine_stop) const`

Show the header and data until "line_stop" line. Print all columns with terminal end-of-line. It uses `boost::format` in order to correct spacing of number and strings.

- `bool write ()`

Write on disk what data are store.

- `const std::vector<_T> select_line (int line) const`

Select the line "line" in data.

- `const std::vector<_T> select_column (int iCol) const`

Select the column "col" in data.

- `const std::vector< std::vector<_T> > select (int iLine_min, int iLine_max, int iCol_min, int iCol_max) const`

Select a sub grid in data, i.e. trim data to the rectangular $[i_{min}, i_{max}] \times [j_{min}, j_{max}]$.

- `bool set_data (const std::vector< std::vector<_T> > &vvData)`

Set data with a vector of a vector.

- `bool set_column (const std::vector<_T> &vCol, int iCol)`

Set a column with a vector.

- `bool set_row (const std::vector<_T> &vRow, int iRow)`

- `bool set_header (const std::vector< std::string > &vsHeader)`

Set the header: the first line containing column name.

- `bool set_filename (const std::string &sFilename)`

Set the filename for output or input. The fstream do not care about extension...

- `bool set_filename_out (const std::string &sFilename)`

Set the filename for output. The fstream do not care about extension...

- `bool set_separator (const char &cSep)`

Set the csv separator. Usually: '\t', ',', ';;', ';'...

- `bool set_separator (const std::string &sSep)`

Set the csv separator. Usually: '\t', ',', ';;', ';'...

- `void set_verbose (eVerbose evV)`

Set the verbose mode for debug. It does not deactivate error raising.

- `const std::string get_filename () const`

Get the filename.

- `const std::string get_filename_out () const`

Get the output filename.

- `const char get_separator () const`

Get the separator.

- `const size_t get_header_size () const`

Get size of the header.

- `const size_t get_data_size_i () const`

Get data line size.

- `const size_t get_data_size_j () const`

Get data column size.

- `const std::vector< std::vector<_T> > & get_data () const`

Get data and return it as a vector of vector.

- `const std::vector< std::string > & get_header () const`

Get column names and return it in a vector.

- `bool empty () const`

Check if data are empty, and the emptiness of the first line, i.e. this->data[0].

- bool **check_dim** ()

Check data dimension consistency, i.e. if all line dimensions are all equal.

- bool **genrandspec** (_T TMin, _T TMax, _T TStep)
- bool **transform_lin** (_T TA, _T TB, int iCol)

Do $Y=aX+b$ to the iCol-column.

- bool **shift** (_T TVal)
- bool **shift** (_T TVal, int iCol)
- bool **apply_max_threshold** (_T TVal)

Delete i line from the grid where $\text{data}[i][j] > \text{val}$.

- bool **apply_min_threshold** (_T TVal)

Delete i line from the grid where $\text{data}[i][j] < \text{val}$.

- bool **apply_max_threshold** (_T TVal, int iCol)

Delete i line from the grid where $\text{data}[i][j] \neq \text{list} > \text{val}$.

- bool **apply_min_threshold** (_T TVal, int iCol)

Delete i line from the grid where $\text{data}[i][j] \neq \text{list} < \text{val}$.

- void **zeroize** ()

Set to zero data. One should find this useful...

- void **clear** ()

Delete data and header.

- **_csv & operator=** (const **_csv** &other) const
- bool **operator==** (const **_csv** &other) const
- bool **operator!=** (const **_csv** &other) const
- **_csv & operator+** (const **_csv** &other) const

Sum with the 2nd column.

- **_csv & operator+** (const _T &other) const

Add a constant to the 2nd column.

- **_csv & operator-** (const **_csv** &other) const

Sum with the 2nd column.

- **_csv & operator-** (const _T &other) const

Subtract a constant to the 2nd column.

- **_csv & operator*** (const **_csv** &other) const

Inner product with the 2nd column.

- **_csv & operator*** (const _T &other) const

Multiply by a constant the 2nd column.

- **_csv & operator/** (const **_csv** &other) const

Divide element by element the two columns.

- **_csv & operator/** (const _T &other) const

Divide by a non zero constant the 2nd column.

2.1.1 Detailed Description

```
template<typename _T = double>
class _csv<_T>
```

This is the templated **_csv** class, initialized with double by default. STL parallel execution policy does not provide enhancements for simple operations.

2.1.2 Constructor & Destructor Documentation

2.1.2.1 `_csv()` [1/6]

```
template<typename _T = double>
_csv<_T>::_csv ( )
```

Default constructor without parameters. These parameters must be set after by methods. It will rise lot of errors if something is missing.

Default constructor

2.1.2.2 `_csv()` [2/6]

```
template<typename _T = double>
_csv<_T>::_csv (
    const std::string & sFilename,
    const char & cSep ) [explicit]
```

Constructor with two parameters such as the name of the working file and the separator character as usual with csv.

Constructor

Parameters

<i>sFilename</i>	string Name of the input or output file with extension
<i>cSep</i>	char Separator char between column

2.1.2.3 `_csv()` [3/6]

```
template<typename _T = double>
_csv<_T>::_csv (
    const std::string & sFilename,
    const std::string & sSep ) [explicit]
```

Parameters

<i>sFilename</i>	string Name of the input or output file with extension
<i>sSep</i>	string Separator char between column

2.1.2.4 `_csv()` [4/6]

```
template<typename _T = double>
```

```
_csv< _T >::_csv (
    const std::vector< std::vector< _T > > & vvData ) [explicit]
```

Constructor fed with external data.

Parameters

<i>vvData</i>	the data
---------------	----------

2.1.2.5 _csv() [5/6]

```
template<typename _T = double>
_csv< _T >::_csv (
    const std::vector< std::string > & vsHeader,
    const std::vector< std::vector< _T > > & vvData ) [explicit]
```

Constructor fed with external header and data.

Parameters

<i>vsHeader</i>	The vector of column name
<i>vvData</i>	the data

2.1.2.6 _csv() [6/6]

```
template<typename _T = double>
_csv< _T >::_csv (
    const std::vector< std::string > & vsHeader,
    const std::vector< std::vector< _T > > & vvData,
    const char & cSep ) [explicit]
```

Constructor fed with external header and data.

Parameters

<i>vsHeader</i>	the vector of column name
<i>vvData</i>	the data
<i>cSep</i>	char Separator char between column

2.1.3 Member Function Documentation

2.1.3.1 `apply_max_threshold()` [1/2]

```
template<typename _T = double>
bool _csv<_T>::apply_max_threshold (
    _T TVal )
```

Delete i line from the grid where `data[i][j] > val`.

Parameters

<i>TVal</i>	The max threshold
-------------	-------------------

Returns

true if all seems OK

2.1.3.2 `apply_max_threshold()` [2/2]

```
template<typename _T = double>
bool _csv<_T>::apply_max_threshold (
    _T TVal,
    int iCol )
```

Delete i line from the grid where `data[i][j ≠ list] > val`.

Parameters

<i>TVal</i>	The max threshold
<i>iCol</i>	Select a column

Returns

true if all seems OK

2.1.3.3 `apply_min_threshold()` [1/2]

```
template<typename _T = double>
bool _csv<_T>::apply_min_threshold (
    _T TVal )
```

Delete i line from the grid where `data[i][j] < val`.

Parameters

<i>TVal</i>	The min threshold
-------------	-------------------

Returns

true if all seems OK

2.1.3.4 apply_min_threshold() [2/2]

```
template<typename _T = double>
bool _csv< _T >::apply_min_threshold (
    _T TVal,
    int iCol )
```

Delete *i* line from the grid where **data**[*i*][*j* ≠ *list*] < *val*.

Parameters

<i>TVal</i>	The min threshold
<i>iCol</i>	Select a column

Returns

true if all seems OK

2.1.3.5 check_dim()

```
template<typename _T = double>
bool _csv< _T >::check_dim ( )
```

Check data dimension consistency, i.e. if all line dimensions are all equal.

Returns

true if dimensions seem OK

2.1.3.6 `empty()`

```
template<typename _T = double>
bool _csv<_T>::empty ( ) const
```

Check if data are empty, and the emptiness of the first line, i.e. `this->data[0]`.

Returns

true if data are empty

2.1.3.7 `get_data()`

```
template<typename _T = double>
const std::vector< std::vector<_T> > & _csv<_T>::get_data ( ) const
```

Get data and return it as a vector of vector.

Returns

`std::vector<std::vector<_T>>`

2.1.3.8 `get_data_size_i()`

```
template<typename _T = double>
const size_t _csv<_T>::get_data_size_i ( ) const
```

Get data line size.

Returns

`size_t`

2.1.3.9 `get_data_size_j()`

```
template<typename _T = double>
const size_t _csv<_T>::get_data_size_j ( ) const
```

Get data column size.

Returns

`size_t`

2.1.3.10 `get_filename()`

```
template<typename _T = double>
const std::string _csv<_T>::get_filename ( ) const
```

Get the filename.

Returns

`std::string`

2.1.3.11 `get_filename_out()`

```
template<typename _T = double>
const std::string _csv<_T>::get_filename_out ( ) const
```

Get the output filename.

Returns

`std::string`

2.1.3.12 `get_header()`

```
template<typename _T = double>
const std::vector<_T> & _csv<_T>::get_header ( ) const
```

Get column names and return it in a vector.

Returns

`std::vector<_T>`

2.1.3.13 `get_header_size()`

```
template<typename _T = double>
const size_t _csv<_T>::get_header_size ( ) const
```

Get size of the header.

Returns

`size_t`

2.1.3.14 `get_separator()`

```
template<typename _T = double>
const char _csv<_T>::get_separator ( ) const
```

Get the separator.

Returns

char

2.1.3.15 `read()`

```
template<typename _T = double>
bool _csv<_T>::read ( )
```

Read the content of the file given to the constructor using boost. It detects the header and data consistency with digit sequence: {0123456789e+-, tab std::endl} and basic regex and dimension matching between header and data line. It is able to recover basic errors such as 'tab'=='. The method put NaN in the grid if an unrecoverable error appends. Data will be store in private variables.

Returns

true if all seems OK

2.1.3.16 `select()`

```
template<typename _T = double>
const std::vector< std::vector<_T> > & _csv<_T>::select (
    int iLine_min,
    int iLine_max,
    int iCol_min,
    int iCol_max ) const
```

Select a sub grid in data, i.e. trim data to the rectangular $[i_{min}, i_{max}] \times [j_{min}, j_{max}]$.

Parameters

<i>iLine_min</i>	upper line i_{min}
<i>iLine_max</i>	lower line i_{max}
<i>iCol_min</i>	left column j_{min}
<i>iCol_max</i>	right column j_{max}

Returns

`std::vector<std::vector<_T> >`

2.1.3.17 select_column()

```
template<typename _T = double>
const std::vector< _T > & _csv< _T >::select_column (
    int iCol ) const
```

Select the column "col" in data.

Parameters

<i>iCol</i>	The column to select
-------------	----------------------

Returns

`std::vector<_T>`

2.1.3.18 select_line()

```
template<typename _T = double>
const std::vector< _T > & _csv< _T >::select_line (
    int iLine ) const
```

Select the line "line" in data.

Parameters

<i>iLine</i>	The line to select
--------------	--------------------

Returns

`std::vector<_T>`

2.1.3.19 set_column()

```
template<typename _T = double>
bool _csv< _T >::set_column (
    const std::vector< _T > & vRow,
    int iRow )
```

Set a column with a vector.

Set a row with a vector.

Parameters

<i>vCol</i>	std::vector<_T> vCol
<i>iCol</i>	Select a column

Returns

true if all seems OK

Parameters

<i>vRow</i>	std::vector<_T> vRow
<i>iRow</i>	Select a row

Returns

true if all seems OK

2.1.3.20 set_data()

```
template<typename _T = double>
void _csv< _T >::set_data (
    const std::vector< std::vector< _T > > & vvData )
```

Set data with a vector of a vector.

Parameters

<i>vvData</i>	std::vector<std::vector<_T> > grid
---------------	------------------------------------

Returns

true if all seems OK

2.1.3.21 set_filename()

```
template<typename _T = double>
bool _csv< _T >::set_filename (
    const std::string & sFilename )
```

Set the filename for output or input. The fstream do not care about extension...

Parameters

<i>sFilename</i>	The filename with extension or not.
------------------	-------------------------------------

Returns

true if all seems OK

2.1.3.22 `set_filename_out()`

```
template<typename _T = double>
bool _csv<_T>::set_filename_out (
    const std::string & sFilename )
```

Set the filename for output. The fstream do not care about extension...


Parameters

<i>sFilename</i>	The filename with extension or not.
------------------	-------------------------------------

Returns

true if all seems OK

Here is the caller graph for this function:

2.1.3.23 `set_header()`

```
template<typename _T = double>
bool _csv<_T>::set_header (
    const std::vector< std::string > & vsHeader )
```

Set the header: the first line containing column name.

Parameters

<i>vsHeader</i>	string vector
-----------------	---------------

Returns

true if all seems OK

2.1.3.24 set_separator() [1/2]

```
template<typename _T = double>
bool _csv< _T >::set_separator (
    const char & cSep )
```

Set the csv separator. Usually: '\t', ',', ';;', ';' ...


Parameters

<i>cSep</i>	The sep character: '\t' for tabulation
-------------	--

Returns

true if all seems OK

Here is the caller graph for this function:

**2.1.3.25 set_separator()** [2/2]

```
template<typename _T = double>
bool _csv< _T >::set_separator (
    const std::string & sSep )
```

Set the csv separator. Usually: '\t', ',', ';;', ';' ...

Todo

Parameters

<code>sSep</code>	The sep character: '\t' for tabulation
-------------------	--

Returns

true if all seems OK

2.1.3.26 `set_verbose()`


```
template<typename _T = double>
bool _csv<_T>::set_verbose (
    eVerbose evV )
```

Set the verbose mode for debug. It does not deactivate error raising.

Parameters

<code>evV</code>	<code>eVerbose::DEBUG</code> for verbose mode and <code>eVerbose::QUIET</code> to keep quiet
------------------	--

Here is the caller graph for this function:

2.1.3.27 `show()` [1/2]

```
template<typename _T = double>
void _csv<_T>::show ( ) const
```

Show whole data, i.e. the header and data with no restriction on length or terminal size. It uses `boost::format` in order to correct spacing of number and strings.

Returns

true if all seems OK

2.1.3.28 show() [2/2]

```
template<typename _T = double>
bool _csv< _T >::show (
    int iLine_stop ) const
```

Show the header and data until "line_stop" line. Print all columns with terminal end-of-line. It uses boost::format in order to correct spacing of number and strings.

Parameters

<i>iLine_stop</i>	The number of lines where stop the display
-------------------	--

Returns

true if all seems OK

2.1.3.29 transform_lin()

```
template<typename _T = double>
bool _csv< _T >::transform_lin (
    _T TA,
    _T TB,
    int iCol )
```

Do $Y=aX+b$ to the iCol-column.

Returns

true if all seems OK

2.1.3.30 write()

```
template<typename _T = double>
bool _csv< _T >::write ( )
```

Write on disk what data are store.

Returns

true if all seems OK

Here is the caller graph for this function:



The documentation for this class was generated from the following file:

- [csv.h](#)

2.2 `_io<_T>` Class Template Reference

the purpose of this class is only to provide methods to read ascii or FITS spectrum, and to convert vector to valarray.

```
#include <waverage.hpp>
```

Classes

- struct [vec](#)
Define a (x,y) vector (seems better than std::pair)

Public Member Functions

- bool [read](#) (std::string sFilename)
- bool [read_dir](#) (std::string sExtension)
- bool [read_fits](#) (std::string sFilename)
- bool [read_fits_dir](#) (std::string sExtension)
- bool [write](#) (std::string sFilename)
- void [set_fileIn](#) (std::string sFilename)
- void [set_fileOut](#) (std::string sFilename)
- const std::vector< [vec](#) > [get_vector](#) () const
- const std::vector< std::vector< [vec](#) > > [get_vectors](#) () const
- const std::valarray< std::valarray<_T> > [get_valarray](#) ()
- const std::vector< std::valarray< std::valarray<_T> > > [get_valarrays](#) ()

2.2.1 Detailed Description

```
template<typename _T = double>
class _io<_T>
```

the purpose of this class is only to provide methods to read ascii or FITS spectrum, and to convert vector to valarray.

Todo bool `write(std::string sFilename)`

2.2.2 Member Function Documentation

2.2.2.1 `get_valarray()`

```
template<typename _T = double>
const std::valarray<std::valarray<_T>> > _io<_T>::get_valarray ( )
```

convert vector to an valarray

2.2.2.2 `get_vector()`

```
template<typename _T = double>
const std::vector<vec> _io<_T>::get_vector ( ) const
```

get spectrum

2.2.2.3 `get_vectors()`

```
template<typename _T = double>
const std::vector<std::vector<vec>> > _io<_T>::get_vectors ( ) const
```

get spectra

2.2.2.4 `read()`

```
template<typename _T = double>
bool _io<_T>::read (
    std::string sFilename )
```

read one file

2.2.2.5 `read_dir()`

```
template<typename _T = double>
bool _io<_T>::read_dir (
    std::string sExtension )
```

read the whole directory, only need the extension of files

2.2.2.6 `read_fits()`

```
template<typename _T = double>
bool _io< _T >::read_fits (
    std::string sFilename )
```

convert fits to vectors

2.2.2.7 `set_fileIn()`

```
template<typename _T = double>
void _io< _T >::set_fileIn (
    std::string sFilename )
```

set the input file name

2.2.2.8 `set_fileOut()`

```
template<typename _T = double>
void _io< _T >::set_fileOut (
    std::string sFilename )
```

set the output name

2.2.2.9 `write()`

```
template<typename _T = double>
bool _io< _T >::write (
    std::string sFilename )
```

write the results

The documentation for this class was generated from the following file:

- `waverage.hpp`

2.3 `_log` Class Reference

Public Member Functions

- `_log` (char **argv, const std::string &sFilename)
Initialize with the first argument of the command line, and the log name.
- const std::string **get_execname** () const
- const std::string **get_logname** () const
- const std::string **get_historyname** () const
- bool **set_execname** (char **argv)
- bool **set_logname** (const std::string &sFilename)
- bool **set_historyname** (const std::string &sFilename)
- bool **write** (const std::string &sS)

Write a string in the log file.

- bool **write** (const std::stringstream &ssS)
- bool **write_history** (const boost::program_options::variables_map &vm)

Write history file with information from boost::program_options.

- bool **remove_duplicate** ()

Remove duplicates in history file.

The documentation for this class was generated from the following files:


- [log.h](#)
- [log.cpp](#)

2.4 `_marker<_T>` Class Template Reference

A class to plot spectra with line markers using py matplotlib.

```
#include <marker.h>
```

Collaboration diagram for `_marker<_T>`:



Classes

- struct [Line](#)
Define a line.

Public Types

- typedef std::vector< [Line](#) > **vList**

Public Member Functions

- void **set_verbose** (const bool bVerbose)
- bool **set_data** (const std::vector<_T> &vTX, const std::vector<_T> &vTY)
- bool **set_title** (const std::string &sTitle)
- bool **set_label** (const std::string &sLabel)
- bool **set_xlabel** (const std::string &sXlabel)
- bool **set_ylabel** (const std::string &sYlabel)
- bool **set_xunit** (const std::string &sXunit)
- bool **set_yunit** (const std::string &sYunit)
- bool **set_output** (const std::string &sFilename)
- bool **set_output** (const std::string &sFilename, const int iDpi)
 - Set the picture filename with the extension (png, pdf, jpeg...) and the density (iDpi>50)*
- bool **set_continuum** (const _T TContinuum)
 - Set the continuum position and therefore ymax. Default is y=1.*
- bool **set_supp** (const _T TXmin, const _T TXmax)
 - Set the support of the first spectrum.*
- bool **set_xmin** (const _T TXmin)
- bool **set_xmax** (const _T TXmax)
- bool **set_ymin** (const _T TYmin)
- bool **set_ymax** (const _T TYmax)
- bool **set_figsize** (int iHeight, int iWidth)
- void **set_colorline** (const std::string &sColor)
 - Set the color of the first curve.*
- bool **set_linewidth** (float fWidth)
- bool **set_titlesize** (int iSize)
- bool **set_labelsize** (int iSize)
- bool **set_ticklabelsiz** (int iSize)
- bool **set_annotatesize** (int iSize)
 - Set the font size of markers.*
- bool **set_legendsize** (int iSize)
- void **set_legend** (bool bLegend)
 - Enable or disable the legend.*
- void **set_halfbox** (bool bHalfbox)
 - Show only left and bottom axis.*
- bool **set_continnumsize** (float fWidth)
- void **set_showgrid** (bool bShowgrid)
- void **set_dotted** (bool bDotted)
 - Set secondary curves with dotted-style.*
- void **set_dotdashed** (bool bDotdashed)
 - Set secondary curves with dot-dashed-style.*
- void **set_wide** (bool bWide)
 - Define if the spectrum range is wide in order to reduce marker size with no overlaps.*
- bool **set_scriptname** (const std::string &sScriptname)
 - Set the name of the py script. Default is .plot.py.*
- bool **set_log** (const std::string &sLog)
 - Enable or disable log file. Default is .marker.log.*
- bool **add_line** (_T TWI, const std::string &sName)
 - Add a marker with a name on the figure.*

- bool [add_line](#) (_T TWI, const std::string &sName, bool bBold)
Add a marker with a name on the figure. bBold determines if the line must be highlighted.
- bool [add_data](#) (const std::vector< _T > &vTX, const std::vector< _T > &vTY)
Add an additionnal spectrum which has to be plot.
- bool [add_data](#) (const std::vector< _T > &vTX, const std::vector< _T > &vTY, const std::string &sLabel)
Add an additionnal spectrum which has to be plot.
- _T [get_continuum](#) () const
- const std::pair< _T, _T > [get_supp](#) ()
Get the support of the first spectrum.
- const std::string & [get_scriptname](#) ()
- const std::string & [get_output](#) ()
- const std::string & [get_title](#) () const
- const std::string & [get_label](#) () const
- const std::string & [get_xlabel](#) () const
- const std::string & [get_xunit](#) () const
- const std::string & [get_ylabel](#) () const
- const std::string & [get_yunit](#) () const
- const std::pair< int, int > [get_figsize](#) () const
Get the defined figsize, if defined. First: Height and Second: Width.
- int [get_dpi](#) () const
- bool [make](#) ()
Write spectra, write script with markers.
- int [plot](#) ()
Run the py script?

Static Public Member Functions

- static bool [sort_elemlist](#) (const std::string &sElemlist)
Sort the elemlist.

Protected Attributes

- [_msg msgM](#)

2.4.1 Detailed Description

```
template<typename _T = float>
class _marker< _T >
```

A class to plot spectra with line markers using py matplotlib.

Todo [marker](#)(const _marker<_T>&)

2.4.2 Member Function Documentation

2.4.2.1 `get_figsize()`

```
template<typename _T = float>
const std::pair< int, int > _marker< _T >::get_figsize ( ) const
```

Get the defined figsize, if defined. First: Height and Second: Width.

Returns

`std::pair` of 2 int

2.4.2.2 `get_supp()`

```
template<typename _T = float>
const std::pair< _T, _T > _marker< _T >::get_supp ( )
```

Get the support of the first spectrum.

Returns

`std::pair` of 2 `_T`: $[x_{min} \ x_{max}]$

2.4.2.3 `set_colorline()`

```
template<typename _T = float>
void _marker< _T >::set_colorline (
    const std::string & sColor )
```

Set the color of the first curve.

Parameters

<code>sColor</code>	A string like "red", "green", "blue" or and a rgba hex string like "#rrggbbaa"
---------------------	--

2.4.2.4 `set_output()`

```
template<typename _T = float>
bool _marker< _T >::set_output (
```

```
const std::string & sFilename,
const int iDpi )
```

Set the picture filename with the extension (png, pdf, jpeg...) and the density (iDpi>50)

Parameters

<i>sFilename</i>	Picture name
<i>iDpi</i>	Density

2.4.2.5 set_supp()

```
template<typename _T = float>
bool _marker< _T >::set_supp (
    const _T TXmin,
    const _T TXmax )
```

Set the support of the first spectrum.

Parameters

<i>TXmin</i>	x_{min}
<i>TXmax</i>	x_{max}

2.4.3 Member Data Documentation

2.4.3.1 msgM

```
template<typename _T = float>
_msg _marker< _T >::msgM [protected]
```

Interface to print message to std output

The documentation for this class was generated from the following file:

- marker.h

2.5 _msg Class Reference

A class that sends string to std output and in a file...

```
#include <msg.h>
```

Public Types

- enum `eMsg` {
START, MID, END, ERROR,
THREADS }
enum for method in order to define whether the message is at the begin, at the end or an error,

Public Member Functions

- `_msg` (const `_msg` &other)
- bool `msg` (const std::string &sMsg)
Send a message with eMsg::MID as default.
- bool `msg` (`eMsg` emType, const std::string &sMsg)
Send a message...
- bool `error` (const std::string &sMsg)
Send an error message...
- template<typename ... Args>
bool `msg` (const Args &...args)
A variadic formatter method that indeed sends arbitratry number of variable to the std output... with eMsg::MID as default.
- template<typename ... Args>
bool `msg` (`eMsg` emType, const Args &...args)
A variadic formatter method that indeed sends arbitratry number of variable to the std output... The first parameter is always the enum eMsg.
- template<typename ... Args>
bool `error` (const Args &...args)
A variadic formatter method that indeed sends arbitratry number of variable to the std error output... with eMsg::ERROR as default.
- bool `set_name` (const std::string sName)
Set the name of the main instance.
- bool `set_threadname` (const std::string sName)
Set the name of threads.
- bool `set_log` (const std::string sLog)
Enable or disable log file.
- void `enable_log` (bool bLog)
Enable or disable the log file.

2.5.1 Detailed Description

A class that sends string to std output and in a file...

2.5.2 Member Function Documentation

2.5.2.1 `msg()`

```
bool _msg::msg (
    eMsg emType,
    const std::string & sMsg )
```

Send a message...

Parameters

<i>emType</i>	See enum eMsg::
---------------	--------------------

The documentation for this class was generated from the following files:


- [msg.h](#)
- [msg.cpp](#)

2.6 `_marker<_T>::Line` Struct Reference

Define a line.

```
#include <marker.h>
```

Collaboration diagram for `_marker<_T>::Line`:



Public Attributes

- `_T` **TWI**
- `std::string` **sElem**
- `bool` **bBold**

2.6.1 Detailed Description

```
template<typename _T = float>
struct _marker<_T>::Line
```

Define a line.

The documentation for this struct was generated from the following file:

- marker.h

2.7 `_io<_T>::vec` Struct Reference

Define a (x,y) vector (seems better than `std::pair`)

```
#include <waverage.hpp>
```

Public Attributes

- `_T x`
- `_T y`

2.7.1 Detailed Description

```
template<typename _T = double>
struct _io<_T>::vec
```

Define a (x,y) vector (seems better than `std::pair`)

The documentation for this struct was generated from the following file:

- waverage.hpp


3 File Documentation

3.1 csv.h File Reference


A basic class for csv manipulation.

```
#include <iostream>
#include <fstream>
#include <chrono>
#include <cmath>
#include <numeric>
#include <random>
#include <cstdint>
#include <vector>
#include <algorithm>
#include <functional>
#include <iterator>
#include <string>
#include <iomanip>
#include <regex>
#include <boost/spirit/include/qi_parse.hpp>
#include <boost/spirit/include/qi_numeric.hpp>
#include <boost/tokenizer.hpp>
#include "csv.hpp"
```

Include dependency graph for csv.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `_csv<_T>`

This is the templated `_csv` class, initialized with double by default. STL parallel execution policy does not provide enhancements for simple operations.

3.1.1 Detailed Description

A basic class for csv manipulation.

Author

Audric Lemonnier

Version

0.9

Date


07/04/2020

3.2 der_snr.cpp File Reference

An C++ implementation of the der_snr fortran code from: F. Stoehr et al: DER_SNR: A Simple & General Spectroscopic Signal-to-Noise Measurement Algorithm, 394, Astronomical Data Analysis Software and Systems (ADASS) XVII 2008ASPC..394..505S.

```
#include <iostream>
#include <cstdlib>
#include <cstdio>
#include <fstream>
#include <vector>
#include <algorithm>
#include <string>
#include <cmath>
#include <functional>
#include <thread>
#include <future>
#include <tuple>
#include <chrono>
#include <boost/program_options.hpp>
#include <csv.h>
#include <msg.h>
#include <log.h>
#include <der_snr.h>
```

Include dependency graph for der_snr.cpp:



Functions

- int **main** (int argc, char **argv)

3.2.1 Detailed Description

An C++ implementation of the der_snr fortran code from: F. Stoehr et al: DER_SNR: A Simple & General Spectroscopic Signal-to-Noise Measurement Algorithm, 394, Astronomical Data Analysis Software and Systems (ADASS) XVII 2008ASPC..394..505S.

Remove value under a threshold in a folder or in a file. This code is multi-threaded or not if not available.

Author

Audric Lemonnier

Version

0.2

Date


18/04/2020

3.3 elemlist.cpp File Reference

Add a line to the elemlist.

```
#include <iostream>
#include <cstdlib>
#include <cstdio>
#include <fstream>
#include <string>
#include <sstream>
#include <boost/program_options.hpp>
#include <boost/spirit/include/qi_parse.hpp>
#include <boost/spirit/include/qi_numeric.hpp>
#include <msg.h>
#include <log.h>
```

Include dependency graph for elemlist.cpp:



Macros

- #define LOGFILE ".elemlist.log"
- #define HISTFILE ".history"

Functions

- template<typename _T = std::string>
bool add_elem (const std::string &sElem, _T TWI, const std::string &sFilename)
Add a line to a file.
- template<typename _T = std::string>
bool add_elem (const std::string &sSymbol, const std::string &sElem, _T TWI, const std::string &sFilename)
Add a line to a file, with the indicator symbol.
- bool is_float (const std::string &sVal)
Determine if a string is a number.
- int main (int argc, char **argv)

3.3.1 Detailed Description

Add a line to the elemlist.

Author

Audric Lemonnier

Version

0.1

Date

30/03/2020

3.3.2 Macro Definition Documentation

3.3.2.1 HISTFILE

```
#define HISTFILE ".history"
```

Define the default histfile (shared)

3.3.2.2 LOGFILE

```
#define LOGFILE ".elemlist.log"
```


Define the default logfile

3.4 findncopy.cpp File Reference

Copy files from a list in a new folder.

```
#include <iostream>
#include <cstdlib>
#include <cstdio>
#include <fstream>
#include <vector>
#include <string>
#include <algorithm>
#include <functional>
#include <boost/program_options.hpp>
#include <msg.h>
#include <log.h>
#include <findncopy.h>
```

Include dependency graph for findncopy.cpp:



Macros

- `#define LOGFILE ".findncopy.log"`
- `#define HISTFILE ".history"`

Functions

- `int main (int argc, char **argv)`

3.4.1 Detailed Description

Copy files from a list in a new folder.

Author

Audric Lemonnier

Version

0.1

Date

09/03/2020

3.4.2 Macro Definition Documentation

3.4.2.1 HISTFILE

```
#define HISTFILE ".history"
```

Define the default histfile (shared)

3.4.2.2 LOGFILE

```
#define LOGFILE ".findncopy.log"
```

Define the default logfile

3.5 genrandspec.cpp File Reference

Generate a set of randomized-flux spectra between two wavelengths for test purposes.

```
#include <iostream>
#include <cstdlib>
#include <cstdio>
#include <fstream>
#include <vector>
#include <algorithm>
#include <numeric>
#include <string>
#include <cmath>
#include <random>
#include <thread>
```

```

#include <future>
#include <ctime>
#include <tuple>
#include <chrono>
#include <boost/program_options.hpp>
#include <csv.h>
#include <msg.h>
#include <log.h>

```

Include dependency graph for genrandspec.cpp:



Macros

- #define LOGFILE ".genrandspec.log"
- #define HISTFILE ".history"
- #define MaxFileDir 10

Set the maximum number of files to create in a folder.

Functions

- void run (const std::string &sOutput, char cSep, float fMinw, float fMaxw, float fStep)
Write random spectra on disk.
- double long CPU_utilization ()
- std::tuple< double long, double long > get_stat ()
- int main (int argc, char **argv)

3.5.1 Detailed Description

Generate a set of randomized-flux spectra between two wavelengths for test purposes.

Author

Audric Lemonnier

Version

0.4

Date

18/04/2020

3.5.2 Macro Definition Documentation

3.5.2.1 HISTFILE

```
#define HISTFILE ".history"
```

Define the default histfile (shared)

3.5.2.2 LOGFILE

```
#define LOGFILE ".genrandspec.log"
```

Define the default logfile

3.5.2.3 MaxFilepDir

```
#define MaxFilepDir 10
```

Set the maximum number of files to create in a folder.


MaxFilepDir

3.6 log.h File Reference

A class to write log file.

```
#include <iostream>
#include <fstream>
#include <string>
#include <sstream>
#include <ctime>
#include <algorithm>
#include <mutex>
#include <boost/program_options.hpp>
```

Include dependency graph for log.h:




```
#include <boost/program_options.hpp>
#include <boost/spirit/include/qi_parse.hpp>
#include <boost/spirit/include/qi_numeric.hpp>
#include <marker.h>
#include <msg.h>
#include <log.h>
#include <csv.h>
```

Include dependency graph for marker.cpp:



Macros

- #define LOGFILE ".marker.log"
- #define HISTFILE ".history"

Functions

- `int main (int argc, char **argv)`

3.7.1 Detailed Description

Highlight lines on spectrum.

Author

Audric Lemonnier

Version

0.6

Date _____

29/04/2020

3.7.2 Macro Definition Documentation

3.7.2.1 HISTFILE

```
#define HISTFILE ".history"
```

Define the default histfile (shared)

3.7.2.2 LOGFILE

```
#define LOGFILE ".marker.log"
```


Define the default logfile

3.8 msg.h File Reference


A class to print and write message.

```
#include <iostream>
#include <fstream>
#include <string>
#include <sstream>
#include <ctime>
#include <algorithm>
#include <mutex>
#include <log.h>
```

Include dependency graph for msg.h:



This graph shows which files directly or indirectly include this file:



Macros

- `#define CLIGHT 299792.458`
- `#define LOGFILE ".shift.log"`
- `#define HISTFILE ".history"`

Functions

- `int main (int argc, char **argv)`

3.9.1 Detailed Description

Shift whole spectrum by a given wavelength. This code is multi-threaded or not if not available.

Author

Audric Lemonnier

Version

0.3

Date

18/04/2020

3.9.2 Macro Definition Documentation

3.9.2.1 HISTFILE

```
#define HISTFILE ".history"
```

Define the default histfile (shared)

3.9.2.2 LOGFILE

```
#define LOGFILE ".shift.log"
```


Define the default logfile

3.10 waverage.cpp File Reference

Compute average of spectra from FITS weighted by the SNR or the exposition time.

```
#include <iostream>
#include <fstream>
#include <cmath>
#include <string>
#include <sstream>
#include <iomanip>
#include <algorithm>
#include <vector>
#include <valarray>
#include <tuple>
#include <waverage.hpp>
```

Include dependency graph for waverage.cpp:



Functions

- `int main (int argc, char **argv)`

3.10.1 Detailed Description

Compute average of spectra from FITS weighted by the SNR or the exposition time.

Author

Audric Lemonnier

Version

0.0

Date _____

16/07/2020

Index

- `_csv`
 - `_csv`, [5](#), [6](#)
 - `apply_max_threshold`, [6](#), [7](#)
 - `apply_min_threshold`, [7](#), [8](#)
 - `check_dim`, [8](#)
 - `empty`, [8](#)
 - `get_data`, [9](#)
 - `get_data_size_i`, [9](#)
 - `get_data_size_j`, [9](#)
 - `get_filename`, [9](#)
 - `get_filename_out`, [10](#)
 - `get_header`, [10](#)
 - `get_header_size`, [10](#)
 - `get_separator`, [10](#)
 - `read`, [11](#)
 - `select`, [11](#)
 - `select_column`, [12](#)
 - `select_line`, [12](#)
 - `set_column`, [12](#)
 - `set_data`, [14](#)
 - `set_filename`, [14](#)
 - `set_filename_out`, [15](#)
 - `set_header`, [15](#)
 - `set_separator`, [16](#)
 - `set_verbose`, [17](#)
 - `show`, [17](#)
 - `transform_lin`, [18](#)
 - `write`, [18](#)
- `_csv<_T>`, [2](#)
- `_io`
 - `get_valarray`, [20](#)
 - `get_vector`, [20](#)
 - `get_vectors`, [20](#)
 - `read`, [20](#)
 - `read_dir`, [20](#)
 - `read_fits`, [20](#)
 - `set_fileIn`, [21](#)
 - `set_fileOut`, [21](#)
 - `write`, [21](#)
- `_io<_T>`, [19](#)
- `_io<_T>::vec`, [29](#)
- `_log`, [21](#)
- `_marker`
 - `get_figsize`, [25](#)
 - `get_supp`, [25](#)
 - `msgM`, [26](#)
 - `set_colorline`, [25](#)
 - `set_output`, [25](#)
 - `set_supp`, [26](#)
- `_marker<_T>`, [22](#)
- `_marker<_T>::Line`, [28](#)
- `_msg`, [26](#)
 - `msg`, [27](#)
- `apply_max_threshold`
 - `_csv`, [6](#), [7](#)
- `apply_min_threshold`
 - `_csv`, [7](#), [8](#)
- `check_dim`
 - `_csv`, [8](#)
- `csv.h`, [30](#)
- `der_snr.cpp`, [31](#)
- `elemlist.cpp`, [32](#)
 - `HISTFILE`, [33](#)
 - `LOGFILE`, [33](#)
- `empty`
 - `_csv`, [8](#)
- `findncopy.cpp`, [34](#)
 - `HISTFILE`, [35](#)
 - `LOGFILE`, [35](#)
- `genrandspec.cpp`, [35](#)
 - `HISTFILE`, [37](#)
 - `LOGFILE`, [37](#)
 - `MaxFilepDir`, [37](#)
- `get_data`
 - `_csv`, [9](#)
- `get_data_size_i`
 - `_csv`, [9](#)
- `get_data_size_j`
 - `_csv`, [9](#)
- `get_figsize`
 - `_marker`, [25](#)
- `get_filename`
 - `_csv`, [9](#)
- `get_filename_out`
 - `_csv`, [10](#)
- `get_header`
 - `_csv`, [10](#)
- `get_header_size`
 - `_csv`, [10](#)
- `get_separator`
 - `_csv`, [10](#)
- `get_supp`
 - `_marker`, [25](#)
- `get_valarray`
 - `_io`, [20](#)
- `get_vector`
 - `_io`, [20](#)

get_vectors
 _io, 20

HISTFILE
 elemlist.cpp, 33
 findncopy.cpp, 35
 genrandspec.cpp, 37
 marker.cpp, 39
 shift.cpp, 42

LOGFILE
 elemlist.cpp, 33
 findncopy.cpp, 35
 genrandspec.cpp, 37
 marker.cpp, 40
 shift.cpp, 42

log.h, 37

marker.cpp, 38
 HISTFILE, 39
 LOGFILE, 40

MaxFileDir
 genrandspec.cpp, 37

msg
 _msg, 27

msg.h, 40

msgM
 _marker, 26

read
 _csv, 11
 _io, 20

read_dir
 _io, 20

read_fits
 _io, 20

select
 _csv, 11

select_column
 _csv, 12

select_line
 _csv, 12

set_colorline
 _marker, 25

set_column
 _csv, 12

set_data
 _csv, 14

set_fileIn
 _io, 21

set_fileOut
 _io, 21

set_filename
 _csv, 14

set_filename_out
 _csv, 15

set_header
 _csv, 15

set_output
 _marker, 25

set_separator
 _csv, 16

set_supp
 _marker, 26

set_verbose
 _csv, 17

shift.cpp, 41
 HISTFILE, 42
 LOGFILE, 42

show
 _csv, 17

transform_lin
 _csv, 18

waverage.cpp, 43

write
 _csv, 18
 _io, 21