

```

1  # implementation_from_scratch.py
2  # Main file for the implementation of the C4.5 algorithm
3  import pandas as pd
4  import numpy as np
5  import graphviz
6  from graphviz import Digraph
7  from math import log2
8  from copy import deepcopy
9  from weka_implementation import build_weka_tree
10 import PySimpleGUI as sg
11 from PIL import Image, ImageTk, ImageSequence
12 from multiprocessing import Process, Queue
13 import multiprocessing as mp
14 import time
15 import os.path
16 from os import path
17 import PIL.Image
18 import io
19 import base64
20 import math
21
22
23 # Louise and Aideen
24 def main():
25
26     # Get the data, the train/test split percentage and the filepath of the data location
27     data, split = gather_data()
28
29     # While animate a 'loading' gif to show that the process is running,
30     # Build a C4.5 tree from the data.
31     # Return the root node of the tree, the dataset to use in testing and the time it
32     # took to build the tree
33     root_node, testing_data, python_time_to_build =
34     createTreeWhileShowingLoadingWindow(data, split)
35
36     # Draw the tree and store it in png format
37     print_tree(root_node)
38
39     # Calculate the accuracy of the built tree using the testing data
40     python_accuracy = test_tree(root_node, testing_data, split)
41
42     # Build a tree using the same data in weka.
43     # Draw the weka tree and store it in png format
44     # Get the accuracy of the weka tree, and the time it took to construct
45     weka_accuracy, weka_time_to_build = build_weka_tree(split)
46
47     # Scale and format the times it took to run each implementation
48     python_time = processTimes(python_time_to_build)
49     weka_time = processTimes(weka_time_to_build)
50
51     # Display both trees side to side, with their accuracies, and the time it took to
52     # build them
53     DisplayTreesPopup(python_accuracy, weka_accuracy, python_time, weka_time)
54
55 # Aideen McLoughlin - 17346123
56 # Take in the time it took to run a process in seconds
57 # and return a nicely scaled representation of that value
58 def processTimes(time):
59     if time < 1:
60         scaledtime = round(time * 1000)
61         timemsg = str(scaledtime) + " milliseconds"
62     elif time <= 60:
63         timemsg = str(round(time)) + " seconds"
64     else:
65         minutes = math.floor(time/60)
66         seconds = round(time - minutes*60)

```

```

65         timemsg = str(minutes) + " minutes and "+str(seconds)+" seconds"
66     return "The tree took " + timemsg + " to build"
67
68
69 # Aideen McLoughlin - 17346123
70 # Using python multiprocessing, build a tree while showing a 'loading' animation
71 def createTreeWhileShowingLoadingWindow(data, split):
72
73     # Create an 'Event' to indicate when the tree is built
74     quit = mp.Event()
75     # Create a 'Queue' to store generated values in
76     Q = Queue()
77
78     # Define both processes in the multiprocessing - the tree creation and the loading
    animation
79     p1 = Process(target = createTree, args=(data, split, quit, Q,))
80     p2 = Process(target = renderLoadingWindow, args=(quit, ))
81
82     # Store the time before starting to build the tree
83     starttime = time.time()
84
85     # Start both processes
86     p1.start()
87     p2.start()
88
89     # Wait for the quit event to be set, which will happen once the tree is built
90     quit.wait()
91
92     # Store the time once the tree has been built
93     endtime = time.time()
94
95     # Get the data stored in the Queue
96     queue_data = Q.get()
97
98     # Return the Queue data and the time to build
99     return queue_data[0], queue_data[1], endtime-starttime
100
101
102 # louise Kilheeney -16100463
103 def createTree(data, data_split, quit, queue):
104
105     #call function to split the data into training and test data.
106     train_data, test_data = split_data_training_testing(data, (data_split))
107
108     #list of attributes in the data
109     attributes =
    ['calorific_value','nitrogen','turbidity','style','alcohol','sugars','bitterness','co
    lour','degree_of_fermentation']
110
111     #calling function to build tree with the traning data and list of attributes
112     root_node = build_tree(train_data, attributes)
113
114     queue.put([root_node, test_data])
115     queue.cancel_join_thread()
116     quit.set()
117     return True
118
119
120 # Aideen McLoughlin - 17346123
121 def renderLoadingWindow(quit):
122     # Declare the PySimpleGUI layout for the popup window
123     layout_loading = [[sg.Text("Loading")],[sg.Image(r'loading.gif', key='-IMAGE-')]]
124
125     # Create the popup window
126     window = sg.Window("Building C4.5 Tree", layout_loading, element_justification='c',
    margins=(0,0), element_padding=(0,0), finalize=True)
127

```

```

128 # Animate the loading gif for the duration of time that 'quit' is not set
129 interframe_duration = Image.open(r'loading.gif').info['duration']
130 while not quit.is_set():
131     event, values = window.read(timeout=interframe_duration)
132     if event == sg.WIN_CLOSED:
133         exit()
134         break
135
136     window.FindElement("-IMAGE-").UpdateAnimation("loading.gif",time_between_frames=i
137         nterframe_duration)
138
139 # Close the popup window
140 window.close()
141 return True
142
143 # Aideen McLoughlin - 17346123
144 def getInputData():
145     # Declare the PySimpleGUI layout for the popup window
146     layout = [
147         [sg.Text('Data file: '), sg.InputText("beer.csv", key="file")],
148         [sg.Text("Select Train/Test Data Split")],
149         [sg.Radio('1/3',"1", key="1/3"),
150          sg.Radio('1/2',"1", key="1/2"),
151          sg.Radio('2/3',"1", key="2/3", default=True)],
152         [sg.Button('Ok'), sg.Button('Quit')]]
153
154 # Create the popup window
155 window = sg.Window("Select Train/Test Split", layout)
156
157 # Loop until the window is closed with 'x' 'OK' or 'Quit'
158 # Set split to be the selected train/test split value
159 # And set the filepath to be the contents of the InputText box (default beer.csv)
160 while True:
161     event, values = window.read()
162     if event == sg.WIN_CLOSED or event == 'Quit':
163         break
164     if event == 'Ok':
165         if values["1/3"] == True:
166             split = (1/3)
167         elif values["1/2"] == True:
168             split = (1/2)
169         elif values["2/3"] == True:
170             split = (2/3)
171         break
172     filepath = values["file"]
173
174 # Close the popup window
175 window.close()
176 return split, filepath
177
178 # Aideen McLoughlin - 17346123
179 def errorWindow(text):
180     # Declare the PySimpleGUI layout for the popup window
181     layout = [[sg.Text(text)],[sg.Button('Ok')]]
182
183 # Create the popup window
184 window = sg.Window("Error", layout)
185
186 # Display a popup window with the text passed as a function param, until the user
187 # closes the window
188 while True:
189     event, values = window.read()
190     if event == sg.WIN_CLOSED or event == 'Ok':
191         break

```

```

192
193     # Close the popup window
194     window.close()
195
196
197 # Aideen McLoughlin - 17346123
198 # Resize the tree png images to be equal and fit nicely into the popup window
199 def resize_images():
200     for image in (r'weka-test.gv.png', r'test.gv.png'):
201         img = PIL.Image.open(image)
202         img = img.resize((400, 400), PIL.Image.ANTIALIAS)
203         img.save(image, format="PNG")
204
205
206 # Aideen McLoughlin - 17346123
207 def DisplayTreesPopup(python_accuracy, weka_accuracy, p_time, w_time):
208
209     # Resize the tree images to be the right size for the popup
210     resize_images()
211
212     # Define 2 columns for the layout
213     # The right one for the custome python implementation from scratch
214     # The left one for the implementation with weka
215     weka_column = [
216         [sg.Text("Weka Implementation",font=('Helvetica 20'))],
217         [sg.Image(r'weka-test.gv.png',key='-IMAGE-')],
218         [sg.Text("Accuracy: "+str(weka_accuracy)+"%")],
219         [sg.Text(w_time)]
220     ]
221     python_column = [
222         [sg.Text("Our Python Implementation",font=('Helvetica 20'))],
223         [sg.Image(r'test.gv.png',key='-IMAGE-')],
224         [sg.Text("Accuracy: "+str(python_accuracy*100)+"%")],
225         [sg.Text(p_time)]
226     ]
227
228     # Declare the PySimpleGUI layout for the popup window with the two columns, and a
229     # QUIT button
230     layout = [
231         [
232             sg.Column(weka_column),
233             sg.Column(python_column)
234         ],
235         [sg.Button('Quit')],
236     ]
237
238     # Create the popup window
239     window = sg.Window("Generated C4.5 Tree", layout)
240
241     # Display the popup window until the user closes it
242     while True:
243         event, values = window.read()
244         if event == sg.WIN_CLOSED or event == 'Quit': # if user closes window or clicks
245             # cancel
246             break
247
248     # Close the popup window
249     window.close()
250
251 # louise Kilheeneey - 16100463
252 def build_tree(data, attributes):
253     #1. check the base cases
254     #• All the examples from the training set belong to the same class ( a tree
255     #   leaf labeled with that class is returned ).
256     if data['style'].nunique() == 1:
257         return Node(True, data['style'][0], None)

```

```

256     #• The training set is empty ( returns a tree leaf called failure ).
257     if len(data) == 0:
258         return Node(True, "Fail", None)
259
260     #2. find attribute with highest info gain, retrun best_attribute
261     # calling function find-best-attribute which retruns the best attribute, the
        attribute subsets and the threshold divisor
262     best_attribute, attribute_subsets, threshold_divisor = find_best_attribute(data,
        attributes)
263
264     #if best attribute is empty
265     if best_attribute == "":
266         #calling function get majorityclass to return the majority class
267         majClass = getMajorityClass(data)
268         return Node(True, majClass, None)
269     else:
270         #3. split the set (data) in subsets arrcording to value of best_attribute
271         #attribute_subsets = split_into_subsets(best_attribute, data)
272         remainColumns = deepcopy(data)
273         remainColumns = data.drop(columns=[best_attribute])
274
275         #4. repeat steps for each subset
276         node = Node(False, best_attribute, threshold_divisor)
277         for attr_subset in attribute_subsets:
278             node.children.append(build_tree(attr_subset, remainColumns))
279
280         return node
281
282
283
284 # Louise Kilheeney - 16100463
285 # Generate a png of the tree from the root node
286 def print_tree(root_node):
287
288     # Create a diagraph in which to store the tree data
289     g = Digraph('python_tree_implementation')
290
291     # Add the root node, and all its children recursively
292     addEl(root_node, g, 'a')
293
294     # Format the graph as a png, and save it
295     g.format = "png"
296     g.render('test.gv', view=False)
297
298 # Louise Kilheeney - 16100463
299 # Add a node to the tree
300 def addEl(node, g, rootname):
301
302     # If the node is not a leaf
303     if not node.isLeaf:
304         #Create the node
305         g.node(name=str(rootname), label=node.label)
306
307         # Create an edge from the node to its left child
308         nodename1 = rootname+'b'
309         g.edge(rootname, nodename1, label="<= "+str(round(node.divisor,2)))
310         # Recursively add the nodes left child
311         addEl(node.children[0],g,nodename1)
312
313         # Create an edge from the node to its right child
314         nodenamec = rootname + 'c'
315         g.edge(rootname, nodenamec, label="> "+str(round(node.divisor,2)))
316         # Recursively add the nodes right child
317         addEl(node.children[1],g,nodenamec)
318     else:
319         # If the node is a leaf, add it while styling it as a leaf
320         g.node(name=rootname, label=node.label, shape='box', style='filled')

```

```

321
322 # Louise Kilheeneey - 16100463
323 def find_best_attribute(train_data, attributes):
324     # Returns the best attribute from all
325     best_information_gain = 0
326     best_attribute = ""
327     threshold_divisor = ""
328     subsets = []
329     for attribute in attributes:
330         #making sure not to include style
331         if attribute != 'style':
332
333             #calling function split_into_subsets
334             temp_subsets, temp_divisor = split_into_subsets(attribute, train_data)
335
336             # temp gain is equal to the information gain function for the train_data
337             # and the subsets.
338             temp_gain = information_gain(train_data, temp_subsets)
339
340             #check for the best attribute
341             if temp_gain > best_information_gain:
342                 best_attribute = attribute
343                 best_information_gain = temp_gain
344                 subsets = temp_subsets
345                 threshold_divisor = temp_divisor
346             # return the best attribute , subsets and the threshold divisor
347             return best_attribute, subsets, threshold_divisor
348
349 # Louise Kilheeneey - 16100463
350 # Function to get the majority class of the data been passed in.
351 def getMajorityClass(data):
352     #find the majority class in the data with the data - style
353     grouped = data.groupby(data['style'])
354     #return majority class
355     return max(grouped.groups)
356
357
358 # Louise Kilheeneey - 16100463
359 def split_into_subsets(column_header, training_data):
360     split_values = []
361     maxEnt = -1*float("inf")
362     best_threshold = ""
363     sorted_data = training_data.sort_values(by=[column_header])
364     for item in range(0, len(training_data) - 1):
365         if type(sorted_data.iloc[item][column_header]) != 'style':
366             if sorted_data.iloc[item][column_header] !=
367                 sorted_data.iloc[item+1][column_header]:
368                 threshold = (sorted_data.iloc[item][column_header] +
369                             sorted_data.iloc[item+1][column_header]) / 2
370                 smaller_than_threshold = pd.DataFrame()
371                 bigger_than_threshold = pd.DataFrame()
372                 for index, row in sorted_data.iterrows():
373                     if(row[column_header] > threshold):
374                         bigger_than_threshold = bigger_than_threshold.append(row,
375                                     ignore_index = True)
376                     else:
377                         smaller_than_threshold = smaller_than_threshold.append(row,
378                                     ignore_index = True)
379
380                 igain = information_gain(training_data, [smaller_than_threshold,
381                                     bigger_than_threshold])
382
383                 if igain >= maxEnt:
384                     split_values = [smaller_than_threshold, bigger_than_threshold]
385                     best_threshold = threshold
386                     maxEnt = igain

```

```

382     return split_values, best_threshold
383
384
385 # Aideen McLoughlin - 17346123
386 # Split the python DataFrame object into 3 DataFrame objects
387 # One storing all the values with the style 'ale'
388 # One storing all the values with the style 'lager'
389 # and One storing all the values with the style 'stout'
390 def split_data_styles(data):
391
392     # Declare empty subsets array
393     subsets = {}
394
395     # Group the data passed to the function by its style
396     grouped = data.groupby(data['style'])
397
398     # For each style name, add the values in that group to the subsets array as a new
399     # DataFrame object
400     for index, beer_style in enumerate(['ale', 'lager', 'stout']):
401         if beer_style in grouped.groups.keys():
402             subsets[index] = grouped.get_group(beer_style)
403         else:
404             subsets[index] = {}
405
406     # return the subsets array of DataFrame objects
407     return subsets
408
409 # Louise Kilheeney - 16100463
410 # Split the data into training and testing datasets
411 def split_data_training_testing(data, ratio):
412
413     # Drop the beer_id column as it is not relevant to the beer style
414     data = data.drop(columns=['beer_id'])
415
416     # Get a random sample from the data file as the training data
417     # This data will be ratio% of the initial dataset
418     train = data.sample(frac=ratio, random_state=5)
419
420     # Get the rest of the dataset values as the testing data
421     test = data.merge(train, how='left', indicator=True)
422     test = test[(test['_merge']=='left_only')].copy()
423     test = test.drop(columns='_merge').copy()
424
425     # Save the divided dataset so that it can be used in the weka implementation
426     train.to_csv('train_data_generated.csv', index=False, header=True)
427     test.to_csv('test_data_generated.csv', index=False, header=True)
428
429     # Create a folder to store the results in if it does not already exist
430     if not path.exists('results'):
431         print("Create results folder")
432         os.mkdir('results')
433
434     # Return the training and testing data
435     return train, test
436
437 from pandas.errors import EmptyDataError
438 # Louise Kilheeney - 16100463
439 # Get the filepath of the data file, and the train/test data split from user input in a
440 # PySimpleGUI popup
441 # If a filepath provided is not valid, prompt the user to input a new filepath.
442 # Repeat until a valid filepath is provided
443 def gather_data():
444
445     # Get the train/test split and the filepath of the data file
446     split, filepath = getInputData()

```

```

447     # Create an empty pandas dataframe element
448     data = pd.DataFrame()
449
450     # While the dataframe element remains empty
451     while data.empty:
452
453         # Check If the filepath is valid
454         if path.isfile(filepath):
455             # If it is, set the data to be the csv data at that filepath
456             data = pd.read_csv(filepath)
457         else:
458             # If it is not valid, Display an error pop-up and prompt the user to input
459             # the split and filepath again
460             errorWindow("File not found, please try again")
461             split, filepath = getInputData()
462
463     # Once the dataframe element is filled, return the data, the train/test split
464     # percentage and the filepath (For use in the weka implementation)
465     return data, split
466
467 # Aideen McLoughlin - 17346123
468 # Calculate the entropy of the passed data set
469 def entropy(dataset):
470
471     # Initialise entropy to zero value
472     entropy = 0
473
474     # Get the ale, lager and stout subset DataFrames from the passed dataset
475     subsets = split_data_styles(dataset)
476
477     # For each subset
478     for index in range(len(subsets)):
479
480         # Get the percentage of the dataset which is in the subset
481         probability = len(subsets[index]) / len(dataset)
482
483         # If the probability is not zero,
484         # Subtract  $\log_2(p)$  from the entropy value where p is probability
485         if probability != 0:
486             entropy = entropy - (probability) * log2(probability)
487
488     # Return the entropy value
489     return entropy
490
491 # Louise Kilheeney - 16100463
492 # function to calculate the information gain
493 def information_gain(train_target, subsets):
494     # getting the entropy value of the train_target
495     entropyTarget = entropy(train_target)
496     total = len(train_target)
497
498     Gain = entropyTarget
499
500     # for each subset
501     for i in range(0, len(subsets)):
502         # length of each subset
503         numBeer = len(subsets[i])
504         # Gain = Ent(S) - |S| beer = ale |S| * ( Ent( S beer = ale )) - |S| beer = stout
505         # |S| * ( Ent( S beer = stout )) - |S| beer = lager |S| * ( Ent( S beer = lager )) - ....
506         firstPart = numBeer / total
507         secondPart = entropy(subsets[i])
508         Gain -= (firstPart * secondPart)
509     # Return the information gain value
510     return Gain

```



```

511
512 # Aideen McLoughlin - 17346123
513 # Test the built tree using the testing data
514 def test_tree(root_node, testing_data, split):
515
516     # Get the style as the target values, and then drop them from the testing dataset
517     test_target = testing_data['style'].values
518     testing_data = testing_data.drop(columns=['style'])
519
520     # get the results of the tree predictions for all the testing data values
521     test_results = test_data(testing_data, root_node, [])
522
523     # Initialise the number of correct entries to 0
524     correct = 0
525
526     accurate = []
527     # For each test result, check if it is accurate using the style values we removed
528     # from the Dataframe earlier
529     # Keep a count of the number of correct predictions
530     # If the prediction is wrong, print the incorrect prediction
531     for index in range(0, len(test_results)):
532         if test_results[index] == test_target[index]:
533             correct = correct + 1
534             accurate.append(1)
535         else:
536             accurate.append(0)
537
538     # Calculate the accuracy to 2 decimal places, and return it
539     accuracy = round(correct/len(test_results), 2)
540
541     df = pd.DataFrame()
542     df['Actual'] = test_target
543     df['Predicted'] = test_results
544     df['Accuracy'] = accurate
545
546     filename =
547     "results/python-results-"+str(round(split, 2))+ "-" + str(round(accuracy, 2)) + ".csv"
548     df.to_csv(filename, index=False, header=True)
549
550     return accuracy
551
552 # Aideen McLoughlin - 17346123
553 # Using the root node of the constructed tree, predict the output of all the test data
554 # inputs
555 def test_data(data, node, test_results):
556
557     # For each data value, get the predicted result
558     for item in range(0, len(data)):
559         test_results.append(test_lr(node, data.iloc[item]))
560
561     # return the set of all predicted results
562     return test_results
563
564 # Aideen McLoughlin - 17346123
565 # Get the final leaf node destination for a data row
566 def test_lr(node, row):
567
568     # Decide which child path of a node to proceed into, based on the input value.
569     # This function will call itself recursively until it reaches a leaf node
570     # That leaf node will be returned to the function which called it
571     if node.isLeaf:
572         return node.label
573     else:
574         if row[node.label] <= node.divisor:
575             return test_lr(node.children[0], row)

```

```
575         else:
576             return test_lr(node.children[1], row)
577
578
579 # Louise Kilheeney - 16100463
580 # Node class
581 class Node:
582     def __init__(self, isLeaf, label, divisor):
583         self.label = label
584         self.isLeaf = isLeaf
585         self.divisor = divisor
586         self.children = []
587
588
589 # Louise Kilheeney - 16100463
590 # Set the main function to run when the file is run
591 if __name__ == '__main__':
592     main()
593
```