


[🏠](#) / [cookbook](#) / [app-multiccy](#) / [sequencediag-auth](#)


## multiccy AUTH sequence diagram


This is the sequence diagram of the http requests between your browser and the application [multiccy](#) .


The IAM is managed by the combo AWS ALB + AWS Cognito IdP + AWS Cognito hosted UI.

With this combination, your application does NOT have to:

- keep a users database;
  - implement sign in, sign up, password reset services and emailing;
  - use a session-management database like Redis/Dynamodb; should:
  - be using the http header 'X-Amzn-Oidc-Identity', which is the authenticated cognito user id, as a session userid
  - delete the AWSELBAuthSessionCookie in the logout callback URL call
-







by wrapping your application with AWS ALB + AWS Cognito + AWS Cognito hosted UI, the changes to apply to your application are:

- using `request.getHeader('X-Amzn-Oidc-Identity')` (= the authenticated cognito user id) as a session userid

- deleting the AWSELBAuthSessionCookie in the logout callback URL

ref: <https://docs.aws.amazon.com/elasticloadbalancing/latest/application/listener-authenticate-users.html> 

the numbers in the AWS doc workflow are referenced as (#1) above.

cookies:

- X-Amzn-Oidc-Identity = cognito user id
- X-Amzn-Oidc-Data = JWT with e.g. username inside
- AWSELBAuthSessionCookie-xxx = ALB session cookie
- JSESSIONID = application session - irrelevant.

---

back to [app-multiccy](#)