Naver Clova Sentiment API 연결

iOS

```ios
private func analyzeHaru() async {
    isFetching = true
    let url = "http://127.0.0.1:8000/analyzeEmotion?inputText=\(inputs)"
    guard let encodingUrl = url.addingPercentEncoding(withAllowedCharacters: .urlQueryAllowed),
          let url = URL(string: encodingUrl) else { return }
    print(url)
    do {
        let (data, _) = try await URLSession.shared.data(from: url)
        let returnValue = try JSONDecoder().decode(BackendTestStruct.self, from: data)
        sentiment = returnValue.sentiment
        confidence = returnValue.confidence
        print(sentiment, confidence)
        DispatchQueue.global().asyncAfter(deadline: .now() + 2) {
            showRecommendedContent = true
            isFetching = false
            currentStatus = .isNotRecording
        }
    } catch {
        print(error)
    }
}
```

백엔드

```backend
from fastapi import FastAPI
import requests
import json
# uvicorn main:app --reload

# init
app = FastAPI()
client_id = "your client id"
client_secret = "your client secret"
apiUrl="https://naveropenapi.apigw.ntruss.com/sentiment-analysis/v1/analyze"

headers = {
    "X-NCP-APIGW-API-KEY-ID": client_id,
    "X-NCP-APIGW-API-KEY": client_secret,
    "Content-Type": "application/json"
}

@app.get("/analyzeEmotion")
async def analyzeEmotion(inputText: str):
    data = {"content" : inputText}
    response = requests.post(apiUrl, data=json.dumps(data), headers=headers).json()
    return {
        "sentiment" : str(response["document"]["sentiment"]),
        "confidence" : str(response["document"]["confidence"])
        }

@app.get("/recommend")
async def recommend(value: float, age: str, hobby: str):
    print(value, age, hobby)
    return {"recommend" : "애니메이션"}
```

데모영상: https://github.com/a-mystic/GraduationProject/blob/main/README.md