

# Recurrences

# A side note about induction

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

We have seen many examples with induction used to prove summation formulas. But we have to make it clear: *Induction does not have to be applied to summations* or any arithmetic expressions. It is a much more general approach:

$$\frac{P(0) \quad P(n) \rightarrow P(n+1) \text{ for all } n \geq 0}{P(k) \text{ for all } k \geq 0}$$

For example, the problem, where we were tiling checkerboards. There were no summation, but it was a good example of induction.

# Recurrence

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

Recall that we used induction to prove statements like

$$\sum_{k=0}^n k = 0 + 1 + 2 + 3 + \dots + n = \frac{n(n+1)}{2}$$

In problems like this, we used a common pattern:

$$\sum_{k=0}^0 k = 0$$

$$\sum_{k=0}^n k = \left( \sum_{k=0}^{n-1} k \right) + n, \quad \text{when } n > 0$$

That is, we can express the sum of natural numbers recursively in terms of a smaller sum.

# Recurrence

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

Let  $S(n)$  be the sum of all natural numbers not greater than  $n$ :

$$S(n) = \sum_{k=0}^n k,$$

It can be convenient to redefine the sum  $S(n)$  as a *recurrence*:

$$S(0) = 0$$

$$S(n) = S(n-1) + n \quad (\forall n > 0)$$

This is just another way to express the same function  $S$ .

# Recurrence

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

Exponentiation:

$$E(a, n) = a^n$$

Recursively:

$$E(a, 0) = 1$$

$$E(a, n) = E(a, n-1) \cdot a \quad (\forall n > 0)$$

# Recurrence

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

Factorial:

$$n! = 1 \cdot 2 \cdot \dots \cdot n$$

Recursively:

$$0! = 1$$

$$n! = (n-1)! \cdot n \quad (\forall n > 0)$$

# The towers of Hanoi

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms





<http://www.mathsisfun.com/games/towerofhanoi.html>

# The towers of Hanoi

Our recursive algorithm to move a tower of height  $n$  from #1 to #3:

1. Move an  $(n-1)$ -tower from #1 to #2.
2. Move an 1-tower from #1 to #3.
3. Move an  $(n-1)$ -tower from #2 to #3.



About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms




# The towers of Hanoi

Our recursive algorithm to move a tower of height  $n$  from #1 to #3:

1. Move an  $(n-1)$ -tower from #1 to #2.
2. Move an 1-tower from #1 to #3.
3. Move an  $(n-1)$ -tower from #2 to #3.

There is a way to find a recurrent formula for  $T_n$ , the total number of steps to move the tower from the peg 1 to the peg 3.



About induction

Recurrence

Towers of Hanoi

Merge sort


Time complexity of algorithms

# The towers of Hanoi

$T_n$ , the time to move a tower of height  $n$ :

$$T_1 = 1$$

$$T_n = T_{n-1} + 1 + T_{n-1} \quad (\forall n > 1)$$



About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms


# The towers of Hanoi

$T_n$ , the time to move a tower of height  $n$ :

$$T_1 = 1$$

$$T_n = T_{n-1} + 1 + T_{n-1} \quad (\forall n > 1)$$

There is a proof by induction that this time is optimal for any algorithm.



About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

# The towers of Hanoi

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

$$T_1 = 1$$

$$T_n = 2T_{n-1} + 1 \quad (\forall n > 1)$$

Our goal is to find a closed form expression for  $T_n$  as a function of  $n$ , without any recurrence.

# The towers of Hanoi

Before we get a closed form formula for  $T_n$ ,  
what are the numbers?

$$T_1 = 1$$

$$T_n = 2T_{n-1} + 1 \quad (\forall n > 1)$$

We can compute a list like this:

$$T_1 = 1$$

$$T_2 = 3$$

$$T_3 = 7$$

$$T_4 = 15$$

$$T_5 = 31$$

$$T_6 = 63$$

...

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

# The towers of Hanoi

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

$$T_1 = 1$$

$$T_n = 2T_{n-1} + 1 \quad (\forall n > 1)$$

$$T_1 = 1$$

$$T_2 = 3$$

$$T_3 = 7$$

$$T_4 = 15$$

$$T_5 = 31$$

$$T_6 = 63$$

...

*Guess and verify* method... Let's try  $T_n = 2^n - 1$ ?

# The towers of Hanoi

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

$$T_1 = 1$$

$$T_n = 2T_{n-1} + 1 \quad (\forall n > 1)$$

*Guess and verify* method... Let's try  $T_n = 2^n - 1$ ? We can show by induction that this formula is correct.

*The base case*,  $n = 1$ :

$$T_1 = 2^1 - 1 = 1.$$

Ok, the base case is true.

# The towers of Hanoi

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

$$T_1 = 1$$

$$T_n = 2T_{n-1} + 1 \quad (\forall n > 1)$$

We want to prove the closed form formula  $T_n = 2^n - 1$ .

*The inductive step*,  $n > 1$ :

Assume that  $T_n = 2^n - 1$ , and show that then  $T_{n+1} = 2^{n+1} - 1$ .

Proof. From the recurrence:

$$T_{n+1} = 2T_n + 1$$

By the inductive hypothesis:

$$2T_n + 1 = 2(2^n - 1) + 1 = 2^{n+1} - 2 + 1 = 2^{n+1} - 1$$



# The towers of Hanoi

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

Why is it useful to know that the recurrence

$$T_1 = 1$$

$$T_n = 2T_{n-1} + 1 \quad (\forall n > 1)$$

is equivalent to the closed form formula  $T_n = 2^n - 1$ ?

The 7-disk puzzle will require  $T_7 = 2^7 - 1 = 127$  moves to complete.

And the 100-disk puzzle will require

$$T_{100} = 2^{100} - 1 = 1267650600228229401496703205375 \text{ moves.}$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

## function Merge:

Given two sorted lists, combine them into a single sorted list:

$$[1, 2, 4, 5] + [3, 4, 5, 6] \mapsto [1, 2, 3, 4, 4, 5, 5, 6]$$

## function Sort:

Given a list: if it contains a single element, return it. Otherwise, split it in two halves sort them separately and merge the results:

$$S[5] \mapsto [5]$$

$$S[6, 7, 1, 8, 9, 7, 4, 3] \mapsto S[6, 7, 1, 8] + S[9, 7, 4, 3]$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

$S[1, 8, 3, 6, 5, 4, 7, 2] \mapsto$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

$$\begin{aligned} S[1, 8, 3, 6, 5, 4, 7, 2] &\mapsto \\ S[1, 8, 3, 6] + S[5, 4, 7, 2] &\mapsto \end{aligned}$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

$$S[1, 8, 3, 6, 5, 4, 7, 2] \mapsto$$

$$S[1, 8, 3, 6] + S[5, 4, 7, 2] \mapsto$$

$$(S[1, 8] + S[3, 6]) + (S[5, 4] + S[7, 2]) \mapsto$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

$$S[1, 8, 3, 6, 5, 4, 7, 2] \mapsto$$

$$S[1, 8, 3, 6] + S[5, 4, 7, 2] \mapsto$$

$$(S[1, 8] + S[3, 6]) + (S[5, 4] + S[7, 2]) \mapsto$$

$$((S[1] + S[8]) + (S[3] + S[6])) + ((S[5] + S[4]) + (S[7] + S[2])) \mapsto$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

$$S[1, 8, 3, 6, 5, 4, 7, 2] \mapsto$$

$$S[1, 8, 3, 6] + S[5, 4, 7, 2] \mapsto$$

$$(S[1, 8] + S[3, 6]) + (S[5, 4] + S[7, 2]) \mapsto$$

$$((S[1] + S[8]) + (S[3] + S[6])) + ((S[5] + S[4]) + (S[7] + S[2])) \mapsto$$

$$((([1] + [8]) + ([3] + [6])) + (([5] + [4]) + ([7] + [2]))) \mapsto$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

$$S[1, 8, 3, 6, 5, 4, 7, 2] \mapsto$$

$$S[1, 8, 3, 6] + S[5, 4, 7, 2] \mapsto$$

$$(S[1, 8] + S[3, 6]) + (S[5, 4] + S[7, 2]) \mapsto$$

$$((S[1] + S[8]) + (S[3] + S[6])) + ((S[5] + S[4]) + (S[7] + S[2])) \mapsto$$

$$([1] + [8]) + ([3] + [6]) + ([5] + [4]) + ([7] + [2]) \mapsto$$

$$[1, 8] + [3, 6] + [4, 5] + [2, 7] \mapsto$$



# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

$$S[1, 8, 3, 6, 5, 4, 7, 2] \mapsto$$

$$S[1, 8, 3, 6] + S[5, 4, 7, 2] \mapsto$$

$$(S[1, 8] + S[3, 6]) + (S[5, 4] + S[7, 2]) \mapsto$$

$$((S[1] + S[8]) + (S[3] + S[6])) + ((S[5] + S[4]) + (S[7] + S[2])) \mapsto$$

$$((([1] + [8]) + ([3] + [6])) + (([5] + [4]) + ([7] + [2]))) \mapsto$$

$$([1, 8] + [3, 6]) + ([4, 5] + [2, 7]) \mapsto$$

$$[1, 3, 6, 8] + [2, 4, 5, 7] \mapsto$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

$$S[1, 8, 3, 6, 5, 4, 7, 2] \mapsto$$

$$S[1, 8, 3, 6] + S[5, 4, 7, 2] \mapsto$$

$$(S[1, 8] + S[3, 6]) + (S[5, 4] + S[7, 2]) \mapsto$$

$$((S[1] + S[8]) + (S[3] + S[6])) + ((S[5] + S[4]) + (S[7] + S[2])) \mapsto$$

$$((([1] + [8]) + ([3] + [6])) + (([5] + [4]) + ([7] + [2]))) \mapsto$$

$$([1, 8] + [3, 6]) + ([4, 5] + [2, 7]) \mapsto$$

$$[1, 3, 6, 8] + [2, 4, 5, 7] \mapsto$$

$$[1, 2, 3, 4, 5, 6, 7, 8]$$

# Merge sort

About induction


Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

Split in two and  
sort the parts



Merge  
sorted lists

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

How much time does it take to sort a list of  $n$  elements?

To estimate the time complexity, we are going to *count the number of comparisons* between the elements.

We assume that the size of the given list is a power of 2. It makes the analysis easier, but does not affect the result.

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

- (a) To merge two lists of size  $n/2$ , we need to do at most  $n - 1$  comparisons.
- (b) To sort a list, we have to split it in two, sort both halves, and merge them.

Therefore,

$$T(1) = 0$$

$$T(n) = 2T(n/2) + n - 1 \quad (\forall n > 1)$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

Given

$$T(n) = 2T(n/2) + n - 1 \quad (\forall n > 1)$$

Since  $n = 2^k$ ,

$$\begin{aligned} T(n) &= T(2^k) = 2T(2^{k-1}) + (2^k - 1) \\ &= 2(2T(2^{k-2}) + 2^{k-1} - 1) + (2^k - 1) \\ &= 2^2 T(2^{k-2}) + (2^k - 2) + (2^k - 1) \\ &= 2^2 (2T(2^{k-3}) + 2^{k-2} - 1) + (2^k - 2) + (2^k - 1) \\ &= 2^3 T(2^{k-3}) + (2^k - 4) + (2^k - 2) + (2^k - 1) \\ &= 2^3 (2T(2^{k-4}) + 2^{k-3} - 1) + (2^k - 4) + (2^k - 2) + (2^k - 1) \\ &= 2^4 T(2^{k-4}) + (2^k - 8) + (2^k - 4) + (2^k - 2) + (2^k - 1) \\ &= \dots = 2^k \underbrace{T(2^{k-k})}_{T(1)=0} + \sum_{i=0}^{k-1} (2^k - 2^i) = \sum_{i=0}^{k-1} (2^k - 2^i). \end{aligned}$$

# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

$$T(n) = T(2^k) = \sum_{i=0}^{k-1} (2^k - 2^i) = \sum_{i=0}^{k-1} (n - 2^i) = n \cdot k - \sum_{i=0}^{k-1} 2^i.$$

The sum of the geometric progression is

$$\sum_{i=0}^{k-1} 2^i = \frac{2^k - 1}{2 - 1} = 2^k - 1 = n - 1.$$

Thus  $T(n) = n \cdot k - n + 1$ . And since  $n = 2^k$ ,  $k = \log_2 n$ , so

$$T(n) = n \log_2 n - n + 1.$$

# Merge sort

About induction

Recurrence



Towers of Hanoi

Merge sort

Time complexity of algorithms

To sort a list of length  $n$ , takes time (the number of comparisons)

$$T(n) = n \log_2 n - n + 1 \approx n \log_2 n.$$





# Merge sort

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of algorithms

In merge sort, we had a recurrence:

$$T(n) = 2T(n/2) + n - 1$$

In general, if the time complexity of an algorithm is expressed by a recurrence:

$$T(n) = a \cdot T(n/b) + f(n)$$

To solve such recurrences, there is a so called *Master theorem*:

[https://en.wikipedia.org/wiki/Master\\_theorem](https://en.wikipedia.org/wiki/Master_theorem)

It covers different forms of the function  $f$ , as well as difference values of the constants  $a$  and  $b$ .

# Time complexity, big-O

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

Let's say that we've got this function as an estimation of the time complexity of an algorithm:

$$T(n) = 6n \log_2 n + 100n + \log_2 n + 50$$

**Informally:**



- (a) If  $T(n)$  is a sum, we take the fastest growing term only.
- (b) We don't really care about constant factors.

$$T(n) = O(n \log_2 n)$$

# Time complexity, big-O

Some common time complexities, from the slowest to the fastest:

Running time	Name
$O(1)$	constant
$O(\log(\log n))$	log-logarithmic
$O(\log n)$	logarithmic
$O(\sqrt{n})$	square root (sub-linear)
$O(n)$	linear
$O(n \log n)$	n-log-n
$O(n^2)$	quadratic
$O(2^n)$	exponential
$O(n!)$	factorial
$O(2^{(2^n)})$	double exponential



About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

# Time complexity, big-O

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

*Faster than linear* algorithms, for example  $O(\log n)$ , cannot go through the whole input. They are cherry-picking in some sense, knowing where to search for the answer. Usually the input is structured in some way.

**Example:** *Binary search in a sorted array.*

*Linear* time algorithms,  $O(n)$ , usually have to read the whole input.

**Example:** *Search for the largest element in an unsorted array.*

# Time complexity, big-O

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

Algorithms *slower than linear*,  $O(n \log n)$  or  $O(n^2)$ ,  $O(n^7)$ . Not only read the whole input, but also perform some extra work, but in a reasonably efficient way.

**Example:** *Sorting algorithms.*

Algorithms *much slower than linear*, exponential, for example,  $O(2^n)$ , are doing some non-trivial work.

**Example:** *Satisfiability of a statement in propositional logic.*

# Time complexity, big-O

About induction

Recurrence

Towers of Hanoi

Merge sort

Time complexity of  
algorithms

## Formally:

We say that

$$T(n) = O(f(n))$$

if there are constants  $C$  and  $k$  such that

$$|T(n)| \leq C|f(n)| \quad \text{for all } n > k$$

This definition says that after  $n > k$ , all slowly-growing terms don't really matter, and  $T(n)$  behaves similarly to  $f(n)$ . To be more exact,  $T(n)$  never exceeds  $C \cdot f(n)$  when  $n$  is large enough.

$$T(n) = 6n \log_2 n + 100n + \log_2 n + 50$$

$$T(n) = O(n \log_2 n)$$