# Will the Next Word Switch Language? Anticipatory Code-Switch Prediction Across 15 Language Pairs

CS 6140 Machine Learning, Project Update 1 (Week 6, Fall 2026)

Artykzhan Ospan
Northeastern University
Seattle, WA, USA

Mahamane Bachir Sadou
Northeastern University
Seattle, WA, USA

Mukaila Rafiu
Northeastern University
Seattle, WA, USA

## Abstract

We predict code-switching before it happens: at every token of an utterance, using only the prefix, a model predicts whether the next token changes language and how long the new segment will last. This update covers data engineering, labeling, a leak-free streaming loader and the first baselines on all 15 language pairs of the SwitchLingua corpus (974,994 sentences). A logistic regression on prefix-only features reaches a macro switch F1 of 0.555 (PR-AUC 0.528) and a duration macro-F1 of 0.531, with large gaps between pairs. Code: https://github.com/a-ospan/streaming-code-switching.

## 1 Problem Description

Code-switching (CS), alternating between languages inside one utterance, is common among bilinguals, yet most NLP work identifies languages after the whole sentence is seen. Streaming speech recognition, predictive keyboards and dialogue agents instead need to *anticipate* a switch. We formulate anticipatory CS prediction: given only the prefix $w_1, \ldots, w_t$, a causal model predicts (i) $y_{sw} \in \{0, 1\}$, whether $w_{t+1}$ is in a different language than $w_t$, and (ii) $y_{dur} \in \{1{-}2, 3{-}6, 7{+}\}$, the length in tokens of the new segment, defined only when $y_{sw} = 1$. We use the SwitchLingua text corpus [13] and evaluate the switch F1, the duration macro-F1, and *universality*: the standard deviation $\sigma$ of switch F1 across language pairs, where lower means more consistent.

## 2 Background

**Predicting switches.** Solorio and Liu [9] were the first to learn where a speaker may switch, on a 40-minute Spanish–English conversation (about 8k words, 239 switches). They trained Naive Bayes and VFI classifiers on lexical, language and POS features of only the one or two preceding words, to suit real-time use. The best F1 was 0.28 with 96% negative instances, which shows how hard and imbalanced the task is. Chan et al. [3] ask whether word predictability drives switch points in 1,010 Cantonese–English switches from 41 bilinguals. They regressed switching on surprisal from autoregressive and masked language models. Less predictable words were switched more, consistently across bilingual groups. Xie et al. [12] predict upcoming switches token by token in Chinese–English dialogue (ASCEND). They compared windowed RNNs over BERT embeddings with fine-tuned mBERT and XLM-R. mBERT reached an AUC of 0.98, but on one language pair only.

**Language identification in CS text.** Burchell et al. [2] test whether scalable language identification can find CS text for corpus building. They recast it as sentence-level multi-label tagging and compared three systems on six CS test sets. Exact-match accuracy stayed below 0.16, so no current approach is adequate. Sterner [10] builds one word-level tagger that separates English from any other language. He merged five CS corpora and fine-tuned XLM-R with a named-entity head. It beat pair-specific systems by 2.3 to 4.6 points zero-shot on unseen pairs. Kargaran et al. [6] ask why sentence-level identifiers return only the dominant language of a CS sentence. Their training-free MaskLID masks words of the dominant language and re-runs the identifier. Detected CS rose up to 22-fold, yet one-word insertions were still mostly missed. Iakovenko and Hain [5] identify the matrix language that frames a CS utterance. They implemented Matrix Language Frame principles on text and trained audio classifiers on those labels for Mandarin–English and Spanish–English. Their best audio systems beat acoustic LID, but agreement between principles was sometimes low.

**Benchmarks and models for CS.** Aguilar et al. [1] built LinCE, a benchmark of 11 corpora over 4 language pairs and 4 tasks (LID, NER, POS, sentiment). They report LSTM, ELMo and mBERT baselines with a public leaderboard. It standardizes evaluation, but covers only four pairs. Khanuja et al. [7] built GLUECoS for Hindi–English and Spanish–English, with six tasks including QA and NLI. They compared cross-lingual embeddings with multilingual models, also fine-tuned on synthetic CS text. Multilingual models won, best when fine-tuned on CS data. Winata et al. [11] ask whether multilingual models handle CS. They compared them with bilingual embeddings and meta-embeddings on NER and POS for three pairs. Pretrained multilingual models did not guarantee good CS representations.

**Multilingual backbones.** Conneau et al. [4] train XLM-R, a masked language model, on more than two terabytes of text in 100 languages. It beat mBERT by 14.6 points on XNLI, most for low-resource languages, but it is bidirectional, so streaming use needs a causal mask. Xue et al. [14] pretrain mT5 on 101 languages and balance languages with exponent-smoothed sampling. It set the state of the art on many multilingual benchmarks; we reuse its sampling idea for unbalanced pairs. Lin et al. [8] train XGLM, left-to-right multilingual language models, and evaluate few-shot learning. Their largest model beat GPT-3 on multilingual reasoning and translation, making XGLM a natural causal backbone for us.

**Our gap.** Prior switch prediction covers one pair at a time, and CS benchmarks label switches after the fact. We predict switches and their duration from the prefix alone, on 15 pairs at once, and measure how consistent the predictor is across them.

## 3 Dataset

### 3.1 Corpus

SwitchLingua [13] contains 234,172 LLM-generated conversations with 19 columns (topic, speaker profile, CS type, quality scores). The

released text has **15 pairs**, more than the 12 languages in the paper: 7 non-Latin-script pairs with English (Arabic, Cantonese, Chinese, Hindi, Japanese, Korean, Russian), 7 Latin-script pairs with English (French, German, Italian, Malay, Filipino, Spanish, Vietnamese), and German–French. We pin version `6e048d27` of the corpus. Generation controls are balanced by design: 50% single-turn and 50% multi-turn conversations; three CS types (tag, inter-sentential, intra-sentential), each about a third; and six CS functions in equal shares. An LLM judge scored each row for fluency, naturalness, ratio and socio-cultural fit (mean 8.42 on a 10-point scale, range 5.0 to 9.75). A conversation holds 4.2 sentences on average, and a sentence 19.5 tokens (19.0M tokens in total). The pairs are very unbalanced: Cantonese–English is 64% of all sentences, while every other pair has 20k to 30k.

## 3.2 Pre-processing

**Parsing.** The text column is a stringified Python object: mostly lists of sentences, but also dictionaries (with topic, instances, speaker or message keys), nested lists and plain strings. Our parser handles all formats and keeps text fields only, giving 974,994 sentences; 5 empty or pasted-conversation sentences are removed and counted.

**Tokenization.** Words are split on whitespace and punctuation. Each Chinese character is one token, the mBERT convention. A whole run of characters as one token would leak the future: a run only ends when a non-Chinese character arrives, and 85% of the Cantonese runs that end glued to a letter end at a switch. Punctuation is not a token; it is kept as context for the preceding token.

**Token-level language ID.** The corpus gives only each row's two languages, so we tag every token with three rules: (1) script, when the two languages use different scripts; (2) word frequency from the `wordfreq` lists, for Latin-script pairs; (3) context, where undecided tokens (names, numbers, words shared by both languages) take the nearest decided neighbor's language. 56% of Hindi–English rows are romanized, so we built a romanized-Hindi lexicon (1,056 words) from the corpus itself, using the Latin words in Devanagari rows as the English reference. Hindi is therefore reported as two strata, giving 16 evaluation strata. As a sanity check, our per-row share of second-language tokens correlates with the ratio estimated by the corpus's own LLM judge (Pearson 0.47 to 0.60 for 13 pairs, 0.32 for Hindi and 0.29 for Filipino, on 300 rows per pair). Since that estimate is itself noisy, a hand-validation sample of 450 sentences (30 per pair) is prepared.

## 3.3 Labels and splits

$y_{sw}$ and $y_{dur}$ are derived from the token tags (Table 1); the last token of a sentence has no target. Unit tests check them on hand-worked sentences.

We split 80/10/10 *by conversation*, stratified by stratum with a fixed seed, and keep conversations sharing a sentence (5,586 duplicates) in one split (Table 2). Table 3 and Figure 1 summarize the labels. Switches are rare (5 to 13% of positions for most pairs), so we report F1 and PR-AUC rather than accuracy.

**Table 1: Labels for a Spanish–English sentence. The switch is predicted at *sé*; the comma typed after it is part of the prefix.**

| Token | Yo | no | sé, | but | I | think | so |
|---|---|---|---|---|---|---|---|
| Language | es | es | es | en | en | en | en |
| $y_{sw}$ | 0 | 0 | **1** | 0 | 0 | 0 | – |
| $y_{dur}$ | – | – | **3–6** | – | – | – | – |

**Table 2: Fixed splits, by conversation and stratified by stratum.**

| Split | Conversations | Sentences | Target positions |
|---|---|---|---|
| Train (80%) | 187,329 | 778,867 | 14.4M |
| Validation (10%) | 23,418 | 98,046 | 1.8M |
| Test (10%) | 23,422 | 98,081 | 1.8M |

**Table 3: Sentences and switch rate per stratum (all splits).**

| Stratum | Sentences | Switch rate |
|---|---|---|
| Chinese–English | 29,561 | 5.1% |
| Japanese–English | 27,893 | 6.3% |
| Cantonese–English | 619,863 | 6.8% |
| Italian–English | 24,165 | 8.4% |
| German–French | 23,598 | 8.6% |
| Arabic–English | 26,791 | 9.1% |
| Vietnamese–English | 26,803 | 9.1% |
| Russian–English | 24,625 | 9.3% |
| Spanish–English | 24,517 | 9.6% |
| German–English | 19,583 | 9.8% |
| French–English | 23,563 | 10.3% |
| Korean–English | 25,388 | 10.6% |
| Malay–English | 26,127 | 13.3% |
| Hindi–English (Devanagari) | 11,186 | 16.1% |
| Filipino–English | 25,826 | 19.1% |
| Hindi–English (romanized) | 15,505 | 31.4% |

# 4 Experimentation and Results

## 4.1 Streaming setup

At token $t$ the input is the prefix only. For transformers, each sentence is encoded once with the model's subword tokenizer and the prediction for word $t$ is read at the last subword that ends before word $t+1$. A position is skipped if a subword spans the boundary or if the prefix tokenizes differently on its own, so no future character can leak; automated tests change every word after $t$ and check that inputs at $t$ do not change. To keep Cantonese from dominating training, pairs are drawn with probability proportional to $n_p^{0.3}$, as in mT5 [14], which lowers Cantonese from 64% to 16% of samples.

## 4.2 Baselines

**Majority class** always predicts no switch and the most frequent duration (1–2). **Logistic regression** uses prefix-only features: current language, length of the current run, switches so far, position, punctuation typed after the token, script, stratum, and stratum × current language. Tags are rebuilt from the prefix only, since the





**Figure 1: Duration class of the segment after a switch, per stratum. Hindi and Filipino are dominated by short insertions; Chinese and Japanese segments, counted in characters, are often 7+.**





**Figure 2: Logistic regression switch F1 per stratum (validation). The line is the macro average.**

**Table 4: Baselines on the validation split (macro average over 16 strata). $\sigma$: standard deviation of switch F1 across strata.**

| Model | F1 | PR-AUC | P | R | $\sigma$ | Dur. F1 |
|---|---|---|---|---|---|---|
| Majority | 0.000 | 0.114 | 0.000 | 0.000 | n/a | 0.202 |
| Logistic reg. | **0.555** | **0.528** | 0.550 | 0.571 | 0.076 | **0.531** |

context rule may look right. A binary model predicts $y_{sw}$ and a multinomial (softmax) model predicts $y_{dur}$, trained on true switch points. Both use 3,000 training sentences per stratum (838k positions); the switch threshold (0.225) is tuned on training data. All results are on the validation split (1.8M positions), macro-averaged over the 16 strata.

## 4.3 Results

Table 4 shows the logistic regression far above the majority class, with balanced precision and recall. Figure 2 shows large gaps between pairs: Korean (0.717) and Japanese (0.633) are easiest, Filipino (0.397) and Cantonese (0.409) hardest, giving $\sigma = 0.076$.

**Why Korean is easy and Cantonese hard.** The strongest feature is punctuation (Table 5). In Korean, Chinese and Japanese, 68 to 70% of switches follow a comma or sentence end, versus 2 to 4% of other positions. In Cantonese only 38% do: English words are inserted mid-clause (呢個IG update好正), with no visible cue. The baseline thus learns clause-level switching but not insertions.

**Duration.** Short (1–2) and long (7+) segments are recognized well (87% and 69% recall), but only 13% of 3–6 segments are (Table 6), since prefix features cannot tell a phrase from a clause.

**Table 5: Share of positions right after punctuation (2,500 validation sentences per pair) and baseline switch F1.**

| Pair | Switches | Other positions | Switch F1 |
|---|---|---|---|
| Korean–English | 68.6% | 2.4% | 0.717 |
| Japanese–English | 69.9% | 3.7% | 0.633 |
| Chinese–English | 67.5% | 3.4% | 0.584 |
| Cantonese–English | 38.0% | 5.5% | 0.409 |

**Table 6: Duration confusion matrix of the logistic regression at true switch points (validation, all strata).**

| True \ predicted | 1–2 | 3–6 | 7+ | Recall |
|---|---|---|---|---|
| 1–2 | **56,337** | 3,011 | 5,777 | 86.5% |
| 3–6 | 17,264 | **4,737** | 14,357 | 13.0% |
| 7+ | 10,395 | 3,914 | **31,844** | 69.0% |

**Tokenizer alignment.** We checked how the streaming loader fits each backbone's tokenizer on 300 training sentences per stratum (Table 7). In Chinese-character text, 20 to 30% of character positions fall inside one XLM-R subword and are skipped, but no true switch point is lost. XGLM lacks common Cantonese characters (5.4% unknown subwords) and loses 4 to 5% of switch points in Chinese and Cantonese. All other strata keep at least 96% of positions with both tokenizers. Later model comparisons will therefore use positions valid for both models.

## 5 Plan for Next

Week 7: causal masking and the two prediction heads, already implemented with a test showing that later tokens cannot change earlier outputs. Weeks 8 to 10: multitask training of XLM-R with a

**Table 7: Usable prediction positions per tokenizer (lowest strata) and XGLM unknown-subword rate.**

| Stratum | XLM-R | XGLM | XGLM unknown |
|---|---|---|---|
| Chinese–English | 68.9% | 75.2% | 0.6% |
| Japanese–English | 78.4% | 85.3% | 0.2% |
| Cantonese–English | 79.6% | 85.3% | 5.4% |
| Korean–English | 99.9% | 95.8% | 0.6% |

causal mask [4] and the natively causal XGLM [8], tuning the loss weights, comparing sampling exponents 0.3 and 0, and comparing backbones against these baselines. Weeks 11 and 12: per-pair evaluation, universality $\sigma$ and bootstrap confidence intervals, and hand validation of the language tags. Weeks 13 and 14: error analysis by script and switch type, the streaming demo and the final paper.

## References


[1] Gustavo Aguilar, Sudipta Kar, and Thamar Solorio. 2020. LinCE: A Centralized Benchmark for Linguistic Code-switching Evaluation. In *Proceedings of the Twelfth Language Resources and Evaluation Conference (LREC)*. 1803–1813.

[2] Laurie Burchell, Alexandra Birch, Robert Thompson, and Kenneth Heafield. 2024. Code-Switched Language Identification is Harder Than You Think. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (EACL)*. 646–658.

[3] Ariel Shuk Ling Chan, Yanting Li, and Jacob Poschl. 2026. Word Predictability on Code-switching Points in Cantonese–English Discourse. In *Proceedings of the Society for Computation in Linguistics (SCiL)*. 230–243.

[4] Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised Cross-lingual Representation Learning at Scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*. 8440–8451.

[5] Olga Iakovenko and Thomas Hain. 2024. Methods of Automatic Matrix Language Determination for Code-Switched Speech. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. 5791–5800.

[6] Amir Hossein Kargaran, François Yvon, and Hinrich Schütze. 2024. MaskLID: Code-Switching Language Identification through Iterative Masking. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL), Volume 2: Short Papers*. 459–469.

[7] Simran Khanuja, Sandipan Dandapat, Anirudh Srinivasan, Sunayana Sitaram, and Monojit Choudhury. 2020. GLUECoS: An Evaluation Benchmark for Code-Switched NLP. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*. 3575–3585.

[8] Xi Victoria Lin, Todor Mihaylov, Mikel Artetxe, et al. 2022. Few-shot Learning with Multilingual Generative Language Models. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. 9019–9052.

[9] Thamar Solorio and Yang Liu. 2008. Learning to Predict Code-Switching Points. In *Proceedings of the 2008 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. 973–981.

[10] Igor Sterner. 2024. Multilingual Identification of English Code-Switching. In *Proceedings of the Eleventh Workshop on NLP for Similar Languages, Varieties, and Dialects (VarDial)*. 163–173.

[11] Genta Indra Winata, Samuel Cahyawijaya, Zihan Liu, Zhaojiang Lin, Andrea Madotto, and Pascale Fung. 2021. Are Multilingual Models Effective in Code-Switching?. In *Proceedings of the Fifth Workshop on Computational Approaches to Linguistic Code-Switching (CALCS)*. 142–153.

[12] Jiawen Xie, Peng Zhang, Jayash Koshal, and Shanu Sushmita. 2025. Beyond Detection: Predicting Code-Switch Points in Multilingual Conversations. In *Women in Machine Learning Workshop at NeurIPS*.

[13] Peng Xie, Xingyuan Liu, Tsz Wai Chan, Yequan Bie, Yangqiu Song, Yang Wang, Hao Chen, and Kani Chen. 2025. SwitchLingua: The First Large-Scale Multilingual and Multi-Ethnic Code-Switching Dataset. In *Advances in Neural Information Processing Systems (NeurIPS)*. arXiv:2506.00087.

[14] Linting Xue, Noah Constant, Adam Roberts, Mihir Kale, Rami Al-Rfou, Aditya Siddhant, Aditya Barua, and Colin Raffel. 2021. mT5: A Massively Multilingual Pre-trained Text-to-Text Transformer. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*. 483–498.