

EX.NO 7: Deploy python Web application using Google AppEngine

Date:

READING MATERIALS:

Google AppEngine is a PaaS implementation that provides services for developing and hosting scalable Web applications. AppEngine is essentially a distributed and scalable runtime environment that leverages Google's distributed infrastructure to scale out applications facing a large number of requests by allocating more computing resources to them and balancing the load among them. The runtime is completed by a collection of services that allow developers to design and implement applications that naturally scale on AppEngine. Developers can develop applications in Java, Python, and Go, a new programming language developed by Google to simplify the development of Web applications. Application usage of Google resources and services is metered by AppEngine, which bills users when their applications finish their free quotas.

Application services Applications hosted on AppEngine take the most from the services made available through the runtime environment. These services simplify most of the common operations that are performed in Web applications: access to data, account management, integration of external resources, messaging and communication, image manipulation, and asynchronous computation. UrlFetch Web 2.0 has introduced the concept of composite Web applications. Different resources are put together and organized as meshes within a single Web page. Meshes are fragments of HTML generated in different ways. They can be directly obtained from a remote server or rendered from an XML document retrieved from a Web service, or they can be rendered by the browser as the result of an embedded and remote component. A common characteristic of all these examples is the fact that the resource is not local to the server and often not even in the same administrative domain. Therefore, it is fundamental for Web applications to be able to retrieve remote resources.

The sandbox environment does not allow applications to open arbitrary connections through sockets, but it does provide developers with the capability of retrieving a remote resource through HTTP/HTTPS by means of the UrlFetch service. Applications can make synchronous and asynchronous Web requests and integrate the resources obtained in this way into the normal requesthandling cycle of the application. One of the interesting features of UrlFetch is the ability to set deadlines for requests so that they can be completed (or aborted) within a given time. Moreover, the ability to perform such requests asynchronously allows the

applications to continue with their logic while the resource is retrieved in the background. `UrlFetch` is not only used to integrate meshes into a Web page but also to leverage remote Web services in accordance with the SOA reference model for distributed applications.

MemCache

AppEngine provides developers with access to fast and reliable storage, which is `DataStore`. Despite this, the main objective of the service is to serve as a scalable and long-term storage, where data are persisted to disk redundantly in order to ensure reliability and availability of data against failures. This design poses a limit on how much faster the store can be compared to other solutions, especially for objects that are frequently accessed—for example, at each Web request. AppEngine provides caching services by means of `MemCache`. This is a distributed in-memory cache that is optimized for fast access and provides developers with a volatile store for the objects that are frequently accessed. The caching algorithm implemented by `MemCache` will automatically remove the objects that are rarely accessed. The use of `MemCache` can significantly reduce the access time to data; developers can structure their applications so that each object is first looked up into `MemCache` and if there is a miss, it will be retrieved from `DataStore` and put into the cache for future lookups.

Mail and instant messaging

Communication is another important aspect of Web applications. It is common to use email for following up with users about operations performed by the application. Email can also be used to trigger activities in Web applications. To facilitate the implementation of such tasks, AppEngine provides developers with the ability to send and receive mails through `Mail`. The service allows sending email on behalf of the application to specific user accounts. It is also possible to include several types of attachments and to target multiple recipients. `Mail` operates asynchronously, and in case of failed delivery the sending address is notified through an email detailing the error. AppEngine provides also another way to communicate with the external world: the Extensible Messaging and Presence Protocol (XMPP). Any chat service that supports XMPP, such as Google Talk, can send and receive chat messages to and from the Web application, which is identified by its own address. Even though the chat is a communication medium mostly used for human interactions, XMPP can be conveniently used to connect the Web application with chat bots or to implement a small administrative console.


Account management

Web applications often keep various data that customize their interaction with users. These data normally go under the user profile and are attached to an account. AppEngine simplifies account management by allowing developers to leverage Google account management by means of Google Accounts. The integration with the service also allows Web applications to offload the implementation of authentication capabilities to Google's authentication system. Using Google Accounts, Web applications can conveniently store profile settings in the form of key-value pairs, attach them to a given Google account, and quickly retrieve them once the user authenticates. With respect to a custom solution, the use of Google Accounts requires users to have a Google account, but it does not require any further implementation. The use of Google Accounts is particularly advantageous for developing Web applications within a corporate environment using Google Apps. In this case, the applications can be easily integrated with all the other services (and profile settings) included in Google Apps.

Image manipulation Web applications render pages with graphics. Often simple operations, such as adding watermarks or applying simple filters, are required. AppEngine allows applications to perform image resizing, rotation, mirroring, and enhancement by means of Image Manipulation, a service that is also used in other Google products. Image Manipulation is mostly designed for lightweight image processing and is optimized for speed.

Compute services

Web applications are mostly designed to interface applications with users by means of a ubiquitous channel, that is, the Web. Most of the interaction is performed synchronously: Users navigate the Web pages and get instantaneous feedback in response to their actions. This feedback is often the result of some computation happening on the Web application, which implements the intended logic to serve the user request. Sometimes this approach is not applicable—for example, in long computations or when some operations need to be triggered at a given point in time. A good design for these scenarios provides the user with immediate feedback and a notification once the required operation is completed. AppEngine offers additional services such as Task Queues and Cron Jobs that simplify the execution of computations that are off-bandwidth or those that cannot be performed within the timeframe of the Web request.



EX.NO 7: Deploy python Web application using Google AppEngine


Date:


AIM:

To Deploy Python web application using Google AppEngine.


PROCEDURE with SCREENSHOTS:

Step 1: Setup Google Cloud Environment





Step 2: Develop the Application




Step 3: Configure App Engine

```
cloud-shell
Terminal
b3cc0d4-439715 K +
Open Editor

/app/lib/google-cloud-sdk/platform/google_appengine/appengine/ext/db/_init_.py:281: SyntaxWarning: invalid escape sequence "\a"
  """\a"""
/app/lib/google-cloud-sdk/platform/google_appengine/appengine/ext/db/_init_.py:281: SyntaxWarning: invalid escape sequence "\a"
  """\a"""
INFO 2024-10-25 17:32:25,478 settings.py:317] Skipping run update check.
WARN/BC 2024-10-25 17:32:25,479 settings.py:324] The default encoding of your local Python interpreter is set to 'utf-8' while App Engine's production environment uses 'ascii'; as a result your
code may behave differently when deployed.
WARN/BC 2024-10-25 17:32:25,574 sample_search_stub.py:1288] Could not read search indexes from /tmp/appengine-home/gcrarwvnd41/search_indexes
WARN/BC 2024-10-25 17:32:25,577 selftest_stub.py:371 /app/lib/google-cloud-sdk/platform/google_appengine/google_appengine/tools/devappserver2/../../../../lib/objects/selftest_detects.txt miss
ing; without this selftest will not be able to validate API modifications.
INFO 2024-10-25 17:32:25,578 settings.py:392] Starting API server at: http://localhost:8080
INFO 2024-10-25 17:32:25,585 instance_factory.py:127] Detected python version "Python 3.12.3" for runtime "python312" at "/home/gcrarwvnd41/python-docs-samples/appengine/standard_p
ython/hello_world/main.py:python".
INFO 2024-10-25 17:32:25,594 instance_factory.py:200] Using pip to install dependency libraries; pip stdout is redirected to /tmp/tmp_alchuat
INFO 2024-10-25 17:32:25,595 instance_factory.py:310] Running /tmp/tmp_alchuat/pip install --upgrade pip
INFO 2024-10-25 17:32:32,744 instance_factory.py:310] Running /tmp/tmp_alchuat/pip install -e /tmp/tmp_qyqjz0me
INFO 2024-10-25 17:32:35,532 dispatcher.py:167] Starting module "default" running at: http://localhost:8080
INFO 2024-10-25 17:32:35,585 admin_server.py:67] Starting admin server at: http://localhost:8080
INFO 2024-10-25 17:32:36,584 instance.py:555] Detected GONCITE_PATH_PREFIX="b3cc0d4-439715" in environment variables
[2024-10-25 17:32:36 +0000] [1637] [INFO] Starting module 23.8.0
[2024-10-25 17:32:36 +0000] [1637] [INFO] Listening at: http://0.0.0.0:8080 [1637]
[2024-10-25 17:32:36 +0000] [1637] [INFO] Using worker: sync
[2024-10-25 17:32:36 +0000] [1637] [INFO] Starting worker with pid: 1639
INFO 2024-10-25 17:32:37,588 instance.py:283] Instance ID: 1637
INFO 2024-10-25 17:32:37,639 module.py:413] [default] Detected file changes:
/app/home/gcrarwvnd41/python-docs-samples/appengine/standard-python3/hello_world/_pycache_
[2024-10-25 17:32:38 +0000] [1637] [INFO] Handling signal: winch
[2024-10-25 17:32:38 +0000] [1637] [INFO] Handling signal: winch
[2024-10-25 17:32:38 +0000] [1637] [INFO] Handling signal: winch
INFO 2024-10-25 17:34:00,248 module.py:380] default: "GET /favicon.ico HTTP/1.1" 300 12
INFO 2024-10-25 17:34:00,594 module.py:380] default: "GET /favicon.ico HTTP/1.1" 304 247
INFO 2024-10-25 17:34:00,743 instance.py:555] Detected GONCITE_PATH_PREFIX="b3cc0d4-439715" in environment variables
[2024-10-25 17:34:00 +0000] [2170] [INFO] Starting module 23.8.0
[2024-10-25 17:34:00 +0000] [2170] [INFO] Listening at: http://0.0.0.0:8080 [2170]
[2024-10-25 17:34:00 +0000] [2170] [INFO] Using worker: sync
[2024-10-25 17:34:00 +0000] [2170] [INFO] Starting worker with pid: 2172
INFO 2024-10-25 17:34:01,749 instance.py:283] Instance ID: 2170
```

Step 4: Deploy the Application

```
8880-c3-7c716c4-d31-4344-84b-54d84075d55-cs-nl-south-east1-helpcloudhelidev@cloudshell:~/python-docs-samples/appengine/standard-python3$ gcloud app deploy
Hello World!
```



Evaluation by faculty	
Criteria	Marks
Preparation	/20
Program	/25
Output/Result	/20
Viva	/10
Total	/75
Faculty Signature with Date	

RESULT: