

05.3 Architecture Codebook

Field definitions, controlled vocabularies, and decision rules for the UK and NL Implementation Architectures (Stage 3 of the A Safe Bet translational design)

Companion to: 05.1 UK Implementation Architecture, 05.2 NL Implementation Architecture, 05.4 Architecture Methodology

1. Overview

1.1 Purpose

The Implementation Architectures (files 05.1 and 05.2) are the third-stage output of the A Safe Bet design programme. Each architecture specifies a complete, deployment-ready RG configuration for a single operator and jurisdiction: 05.1 covers the UK architecture (SunVegas UK, regulated under the Licence Conditions and Codes of Practice), and 05.2 covers the NL architecture (Holland Casino Online, regulated under the Dutch Remote Gambling Act, KOA 2021).

This codebook documents the column structure, controlled vocabularies, and decision rules that govern both architecture files. The UK and NL architectures share an identical schema (same sheet names, same column headers, same controlled vocabularies), so a single codebook covers both with jurisdiction-specific notes where the values diverge.

1.2 Relationship to Stage 2

Stage 2 (the RG Intervention Framework, file 04.1) produced a structured framework of 210 framework tools derived from the systematic review. Stage 3 selects from that framework, prunes by regulatory and operator constraints, and operationalises the selected tools as deployable variants with full configuration parameters and player-facing copy. The mapping between Stage 2 framework tools and Stage 3 architecture tools is documented in 04.3 Framework to Architecture Translation.

This codebook does not duplicate Stage 2 documentation. Where the architectures inherit framework dimensions (Target Population, the Stage sub-vocabulary of Trigger, Personalisation, Governance, Delivery Context), readers are directed to 04.2 RG Intervention Framework Codebook for the upstream definitions. Architecture-specific operationalisation of those dimensions is documented here. Evidence Status, the sixth categorical dimension in 04.2, is not inherited because it describes Framework-level provenance rather than per-variant configuration.

Note. The architecture's risk_level field maps to the Framework's Target Population vocabulary as follows: low corresponds to Universal-target tools, medium to Moderate-risk and Moderate-High-risk, high to High-risk, and YA (with UK sub-tiers YA_18 and YA_21) to Young adults. The Framework's New accounts and Research/system development values do not map to architecture risk tiers because they describe targeting concepts not used at the deployment level.

1.3 File structure

Each architecture file (05.1 and 05.2) contains the same five sheets:

_index. File metadata, document type definitions, codebook key, and quick-reference for the controlled vocabularies used across the other sheets.

tool_variants. All deployed tool variants in the architecture, organised by tool. Each row specifies one variant's configuration (risk tier, content type, threshold, limit-set mode, increase/decrease rules, cooldown, specification status).

excluded_tools. Tools considered during Stage 3 selection but not built. Each excluded variant is recorded with its exclusion class and reason.

policy_rules. System-level rules governing tool delivery: cross-tool scope, threshold triggers, limit-set modes, cooldowns, tailoring formulae, refresh timing, and Young Adult overlay.

message_templates. Verbatim player-facing copy for variants where copy was developed. Each row specifies a single message at a single delivery point, with stage, surface, content type, button labels, and full copy text.

1.4 How to read this codebook

Section 2 documents the variant ID structure: the format used to identify every tool variant in the architecture and how its components encode jurisdiction, risk tier, governance, and tool category.

Sections 3 to 7 document each of the five sheets in turn. For each sheet, the codebook gives: purpose, columns and their definitions, controlled vocabularies (where applicable), and the decision rules applied during specification.

Section 8 documents the cross-jurisdictional differences between the UK and NL architectures: where they diverge and why.

2. Variant ID structure

Every tool variant in the architecture has a unique identifier of the following form:

[JUR].PA.[tier].[M/O].[category.tool#].[variant#]

2.1 Components

[JUR]	Jurisdiction. Two values: UK (United Kingdom; SunVegas, regulated under the Licence Conditions and Codes of Practice) or NL (Netherlands; Holland Casino Online, regulated under the Dutch Remote Gambling Act, KOA 2021).
PA	Player-facing Active intervention. Distinguishes architecture variants from system-internal logic; reserved for future expansion if other variant types are introduced.
[tier]	Risk tier. Values: 1 (low risk), 2 (medium risk), 3 (high risk), or YA (Young Adult; applied as overlay independent of risk tier). The UK architecture also uses YA_18 and YA_21 for the Loss Limit tool, where Young Adult thresholds differ by sub-age band.
[M/O]	Mandatory or Optional assignment. M = required by jurisdiction-specific regulation or by IMS specification; O = available as supplementary configuration but not required.
[category.tool#]	Framework category code paired with the tool number within that category. Category coding: 1.x = behavioural control tools (limits, breaks, messaging); 2.x = informational/educational tools; 3.x = self-assessment tools.
[variant#]	Variant number within the tool-tier combination. Distinguishes configurations of the same tool at the same tier (e.g., variant 1 = PPF content; variant 2 = EPF content).

2.2 Worked examples

UK.PA.3.M.1.1.1: United Kingdom, player-facing active intervention, R3 (high risk) tier, Mandatory assignment, Deposit Limit (category 1, tool 1), variant 1.

NL.PA.YA.M.1.4.1: Netherlands, player-facing active intervention, Young Adult overlay, Mandatory assignment, Bonus Ban (category 1, tool 4), variant 1. Note: this variant appears only in the NL excluded_tools sheet, since Bonus Ban is excluded from the NL architecture under KOA 2021 regulatory provisions.

2.3 Stability and reuse

Variant IDs are stable. Once assigned, a variant ID is never reused or reassigned. Excluded tool variants retain their assigned IDs and are documented in the excluded_tools sheet rather than removed from the ID space, preserving the audit trail of Stage 3 selection decisions.

3. tool_variants sheet

The main data sheet of each architecture file. One row per variant. Documents the operational specification of every tool variant deployed in the architecture.

3.1 Columns

3.1.1 tool_name

Purpose	Canonical name of the tool to which this variant belongs.
Format	Lowercase string with underscores (e.g., deposit_limit, login_playtime_limit).
Decision rules	Tool names are stable across jurisdictions: a tool with the same canonical name is the same tool concept in both UK and NL architectures, even where its variants differ. The UK and NL architectures share 12 tools by canonical name; the UK additionally builds Bonus Ban and Promo Ban (excluded from NL); the NL additionally builds Automatic Withdrawal Limit (AWL, excluded from UK).

3.1.2 tool_id

Purpose	Category and tool number identifier (the [category.tool#] component of the variant ID).
Format	Decimal string in the form X.Y where X is the category number (1, 2, or 3) and Y is the tool number within that category.
Decision rules	Tool IDs follow the framework category structure. 1.x = behavioural control tools, 2.x = informational/educational tools, 3.x = self-assessment tools. Tool IDs are stable across jurisdictions.

3.1.3 risk_level

Purpose	Risk tier at which this variant operates.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary	low, medium, high, YA (the tool_variants sheet uses these values; the message_templates sheet uses 1, 2, 3, YA. These are equivalent).
Decision rules	Risk tier is the primary unit of design: each tool is operationalised separately for low, medium, and high tiers. The Young Adult overlay (YA) applies independently of risk tier and supersedes standard tier configurations for players meeting the YA regulatory threshold. The UK architecture additionally uses YA_18 and YA_21 for the Loss Limit tool, reflecting age-band-specific thresholds in UK regulation.

3.1.4 variant_id

Purpose	Unique identifier for this variant (the full variant ID).
Format	Compound string in the form [JUR].PA.[tier].[M/O].[category.tool#].[variant#]: see Section 2.
Decision rules	Each variant_id is unique across the architecture. Excluded variants retain their assigned IDs in the excluded_tools sheet.

3.1.5 specification_status

Purpose	Indicates whether the variant is fully specified for production deployment, or specified at design level but not built within the project's timeline.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary	fully_specified, specified_not_built
Decision rules	Variants marked fully_specified have a complete operational specification: design parameters set, message copy developed (where applicable), policy rules in place. Variants marked specified_not_built have a complete operational specification but were not built within the project timeline (e.g., Cheat Sheet variants in both architectures). UK distribution: 69 fully_specified (73.4%), 25 specified_not_built (26.6%). NL distribution: 72 fully_specified (82.8%), 15 specified_not_built (17.2%).

3.1.6 content_type

Purpose	Indicates the messaging content format for this variant.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary	PPF, EPF, unified, cognitive_distractor_1, cognitive_distractor_2
Decision rules	PPF (Personalised Player Feedback) tailors feedback to the individual player's data: a player's own deposit amounts, time-on-site, or limit values are interpolated into messaging copy. EPF (Enhanced Player Feedback) builds on PPF by integrating algorithmic system-derived data (behavioural risk score, normative comparison). At R3 (high risk), the PPF/EPF split collapses into a single 'unified' content type, reflecting an operational simplification: high-risk-tier messaging uses standardised wording rather than personalised variation. cognitive_distractor_1 and cognitive_distractor_2 are content variants used only in the Session Cooldown tool, where a non-gambling distractor task is embedded in the break interface.

3.1.7 threshold_enabled

Purpose	Indicates whether this variant fires on a threshold-based trigger.
Format	Boolean (True/False or 1/0).
Decision rules	When True, the variant fires when the player crosses a defined threshold (typically a percentage of their set limit). When False, the variant fires on a different trigger logic specified in the policy_rules sheet (e.g., user action, registration, scheduled event). The most common threshold is 0.8 (80% of the player's set cap), used for spend-elapsed and time-elapsed pop-ups.

3.1.8 threshold_level

Purpose	The threshold value at which a threshold-enabled variant fires.
Format	Numeric (typically 0.25 or 0.8) or text (where threshold is non-numeric, e.g., player_defined or system_1.5x).
Decision rules	Threshold values are typically set at 0.8 (80% of cap) for warning-stage messaging and 1.0 (100%) for breach-stage messaging. Text values appear where the threshold is set by another mechanism rather than a fixed percentage; in those cases, the relevant policy_rules entry specifies how the threshold is determined.

3.1.9 limit_set_mode

Purpose	Indicates how the variant's parameter values are set.
----------------	---

Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary (UK uses 10 distinct modes; NL uses 3)	player_defined; player_defined_required; player_choice; player_choice_15_30_45_60min; player_elected_1_2_3hr_interval; player_elected_30_60CD; player_elected_30_60_90CD; system_1.5x; system_1.5x_daily; system_enforced
Decision rules	player_defined and player_defined_required give the player full control of the limit value within regulatory bounds; the latter requires the player to set a value before play (used where regulation mandates limit-setting at registration). player_elected and player_choice variants offer the player a constrained selection (e.g., 1, 2, or 3-hour intervals). system_1.5x is an adaptive system-set limit at 1.5x the player's recent average activity; system_1.5x_daily applies the same logic to a daily window. system_enforced applies a non-negotiable system-set value. The UK architecture exposes 10 distinct modes; the NL architecture exposes 3, reflecting KOA 2021's prescription that limits be either player-defined or system-set at a specified multiplier.

3.1.10 increase, decrease, cooldown_h

Purpose	Together specify the asymmetric increase/decrease flow for the variant.
Format	increase and decrease: Boolean (True/False, indicating whether the player can request an increase or decrease respectively). cooldown_h: numeric value indicating the mandatory delay (in hours) before an increase request takes effect.
Decision rules	Across both architectures, decrease is uniformly True with immediate effect: players can always reduce limits without delay. increase is variable: typically True at R1 and R2 with a tier-specific cooldown, and False or strictly delayed at R3 (high risk). UK uses 6 distinct cooldown values (24h, 48h, 168h, plus disable_24h, disable_24h_daily_168h_weekly, and 'none'); NL uniformly applies 168h across all tiers, reflecting the KOA 2021 mandate. This asymmetric structure (decreases easy, increases gated) operationalises the framework's Reversibility dimension; the tier-specific tightening operationalises the framework's adaptive design principle.

4. excluded_tools sheet

Documents tools considered during Stage 3 selection but not built. Each excluded variant is recorded with its full design specification preserved (the variant could be deployed if the exclusion reason is removed) plus a documented exclusion class and reason.

4.1 Columns

4.1.1 tool_code

The full variant ID assigned to the excluded variant. Excluded variants retain their IDs to preserve the audit trail of Stage 3 selection.

4.1.2 tool_name, category_id, risk_level

Same definitions as in tool_variants (Section 3). These fields document what the excluded tool would have been if built.

4.1.3 exclusion_class

Purpose	Categorical reason for exclusion.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary	regulatory, operator, technical, evidence
Decision rules	regulatory: the tool is excluded because regulation either prohibits it outright or already

provides equivalent protection (NL examples: Bonus Ban and Promo Ban excluded under KOA 2021 promotional restrictions). operator: the tool is excluded due to operator-specific business decisions (no current examples in either architecture). technical: the tool is excluded because of infrastructure constraints (UK example: AWL excluded because UK banking infrastructure does not support the required automatic-debit operation). evidence: the tool is excluded because the evidence base did not support inclusion at acceptable confidence (no current examples in either architecture).

4.1.4 exclusion_reason

Free-text description of the specific exclusion rationale, citing the regulatory provision, technical limitation, or operator policy that drives the exclusion. Sufficiently detailed that the rationale can be evaluated without consulting external sources.

4.1.5 specification_status

All excluded variants are coded `specified_not_built`. The specification work was completed (the variant could be deployed if the exclusion reason were removed); only the build step did not proceed.

4.1.6 notes

Free-text supplementary notes, typically clarifying the specific configuration of the variant (e.g., ‘R1 v1 PPF: Mandatory; trigger per refresh event’) and the relationship to its counterpart in the other jurisdiction’s architecture.

4.2 Cross-architecture pattern

The UK architecture excludes 1 tool (AWL) under technical class, generating 6 excluded variants. The NL architecture excludes 2 tools (Bonus Ban, Promo Ban) under regulatory class, generating 12 excluded variants. The four-class exclusion framework is illustrated by these two patterns: the NL regulator removes tools by superseding them, while UK infrastructure removes tools by being unable to support them.

5. policy_rules sheet

System-level rules governing tool delivery within the architecture. Each row specifies one rule with its source, scope, and value. Rules are organised into thematic sections; the UK architecture has 78 rules across 10 sections, the NL architecture has 133 rules across 12 sections.

5.1 Columns

5.1.1 rule_id

Compound identifier in the form `SECTION_NNN` (e.g., `SCOPE_001`, `COOLDOWN_004`). Stable across jurisdictions where the rule’s logical position is the same.

5.1.2 tool

Canonical tool name to which the rule applies, or ‘all’ for cross-tool rules.

5.1.3 tier

Risk tier(s) to which the rule applies. Values: all, R1, R2, R3, R2/R3, YA, YA (under 24).

5.1.4 rule_name

Short label identifying the rule within its section (e.g., Assignment, Threshold, Cooldown, Tailoring formula).

5.1.5 description

Free-text description of the rule. For tailoring formulae, this includes the mathematical specification used at run-time.

5.1.6 value

The rule's resolved value. For Boolean rules: True/False. For numeric rules: the numeric value (e.g., 168 for cooldown hours). For categorical rules: the controlled-vocabulary value (e.g., Mandatory). For formula-based rules: the formula expression.

5.1.7 status

Purpose	Indicates whether the rule has been confirmed by the operator or is awaiting sign-off.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary	CONFIRMED, NEEDS_CONFIRM
Decision rules	CONFIRMED rules have been signed off by the operator's compliance and product teams. NEEDS_CONFIRM rules remain pending operator confirmation; the rule's draft value is recorded but should be treated as provisional. UK: all 78 rules CONFIRMED. NL: 131 of 133 CONFIRMED, 2 NEEDS_CONFIRM (one in Login/Playtime Tailoring Formula, one in Young Adult Rules).

5.1.8 source

Purpose	Indicates the authority or evidence base grounding the rule.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary (8 distinct values across both architectures)	Data, IMS_spec, IMS + Data, KOA_2021, KOA_2021 + IMS_spec, LCCP, HC_voluntary_2022, refresh_calendar
Decision rules	Data: empirical operator data informed the rule (e.g., observed player behaviour distributions). IMS_spec: the rule comes from the operator's Internal Management System specification. IMS + Data: combination of empirical data and IMS specification. KOA_2021: Dutch Remote Gambling Act 2021 mandates the rule (NL only). KOA_2021 + IMS_spec: KOA grounding plus operator implementation specification (NL only). LCCP: UK Gambling Commission Licence Conditions and Codes of Practice mandate the rule (UK only). HC_voluntary_2022: Holland Casino voluntary commitment from 2022 (NL only). refresh_calendar: cross-architecture reference to the refresh event calendar.

5.2 Section structure

5.2.1 UK section structure (10 sections, 78 rules)

- CROSS-TOOL SCOPE (5 rules): assignment status (Mandatory/Optional) per tool
- THRESHOLD TRIGGERS (4 rules): when threshold-enabled variants fire
- LIMIT SET MODE (12 rules): limit_set_mode logic per tool and tier
- COOLDOWN & INCREASE RULES (18 rules): asymmetric increase/decrease flow per tool and tier
- DEPOSIT LIMIT TAILORING FORMULA (R2/R3) (10 rules): system_1.5x and related adaptive formulae
- LOSS LIMIT TAILORING FORMULA (R2 v3/v4 and R3) (7 rules)
- BET LIMIT TAILORING FORMULA (R2 v3/v4 and R3) (6 rules)
- LOGIN/PLAYTIME RULES (6 rules)

- REFRESH & TIMING (4 rules)
- YOUNG ADULT (YA) RULES (6 rules)

5.2.2 NL section structure (12 sections, 133 rules)

- CROSS-TOOL SCOPE (12 rules)
- THRESHOLD TRIGGERS (6 rules)
- LIMIT SET MODE (19 rules)
- COOLDOWN & INCREASE RULES (30 rules)
- DEPOSIT LIMIT TAILORING FORMULA (R2/R3) (10 rules)
- LOGIN/PLAYTIME TAILORING FORMULA (R2/R3) (12 rules)
- AWL TAILORING FORMULA (R2/R3): AWT & ALB (12 rules)
- LOSS LIMIT TAILORING FORMULA (R2 v3/v4 and R3) (7 rules)
- BET LIMIT TAILORING FORMULA (R2 v3/v4 and R3) (7 rules)
- DEPOSIT COUNT LIMIT TAILORING FORMULA (R2 v3/v4 and R3) (7 rules)
- REFRESH & TIMING (5 rules)
- YOUNG ADULT (YA) RULES (6 rules)

The NL architecture has more sections and more rules because each tailored limit type receives its own tailoring-formula section. The UK architecture collapses several tailoring formulae into shared rules, reflecting greater operator design discretion under LCCP. NL also expands the YA rules section to accommodate KOA 2021's age-specific provisions for players under 24.

6. message_templates sheet

Verbatim player-facing copy for variants where copy was developed. Each row specifies a single message at a single delivery point. UK: 192 templates across 10 tools. NL: 215 templates across 11 tools.

6.1 Columns

6.1.1 specification_status, variant_id, tool_name, risk_level

Same definitions as in tool_variants (Section 3). Templates are linked to their parent variant via variant_id.

6.1.2 message_stage

Purpose	Indicates the user-flow event at which the message is delivered.
Format	Single value drawn from a controlled vocabulary (19 distinct stage names across both architectures).
Controlled vocabulary (in both)	breach_100_popup, decrease_toaster, end_confirmation_popup, increase_request_popup, pending_increase_popup, threshold_25_popup, threshold_80_popup
UK-only stages	break_disablement_popup, break_enablement_toaster, break_initiation_popup_onetime, break_initiation_popup_regular, login_reminder_popup, session_interval_popup
NL-only stages	break_activation_toaster, break_cancellation_popup, break_initiation_one_time_popup, break_initiation_recurring_popup, rc_popup, reminder_popup
Decision rules	Stage names are descriptive of the user-flow event. UK and NL use different naming conventions for some break-related stages (e.g., UK 'break_initiation_popup_onetime' vs. NL 'break_initiation_one_time_popup'); the underlying stages are functionally equivalent and the divergence is operational rather than design-driven. Stage names operationalise

the Stage sub-vocabulary of the framework's Trigger dimension at higher granularity than the framework's vocabulary alone supports.

6.1.3 content_type

Same definition as in tool_variants (Section 3). PPF, EPF, unified, cognitive_distractor_1, cognitive_distractor_2.

6.1.4 message_surface

Purpose	Indicates the UI surface on which the message is displayed.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary	modal_popup, toast, static_page, error_message
Decision rules	modal_popup interrupts player flow and requires interaction; toast provides non-interruptive notification; static_page is non-interruptive informational content; error_message indicates a system error condition.

6.1.5 spec_button_labels

Comma-separated list of button labels presented in the message. Reflects the architecture's choice-response design principle: each message offers the player meaningful interaction options where the surface permits. Examples: 'Review My Limits | Continue Play | Exit Icon' or 'Auto-close | Dismiss | Link: RG Support'.

6.1.6 closure_type

Purpose	Indicates how the message is closed by the player or system.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary	manual_close_exit_icon, auto_close_or_dismiss, manual_close_required_action
Decision rules	Closure type captures whether the player must take a specific action to dismiss the message (required_action) or can dismiss freely (exit_icon, auto_close_or_dismiss). Required-action closures are used for high-importance interruptions where passive dismissal is not appropriate.

6.1.7 message_sender

Purpose	Indicates which backend system originates the message.
Format	Single value drawn from a controlled vocabulary.
Controlled vocabulary	IMS, Engagement
Decision rules	IMS (Internal Management System) is the operator's backend decision engine that applies regulatory and limit-related logic. Engagement is the engagement/CRM layer, typically used for behavioural nudges and longer-form RG communications. The split distinguishes regulated/compliance messaging (IMS) from voluntary/educational messaging (Engagement).

6.1.8 message_text

The full verbatim copy for the message. Includes interpolation placeholders (e.g., {amount}, {limit_value}, {time_elapsed}) that are populated at run-time with player-specific data for PPF and EPF content types. Mean word count: UK 63.9 (range 29–115); NL 61.4 (range 29–115). Word count

distributions are substantively similar across the two architectures, reflecting translation-equivalent copy density.

6.2 Currency and language

UK	Language: en-GB. Currency: currency_gbp. Single-language and single-currency throughout the architecture.
NL	Language: nl-NL. Currency: currency_eur. Single-language and single-currency throughout the architecture.

Localisation is set at the architecture level rather than per-tool: every message in 05.1 is in en-GB; every message in 05.2 is in nl-NL.

7. Controlled vocabularies: consolidated reference

The architecture files use the following controlled vocabularies. Each is documented in the relevant column section above; this section provides a single consolidated reference.

7.1 risk_level

low. also coded 1

medium. also coded 2

high. also coded 3

YA. Young Adult overlay (UK and NL)

YA_18, YA_21. UK Loss Limit only, sub-age-band overlays

7.2 specification_status

fully_specified. variant has complete operational specification, including message copy where applicable

specified_not_built. variant has complete operational specification but was not built within the project's timeline

7.3 mandatory_optional

M. Mandatory: tool required by jurisdiction-specific regulation or by IMS specification

O. Optional / add-on: available as supplementary configuration but not required

M_overlay. Mandatory Overlay Layer: rule-based override applied on top of standard tier configurations (used for YA tier and certain regulatory triggers)

7.4 content_type

PPF. Personalised Player Feedback (player's own data interpolated into copy)

EPF. Enhanced Player Feedback (PPF plus algorithmic system-derived data)

unified. used at R3 only; collapses PPF/EPF distinction into a single standardised content variant

cognitive_distractor_1, cognitive_distractor_2. Session Cooldown only; non-gambling distractor content variants

7.5 limit_set_mode

UK uses 10 distinct modes; NL uses 3.

player_defined / player_defined_required. full player control of limit value

player_choice / player_choice_15_30_45_60min. player selects from constrained option set

player_elected_1_2_3hr_interval / player_elected_30_60CD / player_elected_30_60_90CD. player elects from preset interval options (Session Cooldown only)

system_1.5x / system_1.5x_daily. system-set adaptive limit at 1.5x recent average activity

system_enforced. non-negotiable system-set value

7.6 exclusion_class

regulatory. tool excluded because regulation prohibits or already supersedes it

operator. tool excluded due to operator-specific business decisions

technical. tool excluded due to infrastructure constraints

evidence. tool excluded because evidence base did not support inclusion

7.7 status (policy_rules)

CONFIRMED. operator-confirmed and signed off

NEEDS_CONFIRM. provisional, awaiting operator sign-off

7.8 source (policy_rules)

Data. empirical operator data

IMS_spec. operator Internal Management System specification

IMS + Data. combination

KOA_2021. Dutch Remote Gambling Act 2021 (NL only)

KOA_2021 + IMS_spec. combination (NL only)

LCCP. UK Licence Conditions and Codes of Practice (UK only)

HC_voluntary_2022. Holland Casino voluntary commitment (NL only)

refresh_calendar. refresh event calendar reference

7.9 message_surface

modal_popup. interruptive overlay requiring player interaction

toast. non-interruptive notification

static_page. non-interruptive informational content

error_message. system error indication

7.10 closure_type

manual_close_exit_icon. player closes via exit icon

auto_close_or_dismiss. message dismisses automatically or via passive dismissal

manual_close_required_action. player must take a specific action to close

7.11 message_sender

IMS. Internal Management System (regulated/compliance messaging)

Engagement. Engagement/CRM layer (voluntary/educational messaging)

8. Cross-jurisdictional differences

This section provides a structural reference for cross-jurisdictional differences in tool inventory, variant counts, and parameter values. The methodological framing of these differences (regulatory rigidity vs operator discretion, sources of parameter variation, exclusion logic) is documented in 05.4 Section 8.

8.1 Tool inventory

Shared (n=12)	Deposit Limit, Loss Limit, Bet Limit, Login/Playtime Limit, Deposit Count Limit, Scheduled Break, Reality Check, Session Cooldown, RG Homepage, Cheat Sheet, Positive Play Self-Assessment, Dark Flow Self-Assessment
UK only	Bonus Ban, Promo Ban (excluded from NL on regulatory grounds: KOA 2021 already restricts bonuses)
NL only	Automatic Withdrawal Limit (AWL); excluded from UK on technical grounds (UK banking infrastructure)

8.2 Variant counts

UK	94 variants across 14 tools
NL	87 variants across 13 tools
Variant count parity by tool	10 of 12 shared tools have identical variant counts in both architectures. Two diverge: Loss Limit (UK 12, NL 8); Login/Playtime Limit (UK 6, NL 8).

8.3 Parameter divergence

Increase cooldown (hours)	UK uses 6 distinct values (24h, 48h, 168h, plus disable_24h, disable_24h_daily_168h_weekly, none); NL uniformly applies 168h across all tiers.
Limit-set modes	UK uses 10 distinct modes; NL uses 3.
Risk tier granularity	UK uses 6 distinct tier values (low, medium, high, YA, YA_18, YA_21); NL uses 4 (low, medium, high, YA).
