

Anthropic API

为了满足大家对 Anthropic API 生态的使用需求，我们的 API 新增了对 Anthropic API 格式的支持，其 `base_url` 为 `https://api.deepseek.com/anthropic`。

通过简单的配置，即可将 DeepSeek 的能力，接入到 Anthropic API 生态中。

将 DeepSeek 模型接入 Claude Code

请参考[接入 Agent 工具](#)

通过 Anthropic API 调用 DeepSeek 模型

1. 安装 Anthropic SDK

```
pip install anthropic
```

2. 配置环境变量

```
export ANTHROPIC_BASE_URL=https://api.deepseek.com/anthropic
export ANTHROPIC_API_KEY=${YOUR_API_KEY}
```

3. 调用 API

```
import anthropic

client = anthropic.Anthropic()

message = client.messages.create(
    model="deepseek-v4-pro",
    max_tokens=1000,
    system="You are a helpful assistant.",
    messages=[
        {
```

```
        "role": "user",
        "content": [
            {
                "type": "text",
                "text": "Hi, how are you?"
            }
        ]
    }
]
)
print(message.content)
```

注意：当您给 DeepSeek 的 Anthropic API 传入不支持的模型名时，API 后端会自动将其映射到 `deepseek-v4-flash` 模型。

Anthropic 模型映射

您在使用 Anthropic API 时，我们会对您传入的 claude 模型名进行映射：

- claude-opus 开头的模型，会映射到 deepseek-v4-pro
- claude-haiku、claude-sonnet 开头的模型，会映射到 deepseek-v4-flash

通过这样的映射，您在使用新版 Claude Desktop APP 的 developer 模式时，可以绕过 APP 对模型名的限制，只需改动 `base_url` 和 `api_key`，即可在其中接入 DeepSeek 模型。

Anthropic API 兼容性细节

HTTP Header

Field	Support Status
anthropic-beta	Ignored
anthropic-version	Ignored
x-api-key	Fully Supported

Simple Fields

Field	Support Status
model	Use DeepSeek Model Instead
max_tokens	Fully Supported
container	Ignored
mcp_servers	Ignored
metadata	<code>user_id</code> is supported, others are ignored Please refer to Rate Limit & Isolation for more information about <code>user_id</code> parameter.
service_tier	Ignored
stop_sequences	Fully Supported
stream	Fully Supported
system	Fully Supported
temperature	Fully Supported (range [0.0 ~ 2.0])
thinking	Supported (<code>budget_tokens</code> is ignored)
output_config	Only <code>effort</code> is supported
top_k	Ignored
top_p	Fully Supported

Tool Fields

tools

Field	Support Status
name	Fully Supported
input_schema	Fully Supported
description	Fully Supported
cache_control	Ignored

tool_choice

Value	Support Status
none	Fully Supported
auto	Supported (disable_parallel_tool_use is ignored)
any	Supported (disable_parallel_tool_use is ignored)
tool	Supported (disable_parallel_tool_use is ignored)

Message Fields

Field	Variant	Sub-Field	Support Status
content	string		Fully Supported
	array, type="text"	text	Fully Supported
		cache_control	Ignored
		citations	Ignored
	array, type="image"		Not Supported

	array, type = "document"		Not Supported
	array, type = "search_result"		Not Supported
	array, type = "thinking"		Supported
	array, type="redacted_thinking"		Not Supported
	array, type = "tool_use"	id	Fully Supported
		input	Fully Supported
		name	Fully Supported
		cache_control	Ignored
	array, type = "tool_result"	tool_use_id	Fully Supported
		content	Fully Supported
		cache_control	Ignored
		is_error	Ignored
	array, type = "server_tool_use"		Supported
	array, type = "web_search_tool_result"		Supported
	array, type = "code_execution_tool_result"		Not Supported
	array, type = "mcp_tool_use"		Not Supported
	array, type = "mcp_tool_result"		Not Supported
	array, type = "container_upload"		Not Supported