

Model & Method	# Trainable									
	Parameters	MNLI	SST-2	MRPC	CoLA	QNLI	QQP	RTE	STS-B	Avg.
RoB _{base} (FT)*	125.0M	87.6	94.8	90.2	63.6	92.8	91.9	78.7	91.2	86.4
RoB _{base} (BitFit)*	0.1M	84.7	93.7	92.7	62.0	91.8	84.0	81.5	90.8	85.2
RoB _{base} (Adpt ^D)*	0.3M	87.1 $\pm$.0	94.2 $\pm$.1	88.5 $\pm$ 1.1	60.8 $\pm$.4	93.1 $\pm$.1	90.2 $\pm$.0	71.5 $\pm$ 2.7	89.7 $\pm$.3	84.4
RoB _{base} (Adpt ^D)*	0.9M	87.3 $\pm$.1	94.7 $\pm$.3	88.4 $\pm$.1	62.6 $\pm$.9	93.0 $\pm$.2	90.6 $\pm$.0	75.9 $\pm$ 2.2	90.3 $\pm$.1	85.4
RoB _{base} (LoRA)	0.3M	87.5 $\pm$.3	95.1$\pm$.2	89.7 $\pm$.7	63.4 $\pm$ 1.2	93.3$\pm$.3	90.8 $\pm$.1	86.6$\pm$.7	91.5$\pm$.2	87.2
RoB _{large} (FT)*	355.0M	90.2	96.4	90.9	68.0	94.7	92.2	86.6	92.4	88.9
RoB _{large} (LoRA)	0.8M	90.6$\pm$.2	96.2 $\pm$.5	90.9$\pm$1.2	68.2$\pm$1.9	94.9$\pm$.3	91.6 $\pm$.1	87.4$\pm$2.5	92.6$\pm$.2	89.0
RoB _{large} (Adpt ^P)†	3.0M	90.2 $\pm$.3	96.1 $\pm$.3	90.2 $\pm$.7	68.3$\pm$1.0	94.8$\pm$.2	91.9$\pm$.1	83.8 $\pm$ 2.9	92.1 $\pm$.7	88.4
RoB _{large} (Adpt ^P)†	0.8M	90.5$\pm$.3	96.6$\pm$.2	89.7 $\pm$ 1.2	67.8 $\pm$ 2.5	94.8$\pm$.3	91.7 $\pm$.2	80.1 $\pm$ 2.9	91.9 $\pm$.4	87.9
RoB _{large} (Adpt ^H)†	6.0M	89.9 $\pm$.5	96.2 $\pm$.3	88.7 $\pm$ 2.9	66.5 $\pm$ 4.4	94.7 $\pm$.2	92.1 $\pm$.1	83.4 $\pm$ 1.1	91.0 $\pm$ 1.7	87.8
RoB _{large} (Adpt ^H)†	0.8M	90.3 $\pm$.3	96.3 $\pm$.5	87.7 $\pm$ 1.7	66.3 $\pm$ 2.0	94.7 $\pm$.2	91.5 $\pm$.1	72.9 $\pm$ 2.9	91.5 $\pm$.5	86.4
RoB _{large} (LoRA)†	0.8M	90.6$\pm$.2	96.2 $\pm$.5	90.2$\pm$1.0	68.2 $\pm$ 1.9	94.8$\pm$.3	91.6 $\pm$.2	85.2$\pm$1.1	92.3$\pm$.5	88.6
DeB _{XXL} (FT)*	1500.0M	91.8	97.2	92.0	72.0	96.0	92.7	93.9	92.9	91.1
DeB _{XXL} (LoRA)	4.7M	91.9$\pm$.2	96.9 $\pm$.2	92.6$\pm$.6	72.4$\pm$1.1	96.0$\pm$.1	92.9$\pm$.1	94.9$\pm$.4	93.0$\pm$.2	91.3