Array Practice Lab (Lab 03)

Part 1: Understanding Array Basics

Refer to the lab03 PowerPoint slides to understand the fundamentals of arrays in C++.

Part 2: Simple Array Application

Example: Find the number of the smaller numbers (LeetCode 1365)

1394. Find Lucky Integer in an Array

Easy | Topics | Companies | Hint

Given an array of integers `arr`, a **lucky integer** is an integer that has a frequency in the array equal to its value.

Return *the largest* ***lucky integer*** *in the array*. If there is no **lucky integer** return `-1`.

```
class Solution {

public:

    int findLucky(vector<int>& arr) {

        // 題目限制數字最大為 500, 設定501 的陣列
```

```
        // 初始化為 0
        vector<int> count(501, 0);
        // 統計每個數字出現的次數
        for (int num : arr) {
            count[num]++;
        }
        // 從 500 開始往回找（由大到小）
        // 這樣第一個符合條件的「幸運數字」就是最大的
        for (int i = 500; i >= 1; i--) {
            if (count[i] == i) {
                return i;
            }
        }
        // 如果迴圈跑完都沒找到，回傳 -1
        return -1;
    }
};
```

描述 社論 解決方案 提交

1394. 在陣列中找出幸運整數

簡單的 主題 公司 暗示

給定一個整數數組 `arr`，**幸運整數**是指在該數組中出現次數等於其值的整數。

傳回*數組中最大的**幸運整數***。如果沒有**幸運整數**，則傳回空值 `-1`。

例 1：

> **輸入：** `arr = [2,2,3,4]`
> **輸出：** `2`
> **解釋：** 陣列中唯一的幸運數字是 `2`，因為 `frequency[2] == 2`。

例 2：

> **輸入：** `arr = [1,2,2,3,3,3]`
> **輸出：** `3`
> **說明：** `1`、`2` 和 `3` 都是幸運數字，傳回其中最大的數字。

例 3：

> **輸入：** `arr = [2,2,2,3,3]`
> **輸出：** `-1`
> **解釋：** 陣列中沒有幸運數字。

限制條件：

- `1 <= arr.length <= 500`
- `1 <= arr[i] <= 500`

GoDaddy

1.6K 176 0 在線

程式碼

C++ 汽車

```cpp
class Solution {
public:
    int findLucky(vector<int>& arr) {
        // 題目限制數字最大為 500，設定 501 的陣列
        // 初始化為 0
        vector<int> count(501, 0);

        // 統計每個數字出現的次數
        for (int num : arr) {
            count[num]++;
        }

        // 從 500 開始往回找（由大到小）
        // 這樣第一個符合條件的「幸運數字」就是最大的
```

已儲存 第 1 行，第 1 列

測試用例 測試結果

公認 運行時間：0 毫秒

案例 1 案例 2 案例 3

輸入

arr =
[2,2,3,4]

輸出

2

預期的

2

貢獻一個測試用例