


Bayesian Decision Theory

Lecture notes by Ethem Alpaydın
Introduction to Machine Learning (Boğaziçi Üniversitesi)



Probability and Inference

- Result of tossing a coin is $\in \{\text{Heads}, \text{Tails}\}$
- Random var $X \in \{1, 0\}$

$$\text{Bernoulli: } P\{X=1\} = p_o^X (1 - p_o)^{(1-X)}$$

- Sample: $\mathbf{X} = \{x^t\}_{t=1}^N$

$$\text{Estimation: } p_o = \# \{\text{Heads}\} / \# \{\text{Tosses}\} = \sum_t x^t / N$$

- Prediction of next toss:

Heads if $p_o > 1/2$, Tails otherwise

Classification

- Credit scoring: Inputs are income and savings.

Output is low-risk vs high-risk

- Input: $\mathbf{x} = [x_1, x_2]^T$, Output: $C \in \{0, 1\}$

- Prediction: choose $\begin{cases} C = 1 \text{ if } P(C = 1 | x_1, x_2) > 0.5 \\ C = 0 \text{ otherwise} \end{cases}$

or

- choose $\begin{cases} C = 1 \text{ if } P(C = 1 | x_1, x_2) > P(C = 0 | x_1, x_2) \\ C = 0 \text{ otherwise} \end{cases}$

Bayes' Rule

$$\begin{array}{c} \text{posterior} \quad \text{prior} \quad \text{likelihood} \\ \quad \quad \quad \swarrow \quad \searrow \\ P(C | \mathbf{x}) = \frac{P(C) p(\mathbf{x} | C)}{p(\mathbf{x})} \\ \quad \quad \quad \nwarrow \\ \quad \quad \quad \text{evidence} \end{array}$$

$$P(C = 0) + P(C = 1) = 1$$

$$p(\mathbf{x}) = p(\mathbf{x} | C = 1)P(C = 1) + p(\mathbf{x} | C = 0)P(C = 0)$$

$$p(C = 0 | \mathbf{x}) + p(C = 1 | \mathbf{x}) = 1$$

Bayes' Rule: $K > 2$ Classes

$$\begin{aligned} P(C_i | \mathbf{x}) &= \frac{p(\mathbf{x} | C_i)P(C_i)}{p(\mathbf{x})} \\ &= \frac{p(\mathbf{x} | C_i)P(C_i)}{\sum_{k=1}^K p(\mathbf{x} | C_k)P(C_k)} \end{aligned}$$

$$P(C_i) \geq 0 \text{ and } \sum_{i=1}^K P(C_i) = 1$$

choose C_i if $P(C_i | \mathbf{x}) = \max_k P(C_k | \mathbf{x})$

Losses and Risks

- Actions: α_i
- Loss of α_i when the state is C_k : λ_{ik}
- Expected risk (Duda and Hart, 1973)

$$R(\alpha_i | \mathbf{x}) = \sum_{k=1}^K \lambda_{ik} P(C_k | \mathbf{x})$$

choose α_i if $R(\alpha_i | \mathbf{x}) = \min_k R(\alpha_k | \mathbf{x})$

Losses and Risks

In the special case of the *0/1 loss* case

$$\lambda_{ik} = \begin{cases} 0 & \text{if } i = k \\ 1 & \text{if } i \neq k \end{cases}$$
$$\begin{aligned} R(\alpha_i | \mathbf{x}) &= \sum_{k=1}^K \lambda_{ik} P(C_k | \mathbf{x}) \\ &= \sum_{k \neq i} P(C_k | \mathbf{x}) \\ &= 1 - P(C_i | \mathbf{x}) \end{aligned}$$

For minimum risk, choose the most probable class

Losses and Risks: Reject

$$\lambda_{ik} = \begin{cases} 0 & \text{if } i = k \\ \lambda & \text{if } i = K + 1, \quad 0 < \lambda < 1 \\ 1 & \text{otherwise} \end{cases}$$

$$R(\alpha_{K+1} | \mathbf{x}) = \sum_{k=1}^K \lambda P(C_k | \mathbf{x}) = \lambda$$

$$R(\alpha_i | \mathbf{x}) = \sum_{k \neq i} P(C_k | \mathbf{x}) = 1 - P(C_i | \mathbf{x})$$

choose C_i if $P(C_i | \mathbf{x}) > P(C_k | \mathbf{x}) \quad \forall k \neq i$ and $P(C_i | \mathbf{x}) > 1 - \lambda$
reject otherwise


Discriminant Functions

choose C_i if $g_i(\mathbf{x}) = \max_k g_k(\mathbf{x})$

$$g_i(\mathbf{x}) = \begin{cases} -R(\alpha_i | \mathbf{x}) \\ P(C_i | \mathbf{x}) \\ p(\mathbf{x} | C_i)P(C_i) \end{cases}$$

K decision regions $\mathcal{R}_1, \dots, \mathcal{R}_K$

$$\mathcal{R}_i = \{\mathbf{x} | g_i(\mathbf{x}) = \max_k g_k(\mathbf{x})\}$$



$K=2$ Classes

- Dichotomizer ($K=2$) vs Polychotomizer ($K>2$)
- $g(\mathbf{x}) = g_1(\mathbf{x}) - g_2(\mathbf{x})$

$$\text{choose } \begin{cases} C_1 & \text{if } g(\mathbf{x}) > 0 \\ C_2 & \text{otherwise} \end{cases}$$