

# MA7010 – Number Theory for Cryptography - Assignment 1

Ajeesh Thattukunnel Vijayan

January 11<sup>th</sup> 2024

## 1 Notes

## 2 Answers

1. Lower Range = 2800, Upper Range = 3100.

- (a) List the elements of the set A = all primes p in the range, B = all composite numbers in the range.

**Answer:**

$A = [2801, 2803, 2819, 2833, 2837, 2843, 2851, 2857, 2861, 2879, 2887, 2897, 2903, 2909, 2917, 2927, 2939, 2953, 2957, 2963, 2969, 2971, 2999, 3001, 3011, 3019, 3023, 3037, 3041, 3049, 3061, 3067, 3079, 3083, 3089]$

$B = [2800, 2802, 2804, 2805, 2806, 2807, 2808, 2809, 2810, 2811, 2812, 2813, 2814, 2815, 2816, 2817, 2818, 2820, 2821, 2822, 2823, 2824, 2825, 2826, 2827, 2828, 2829, 2830, 2831, 2832, 2834, 2835, 2836, 2838, 2839, 2840, 2841, 2842, 2844, 2845, 2846, 2847, 2848, 2849, 2850, 2852, 2853, 2854, 2855, 2856, 2858, 2859, 2860, 2862, 2863, 2864, 2865, 2866, 2867, 2868, 2869, 2870, 2871, 2872, 2873, 2874, 2875, 2876, 2877, 2878, 2880, 2881, 2882, 2883, 2884, 2885, 2886, 2888, 2889, 2890, 2891, 2892, 2893, 2894, 2895, 2896, 2898, 2899, 2900, 2901, 2902, 2904, 2905, 2906, 2907, 2908, 2910, 2911, 2912, 2913, 2914, 2915, 2916, 2918, 2919, 2920, 2921, 2922, 2923, 2924, 2925, 2926, 2928, 2929, 2930, 2931, 2932, 2933, 2934, 2935, 2936, 2937, 2938, 2940, 2941, 2942, 2943, 2944, 2945, 2946, 2947, 2948, 2949, 2950, 2951, 2952, 2954, 2955, 2956, 2958, 2959, 2960, 2961, 2962, 2964, 2965, 2966, 2967, 2968, 2970, 2972, 2973, 2974, 2975, 2976, 2977, 2978, 2979, 2980, 2981, 2982, 2983, 2984, 2985, 2986, 2987, 2988, 2989, 2990, 2991, 2992, 2993, 2994, 2995, 2996, 2997, 2998, 3000, 3002, 3003, 3004, 3005, 3006, 3007, 3008, 3009, 3010, 3012, 3013, 3014, 3015, 3016, 3017, 3018, 3020, 3021, 3022, 3024, 3025, 3026, 3027, 3028, 3029, 3030, 3031, 3032, 3033, 3034, 3035, 3036, 3038, 3039, 3040, 3042, 3043, 3044, 3045, 3046, 3047, 3048, 3050, 3051, 3052, 3053, 3054, 3055, 3056, 3057, 3058, 3059, 3060, 3062, 3063, 3064, 3065, 3066, 3068, 3069, 3070, 3071, 3072, 3073, 3074, 3075, 3076, 3077, 3078, 3080, 3081, 3082, 3084, 3085, 3086, 3087, 3088, 3090, 3091, 3092, 3093, 3094, 3095, 3096, 3097, 3098, 3099, 3100]$

The below images depicts the execution of the code on a powershell terminal:

```
PS D:\workspace\nt-assignments> .\target\debug\nt-assignments.exe list-primes -s 2800 -e 3100
```

Prime Numbers:

| Number | 2851 | 2909 | 2969 | 3037 | 3089 |
|--------|------|------|------|------|------|
| 2801   | 2857 | 2917 | 2971 | 3041 |      |
| 2803   | 2861 | 2927 | 2999 | 3049 |      |
| 2819   | 2879 | 2939 | 3001 | 3061 |      |
| 2833   | 2887 | 2953 | 3011 | 3067 |      |
| 2837   | 2897 | 2957 | 3019 | 3079 |      |
| 2843   | 2903 | 2963 | 3023 | 3083 |      |

Figure 1: Prime Numbers - Code Execution Output

Composite Numbers:

| Number | 2821 | 2842 | 2865 | 2885 | 2907 | 2929 | 2949 | 2973 | 2992 | 3014 | 3035 | 3057 | 3078 | 3100 |
|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 2800   | 2822 | 2844 | 2866 | 2886 | 2908 | 2930 | 2950 | 2974 | 2993 | 3015 | 3036 | 3058 | 3080 |      |
| 2802   | 2823 | 2845 | 2867 | 2888 | 2910 | 2931 | 2951 | 2975 | 2994 | 3016 | 3038 | 3059 | 3081 |      |
| 2804   | 2824 | 2846 | 2868 | 2889 | 2911 | 2932 | 2952 | 2976 | 2995 | 3017 | 3039 | 3060 | 3082 |      |
| 2805   | 2825 | 2847 | 2869 | 2890 | 2912 | 2933 | 2954 | 2977 | 2996 | 3018 | 3040 | 3062 | 3084 |      |
| 2806   | 2826 | 2848 | 2870 | 2891 | 2913 | 2934 | 2955 | 2978 | 2997 | 3020 | 3042 | 3063 | 3085 |      |
| 2807   | 2827 | 2849 | 2871 | 2892 | 2914 | 2935 | 2956 | 2979 | 2998 | 3021 | 3043 | 3064 | 3086 |      |
| 2808   | 2828 | 2850 | 2872 | 2893 | 2915 | 2936 | 2958 | 2980 | 3000 | 3022 | 3044 | 3065 | 3087 |      |
| 2809   | 2829 | 2852 | 2873 | 2894 | 2916 | 2937 | 2959 | 2981 | 3002 | 3024 | 3045 | 3066 | 3088 |      |
| 2810   | 2830 | 2853 | 2874 | 2895 | 2918 | 2938 | 2960 | 2982 | 3003 | 3025 | 3046 | 3068 | 3090 |      |
| 2811   | 2831 | 2854 | 2875 | 2896 | 2919 | 2940 | 2961 | 2983 | 3004 | 3026 | 3047 | 3069 | 3091 |      |
| 2812   | 2832 | 2855 | 2876 | 2898 | 2920 | 2941 | 2962 | 2984 | 3005 | 3027 | 3048 | 3070 | 3092 |      |
| 2813   | 2834 | 2856 | 2877 | 2899 | 2921 | 2942 | 2964 | 2985 | 3006 | 3028 | 3050 | 3071 | 3093 |      |
| 2814   | 2835 | 2858 | 2878 | 2900 | 2922 | 2943 | 2965 | 2986 | 3007 | 3029 | 3051 | 3072 | 3094 |      |
| 2815   | 2836 | 2859 | 2880 | 2901 | 2923 | 2944 | 2966 | 2987 | 3008 | 3030 | 3052 | 3073 | 3095 |      |
| 2816   | 2838 | 2860 | 2881 | 2902 | 2924 | 2945 | 2967 | 2988 | 3009 | 3031 | 3053 | 3074 | 3096 |      |
| 2817   | 2839 | 2862 | 2882 | 2904 | 2925 | 2946 | 2968 | 2989 | 3010 | 3032 | 3054 | 3075 | 3097 |      |
| 2818   | 2840 | 2863 | 2883 | 2905 | 2926 | 2947 | 2970 | 2990 | 3012 | 3033 | 3055 | 3076 | 3098 |      |
| 2820   | 2841 | 2864 | 2884 | 2906 | 2928 | 2948 | 2972 | 2991 | 3013 | 3034 | 3056 | 3077 | 3099 |      |

Figure 2: Composite Numbers - Code Execution Output

### Code Snippet - Prime Number Sieve

```

1
2    /// Returns a boolean representing if the given number is prime or
  not
3    ///
4    /// # Arguments
5    ///
6    /// * 'n' - A BigInt
7    ///
8    /// # Examples
9    ///
10   /// ```
11   /// use crate::primality::is_prime_trial_division_parallel;

```

```

12     /// let is_prime = is_prime_trial_division_parallel(BigInt::from(100
13     u64));
14     /// '''
15     pub fn is_prime_trial_division_parallel(n: &BigInt) -> bool {
16         let (zero, one, _two) = (BigInt::from(0u64), BigInt::from(1u64),
17         BigInt::from(2u64));
18         let three = BigInt::from(3u64);
19
20         // returns true if the number is 2 or 3
21         if n <= &three {
22             return n > &one;
23         }
24
25         if n % 2 == zero || n % 3 == zero {
26             return false;
27         }
28
29         let upper_bound = n.sqrt() + 1; // +1 to get the ceiling value
30
31         if let Some(_divisor) = range_inclusive(BigInt::from(5u64),
32         upper_bound)
33             .par_bridge()
34             .into_par_iter()
35             .find_first(|divisor| n % divisor == zero)
36         {
37             false
38         } else {
39             true
40         }
41     }

```

Listing 1: Prime Number Sieve 

The above code verifies the primality of a number using trial division. It generates a sequence of numbers from 2 to  $\sqrt{n} + 1$  and divides these numbers into chunks of blocks and checks the divisibility in parallel to speed up the execution. The parallelisation library used for this purpose is **Rayon**

The below command execute the Prime Number Sieve:

```

1
2     .\nt-assignments.exe list-primes -s 2800 -e 3100
3

```

Listing 2: Example command - Prime Number Sieve

- (b) List the elements of the set  $C$  where  $C = \{\text{composite numbers } n = pq \text{ in your range which are the product of exactly two distinct primes } p \text{ and } q\}$ .

**Answer:** The code snippet below extracts the numbers of the form  $n = p.q$

```

1
2     ///
3     /// Returns a tuple with a formatted string for output and a Vector
4     which contains a tuple of
5     /// Number and its prime factors
6     ///
7     /// # Arguments
8     /// * 'start' - BigInt

```

```

8      /// * 'end' - BigInt
9      /// * 'NumCategory' - Whether we want the prime factorisation of All
    numbers or composites or composites of the form P.Q
10     /// # Example
11     /// ```
12     /// use crate::presets::list_prime_factors_in_range;
13     /// list_prime_factors_in_range(&start, &end, NumCategory::All);
14     /// ```
15     pub fn list_prime_factors_in_range(
16         start: &BigInt,
17         end: &BigInt,
18         opts: NumCategory,
19     ) -> (Vec<NumFactorTable>, Vec<(BigInt, Vec<(BigInt, usize)>>)>) {
20         let mut table_data: Vec<NumFactorTable> = Vec::new();
21         let mut primes = vec![BigInt::from(2u64)];
22         let mut nums_pfactores: Vec<(BigInt, Vec<(BigInt, usize)>>)> = Vec::
new();
23         for num in range_inclusive(start.clone(), end.clone()) {
24             let mut form: String = String::new();
25             let p_factors = num.prime_factors(&mut primes);
26             match opts {
27                 NumCategory::All => {
28                 format_prime_factors_print(&num, &p_factors, &mut form, &mut
table_data);
29                 nums_pfactores.push((num.clone(), p_factors.clone()));
30             }
31             NumCategory::Composites => {
32                 if p_factors.len() >= 2 {
33                     format_prime_factors_print(&num, &p_factors, &mut form, &
mut table_data);
34                     nums_pfactores.push((num.clone(), p_factors.clone()));
35                 }
36             }
37             NumCategory::CompositesPQ => {
38                 if p_factors.len() == 2 {
39                     let first = p_factors.first().unwrap();
40                     let second = p_factors.get(1).unwrap();
41
42                     match first.1 {
43                         1 => match second.1 {
44                             1 => {
45                                 format_prime_factors_print(
46                                     &num,
47                                     &p_factors,
48                                     &mut form,
49                                     &mut table_data,
50                                 );
51                                 nums_pfactores.push((num.clone(), p_factors.clone()))
;
52                             }
53                             _ => {}
54                         },
55                         _ => {}
56                     }
57                 }
58             }
59             NumCategory::Primes => {}
60         }
61     }
62
63     (table_data, nums_pfactores)
64 }

```

```

65
66     pub trait PrimeFactors {
67         fn prime_factors(&self, primes: &mut Vec<BigInt>) -> Vec<(BigInt,
68         usize)>;
69         //fn is_prime_factors_form_pq(&self) -> (bool, Vec<(BigInt, usize)
70         >);
71     }
72
73     impl PrimeFactors for BigInt {
74         fn prime_factors(&self, primes: &mut Vec<BigInt>) -> Vec<(Self,
75         usize)> {
76             let n = self.clone();
77             // Check if n is prime
78             if miller_rabin_primality(&self) {
79                 return vec![(self.clone(), 1)];
80             }
81
82             let start_no = primes.last().unwrap();
83             let square_root = self.sqrt();
84             if square_root - start_no > BigInt::from(2u64) {
85                 let end_no: BigInt = self.sqrt() + 1; // +1 to get the ceiling
86                 value
87                 // println!("start = {}, end = {}", start_no, end_no);
88
89                 let r = range_inclusive(start_no.clone(), end_no);
90
91                 let new_primes: Vec<BigInt> = r
92                     .into_iter()
93                     .map(|x| x)
94                     .parallel_filter(|x| miller_rabin_primality(x))
95                     .collect();
96                 primes.extend(new_primes);
97                 let mut seen = HashSet::new();
98                 primes.retain(|c| seen.insert(c.clone()));
99             }
100             let _res: HashMap<BigInt, usize> = HashMap::new();
101
102             // The all_divisors vec will contain all the divisors of num
103             with repetition.
104             // The product of the elements of all_divisors will equal the "
105             num"
106             let mut all_divisors = Vec::<BigInt>::new(); //
107             let mut product = BigInt::one();
108
109             while product < n {
110                 let divisors = primes
111                     .par_iter()
112                     .filter(|x| (n.clone() / &product) % *x == BigInt::zero())
113                     .map(|p| p.clone())
114                     .collect::<Vec<BigInt>>();
115                 all_divisors.extend(divisors.clone());
116                 product = product
117                     * divisors
118                     .iter()
119                     .fold(BigInt::one(), |acc: BigInt, a| acc * a);
120                 let q = &n / &product;
121                 if miller_rabin_primality(&q) {
122                     all_divisors.push(q);
123                     break;
124                 }
125             }
126         }
127     }

```

```

121     let mut res = all_divisors
122     .into_iter()
123     .fold(HashMap::::new(), |mut m, x| {
124         *m.entry(x).or_default() += 1;
125         m
126     })
127     .into_iter()
128     .filter_map(|(k, v)| Some((k, v)))
129     .collect::

```

Listing 3: Prime Factorisation 

The above two Rust procedures handle the prime factorisation of the integers in the given range. The below snippet extract the numbers of the form  $p.q$

```

1
2     NumCategory::CompositesPQ => {
3         if p_factors.len() == 2 {
4             let first = p_factors.first().unwrap();
5             let second = p_factors.get(1).unwrap();
6
7             match first.1 {
8                 1 => match second.1 {
9                     1 => {
10                         format_prime_factors_print(
11                             &num,
12                             &p_factors,
13                             &mut form,
14                             &mut table_data,
15                         );
16                         nums_pfactores.push((num.clone(), p_factors.clone()));
17                     }
18                     _ => {}
19                 },
20                 _ => {}
21             }
22         }
23     }
24

```

Listing 4: Code - Prime Factorisation - Search for ‘p.q’

| Composites of the form $N = P.Q$ |                     |        |                     |        |                     |
|----------------------------------|---------------------|--------|---------------------|--------|---------------------|
| Number                           | Factorisation       | Number | Factorisation       | Number | Factorisation       |
| 2807                             | $7^1 \times 401^1$  | 2811   | $3^1 \times 937^1$  | 2813   | $29^1 \times 97^1$  |
| 2815                             | $5^1 \times 563^1$  | 2818   | $2^1 \times 1409^1$ | 2823   | $3^1 \times 941^1$  |
| 2827                             | $11^1 \times 257^1$ | 2831   | $19^1 \times 149^1$ | 2839   | $17^1 \times 167^1$ |
| 2841                             | $3^1 \times 947^1$  | 2845   | $5^1 \times 569^1$  | 2846   | $2^1 \times 1423^1$ |
| 2854                             | $2^1 \times 1427^1$ | 2855   | $5^1 \times 571^1$  | 2858   | $2^1 \times 1429^1$ |
| 2859                             | $3^1 \times 953^1$  | 2863   | $7^1 \times 409^1$  | 2866   | $2^1 \times 1433^1$ |
| 2867                             | $47^1 \times 61^1$  | 2869   | $19^1 \times 151^1$ | 2878   | $2^1 \times 1439^1$ |
| 2881                             | $43^1 \times 67^1$  | 2885   | $5^1 \times 577^1$  | 2893   | $11^1 \times 263^1$ |
| 2894                             | $2^1 \times 1447^1$ | 2899   | $13^1 \times 223^1$ | 2901   | $3^1 \times 967^1$  |
| 2902                             | $2^1 \times 1451^1$ | 2906   | $2^1 \times 1453^1$ | 2911   | $41^1 \times 71^1$  |
| 2913                             | $3^1 \times 971^1$  | 2918   | $2^1 \times 1459^1$ | 2921   | $23^1 \times 127^1$ |
| 2923                             | $37^1 \times 79^1$  | 2929   | $29^1 \times 101^1$ | 2931   | $3^1 \times 977^1$  |
| 2933                             | $7^1 \times 419^1$  | 2935   | $5^1 \times 587^1$  | 2941   | $17^1 \times 173^1$ |
| 2942                             | $2^1 \times 1471^1$ | 2947   | $7^1 \times 421^1$  | 2949   | $3^1 \times 983^1$  |
| 2951                             | $13^1 \times 227^1$ | 2959   | $11^1 \times 269^1$ | 2962   | $2^1 \times 1481^1$ |
| 2965                             | $5^1 \times 593^1$  | 2966   | $2^1 \times 1483^1$ | 2973   | $3^1 \times 991^1$  |
| 2974                             | $2^1 \times 1487^1$ | 2977   | $13^1 \times 229^1$ | 2978   | $2^1 \times 1489^1$ |
| 2981                             | $11^1 \times 271^1$ | 2983   | $19^1 \times 157^1$ | 2986   | $2^1 \times 1493^1$ |
| 2987                             | $29^1 \times 103^1$ | 2991   | $3^1 \times 997^1$  | 2993   | $41^1 \times 73^1$  |
| 2995                             | $5^1 \times 599^1$  | 2998   | $2^1 \times 1499^1$ | 3005   | $5^1 \times 601^1$  |
| 3007                             | $31^1 \times 97^1$  | 3013   | $23^1 \times 131^1$ | 3017   | $7^1 \times 431^1$  |
| 3022                             | $2^1 \times 1511^1$ | 3027   | $3^1 \times 1009^1$ | 3029   | $13^1 \times 233^1$ |
| 3031                             | $7^1 \times 433^1$  | 3035   | $5^1 \times 607^1$  | 3039   | $3^1 \times 1013^1$ |
| 3043                             | $17^1 \times 179^1$ | 3046   | $2^1 \times 1523^1$ | 3047   | $11^1 \times 277^1$ |
| 3053                             | $43^1 \times 71^1$  | 3057   | $3^1 \times 1019^1$ | 3062   | $2^1 \times 1531^1$ |
| 3063                             | $3^1 \times 1021^1$ | 3065   | $5^1 \times 613^1$  | 3071   | $37^1 \times 83^1$  |
| 3073                             | $7^1 \times 439^1$  | 3077   | $17^1 \times 181^1$ | 3085   | $5^1 \times 617^1$  |
| 3086                             | $2^1 \times 1543^1$ | 3091   | $11^1 \times 281^1$ | 3093   | $3^1 \times 1031^1$ |
| 3095                             | $5^1 \times 619^1$  | 3097   | $19^1 \times 163^1$ | 3098   | $2^1 \times 1549^1$ |
| 3099                             | $3^1 \times 1033^1$ | -      | -                   | -      | -                   |

Table 1: List of composite numbers of the form P.Q

```
PS D:\workspace\nt-assignments> .\target\release\nt-assignments.exe prime-factors-range composites-pq -s 2800 -e 3100
```

Prime Factorisation - Composites of the form  $N = P.Q$ :

| Number | Factorisation       | 2881 | $43^1 \times 67^1$  | 2959 | $11^1 \times 269^1$ | 3029 | $13^1 \times 233^1$ | 3099 | $3^1 \times 1033^1$ |
|--------|---------------------|------|---------------------|------|---------------------|------|---------------------|------|---------------------|
| 2807   | $7^1 \times 401^1$  | 2885 | $5^1 \times 577^1$  | 2962 | $2^1 \times 1481^1$ | 3031 | $7^1 \times 433^1$  |      |                     |
| 2811   | $3^1 \times 937^1$  | 2893 | $11^1 \times 263^1$ | 2965 | $5^1 \times 593^1$  | 3035 | $5^1 \times 607^1$  |      |                     |
| 2813   | $29^1 \times 97^1$  | 2894 | $2^1 \times 1447^1$ | 2966 | $2^1 \times 1483^1$ | 3039 | $3^1 \times 1013^1$ |      |                     |
| 2815   | $5^1 \times 563^1$  | 2899 | $13^1 \times 223^1$ | 2973 | $3^1 \times 991^1$  | 3043 | $17^1 \times 179^1$ |      |                     |
| 2818   | $2^1 \times 1409^1$ | 2901 | $3^1 \times 967^1$  | 2974 | $2^1 \times 1487^1$ | 3046 | $2^1 \times 1523^1$ |      |                     |
| 2823   | $3^1 \times 941^1$  | 2902 | $2^1 \times 1451^1$ | 2977 | $13^1 \times 229^1$ | 3047 | $11^1 \times 277^1$ |      |                     |
| 2827   | $11^1 \times 257^1$ | 2906 | $2^1 \times 1453^1$ | 2978 | $2^1 \times 1489^1$ | 3053 | $43^1 \times 71^1$  |      |                     |
| 2831   | $19^1 \times 149^1$ | 2911 | $41^1 \times 71^1$  | 2981 | $11^1 \times 271^1$ | 3057 | $3^1 \times 1019^1$ |      |                     |
| 2839   | $17^1 \times 167^1$ | 2913 | $3^1 \times 971^1$  | 2983 | $19^1 \times 157^1$ | 3062 | $2^1 \times 1531^1$ |      |                     |
| 2841   | $3^1 \times 947^1$  | 2918 | $2^1 \times 1459^1$ | 2986 | $2^1 \times 1493^1$ | 3063 | $3^1 \times 1021^1$ |      |                     |

Figure 3: Sample output on a Windows terminal

The below command execution prints numbers of the form  $n = p.q$  in a table:

```
1
2 .\target\release\nt-assignments.exe prime-factors-range composites-pq -s 2800 -e 3100
3
```

Listing 5: Print numbers of the form n

(c) Choose any three element of the set B and then randomly select 4 values of a for each element.

Apply the gcd test for each of the 12 cases and report on how accurate it is in determining that a number is composite.

**Answer:** The below image shows the output of one execution of the gcd test on three composite numbers selected random in the inclusive range of 2800 to 3100.

| $n = p.q$                            | $a$ (randomly selected) | $\gcd(n, a)$ |
|--------------------------------------|-------------------------|--------------|
| $2914 = 2^1 \times 31^1 \times 47^1$ | $a1 = 517$              | $\gcd1 = 47$ |
|                                      | $a2 = 1710$             | $\gcd2 = 2$  |
|                                      | $a3 = 458$              | $\gcd3 = 2$  |
|                                      | $a4 = 1341$             | $\gcd4 = 1$  |
| $2877 = 3^1 \times 7^1 \times 137^1$ | $a1 = 1732$             | $\gcd1 = 1$  |
|                                      | $a2 = 1799$             | $\gcd2 = 7$  |
|                                      | $a3 = 2525$             | $\gcd3 = 1$  |
|                                      | $a4 = 338$              | $\gcd4 = 1$  |
| $2895 = 3^1 \times 5^1 \times 193^1$ | $a1 = 1421$             | $\gcd1 = 1$  |
|                                      | $a2 = 1618$             | $\gcd2 = 1$  |
|                                      | $a3 = 1891$             | $\gcd3 = 1$  |
|                                      | $a4 = 1883$             | $\gcd4 = 1$  |

Figure 4: Primality Check using GCD Test

At the first glance we could see that the composite number  $n = 2895$  which has a prime factorisation of  $3^1 \times 5^1 \times 193^1$  do not have any Fermat Witnesses to prove that it's a composite number. All the randomly selected  $a = \{1421, 1618, 1891, 1883\}$  values yielded  $\gcd = 1$  which makes all these  $a$  values Fermat Liars.

The accuracy of GCD Test for primality depends on the selection of the  $a$  values. Of course it's not practical to test with all the numbers less than  $n$  to find if  $n$  is composite. It will turn into the sieving process if we do that. Also, there are cases where some numbers (Carmichael Numbers) do not yield any Fermat Witnesses. The Euler Totient Function  $\phi(n)$  gives the total number of relatively prime numbers less than  $n$ . Which means for a composite number  $n$ ,  $n - \phi(n)$  values will attest  $n$  is composite.  $n - \phi(n)$  becomes smaller when  $\phi(n)$  is large. For composite numbers of the form  $n = p.q$ , that's numbers with fewer prime factors have higher values of  $\phi(n)$ .

Let's consider the number  $n = 2881$

$$\begin{aligned}
 2881 &= 43^1 \times 67^1 && \text{(prime factorisation)} \\
 \phi(2881) &= 42 \times 66 = 2772 \\
 n - \phi(n) &= 109 \approx 4\%
 \end{aligned}$$

Only 4% of the numbers are Fermat Witnesses in this case which is much much smaller to form an definite opinion on whether such a number is prime or not when we choose the bases randomly.

The below command execution prints output of GCD Test in a table:

```

1
2  .\target\release\nt-assignments.exe primality gcd -s 2800 -e 3100
3

```

Listing 6: GCD Test Execution



## GCD Test Code snippet:

```

1
2  /// Returns a Vec of randomly selected 'a' value and 'gcd'
3  ///
4  /// # Arguments
5  /// * n - BigInt - Number for which we are checking primality
6  /// * num_trials - u8 - How many trials we do
7  ///
8  /// # Examples
9  /// ```
10 /// use crate::primality::gcd_test
11 /// let result: Vec<BigInt, BigInt> = gcd_test(&BigInt::from(2881u64
12 /// ), 4);
13 /// ```
14 pub fn gcd_test(n: &BigInt, num_trials: u8) -> Vec<BigInt, BigInt> {
15     let mut r = Vec::<BigInt>::new();
16     for _ in 0..num_trials {
17         r.push(generate_random_int_in_range(&BigInt::from(2u8), &(n - 1)))
18     };
19
20     let mut result = Vec::<BigInt, BigInt>::new();
21     for a in r.iter() {
22         result.push((a.clone(), n.gcd_euclid(&a)));
23     }
24
25     result
26 }
27
28 pub trait Gcd {
29     ///
30     /// # Examples
31     ///
32     /// ```
33     /// use utils::Gcd;
34     ///
35     /// assert_eq!(BigInt::from(44u64), BigInt::from(2024u64).gcd_euclid
36     /// (&BigInt::from(748u64)));
37     /// ```
38     /// Determine [greatest common divisor](https://en.wikipedia.org/
39     /// wiki/Greatest_common_divisor)
40     /// using the [Euclidean algorithm](https://en.wikipedia.org/wiki/
41     /// Euclidean_algorithm).
42     fn gcd_euclid(&self, other: &Self) -> Self;
43 }
44
45 impl Gcd for BigInt {
46     ///
47     /// GCD Calculator - The Euclidean Algorithm
48     /// Input: A pair of integers a and b, not both equal to zero
49     /// Output: gcd(a, b)
50     ///
51     fn gcd_euclid(&self, other: &BigInt) -> BigInt {
52         let zero = BigInt::from(0u64);
53         let mut a = self.clone();
54         let mut b = other.clone();
55         let mut gcd: BigInt = zero.clone();
56         if b > a {
57             gcd = b.gcd_euclid(&a);
58         }
59     }
60 }

```

```

56     } else {
57         let mut r: BigInt = &a % &b;
58         while &r > &zero {
59             // let q = &a / &b;
60             r = &a % &b;
61
62             if &r != &zero {
63                 a = b;
64                 b = r.clone();
65             }
66         }
67
68         gcd = b;
69     }
70
71     gcd
72 }
73 }
74

```

Listing 7: Code - Primality using GCD Test”

2. Find all Carmichael Numbers in your range (Lower Range = 2800, Upper Range = 3100) using:

- (a) A direct method employing the Fermat Test that shows that a composite number  $n$  has no Fermat Witnesses.

**Answer:** The below code snippet shows how FLT is employed in finding a Carmichael number:

```

1
2     /// Returns a list of Carmichael Numbers (Absolute Pseudoprimes
3     ) in a range using FLT or Korselt's criterion
4     ///
5     /// # Arguments
6     /// * start: BigInt
7     /// * end: BigInt
8     /// * f: a function pointer to either primality::
9     carmichael_nums_korselt or primality::carmichael_nums FLT
10    /// # Examples
11    /// ' '
12    /// use crate::presets::list_carmichael_nums;
13    /// let carmichael_nums = list_carmichael_nums(&start, &end,
14    carmichael_nums FLT);
15    /// ' '
16    ///
17    pub fn list_carmichael_nums(start: &BigInt, end: &BigInt, f: fn
18    (&BigInt) -> bool) -> (String, Vec<(BigInt, Vec<(BigInt, usize)>)>)
19    {
20        // Get all the composite numbers in the range
21        let composites = list_prime_factors_in_range(start, end,
22        NumCategory::Composites).1;
23
24        // Searching for Carmichael numbers in parallel
25        let carmichael_nums = composites
26        .par_iter()
27        .filter(|x| f(&x.0) == true)
28        .map(|x| x.clone())
29        .collect::<Vec<(BigInt, Vec<(BigInt, usize)>)>>();
30

```

```

25     // Format the data for printing
26     let mut table_data: Vec<NumFactorTable> = Vec::new();
27     for item in carmichael_nums.iter() {
28         let mut form: String = String::new();
29         format_prime_factors_print(&item.0, &item.1, &mut form, &
mut table_data);
30     }
31
32     let mut table1 = Table::new(table_data);
33     table1.with(STYLE_2);
34
35     let output1 = table1.to_string();
36     (output1, carmichael_nums)
37 }
38
39 ///
40 /// Carmichael Numbers using FLT
41 /// n: a composite number
42 ///
43 pub fn carmichael_nums FLT(n: &BigInt) -> bool {
44     let n_minus_one = n - 1;
45     // Get all the coprime numbers less than 'n'
46     let coprimes_n = coprime_nums_less_than_n(n);
47
48     // Search for Fermat Witnesses. A Fermat Witness will yeild
 $a^{n-1} \not\equiv 1 \pmod{n}$ 
49     let fermat_witnesses = coprimes_n
50     .par_iter()
51     .filter(|x| modular_pow(&x, &n_minus_one, n) != BigInt::one()
)
52     .map(|x| x.clone())
53     .collect::<Vec<BigInt>>();
54
55     // No Fermat Witness means n is a Carmichael Number
56     fermat_witnesses.len() == 0
57 }
58

```

Listing 8: Code - Search Carmichael Numbers in the range”

When we run the above code, we get  $2821 = 7^1 \times 13^1 \times 31^1$  as the Carmichael Number between 2800 and 3100 inclusive. A sample execution is given below:

```

PS D:\workspace\nt-assignments> .\target\release\nt-assignments.exe carmichael-nums fermat-lt -s 2800 -e 3100

```

| Number | Factorisation                 |
|--------|-------------------------------|
| 2821   | $7^1 \times 13^1 \times 31^1$ |

Figure 5: Carmichael Number using FLT- Example result

The below command execution prints Carmichael Numbers in the range using FLT:

```

1
2     .\target\release\nt-assignments.exe carmichael-nums fermat-lt -s 2800 -e 3100
3

```

Listing 9: Carmichael Numbers using FLT

(b) Checking which numbers satisfy Korselt’s Criteria.

**Answer:** Korselt’s criteria states:

1.  $n$  is squarefree i.e. the prime decomposition of  $n$  do not contain any repeated factors;

$$2. p|n \implies (p-1)|(n-1);$$

The below code snippet is the implementation of the above criteria:

```

1  ///
2  /// Carmichael Numbers using Korselt's criteria
3  /// n: a composite number
4  ///
5  pub fn carmichael_nums_korselt(n: &BigInt) -> bool {
6      // initialisation to search prime factors
7      let mut primes = vec![BigInt::from(2u64)];
8      // prime factorisation of 'n'
9      let p_factors = n.prime_factors(&mut primes);
10     // checking if the number is squarefree
11     let squarefree = p_factors.iter().fold(true, |squarefree:
12 bool, factor| {
13         squarefree & (factor.1 == 1)
14     });
15
16     let mut p_m_o_divides_n_m_o = true;
17     // if the number is squarefree, then check if 'p minus one'
18     // divides 'n minus one'
19     if squarefree {
20         let n_minus_one = n - 1;
21         for (p, _) in p_factors.iter() {
22             p_m_o_divides_n_m_o &= &n_minus_one % (p - 1) == BigInt
23             ::zero();
24         }
25     }
26
27     // if both are true, return true
28     squarefree & p_m_o_divides_n_m_o

```

Listing 10: Carmichael Number Check - Korselt's criteria

3. Take the first five elements  $n$  of the set  $B$  of composite numbers with 2 factors in your range (or all numbers if you find there are less than 10). The Miller Rabin test states that at most  $\frac{1}{4}$  of numbers  $a$  that are randomly chosen will give the answer that  $n$  is 'probably prime'. How close can you get to this maximum, (i.e. which of your 5 choices has the highest proportion of possible  $a$ 's that would fail the Miller Rabin test).

What composite numbers  $m$  between 50 and 100 have the highest proportion of Miller Rabin failures? (For each number in the range work out the proportion of  $a$ 's that produce the answer 'm is probably prime'). Look at the prime factorisation of these numbers and see if it suggests any patterns about which numbers are vulnerable to giving false answers in Miller Rabin.

**Answer:** For this question, I have filtered out the odd numbers with 2 factors from the set  $B$  of composite numbers. There were 82 such numbers. When I looked for the Miller-Rabin non-witnesses for the first 5 elements, only one number had non-witnesses. Hence I have considered the whole set of odd composites with two factors, i.e., all the 82 numbers and 31 numbers have non-witnesses. The numbers with liars are listed below:

Numbers with Miller-Rabin Liars in the range  $2800 \leq n \leq 3100$ :

$$\begin{aligned}
 &\{2813, 2825, 2845, 2863, 2869, 2873, 2881, 2885, 2899, 2911, \\
 &2923, 2929, 2941, 2947, 2965, 2977, 2981, 2983, 2989, 2993, \\
 &3005, 3007, 3029, 3031, 3053, 3065, 3073, 3077, 3085, 3091, 3097\}
 \end{aligned} \tag{1}$$

For our study, we will consider the first 5 numbers from the above set. Let  $N$  be that set. Let  $N = \{2813, 2825, 2845, 2863, 2869\}$

1.  $n = 2813$

$$2813 = 29^1 \times 97^1 \quad (\text{prime factorisation})$$

$$n - 1 = 2812 = 703 \cdot 2^2 \quad (n - 1 = m \cdot 2^s \text{ form, where } m = 703, s = 2)$$

$$A = \{75, 1380, 1433, 2738\} \quad (\text{Set } A \text{ represents the bases that became liars})$$

$$|A| = 4$$

The Miller–Rabin sequence for  $n$  generated by the set  $A$  is  $(a_i^m, a_i^{2m}) \bmod n$ .

$$(75^{703}, 75^{2 \cdot 703}) \bmod 2813 = (2738, 2812) \quad (2)$$

$$(1380^{703}, 1380^{2 \cdot 703}) \bmod 2813 = (1433, 2812) \quad (3)$$

$$(1433^{703}, 1433^{2 \cdot 703}) \bmod 2813 = (1380, 2812) \quad (4)$$

$$(2738^{703}, 2738^{2 \cdot 703}) \bmod 2813 = (75, 2812) \quad (5)$$

For all the bases, the second number,  $2812 \equiv -1 \pmod{2813}$  and hence 2813 is a prime with respect to these bases. In other words,  $A = \{75, 1380, 1433, 2738\}$  are Miller-Rabin Liars for 2813. Similarly for the other bases.

2.  $n = 2825$

$$2825 = 5^2 \times 113^1 \quad (\text{prime factorisation})$$

$$n - 1 = 2824 = 353 \cdot 2^3 \quad (n - 1 = m \cdot 2^s \text{ form, where } m = 353, s = 3)$$

$$A = \{693, 1032, 1793, 2132\} \quad (\text{Set } A \text{ represents the bases that became liars})$$

$$|A| = 4$$

3.  $n = 2845$

$$2845 = 5^1 \times 569^1 \quad (\text{prime factorisation})$$

$$n - 1 = 2844 = 711 \cdot 2^2 \quad (n - 1 = m \cdot 2^s \text{ form, where } m = 711, s = 2)$$

$$A = \{483, 1052, 1793, 2362\} \quad (\text{Set } A \text{ represents the bases that became liars})$$

$$|A| = 4$$

4.  $n = 2863$

$$2863 = 7^1 \times 409^1 \quad (\text{prime factorisation})$$

$$n - 1 = 2862 = 1431 \cdot 2^1 \quad (n - 1 = m \cdot 2^s \text{ form, where } m = 1431, s = 1)$$

$$A = \{53, 54, 356, 410, 764, 817, 1173, 1174, 1689, 1690, \\ 2046, 2099, 2453, 2507, 2809, 2810\}$$

$$|A| = 16$$

5.  $n = 2869$

$$2869 = 19^1 \times 151^1 \quad (\text{prime factorisation})$$

$$n - 1 = 2868 = 717 \cdot 2^2 \quad (n - 1 = m \cdot 2^s \text{ form, where } m = 717, s = 2)$$

$$A = \{334, 335, 571, 905, 938, 939, 1025, 1360, 1509, 1844, 1930, 1931, 1964, 2298, 2534, 2535\}$$

$$|A| = 16$$

From the set  $N = \{2813, 2825, 2845, 2863, 2869\}$ , we can see that the numbers 2863 and 2869 have 16 Miller-Rabin Liars each. Our bases selection is from the range  $1 < a < n - 1$ , and the number of elements in this range coprime to  $n$  are  $\phi(n)$ . Only these coprime bases may report a number as pseudoprime. Hence we can see that by selecting the number 2863, we get the highest proportion  $\frac{16}{\phi(2863)} = \frac{16}{2448} = \frac{1}{153}$  that the test falsely reporting a number as prime.

The below json listing presents all the numbers between 50 to 100 which are falsely identified as primes by the Miller-Rabin test against some of the bases used.

```

1      {
2          "65": {
3              "n - 1": 64 = 1.26,
4              "prime factorisation": 51 × 131,
5              "Nonwitnesses(Liars)": [ 8, 18, 47, 57 ]
6          },
7          "85": {
8              "n - 1": 84 = 21.22,
9              "prime factorisation": 51 × 171,
10             "Nonwitnesses(Liars)": [ 13, 38, 47, 72 ]
11         },
12         "91": {
13             "n - 1": 90 = 45.21,
14             "prime factorisation": 71 × 131,
15             "Nonwitnesses(Liars)": [ 9, 10, 12, 16, 17, 22, 29, 38,
16                                     53, 62, 69, 74, 75, 79, 81, 82
17         ]
18     }
19 }
20

```

Listing 11: Miller-Rabin failues for numbers between 50 to 100

Let's calculate the proportion of a's that contribute to the false reporting are calculated below for each number:

1.  $n = 65$

$$65 = 5^1 \times 13^1 \quad (\text{prime factorisation})$$

$$\phi(65) = 4 \times 12 = 48$$

$$\text{Number of MR Liars} = 4$$

$$\text{Hence the proportion coprimes which wrongly declares 65 as prime} = \frac{4}{48} = \frac{1}{12}$$

2.  $n = 85$

$$85 = 5^1 \times 17^1 \quad (\text{prime factorisation})$$

$$\phi(85) = 4 \times 12 = 64$$

$$\text{Number of MR Liars} = 4$$

$$\text{Hence the proportion coprimes which wrongly declares 85 as prime} = \frac{4}{64} = \frac{1}{16}$$

3.  $n = 91$

$$91 = 7^1 \times 13^1 \quad (\text{prime factorisation})$$

$$\phi(91) = 6 \times 12 = 72$$

$$\text{Number of MR Liars} = 16$$

$$\text{Hence the proportion coprimes which wrongly declares 85 as prime} = \frac{16}{72} = \frac{9}{12}$$

**Observation:** MR-Liars exist mostly for those numbers with distinct primes in its prime decomposition and many times the factors are sqaurefree. If there are only two prime factors in the prime decomposition of a number, and if the factors are of the form  $p \equiv 1 \pmod{4}$ , then there are 4 MR-Liars and if any of the factors are of the form  $p \equiv 3 \pmod{4}$ , then there are 16 or more MR-Liars exist. When there are three distinct prime factors, and two of them are  $p \equiv 3 \pmod{4}$ , then there are 8 or more MR-Liars exist.

Below listing shows the code used in finding the MR Liars for the numbers in the range  $2800 \leq n \leq 3100$

```

1
2    ///
3    /// Miller-Rabin Test - Returns whether a number is prime or not
4    ///
5    /// # Arguments
6    /// * n: BigInt
7    /// * base: Optional - if base is not passed, 'a' is randomly
  generated in the range
8    ///           2 <= a <= n-2
9    ///
10   pub fn miller_rabin_test(n: &BigInt, base: Option<&BigInt>) -> (
  bool, Vec<MillerRabinTable>) {
11       let mut table_data: Vec<MillerRabinTable> = Vec::new();
12       let _is_prime = false;
13       let (zero, one, two) = (BigInt::from(0u64), BigInt::from(1u64),
  BigInt::from(2u64));
14       let n_minus_one: BigInt = n - 1;
15       let mut m = n_minus_one.clone();
16
17       let mut s = 0;
18       while &m % 2 == zero {
19           m /= 2;
20           s += 1;
21       }
22
23       let n_minus_one_form = format!("{}", n_minus_one, m,
  Superscript(s),);
24
25       let a: BigInt;
26       // If 'base' is not passed, then randomly generate a base "a"
  such that 1 < a < n - 1
27       if let Some(base) = base {
28           a = base.clone();
29       } else {
30           a = generate_random_int_in_range(&two, &(n - 1));
31       }
32       // let a = BigInt::from(1003u64);
33
34       // Calculate  $x \equiv a^m \pmod{n}$ 
35       let mut x = modular_pow(&a, &m, n);
36
37       format_miller_rabin_steps_print(
38           n.clone(),
39           &n_minus_one_form,
40           s,
41           a.clone(),
42           0,
43           m.clone(),
44           x.clone(),
45           &x == &one,
46           &x == &(n - 1),
47           &mut table_data,
48       );
49
50       // if  $x \equiv 1 \pmod{n}$ ,
51       // We know that  $a^{n-1} \equiv (a^{m \cdot 2^s}) \equiv 1 \pmod{n}$ , and we will not
52       // find a square root of 1, other than 1, in repeated squaring
53       // of  $a^m$  to get  $a^{n-1}$ .
54       if &x == &one || &x == &(n - 1) {

```

```

55     return (true, table_data);
56 }
57
58 let mut k = 1;
59 while k <= s - 1 {
60     // searching square-roots for  $1 \pmod n$  other than  $1 \pmod n$ 
61     let e = &m * BigInt::from(2u64).pow(k);
62     x = modular_pow(&a, &e, n);
63
64     format_miller_rabin_steps_print(
65         n.clone(),
66         &n_minus_one_form,
67         s,
68         a.clone(),
69         k,
70         e.clone(),
71         x.clone(),
72         &x == &one,
73         &x == &(n - 1),
74         &mut table_data,
75     );
76
77     // if  $x \equiv -1 \pmod n$  the input number is probably prime
78     if x == n - 1 {
79         return (true, table_data);
80     }
81
82     // if  $x \equiv 1 \pmod n$ , then x is a factor of n
83     if &x == &one {
84         return (false, table_data);
85     }
86
87     k += 1;
88 }
89
90 //  $a^{n-1} \pmod n \neq 1$ , then by FLT, n is composite and return false.
91 return (false, table_data);
92 }
93
94 pub fn test_primality_miller_rabin(n: &BigInt) -> (String, Vec<
String>) {
95     let mut non_witnesses: Vec<String> = Vec::new();
96     let mut n_minus_one_form = String::new();
97     for base in range(BigInt::from(2u64), n - 1) {
98         let output = miller_rabin_test(&n, Some(&base));
99         for item in output.1.iter() {
100             if item.get_message().contains("Prime") {
101                 non_witnesses.push(base.to_string());
102                 if n_minus_one_form.len() == 0 {
103                     n_minus_one_form.push_str(&item.get_n_minus_one_form());
104                 }
105             }
106         }
107     }
108     (n_minus_one_form, non_witnesses)
109 }
110
111 Operations::Question3(s) => {
112     let mut composites =
113     list_prime_factors_in_range(&s.start, &s.end, NumCategory::
Composites).1;
114     // filter only odd composite numbers with only two factors

```



```

115 // composites.retain(|(num, p_factors)| p_factors.len() == 2 &&
    num % 2 != BigInt::zero());
116 composites.retain(|(num, p_factors)| num % 2 != BigInt::zero());
117 // take the first five elements for the test
118 // let sample_data = &composites[0..5];
119 println!(
120     "Total Number of Odd Composites with two factors {}",
121     &composites.len()
122 );
123 let mut json_out: BTreeMap<String, MillerRabinJson> = BTreeMap::
new();
124 for (num, p_factors) in composites.iter() {
125     println!("Processing the number: {}", num);
126     // call miller-rabin test
127     let (n_minus_one_form, non_witnesses) =
test_primality_miller_rabin(num);
128     // Convert prime factors to String format
129     let mut form = String::new();
130     for (factor, exp) in p_factors {
131         form.push_str(&format!("{}", factor, Superscript(exp.
clone())));
132     }
133     let mut form = form.trim_end().to_string();
134     form.pop();
135     if !non_witnesses.is_empty() {
136         let mr_json = MillerRabinJson::new(n_minus_one_form, form,
non_witnesses);
137         json_out.insert(num.to_string(), mr_json);
138     }
139 }
140
141 let my_home = get_my_home()
142 .unwrap()
143 .unwrap()
144 .to_str()
145 .unwrap()
146 .to_string();
147 let mut output_dir = String::new();
148 let mut fname = String::new();
149
150 if cfg!(windows) {
151     output_dir.push_str(&my_home);
152     output_dir.push_str("\\ass1-question3");
153     println!("Path = {}", &output_dir);
154     fname.push_str(&output_dir);
155     fname.push_str("\\");
156     fname.push_str("question3.json");
157 } else if cfg!(unix) {
158     output_dir.push_str(&my_home);
159     output_dir.push_str("/ass1-question3");
160     println!("Path = {}", &output_dir);
161     fname.push_str(&output_dir);
162     fname.push_str("/");
163     fname.push_str("question3.json");
164 }
165 println!("output dir: {}", &output_dir);
166 if !fs::metadata(&output_dir).is_ok() {
167     let _ = fs::create_dir(&output_dir);
168 }
169 match File::create(&fname) {
170     Ok(file) => {
171         println!("Output has been written to the file: {}", &fname);

```

```

172         serde_json::to_writer_pretty(file, &json_out).unwrap();
173     }
174     Err(e) => panic!("Problem creating the file: {:?}", e),
175 }
176 }
177

```

Listing 12: Miller Rabin - Question 3

To find the numbers with Strong Liars using Miller-Rabin, execute the code using the below command:

```

1
2     .\target\release\nt-assignments.exe question3 -s 50 -e 100
3

```

Listing 13: GCD Test Execution

4. (a) Choose any three elements of your set A and calculate the value of  $r$  used in the AKS primality test;

**Answer:** The below code snippet calculates the  $r$  value used in AKS:

```

1
2     ///
3     /// Find smallest r such that the order of n mod r > ln(n)^2.
4     ///
5     pub fn findr(n: &BigInt) -> BigInt {
6         let (zero, one) = (BigInt::zero(), BigInt::one());
7         let mut r = BigInt::from(1u64);
8
9         let s: f64 = abs_log(n).unwrap().pow(2);
10        let s = BigInt::from(s.floor() as u64);
11        let mut nex_r = true;
12
13        while nex_r {
14            r += 1;
15            nex_r = false;
16            let mut k = BigInt::zero();
17            while &k <= &s && nex_r == false {
18                k += 1;
19                if modular_pow(n, &k, &r) == zero || modular_pow(n, &k,
20                &r) == one {
21                    nex_r = true;
22                }
23            }
24
25            r
26        }
27

```

Listing 14: FindR - AKS Step 2

$r$  value calculated for selected numbers:

- i.  $n = 2813$   
'r' value for 2801 is = 83
- ii.  $n = 2837$   
'r' value for 2837 is = 71
- iii.  $n = 2843$   
'r' value for 2843 is = 101

- (b) Write a single procedure that implements the AKS test using the code that we have seen; I couldn't translate the Maple code into Rust exactly as it was. I have adapted some Python code [3] I saw on the GitHub for 'r' value calculation and polynomial multiplication.

```

1  ///
2  /// AKS Steps
3  ///
4  pub enum AksSteps {
5      Step1,
6      Step2,
7      Step3,
8      Step4,
9      Step5,
10     Success,
11 }
12 ///
13 /// AKS Primality test
14 ///
15 /// Returns boolean indicating prime or not and if the step at
16 which it failed
17 ///
18 /// # Arguments
19 /// * n: BigInt
20 ///
21 pub fn aks(n: &BigInt) -> (bool, AksSteps) {
22     fn is_perfect_k_th_power(n: &BigInt) -> bool {
23         let upper_bound = n.sqrt();
24         for k in range_inclusive(BigInt::from(2u64), upper_bound) {
25             let mut m = n.clone();
26             let mut j = BigInt::zero();
27             while &m % &k == BigInt::zero() && m > BigInt::one() {
28                 m /= &k;
29                 j += 1;
30             }
31             if m == BigInt::one() && j > BigInt::one() {
32                 return true;
33             }
34         }
35         false
36     }
37
38     ///
39     /// Find smallest r such that the order of n mod r > ln(n)^2.
40     ///
41     fn findr(n: &BigInt) -> BigInt {
42         let (zero, one) = (BigInt::zero(), BigInt::one());
43         let mut r = BigInt::from(1u64);
44
45         let s: f64 = abs_log(n).unwrap().pow(2);
46         let s = BigInt::from(s.floor() as u64);
47         let mut nex_r = true;
48
49         while nex_r {
50             r += 1;
51             nex_r = false;
52             let mut k = BigInt::zero();
53             while &k <= &s && nex_r == false {
54                 k += 1;
55                 if modular_pow(n, &k, &r) == zero || modular_pow(n, &k,
56 &r) == one {

```

```

57         }
58     }
59 }
60
61     r
62 }
63
64 // Step 1
65 if is_perfect_k_th_power(n) {
66     return (false, AksSteps::Step1);
67 }
68
69 let (zero, one) = (BigInt::zero(), BigInt::one());
70
71 // Step 2
72 let r = findr(n);
73
74 // Step 3
75 for a in range(BigInt::from(2u64), std::cmp::min(r.clone(), n
76 .clone())) {
77     if &a.gcd_euclid(n) > &one {
78         return (false, AksSteps::Step3);
79     }
80 }
81
82 // Step 4
83 if !(n <= &r) {
84     return (false, AksSteps::Step4);
85 }
86
87 // Step 5
88 let phi_r = euler_totient_phi_counting_coprimes(&r);
89 let log_r = abs_log(n).unwrap();
90 let upper_bound = phi_r.sqrt() * log_r as u64;
91 let mut x = Vec::<BigInt>::new();
92 for a in range(BigInt::one(), upper_bound) {
93     x = fastpoly(&vec![a, BigInt::one()], &n, &r);
94     if x.par_iter().any(|b| b != &BigInt::zero()) {
95         return (false, AksSteps::Step5);
96     }
97 }
98
99 (true, AksSteps::Success)
100 }
101

```

Listing 15: AKS Algorithm

- (c) Take the elements of the set B in turn and decide how many fail the test at each of steps 1, 2, 3, 4, 5.

**Answer:** Below json snippet shows which numbers failed at what step:

```

1      {
2          "Step 1": [
3              2916,3025
4          ],
5          "Step 3": [
6              2800,2802,2804,2805,2806,2807,2808,2810, 2811,
7              2812,2813,2814,2815,2816,2817,2818,2820,2821,
8              2822,2823,2824,2825,2826,2827,2828,2829,2830,

```

```

9      2831,2832,2834,2835,2836,2838,2839,2840,2841,
10     2842,2844,2845,2846,2847,2848,2849,2850,2852,
11     2853,2854,2855,2856,2858,2859,2860,2862,2863,
12     2864,2865,2866,2867,2868,2869,2870,2871,2872,
13     2873,2874,2875,2876,2877,2878,2880,2881,2882,
14     2883,2884,2885,2886,2888,2889,2890,2891,2892,
15     2893,2894,2895,2896,2898,2899,2900,2901,2902,
16     2904,2905,2906,2907,2908,2910,2911,2912,2913,
17     2914,2915,2918,2919,2920,2921,2922,2923,2924,
18     2925,2926,2928,2929,2930,2931,2932,2933,2934,
19     2935,2936,2937,2938,2940,2941,2942,2943,2944,
20     2945,2946,2947,2948,2949,2950,2951,2952,2954,
21     2955,2956,2958,2959,2960,2961,2962,2964,2965,
22     2966,2967,2968,2970,2972,2973,2974,2975,2976,
23     2977,2978,2979,2980,2981,2982,2983,2984,2985,
24     2986,2987,2988,2989,2990,2991,2992,2993,2994,
25     2995,2996,2997,2998,3000,3002,3003,3004,3005,
26     3006,3007,3008,3009,3010,3012,3013,3014,3015,
27     3016,3017,3018,3020,3021,3022,3024,3026,3027,
28     3028,3029,3030,3031,3032,3033,3034,3035,3036,
29     3038,3039,3040,3042,3043,3044,3045,3046,3047,
30     3048,3050,3051,3052,3053,3054,3055,3056,3057,
31     3058,3059,3060,3062,3063,3064,3065,3066,3068,
32     3069,3070,3071,3072,3073,3074,3075,3076,3077,
33     3078,3080,3081,3082,3084,3085,3086,3087,3088,
34     3090,3091,3092,3093,3094,3095,3096,3097,3098,
35     3099,3100
36     ]
37     }
38

```

Listing 16: Miller-Rabin failues for numbers between 50 to 100

## References

- [1] C R Jordan & D A Jordan *MODULAR MATHEMATICS Groups* .
- [2] Dr. Ben Fairbairn *GROUP THEORY Solutions to Exercises*.
- [3] <https://github.com/Ssophoclis/AKS-algorithm/blob/master/AKS.py>