# ← Project review - SQL1 Bootcamp. Day09

<b>≡</b> Type of project		Individu
<b>Ouration</b>		20 m
Passed Peer Reviews		0,
Git project		^
ssh://git@repos-ssh.21-school.ru:2289/st	udents/SQL_beginnerDay09.ID_574108/¡	puc
	Copy link	Open
tudent  pucklant@student.21-school.ru	le	vel 8
About		^
You successfully copied the Git-project link!  Please read all guidelines carefully before st	only if peer-to-peer reviews are done se	eriously.

> - Please, stay courteous, polite, respectful and constructive in all communications during t his review.

- Highlight possible malfunctions of the work done by the person and take the time to disc uss and debate it.
- Keep in mind that sometimes there can be differences in interpretation of the tasks and t he scope of features. Please, stay open-minded to the vision of the other.
- If you have not finished the project yet, it is compulsory to read the entire instruction bef ore starting the review.

# **Guidelines**

- Evaluate only the files that are in src folder on the GIT repository of the student or group.
- Ensure to start reviewing a group project only when the team is present in full.
- Use special flags in the checklist to report, for example, an "empty work" if repository do es not contain the work of the student (or group) in the src folder of the develop branch, or "cheat" in case of cheating or if the student (or group) are unable to explain their work at a ny time during review as well as if one of the points below is not met. However, except for



(i) Code Review Points Sale started! You will get back your CRP sp... Sale status: 0%



Main part

### Exercise 00

Checks for the file day09\_ex00.sql

- The SQL script looks like below.

```
create table person_audit
created timestamp with time zone not null default current timestamp,
type_event char(1) not null default 'I',
row_id
         bigint not null,
name varchar,
age integer,
gender varchar,
address varchar,
constraint ch_type_event check (type_event in ('I', 'U', 'D'))
);
```

You successfully copied the Git-project link!

:rg\_person\_insert\_audit()

### **RETURNS TRIGGER AS**

```
$BODY$
   BEGIN
   INSERT INTO person_audit(created, type_event, row_id, name, age, gender, address)
   VALUES(current_timestamp,'I', NEW.id, NEW.name, NEW.age, NEW.gender, NEW.addres
s);
   RETURN NULL;
   END;
   $BODY$
   LANGUAGE plpgsql;
- The SQL for trigger
   CREATE TRIGGER trg person insert audit
   AFTER INSERT ON person FOR EACH ROW
   EXECUTE FUNCTION fnc_trg_person_insert_audit();
- SQL to check
   select * from person_audit
- result of SQL
   "2022-03-21 20:27:40.283551 +00:00" "I" "10"
                                                      "Damir" "22"
                                                                        "male" "Irk
utsk"
  No
             Yes
```

### **Exercise 01**

```
Checks for the file day09_ex01.sql
```

- The SQL for trigger function

```
CREATE OR REPLACE FUNCTION fnc_trg_person_update_audit()
RETURNS TRIGGER AS
$BODY$
BEGIN
INSERT INTO person_audit(created, type_event, row_id, name, age, gender, address)
VALUES(current_timestamp,'U', OLD.id, OLD.name, OLD.age, OLD.gender, OLD.addres
s);
RETURN NULL;
END;
$BODY$
LANGUAGE plpgsql;
- The SQL for trigger
```

You successfully copied the Git-project link!

CREATE TRIGGER trg\_person\_update\_audit
AFTER UPDATE ON person FOR EACH ROW

EXECUTE FUNCTION fnc tra person update\_audit();

select \* from person\_audit

- result of SQL

"2022-03-21 20:27:40.283551 +00:00" "I" "10" "Damir" "22" "male" "Irk utsk" "2022-03-21 20:29:38.834865 +00:00" "U" "10" "Damir" "22" "male" "Irk utsk" "2022-03-21 20:29:39.333943 +00:00" "U" "10" "Bulat" "22" "male" "Irk utsk"

No



### Exercise 02

Checks for the file day09\_ex02.sql

- The SQL for trigger function

CREATE OR REPLACE FUNCTION fnc\_trg\_person\_delete\_audit()

**RETURNS TRIGGER AS** 

\$BODY\$

**BEGIN** 

INSERT INTO person\_audit(created, type\_event, row\_id, name, age, gender, address) VALUES(current\_timestamp,'D', OLD.id, OLD.name, OLD.age, OLD.gender, OLD.addres s);

RETURN NULL;

END;

\$BODY\$

LANGUAGE plpgsql;

- The SQL for trigger

CREATE TRIGGER trg\_person\_delete\_audit

AFTER DELETE ON person FOR EACH ROW

EXECUTE FUNCTION fnc\_trg\_person\_delete\_audit();

- SQL to check

select \* from person\_audit order by created;

- result of SQL

"2022-03-21 20:27:40.283551 +00:00" "I" "10" "Damir" "22" "male" "Irk utsk" "2022-03-21 20:29:38.834865 +00:00" "U" "10" "Damir" "22" "male" "Irk utsk" "2022-03-21 20:29:39.333943 +00:00" "U" "10" "Bulat" "22" "male" "Irk utsk" "2022-03-21 20:30:57.731367 +00:00" "D" "10" "Damir" "22" "male" "Irk

No



```
Exercise 03
Checks for the file day09_ex03.sql
- The SQL script looks like below.
   DROP trigger trg_person_delete_audit on person;
   DROP trigger trg_person_update_audit on person;
   DROP trigger trg_person_insert_audit on person;
   drop function fnc_trg_person_delete_audit();
   drop function fnc_trg_person_update_audit();
   drop function fnc_trg_person_insert_audit();
   truncate person_audit;
- The SQL for trigger function
   CREATE OR REPLACE FUNCTION fnc_trg_person_audit()
   RETURNS TRIGGER AS
   $BODY$
   BEGIN
   IF (TG OP = 'INSERT') THEN
     INSERT INTO person_audit(created, type_event, row_id, name, age, gender, address)
     VALUES(current_timestamp,'I', NEW.id, NEW.name, NEW.age, NEW.gender, NEW.addr
ess);
   ELSEIF (TG OP = 'UPDATE') THEN
     INSERT INTO person_audit(created, type_event, row_id, name, age, gender, address)
     VALUES(current_timestamp, 'U', OLD.id, OLD.name, OLD.age, OLD.gender, OLD.addre
ss);
   ELSE
     INSERT INTO person_audit(created, type_event, row_id, name, age, gender, address)
     VALUES(current_timestamp, 'D', OLD.id, OLD.name, OLD.age, OLD.gender, OLD.addre
ss);
   END IF;
   RETURN NULL;
   END;
   $BODY$
   LANGUAGE plpgsql;
- The SQL for trigger
   CREATE TRIGGER trg person audit
   AFTER DELETE OR UPDATE OR INSERT ON person FOR EACH ROW
   EXECUTE FUNCTION fnc_trg_person_audit();
- SQL to check
```

reated;

Git-project link!

You successfully copied the

- result of SQL "2022-03-21 20:33:30.826364 +00:00" "|" "10" "Damir" "22" "male" "Irk utsk" "2022-03-21 20:33:31.282922 +00:00" "U" "10" "Damir" "22" "male" "Irk utsk" "2022-03-21 20:33:31.746362 +00:00" "U" "10" "Bulat" "22" "male" "Irk utsk" "2022-03-21 20:33:32.228181 +00:00" "D" "10" "Damir" "22" "male" "Irk utsk" ∕ Yes No

# Exercise 04

Checks for the file day09\_ex04.sql - The SQL script looks like below.

```
CREATE FUNCTION fnc_persons_female( )
   RETURNS TABLE(id person.id%TYPE,
         name person.name%TYPE,
         age person.age%TYPE,
         gender person.gender%TYPE,
         address person.address%TYPE) AS $$
   SELECT id, name, age, gender, address
     FROM person
   WHERE gender= 'female';
   $$ LANGUAGE SQL;
   CREATE FUNCTION fnc persons male()
   RETURNS TABLE(id person.id%TYPE,
         name person.name%TYPE,
         age person.age%TYPE,
         gender person.gender%TYPE,
         address person.address%TYPE) AS $$
   SELECT id, name, age, gender, address
     FROM person
   WHERE gender= 'male';
   $$ LANGUAGE SQL;
- The SQL to check
   select * from fnc_persons_male();
```

- The result of SQL

```
"2" "Andrey" "21" "male" "Moscow"
"4" "Denis" "13" "male" "Kazan"
"7" "Peter" "24" "male" "Saint-Petersburg"
You successfully copied the
```

Git-project link!

```
select * from fnc_persons_female();
- The result of SQL
   "1" "Anna" "16"
                         "female" "Moscow"
   "3" "Kate" "33"
                         "female" "Kazan"
   "5"
       "Elvira" "45"
                         "female" "Kazan"
   "6" "Irina" "21"
                         "female" "Saint-Petersburg"
        "Nataly" "30"
   "8"
                         "female" "Novosibirsk"
          / Yes
  No
```

#### **Exercise 05**

```
Checks for the file day09 ex05.sql
- The SQL script looks like below.
   CREATE OR REPLACE FUNCTION fnc_persons(pgender varchar default 'female')
   RETURNS TABLE(id person.id%TYPE,
          name person.name%TYPE,
          age person.age%TYPE,
          gender person.gender%TYPE,
          address person.address%TYPE) AS $$
   SELECT id, name, age, gender, address
      FROM person
   WHERE gender= pgender;
   $$ LANGUAGE SQL;
- The SQL to check
   select * from fnc_persons(pgender := 'male');
- The result of SQL
   "2"
       "Andrey" "21"
                         "male" "Moscow"
   "4" "Denis" "13"
                         "male" "Kazan"
   "7"
        "Peter" "24"
                         "male" "Saint-Petersburg"
   "9" "Dmitriy" "18"
                             "male" "Samara"
- The SQL to check
   select * from fnc_persons();
- The result of SQL
   "1" "Anna" "16"
                         "female" "Moscow"
       "Kate" "33"
                         "female" "Kazan"
   "5" "Elvira" "45"
                         "female" "Kazan"
                                   Saint-Petersburg"
You successfully copied the
```

Novosibirsk"

Git-project link!

No

✓ Yes

# Exercise 06

```
Checks for the file day09_ex06.sql
```

- The SQL script looks like below.

```
CREATE FUNCTION fnc_person_visits_and_eats_on_date(pperson varchar default 'Dmitri y',
```

```
pprice numeric default 500, pdate date default '2022-01-08')
```

RETURNS TABLE(name varchar) AS \$\$

**BEGIN** 

**RETURN QUERY** 

select p.name as pizzeria\_name

from menu inner join pizzeria p on p.id = menu.pizzeria\_id

inner join person\_visits pv on menu.pizzeria\_id = pv.pizzeria\_id

inner join person p2 on p2.id = pv.person\_id

where price < pprice and p2.name = pperson and visit\_date = pdate;

END;

\$\$ LANGUAGE PLPGSQL;

- The SQL to check

```
select * from fnc_person_visits_and_eats_on_date(pprice := 800);
```

- The result of SQL

"Papa Johns"

"DoDo Pizza"

- The SQL to check

select \*

from fnc\_person\_visits\_and\_eats\_on\_date(pperson := 'Anna',pprice := 1300,pdate := '2022
-01-01');

- The result of SQL

"Pizza Hut"

"Pizza Hut"

"Pizza Hut"

"Pizza Hut"

No



# Evercise 07

```
CREATE FUNCTION func_minimum(VARIADIC arr NUMERIC[])

RETURNS NUMERIC AS

$$

SELECT min(i) FROM unnest(arr) g(i);

$$ LANGUAGE SQL;

- The SQL to check

SELECT func_minimum(VARIADIC arr => ARRAY[10.0, -1.0, 5.0, 4.4]);

- The result of SQL

"-1"

No  Yes
```

# Exercise 08

Checks for the file day09\_ex08.sql

- The SQL script looks like below.

```
CREATE OR REPLACE FUNCTION fnc_fibonacci(pstop integer default 10)
RETURNS TABLE(a bigint) AS $$
WITH RECURSIVE f (a,b) AS
(SELECT 0 AS a, 1 AS b
UNION ALL
SELECT b, a+b FROM f WHERE b<pstop)
SELECT a
FROM f;
$$ LANGUAGE SQL;

- The SQL to check

select * from fnc_fibonacci(20)
```

- The result of SQL

"0"
"1"
"2"
"3"
"5"
"8"

No 🗸 Yes

