Toward the Era of Agentic Embodied Intelligence

AutoLab, School of Artificial Intelligence, Shanghai Jiao Tong University

Research Lab, Anyverse Dynamics

Abstract

Frontier foundation models can generate robot actions, yet sustained physical autonomy requires more than a sequence of locally successful movements. We introduce A^2-MEAS, an embodied multi-agent framework built around *language as a scaling interface*. Its action model, A^2-WLA, combines a vision-language-action policy with motion-aware history and a latent world model. This relatively simple architecture, together with action pretraining and task specialization, achieves strong long-horizon performance. On the 50-task BEHAVIOR 2026 public subset, task-specialized A^2-WLA policies achieve 0.5755 Q-score, more than twice the 0.2605 reported for the 2025 competition winner on its public evaluation. The comparison spans different benchmark editions and training configurations. Within the complete system, MetaBrain and diagnostic agents translate recovery language, spatial evidence and execution history into correction codes that modulate continuous actions without updating model parameters. On the full 100-task BEHAVIOR 2026 public set, A^2-MEAS reaches 0.6411 Q-score and 45.40% complete-task success. The evaluation extends from long-horizon whole-body control to short-horizon bimanual manipulation, where A^2-WLA achieves 93.98% average success on RoboTwin 2.0 and the complete system reaches 94.93%. Real-robot experiments span storage, retrieval, food preparation and contact-rich manipulation across five household settings. The recorded results across 16 tabletop tasks give A^2-WLA a provisional average success rate of 41.88%, compared with 20.31% for $\pi_{0.5}$. Long-horizon pour-over coffee preparation further tests recovery during sustained execution. The Adapter raises post-failure completion from 15.00% to 95.00% and from 5.00% to 80.00% at two filter-handling steps. Our training infrastructure reaches 427.1 samples per second, approximately 4.03$\times$ the throughput of a $\pi_{0.5}$ reference implementation on matched hardware. We will release the system, models, training scripts and infrastructure as an efficient, usable framework for embodied learning.

Code and releases https://github.com/AutoLab-SAI-SJTU/A2MEAS

Recent evaluations show that general-purpose models can generate robot actions without task-specific parameter updates. On the 42-task RoboDojo evaluation, GPT-6 Astra ranks above the 40 public policies included in the comparison, although precision and dynamic control remain limitations [1]. In a separate study, RoboICL reports gains from demonstration context and interaction memory under its evaluated task and prompting protocols [2]. These findings raise the question of how reasoning and control should be organized to sustain coherent, goal-directed behavior over a complete activity.

A robot must do more than choose a plausible next action. Each interaction changes the conditions for what follows. A recovered grasp may secure an object in an orientation that prevents its later placement, and a successful local correction may leave the original goal unfinished. Long-horizon autonomy therefore requires reasoning about both the immediate physical state and the consequences of changing it. This motivates our

focus on how learned control, task reasoning, and diagnostic evidence cooperate across complete activities, including failures and the attempts to recover from them.

Prior work has connected high-level reasoning to physical execution in several ways. Language-guided frameworks select grounded skills and revise plans using textual or environmental feedback [3–5]. Spatial planning, joint reasoning-and-action models, and learned recovery methods bring those decisions closer to the observed scene [6–8]. In parallel, vision-language-action (VLA) and world-action (WAM) models learn continuous control from multimodal context and predictive dynamics [9, 10]. An important interface problem remains. A reasoning agent may correctly identify how an attempt should change, but the action policy must turn that instruction into a trajectory that accounts for the current grasp, local geometry, and contact conditions. A reusable connection between these capabilities would allow improvements in reasoning and perception to inform motor behavior during execution.

We introduce A^2-MEAS, an embodied multi-agent framework that coordinates reasoning, diagnostic grounding, and continuous control through a shared execution record. Its action model, A^2-WLA, learns from long-horizon demonstrations and uses recent visual history and predicted scene features to generate actions. A vision-language coordinator, MetaBrain, maintains the task goal and examines unexpected outcomes. Diagnostic agents provide perceptual, spatiotemporal, and interaction evidence, using object localization, segmentation, tracking, available depth, and robot-state signals. These are complementary diagnostic functions rather than a fixed list of mandatory perception models. MetaBrain combines their findings with executed action history to formulate a correction. The action policy then attempts the correction, and the observed result becomes evidence for the next decision.

Our central principle is *language as a scaling interface*. Language lets agents with different capabilities express the intended change and explain the evidence supporting it. A learned condition encoder connects that exchange to continuous control by combining the recovery instruction, grounded spatial evidence, executed history, and a fresh action proposal into a correction code. A residual adapter uses this code to modify the action expert's hidden states during trajectory generation. The policy can therefore change its next movement in response to new evidence while all model parameters remain fixed. Language provides the shared semantic interface, while structured geometry and execution records preserve the physical detail needed to act on it.

A strong action model is the starting point for this cooperation. A^2-WLA uses a simple architecture that augments a vision-language-action policy with a latent world model that predicts future visual features. Its performance is unexpectedly strong relative to the simplicity of this design. On the 50-task public subset of BEHAVIOR 2026, one shared A^2-WLA model reaches 0.4522 Q-score, while task-specialized policies reach 0.5755 before adding the correction system. The latter is approximately 2.21$\times$ the 0.2605 reported for RLC, the 2025 competition winner, in its public evaluation [11]. This is a cross-edition comparison, and the specialized configuration uses multiple checkpoints, so it does not isolate architecture as the only source of the gain. It nevertheless shows how much long-horizon competence can be built into the learned action policy itself (Table 7).

We then ask what grounded intervention adds to that competence. Across all 100 BEHAVIOR 2026 tasks, the multi-model A^2-WLA baseline obtains 0.6040 Q-score and 40.60% complete-task success. Adding MetaBrain, diagnostic evidence and learned correction raises these public-set results to 0.6411 and 45.40%, with at least one successful episode on 88 tasks. Fixed-policy Adapter ablations and a disjoint set of task instances test the correction mechanism separately from model selection. The public-set measurements are distinct from the official hidden-set results, which use a smaller coordinator under the submission memory limit (Section 5.2.3).

We also test the action model beyond long-horizon whole-body control. On RoboTwin 2.0, A^2-WLA achieves

93.98% average success across Clean and Randomized conditions, and the complete system reaches 94.93%. Real-robot experiments span 18 tabletop task definitions across five household settings, with results for 16 tasks and 20 trials per task and configuration. Without high-level correction, the full A^2-WLA recipe reaches 41.88% macro success, compared with 20.31% for $\pi_{0.5}$ [9] and 27.81% for base fine-tuning (Table 9a). These aggregates remain provisional because two per-task counts await checkpoint verification (Table 9b). These tasks cover storage, retrieval, food preparation, insertion and tool use. Long-horizon pour-over coffee preparation takes approximately four minutes per run, with more than 100 cups completed during deployment. At two filter-handling steps, a lightweight history-conditioned Adapter completes 19/20 and 16/20 post-failure trials, compared with 3/20 and 1/20 for base-policy retries. These real-robot recovery tests complement the full correction-interface experiments in simulation.

Long-horizon experiments also make iteration expensive. We therefore develop training and evaluation infrastructure alongside the models. Our implementation processes 427.1 demonstration samples per second on eight GPUs, approximately 4.03$\times$ the throughput of a $\pi_{0.5}$ reference implementation on the same hardware. The reference uses matching image resolution and action horizon, with each implementation's batch size chosen for resource utilization. A full 1,000-episode BEHAVIOR evaluation takes approximately 18.1 hours on the optimized eight-GPU evaluation node, compared with an estimated 1,275 hours for the unoptimized serial reference. This 70.4$\times$ ratio combines software changes with parallel hardware, rather than isolating either contribution (Section 4).

We will progressively release the system code, models, training scripts and optimized infrastructure at `https://github.com/AutoLab-SAI-SJTU/A2MEAS`. The training data are provided by the official BEHAVIOR project. The release is intended to give researchers and developers an efficient, usable framework for training, evaluating and deploying embodied agents across large-scale simulation platforms and real-world tasks.

Our contributions are threefold. ♠ We introduce A^2-MEAS, which connects reasoning, grounded evidence and continuous control through learned correction codes while keeping deployment-time parameters fixed. ♠ We establish the performance of the simple A^2-WLA architecture across long-horizon BEHAVIOR and short-horizon RoboTwin evaluations, and test physical manipulation across diverse tabletop tasks and long-horizon coffee preparation. The complete system reaches 0.6411 Q-score and 45.40% success on the BEHAVIOR 2026 public set. ♠ We provide infrastructure with a 4.03$\times$ training-throughput gain under the stated hardware conditions and a 70.4$\times$ evaluation speedup combining software optimization with additional parallel hardware.

1 The A^2-MEAS framework

General embodied intelligence requires a system to connect its intentions to the physical consequences of its actions. Over a long activity, a robot must remember what remains to be done while responding to changes in objects, contacts, and its own configuration. A successful movement is useful only if the resulting state supports continued progress. A^2-MEAS addresses this problem by coupling learned action generation with task-level reasoning and evidence-based diagnosis.

The framework contains three cooperating groups of agents (Fig. 1). A^2-WLA generates continuous actions from the task instruction and observed history. MetaBrain monitors execution in relation to the full goal and determines when the next attempt should change. Diagnostic agents investigate the physical questions needed to make that decision. All three use a shared record of actions and observations. When execution requires intervention, a learned correction interface converts their instruction and evidence into changes inside the action generator.

Section 1.1 explains how the shared record coordinates these agents. Section 1.2 introduces the action model, its observation and prediction components, and the adapter that accepts corrective guidance. Section 1.3 follows a recovery example from diagnosis through corrected execution. Sections 2 and 3 then develop the interface and action model in detail.



Figure 1 The A²-MEAS framework. The MetaBrain coordinates task reasoning and recovery. Grounding agents provide specialized evidence. The correction interface combines recovery language, spatial evidence and executed history to modulate A²-WLA. These agents cooperate to control one robot.

1.1 Framework architecture and coordination

A²-MEAS couples a local control loop with a task-level reasoning loop. The local loop repeatedly generates action chunks from the task instruction and recent observations. The task-level loop uses the resulting evidence to decide whether execution can continue, whether the goal has been achieved, or whether recovery is needed. A shared execution record stores the goal, dispatched controls, and observed outcomes. It gives all agents a common account of what has actually happened without requiring them to share a backbone or run at the same frequency.

The execution layer dispatches only a prefix of each predicted chunk, then obtains fresh observations before the next policy call. Thus, control is closed-loop across chunks even though an uninterrupted prefix executes without a new policy prediction. A²-WLA handles ordinary changes through this repeated observation–action cycle. When monitoring detects an abnormal outcome, the runtime pauses pending controls and asks MetaBrain to review the evidence. Verified recovery returns execution to the nominal loop, and verified completion ends the episode.

Diagnostic agents are invoked when a decision depends on an unresolved physical condition. Table 1 groups their functions into perceptual grounding, spatiotemporal grounding, and interaction assessment. Perception locates objects and regions. Temporal analysis tracks how they move relative to one another. Interaction assessment combines those observations with available robot-state, contact, and geometric evidence. For example, seeing an object between the gripper fingers does not establish a secure grasp. Tracking whether it moves with the hand, together with gripper-state evidence, supports a more informative assessment. Depth or

Table 1 The three groups of agents in A^2-MEAS. Rows within each group describe its responsibilities or internal components. Diagnostic agents can share tools across functions. A common execution layer dispatches controls, checks outcomes and records the history used by all three groups.

Agents	Responsibility	Function
MetaBrain	Task verification	Maintain the task goal and verify execution progress
	Failure diagnosis	Review attempted actions and request missing evidence
	Recovery instruction	Describe how the next attempt should change
Diagnostic agents	Perceptual grounding	Identify objects, regions and visible properties
	Spatiotemporal grounding	Track identities, relative positions and changes over time
	Interaction and feasibility	Assess contact, support and movement constraints
A^2-WLA	Observation encoding	Represent the current scene and recent motion
	World prediction	Predict scene features relevant to the next movement
	Action generation	Generate continuous controls and estimate local progress
	Correction interface	Encode recovery context and adapt action generation

reconstructed geometry can supply additional evidence when available. Each finding retains its observation source and timestamp so that MetaBrain can distinguish a supported conclusion from a missing observation.

The result determines what happens next. Evidence that supports the required condition permits execution to continue. Evidence of a mismatch prompts a correction. Insufficient evidence prompts another observation within the sensing budget. A negative answer and an unknown answer therefore lead to different decisions. Conditional tool invocation keeps ordinary control inexpensive while allowing several diagnostic capabilities to contribute when a correction needs them.

1.2 Action model and correction interface

Let g denote the complete task instruction, retained throughout nominal execution. We index the physical control step at which the policy executes by t. The policy input x_t aggregates synchronized multiview visual observations, a finite temporal window of past visual frames, and the current proprioceptive state s_t comprising joint positions and end-effector configurations.

A^2-WLA combines three sources of action context. A vision-language backbone encodes the task instruction and visual observations. Its motion-aware history encoder represents changes across recent frames. A latent world model predicts future visual features from a transition representation inferred by the backbone. The action expert uses current context, predicted future context, and proprioception to generate controls. Future observations supervise training but are unavailable at deployment. Section 3 describes these components and the three stages used to train the base policy.

During standard nominal operation, A^2-WLA executes with the correction branch deactivated. We designate this default configuration as the base policy π_θ, parameterized by θ. At invocation step t, with sampling randomness suppressed in the notation, it jointly predicts a multi-step continuous action chunk and an auxiliary local-phase progress estimate

$$(\hat{A}_t, \hat{p}_t) = \pi_\theta(x_t, g), \qquad \hat{A}_t \in \mathbb{R}^{H \times d_a}, \quad \hat{p}_t \in [0,1]^H, \tag{1}$$

where H is the prediction horizon and d_a is the number of values in each robot control command. Row $\hat{a}_{t,j} \in \mathbb{R}^{d_a}$ proposes the control for step $t+j$, with $j \in \{0, \ldots, H-1\}$. The corresponding entry $\hat{p}_{t,j}$ estimates

relative progress within the annotated local-phase interval. Its training target follows position within a demonstrated skill phase, from values near zero at the beginning to one at the final annotated step. This estimate supports execution monitoring, while observed physical outcomes determine whether to continue execution, request correction, or confirm task completion.

The correction branch adds a second way to influence action generation. Its condition encoder combines a recovery instruction, verified spatial evidence, relevant executed history, and an uncorrected proposal from the base policy. The resulting code conditions a residual adapter inside the action expert. The code is computed once per generated chunk, while the adapter recomputes its hidden-state adjustment at each flow-integration step. Later action layers turn the modified representation into a corrected trajectory. This mechanism supplements the policy's ordinary visual and predictive context without updating its weights (Section 2).

The robot executes only an initial prefix of the generated chunk. Let L_t be the number of controls actually dispatched at call t, with $1 \leq L_t \leq H_{\text{exec}} \leq H$ whenever execution starts. The BEHAVIOR reference configuration predicts $H = 50$ controls, executes at most $H_{\text{exec}} = 32$, and uses $d_a = 23$ control dimensions. After an uninterrupted prefix, the next observation is acquired at $t + 32$, and a new prediction replaces the unused 18 controls. If monitoring interrupts the prefix, the next observation corresponds to $t + L_t$. A candidate rejected before dispatch produces no executed controls and is not logged as an action prefix.

The execution record R_t stores the history available at physical step t. Each entry links observations before and after a dispatched prefix to its actual controls, executed length, and timestamps. Camera identifiers, coordinate frames, task identifiers, and available local-phase annotations preserve the meaning of those records. Unexecuted proposals are stored separately. The short visual window in x_t serves immediate action prediction, whereas R_t supplies a longer history for diagnosis and recovery.

After a prefix finishes or is interrupted, the runtime returns a feedback bundle b_t containing the relevant execution records, diagnostic findings, progress estimates, and status. The status is `RUNNING` during nominal execution, `TASK_COMPLETE` after completion checks succeed, or `ABNORMAL` when execution requires review. Progress predictions describe the proposed chunk and are interpreted together with the executed controls and observed outcomes. MetaBrain uses this feedback to decide what evidence or corrective instruction is needed next.

1.3 From failure diagnosis to corrected action

The correction interface becomes useful when observing the changed scene is not enough to change an ineffective behavior. Figure 2 illustrates a filter-placement example. The support ring should rest on the cup rim, with the filter hanging inside the opening. If one edge slips below the rim, continuing downward may wedge the ring or disturb the cup. Recovery instead calls for lifting the ring, aligning it above the opening, and lowering it again. This is a schematic example of the mechanism, not one of the measured trials.

After detecting an anomaly, the framework pauses pending controls and establishes a recovery state. MetaBrain examines the observations and executed controls between the last verified nominal state and the detected deviation. It asks the diagnostic agents to assess contact stability and the spatial conditions required for another placement attempt. Perceptual tools identify the filter and cup regions, while temporal tracking helps bound the interval in which support was lost. Available robot-state and contact evidence informs the recovery assessment. Geometric and kinematic checks assess whether the proposed lifting motion is feasible. The recovery instruction is finalized once its required premises have been resolved. If occlusion leaves a necessary condition unknown, the system requests another observation within its sensing budget. The instruction specifies the adjustment and reference frame, while A^2-WLA generates the continuous trajectory.

At the recovery state, the base policy first generates an uncorrected proposal. This proposal shows what the



Figure 2 State progression during the closed-loop recovery of a misaligned filter placement. Following a loss of contact support along one edge of the support ring, the execution layer pauses to verify spatial relationships and synthesizes a sequence of lifting, realigning, and reseating actions conditioned on grounded high-level guidance. Faded outlines trace the initial misaligned pose, orange arrows indicate the directional motion flow, vertical dashed lines mark the central axis of the cup opening, and green indicators highlight the restored planar support. This sequence illustrates the underlying correction mechanism rather than an empirical experimental trial.

policy would attempt without intervention. The condition encoder combines it with the instruction, spatial evidence, and executed history. In the filter example, "realign the filter" is therefore interpreted in relation to a particular ring orientation, cup opening, and attempted movement. The adapter can then apply different residuals to different action positions, allowing a chunk to lift first and approach again later. These are learned adjustments rather than a prescribed geometric trajectory.

Before dispatch, the runtime checks that the evidence remains current and that the candidate satisfies the available joint-limit and obstacle-clearance checks. It executes a prefix, records the outcome, and checks whether the support condition has been restored. Successful recovery returns the robot to the unfinished task. Otherwise, the new observations and failed attempt inform another recovery pass. The reference configuration allows at most three physical retries and 60 seconds per anomaly, with separate sensing and reasoning limits specified in Section 2.6. These checks reduce avoidable errors but do not guarantee successful contact or complete task execution.

The methodological contribution is the learned interface between a grounded recovery description and the action policy's internal representation. MetaBrain can express what should change, diagnostic tools can establish where and under what conditions, and the action model can translate that context into movement. The condition encoder and adapter are trained with a frozen base checkpoint using offline-mined candidate deviations and their expert continuations (Section 2.5). At deployment, all parameters remain fixed. Adaptation comes from new evidence and the resulting correction code, making language-based agent cooperation actionable within continuous control.

2 Cooperation through grounded correction codes

A diagnosis is useful to a robot only if it changes what the robot does next. Our organizing principle, *language as a scaling interface*, provides a way to make that connection. MetaBrain describes the change needed for the next attempt, and diagnostic agents provide the observations that explain where and why the change is needed. A learned encoder converts this information into a correction code. The correction adapter then uses the code inside A²-WLA to influence the generated movement. Different agents can contribute reasoning and

evidence through this interface while retaining their own model architectures.

2.1 MetaBrain diagnosis and recovery instructions

MetaBrain formulates a recovery instruction u_t from the task goal g and feedback b_t, including relevant executed history and diagnostic findings. The public-set system uses Qwen3.8 27B for this role, separately from the 2B vision-language backbone inside A^2-WLA. It compares the observed outcome with the intended operation and requests further evidence when a condition is unresolved. The instruction describes how the next attempt should change while preserving the original goal. The memory-limited hidden-set deployment uses a smaller coordinator, as described in Section 5.2.3.

A visible failure may occur several controls after the action that caused it. An unstable grasp, for example, may become apparent only when the object slips during transport. MetaBrain therefore examines the interval from the last verified nominal state to the detected anomaly, including the controls actually executed. This history helps distinguish errors during approach, grasp closure, and transport. When u_t requests a spatial adjustment, it also identifies the reference frame, such as the camera, robot base, or object. MetaBrain specifies the intended change, while A^2-WLA determines the continuous controls.

2.2 Diagnostic agents and evidence verification

Before a recovery instruction is executed, the framework checks the physical conditions on which it depends. The three grounding modules introduced in Section 1 contribute complementary evidence. For grasp assessment, perception identifies the target, temporal tracking measures its motion relative to the hand, and available proprioceptive signals describe the gripper state. Together, these observations help assess whether the object moves consistently with the gripper. If the evidence is insufficient to answer the query, the result remains unknown.

A request planner routes each question to tools that can supply the necessary evidence. DINO-based features support visual matching, while SAM-based segmentation supplies object masks [12, 13]. Tracking, depth or 3D estimation, robot-state readings, and analytical kinematics provide additional evidence when available. These tools support the diagnostic functions in Table 1. They are selected according to the query and sensor configuration, and their outputs retain the source image, timestamp, and coordinate frame.

The interface supports six kinds of questions. **(i)** State and attribute queries assess visible properties. **(ii)** Spatial queries assess relative positions and region membership. **(iii)** Interaction queries assess grasp, contact, or support. **(iv)** Temporal queries identify changes such as release or slippage. **(v)** Instance queries track identity and detect objects that have appeared or disappeared. **(vi)** Feasibility queries assess reachability and clearance under the available geometry and robot model. These are query types, not six separate neural networks. One query may require several tools, and one tool may support several query types.

Verification distinguishes a negative answer from insufficient evidence. An observed obstacle calls for a different path, while an occluded region may require another view. All conditions required by an instruction must be supported before that instruction is dispatched. Geometric evidence must also be internally consistent. A point and mask must refer to the same view and frame, or be transformed into a common coordinate system, and the selected interaction point must lie in the intended region. Available robot-model checks assess reachability, joint limits, and obstacle clearance. Ordinary deployment uses observations and robot-state readings, without ground-truth object poses or privileged simulator segmentation. The simulator-assisted scheduling controls in Section 6.4.2 are a separate diagnostic experiment.

Table 2 Structure of the correction context provided to the model to guide recovery. It combines the task objective, failure evidence, executed action history, and corrective guidance. Spatial evidence includes camera, frame, and coordinate references. $\hat{A}_t^{\text{base}}$ denotes a fresh, uncorrected action proposal generated from the current recovery state.

```
CorrectionContext {
  task: {
    goal, observed_phase
  },
  failure_window: {
    start_time, end_time, image_refs
  },
  executed_action: {
    chunk_id, executed_steps, actual_controls
  },
  history_action_chunks: [
    {executed_prefix, observation_before, observation_after}
  ],
  correction_text: "Intended change in behaviour",
  offset_direction: {
    reference_frame, direction
  },
  spatial_evidence: {
    camera_id, frame_id, coordinate_frame,
    image_refs, object_regions, interaction_points,
    spatial_relations
  },
  inferred_action_chunk: A_base,
  input_features: {
    observation_features, action_hidden_states_ref
  }
}
```

2.3 Correction context and code construction

An instruction such as “realign toward the opening” leaves several questions unanswered. The policy must know which opening is intended, where it is in the current observation, and what the previous attempt did. The `CorrectionContext` in Table 2 keeps the instruction, spatial evidence, executed history, and uncorrected proposal in separate fields. Each field retains enough provenance to associate it with the correct recovery state.

MetaBrain supplies the instruction after reviewing diagnostic findings. Grounding agents attach object regions, interaction points, and spatial relations. The runtime supplies executed controls and their observed outcomes. Feasibility assessments inform both instruction construction and the decision to dispatch a candidate. This division lets different tools contribute through a common schema while preserving the distinction between an observation, an inferred relation, and a proposed action.

The recovery text and its referenced offset direction jointly form u_t. The failure window selects and links relevant executed records in R_t, while verified spatial evidence is encoded as G_t. These fields enter the four existing condition inputs. The task instruction g enters the ordinary language-conditioning path. Local interaction descriptions and recovery goals provide the diagnostic and corrective context.

After recovery preparation, the runtime acquires fresh observations at step t. With correction disabled, A^2-WLA generates the unexecuted proposal $\hat{A}_t^{\text{base}}$. Let G_t encode the verified spatial evidence and let R_t



Figure 3 The correction interface within action generation. Language, spatial evidence, executed history and a fresh base proposal are encoded once per candidate. At every flow step, the adapter uses the current action hidden states to produce position-dependent residuals. Injection after the ninth of 18 action layers allows subsequent layers to convert the modified state into a corrected flow velocity. Orange modules are trained during correction learning while the base model is frozen. All parameters remain fixed during deployment.

supply the relevant executed history. The condition encoder combines these inputs with u_t to produce a correction code

$$c_t = E_\phi(u_t, G_t, R_t, \hat{A}_t^{\text{base}}), \tag{2}$$

where ϕ denotes all trainable correction-branch parameters, including the encoder, adapter, and residual scale below. The code c_t is a learned representation, not an executable program. It stays fixed while one corrected chunk is generated. The same verbal instruction can therefore produce different corrections when the evidence, history, or base proposal changes. Current visual features and predicted future context still enter through the policy's ordinary conditioning paths.

2.4 Correction adapter for action generation

The action expert generates a chunk by integrating a learned flow field. Physical time is indexed by t, while $\tau \in [0,1]$ indexes the internal noise-to-action process. For one policy call, let $h_\tau \in \mathbb{R}^{H \times d_h}$ be the action hidden states after layer nine, with hidden width d_h. We suppress the fixed physical index t on these states. The residual adapter applies

$$h'_\tau = h_\tau + \alpha \odot C_\phi(h_\tau, c_t), \tag{3}$$

where $\alpha \in \mathbb{R}^{d_h}$ is a learned channel scale, broadcast over the H action positions, and $\odot$ denotes element-wise multiplication. The code c_t is fixed for the chunk, but h_τ and the adapter output are recomputed at every integration step. The remaining nine transformer layers predict the corrected flow velocity (Fig. 3). The residual acts in hidden-feature space rather than directly specifying a joint-space offset.

Because the adapter reads each action position's hidden state, its adjustment can vary across the chunk. A change in approach direction need not impose the same offset on later transport actions. The adapter's output projection is initialized to zero and α to 0.1, so the initial residual is zero and the base network output is unchanged. The adapter uses a bottleneck width of 256. The complete correction branch, including the condition encoder, has fewer than 100M trainable parameters.

The task of turning on a radio (BEHAVIOR Task 000), shown in Fig. 4, illustrates how this adapter translates a recovery instruction into a local motion adjustment. To activate the radio, the gripper must align with the small power button and then press toward the front panel. MetaBrain expresses this adjustment in language. Combined with spatial evidence, executed history, and a fresh base-policy proposal, the instruction is encoded as c_t (Eq. (2)) and guides residual modulation of the action hidden states (Eq. (3)). The remaining action layers turn the modified representation into continuous controls while the base model parameters remain fixed.



Figure 4 Correction during radio activation (BEHAVIOR Task 000). (a) Task context. (b) Adapter-guided motion (orange), followed by base-policy execution (teal). (c) Successful completion. (d–e) A separate A^2-WLA-only rollout and wrist view show the gripper missing the circled button. Dots and small arrows trace projected left-end-effector motion. Large arrows indicate reading order. Success and Failure label complete-episode outcomes. The branches are different rollout instances. Panel (a) supplies context rather than a shared initial state.

In the upper branch, the orange trajectory shows the adapter-guided adjustment, followed by continued base-policy execution in teal and successful task completion. The lower branch shows a separate A^2-WLA-only rollout in which the gripper approaches beside the button. These examples illustrate how the correction interface supports recovery. MetaBrain specifies the intended adjustment, the adapter shapes the local motion, and the base policy continues the task.

2.5 Correction data and adapter training

We construct correction supervision offline from the demonstration corpus (Fig. 5). At a recorded state, the frozen base policy proposes an action chunk, which is compared with the expert continuation from that same state. Large deviations at critical manipulation steps provide candidate correction examples. These are unexecuted policy deviations, not observed physical failures. They teach the adapter how to change a proposal toward an expert continuation, while leaving a distribution gap to the failed execution states encountered at deployment.

Data mining focuses on skill transitions, pre-contact approach phases, and gripper actuation boundaries. At each sampled start t, the frozen base policy receives the task prompt, robot state, current images, and causal observation history. It generates one uncorrected candidate chunk using the standard inference procedure, including the configured flow-integration steps. Future observations and expert continuations do not enter this candidate generation.



Figure 5 Offline construction of correction supervision. A frozen policy predicts a candidate at a demonstration state. Candidate and expert actions are aligned in time, units and coordinates, and windows with a large deviation at critical manipulation steps are retained. Visual evidence and the candidate-to-expert direction support context construction. The expert continuation is a training target. The projected positions in the example are an offline quality check and are not privileged inputs during deployment.

To quantify divergence between the policy's proposal and the expert demonstration, both trajectories are mapped into an identical coordinate frame, kinematic unit system, and temporal indexing convention. A 32-step comparison window defines the directional residual and normalized error

$$\Delta a_{t,j} = a_{t,j} - \hat{a}^{\text{base}}_{t,j}, \qquad e_t = \max_{j \in J_t} d(\hat{a}^{\text{base}}_{t,j}, a_{t,j}), \tag{4}$$

where $a_{t,j}$ is the expert action at local index j in the segment starting at t, and $\hat{a}^{\text{base}}_{t,j}$ is the corresponding base-policy prediction. The set J_t contains positions within the 32-step comparison window that are both valid and marked as critical manipulation steps. Positions beyond a skill boundary or demonstration termination are excluded. The distance $d(\cdot,\cdot)$ normalizes differences using the configured scale of each action component. A window is retained when e_t exceeds the threshold δ. Windows without a valid critical position are skipped. Small perturbations of the sampled start around critical events provide coverage of approach and timing variations.

The annotation pipeline uses open-vocabulary object localization, SAM-based masks, and MetaBrain to construct corrective instructions. The candidate-to-expert deviation indicates the required change, while recorded images locate the relevant objects and regions. The annotation prompt includes the task, local phase, deviation, and grounded entities with their camera and frame identifiers. Unresolved spatial fields remain null. Expert actions and future frames can inform offline labels, but they are not supplied to the base-policy proposal. The correction text describes the intended change and its reference frame, while the expert continuation supervises its metric realization.

Training and deployment use the same context schema with different evidence sources. Online, `failure_window` identifies an observed execution anomaly. Offline, it marks the interval where an unexecuted proposal

deviates from the demonstration. The historical fields contain only the demonstrated prefix before t, and the proposal is stored separately in `inferred_action_chunk`. This separation prevents an unexecuted candidate or a future target from being treated as experienced history.

Each sample retains its trajectory identifier, timestamps, and base-checkpoint metadata. Overlapping windows are consolidated when measuring dataset duration. Mining makes one candidate-generation call at each sampled start, and previously mined samples can be reused or refreshed for another checkpoint. Retained supervision is capped at 2% of the 1,950-hour corpus, or 39 hours, with priority given to critical steps that have complete spatial evidence. Schema checks and sampled manual inspection assess whether annotations agree with the images and trajectory deviations. Training freezes the base parameters θ and updates only the correction parameters ϕ against the expert continuation.

Correction training minimizes the masked flow-matching objective in equation (14), with c_t supplied as an additional condition. The base parameters θ remain frozen, and only the correction-branch parameters ϕ are updated. Expert continuations provide the action targets, using the same validity masks and flow-time convention as base-policy training. The mining offset $\Delta a_{t,j}$ is defined in control space, whereas the adapter predicts hidden-state residuals. The flow objective learns how those residuals should change the generated actions.

Correction training uses eight GPUs, BF16 precision, and a global batch size of 256. AdamW uses $\beta = (0.9, 0.999)$, weight decay 0.01, and gradient-norm clipping at 1.0. Training runs for 6,000 steps, with a 1,000-step linear warm-up to 10^{-4} followed by cosine decay toward 10^{-5}. Validation and checkpoint saving occur every 400 steps. Each evaluated adapter is paired with its corresponding base checkpoint.

2.6 Closed-loop runtime orchestration

Figure 6 summarizes the recovery loop. After detecting an anomaly, the runtime pauses pending controls and saves the observations, robot state, and executed history. Recovery preparation may include controlled stopping, posture adjustment, or contact release when required. The runtime then reacquires observations and robot state. Returning the robot to an earlier pose does not imply that the object or environment has been restored. MetaBrain and the required diagnostic agents use this updated evidence to prepare the recovery instruction. Spatial evidence, the relevant observation history, the base proposal, and the corrected candidate must all correspond to the current recovery state. Before dispatch, the runtime checks evidence freshness, joint limits, and obstacle clearance. If the state changes during candidate generation, it refreshes the affected evidence and regenerates the candidate before execution.

After each corrective prefix, the runtime checks whether the required physical condition has been restored. If so, nominal execution resumes. Otherwise, the failed attempt and updated observations inform another recovery query. Each anomaly allows at most two additional viewpoints, each with a five-second allowance, and three physical retries. A MetaBrain request times out after ten seconds, and the entire recovery event is limited to 60 seconds. Resubmitting a query does not reset these counters. The runtime aborts recovery when a required condition cannot be verified or an applicable budget is exhausted.

MetaBrain determines how the intended operation should change, grounding agents assess the physical conditions needed for that change, and A^2-WLA generates the continuous controls. This division of labor allows reasoning and diagnostic capabilities to contribute through the shared `CorrectionContext`. New tools can be incorporated when their outputs preserve the field semantics, coordinate conventions, and representations expected by the correction encoder.



Figure 6 Execution and recovery as one feedback loop. Ordinary action generation records the executed prefix and its observed outcome. An abnormal event invokes the MetaBrain and the required grounding agents. A fresh recovery state conditions both the base proposal and corrected generation. Failed attempts update the evidence and consume the remaining event budget. Verified recovery resumes execution toward the unfinished task goal. A timeout, exhausted budget or failed feasibility check exits recovery.

3 The A²-WLA action model

A²-WLA supplies the continuous control capability on which grounded correction operates. It combines a 2B-parameter Qwen3-VL backbone [14], a multiview latent world model, and an approximately 300M-parameter Gemma-style action expert with 18 transformer layers (Fig. 7). The backbone interprets the task and visual history. The world model predicts future scene features. The action expert uses both current and predicted context, together with proprioception, to generate continuous controls. The history encoder, world model, and action expert are described first, followed by data construction and training. The architecture is shared across embodiments through a masked action representation, while camera inputs, state fields, and control semantics follow each robot's configuration.

The base policy is trained in three stages. World-model pretraining learns from multiview transitions. Vision-language pretraining adds action and embodied-language supervision. Joint optimization then trains the continuous policy and its auxiliary objectives. Correction learning is a separate fourth stage that freezes the base policy and trains the interface described in Section 2.5.

3.1 Motion-aware visual history encoding

A single image often leaves an interaction ambiguous. An object between the gripper fingers may be securely held, slipping, or still resting on a surface. The history encoder supplies temporal evidence before visual



Figure 7 Architecture of A^2-WLA. A motion-aware history encoder converts six-frame multiview histories into visual tokens. A 2B Qwen3-VL backbone combines these tokens with the task instruction to produce current context and a latent action. The world model predicts future visual features, which a spatial compressor aggregates into future context. An 18-layer action expert uses both contexts to generate a 50-step action chunk through ten-step flow integration, while a separate head estimates per-step progress. During recovery, a correction adapter injects a code-conditioned residual after the ninth layer. The lower panel shows how adjacent differences between paired-frame representations provide motion features for gated cross-attention and residual fusion before visual token merging.

tokens enter the language backbone. Each camera contributes five past frames and the current frame, arranged chronologically. A temporal patch kernel of size two groups them into three frame pairs. The first four visual blocks process the pairs with shared parameters.

Each paired representation is compressed with adaptive 4×4 pooling and learned queries. Let f_k denote the compressed representation of pair $k \in \{0,1,2\}$. Adjacent differences provide temporal features

$$d_k = \mathrm{LN}\big(W(f_{k+1} - f_k) + b_k\big), \qquad k \in \{0,1\}, \tag{5}$$

where W is a learned projection, b_k is an interval-position embedding, and LN denotes layer normalization. These features supply keys and values for gated cross-attention in later visual blocks. Residual fusion, the remaining visual blocks, and token merging produce the sequence passed to the language backbone. This design combines appearance with changes across the sampled observation window.

The history representation is recomputed from the sliding window at each policy call, without recurrent hidden-state accumulation. Its feature differences encode observed change rather than calibrated velocity, because the sampled frame intervals can vary. The longer execution record R_t remains separate and is used for diagnosis. Section 3.4.1 specifies frame sampling and camera alignment.

3.2 Multiview latent world model

Visual history describes recent changes, while the world model predicts the scene features relevant to the next action. The head camera captures workspace layout, and wrist cameras provide local views of the gripper and nearby objects. Occlusion and camera motion can make a transition ambiguous in any single view. Building on latent-action modeling in LaWAM [10], we train a shared latent variable to explain changes across these complementary views. The representation is learned from visual transitions and is not tied to a fixed joint-vector dimensionality.

The world model contains a frozen visual encoder, an inverse model, and a future-feature predictor. For clarity, we suppress the physical step index t within this subsection. Let $F = (F_1, \ldots, F_V)$ be the current patch features from V camera views, and let F^+ contain features observed 50 control steps later. During world-model pretraining, the inverse encoder E_{inv} produces a shared transition latent z^*. The predictor then reconstructs future features for each view

$$z^* = E_{\text{inv}}(F, F^+), \qquad \hat{F}_v^+ = D_v(F, z^*). \tag{6}$$

Reconstructing all views from a shared latent variable encourages consistency across their predicted changes. This joint constraint reduces single-view ambiguity, but does not by itself guarantee viewpoint invariance or complete separation of object motion from camera motion.

At deployment, future frames are unavailable. Learned queries in the vision-language backbone instead predict a latent $\hat{z}$ from current and historical observations and the task instruction. The backbone also supplies current-context tokens C. The future predictor uses $\hat{z}$, and a spatial compressor P aggregates its outputs into future-context tokens

$$\hat{F}_v^+ = D_v(F, \hat{z}), \qquad C^+ = P(\hat{F}^+), \tag{7}$$

where $\hat{F}^+ = (\hat{F}_1^+, \ldots, \hat{F}_V^+)$. Camera embeddings preserve view identity, and validity masks exclude missing views. We write $C^+ \in \mathbb{R}^{N_{\text{fut}} \times d_c}$, where N_{fut} is the total number of compressed tokens across views and d_c is their context width. Attention projections map these tokens to the action expert's hidden width d_h.

3.3 Action expert with correction adapter

The action expert receives current-context tokens C, future-context tokens C^+, and a projection of the proprioceptive state s_t. Its 18 transformer layers alternate between the two context streams. With zero-based indexing, even layers cross-attend to C and odd layers cross-attend to C^+. Every layer also applies self-attention among the action tokens. This gives both observed and predicted scene information repeated opportunities to influence the generated trajectory.

An embodiment-specific input/output mapping handles each robot's state fields and control semantics. For shared tensor processing, an action chunk with d_a active control dimensions is padded to width $d_{\max}$. A validity mask excludes padded dimensions and invalid timesteps from losses and dispatch. In the learning equations below, A and $\hat{A}$ denote these normalized, padded chunks. At execution, the output mapping removes padding and restores native units. This keeps the learning representation distinct from the physical control interface in Eq. (1).

The action expert uses conditional flow matching [15]. For one policy call, we omit the fixed physical index t and write the noisy chunk as A^τ. The velocity network $v_\theta(A^\tau, \tau \mid s, C, C^+)$ is conditioned on the current state $s = s_t$ and both context streams. Inference starts from Gaussian noise at $\tau = 1$ and integrates toward $\tau = 0$ in ten numerical steps. The integration rule is deterministic conditional on the initial noise, while the sampled noise makes the policy stochastic. Physical execution time and internal flow time are separate. Section 3.4 defines the path and target velocity.

Condition tokens remain fixed during numerical integration, so their projected keys and values are computed once and cached across flow steps. The noisy action tokens and velocity estimates are updated at each step. During recovery, the continuous correction code c_t conditions a residual adapter after the ninth transformer layer, corresponding to zero-based index 8. The adapter adds $\alpha \odot C_\phi(h_\tau, c_t)$ to the action hidden states, and the remaining nine layers predict the corrected flow velocity. The code stays fixed for one candidate, while the hidden states and residual are recomputed at every integration step. All policy and correction-branch parameters remain fixed during deployment.

A separate head predicts local-phase progress at each action position. The BEHAVIOR reference configuration predicts 50 controls and executes at most 32 before requesting a new chunk. Longer predictions provide context for the dispatched prefix, and the next observation allows the policy to revise the remaining movement. Predicted progress helps monitoring but does not establish physical completion. A detected abnormal outcome invokes the recovery interface.

3.4 Training details

3.4.1 Training sample construction

Each training sample is anchored at one physical step. It contains the task instruction, robot state, synchronized multiview history, and a target action chunk. Recorded future frames and phase annotations provide additional targets when available. Input histories end at the anchor step. Future observations and actions appear only as supervised targets or offline annotation evidence.

For the BEHAVIOR 2026 configuration described here, training uses the official corpus of 20,000 teleoperated demonstrations, totaling approximately 1,950 hours across 100 household tasks and seven scenes [16]. Demonstrations are collected through the JoyLo whole-body interface, which coordinates the mobile base, torso, arms, and grippers. The average trajectory lasts 5.9 minutes, and the annotations cover 31 skill primitives, including grasping, pouring, wiping, and articulated-object manipulation [17]. These extended trajectories require the policy to handle object-state changes and dependencies between successive operations.

Multiview imagery, proprioceptive joint states, linguistic instructions, and continuous robot control streams are temporally aligned by hardware timestamps into training segments anchored at task and skill intervals. Official head-camera streams recorded at 720×720 resolution and dual wrist-camera streams recorded at 480×480 resolution are bilinearly downsampled to 224×224 for policy training, matched with continuous robot states and controls at 30 Hz. Self-supervised world model pretraining ingests visual inputs at 256×256 spatial resolution. Proprioceptive states and multi-axis action dimensions undergo quantile normalization based on calibrated empirical distributions across the training split. The embodiment adapter instantiates 23-dimensional absolute continuous commands encompassing whole-body actuation channels.

Training windows retain the complete task instruction, while skill annotations define the temporal boundaries used for auxiliary progress supervision and transition sampling. In temporal segments where primitive intervals overlap, precedence is granted to the earlier-initiated skill phase. Action supervision follows valid trajectory steps across skill boundaries. Autonomous training protocols maintain separate boolean masks across task phases, progress estimators, and embodiment channels, ensuring that missing sensory annotations or auxiliary labels do not contaminate valid supervisory signals.

History sampling schedule. Each training input contains five past frames and the current frame. We sample one positive look-back offset from each of the five intervals bounded by $[30, 84, 138, 192, 246, 300]$, using a log-uniform distribution within each interval. The frame at offset Δ is taken from $t - \Delta$. We append the frame at t and sort the six frames chronologically, using the same timestamps across cameras. Deployment

uses fixed relative offsets $[-256, -205, -154, -102, -51, 0]$. At 30 Hz, training look-back offsets span one to ten seconds, and the oldest deployment frame is 8.53 seconds old. A lookup before episode start repeats the initial frame and carries a temporal-padding flag.

Transition sampling and regularization. The boundary-sampling configuration increases sample weights fivefold within 60 frames on either side of a primitive transition. Proprioceptive dropout decreases linearly from 0.3 to 0.05 over the first 60% of training. This encourages the policy to use visual context rather than rely only on robot state. Non-gripper action errors receive velocity-dependent weights in $[0.5, 1.5]$, giving more emphasis to faster demonstrated movements. These weights are distinct from the binary validity masks. Optional pace conditioning appends a quantized demonstration-duration category to the task text. At inference, the category comes from a checkpoint-specific task mapping or an explicit request, not the unknown duration of the ongoing episode.

3.4.2 World-model and vision-language pretraining

The first two stages learn representations before continuous-policy optimization. Stage 1 trains the world model from multiview transitions. Stage 2 trains the vision-language backbone with latent-action targets, FAST action tokens, continuous action candidates, and embodied question answering.

We denote losses by L and stop-gradient by $\mathrm{sg}(\cdot)$. The operators MSE_M and MAE_M average squared and absolute error over entries enabled by mask M. Masks refer to the domain of each loss. They may select valid action dimensions, timesteps, camera views, or annotations. A loss with no valid target entries is omitted.

World-model pretraining. Stage 1 initializes the inverse dynamics model and the future feature predictor independently, optimizing both modules while maintaining the primary visual encoder frozen. Let $m_v \in \{0,1\}$ represent the binary sensor-validity indicator for viewpoint v, and let w_v denote its corresponding reconstruction weight. Utilizing the teacher latent representation z^* from the inverse dynamics model, the pretraining objective is formulated as

$$L_{\text{world}} = \frac{\sum_{v=1}^{V} w_v m_v \,\mathrm{SmoothL1}(\hat{F}_v^+, F_v^+)}{\sum_{v=1}^{V} w_v m_v} + \lambda_{\text{reg}} \,\mathrm{Reg}(z^*), \tag{8}$$

where SmoothL1 compares predicted and observed feature tensors, Reg denotes latent regularization, and λ_{reg} controls its weight. Samples without a valid current–future view pair are excluded. After Stage 1, the inverse encoder is frozen to provide latent-action targets. The future predictor is transferred to the policy and updated again during joint continuous-action training.

Shared vision-language supervision. Stage 2 exposes the core VLM backbone and its dedicated prediction queries to a composite multi-task objective governed by

$$L_{\text{pre}} = L_{\text{FAST}} + \lambda_{\text{AQ}} L_{\text{AQ}} + \lambda_{\text{LA}} L_{\text{LA}} + \lambda_{\text{VQA}} L_{\text{VQA}}. \tag{9}$$

Each loss is evaluated only for samples with the corresponding targets. The shared backbone processes visual context and task language, while output queries and heads supply the different predictions. The following paragraphs define each supervision stream. During teacher-forced language or action-token training, causal masking prevents a prediction from seeing later target tokens. Policy-conditioning queries must likewise remain independent of answer and action targets.

▶ *Latent-action prediction.* To endow the VLM backbone with temporal forward-looking dynamics without violating causal inference, a dedicated latent-action head maps transformed query tokens to an estimated transition vector $\hat{z}$. The supervisory target is distilled directly from the frozen inverse dynamics model through

$$L_{\mathrm{LA}} = \|\hat{z} - \mathrm{sg}(z^*)\|_2^2. \tag{10}$$

The frozen teacher uses current and future observations to produce the target z^*. The student predicts $\hat{z}$ from current and past observations and language. Stop-gradient keeps the teacher fixed while the student learns to predict its transition representation. Future observations are therefore used for supervision, not as deployed policy inputs.

▶ *Discrete actions with FAST.* To link the linguistic autoregressive capacities of the transformer backbone with macroscopic trajectory structure, continuous control segments are quantized through the FAST frequency-domain action tokenizer [18]. Given an action trajectory A transformed into an autoregressive token sequence $y_1, \ldots, y_T$, the backbone minimizes the standard sequence cross-entropy loss under teacher forcing via

$$L_{\mathrm{FAST}} = -\sum_{r=1}^{T} \log p_\theta(y_r \mid x, g, y_{<r}), \tag{11}$$

where T is the token-sequence length, p_θ is the conditional distribution over the discrete vocabulary, and $y_{<r}$ is the target token prefix. The FAST configuration uses a vocabulary of 2,048 tokens and a sequence budget of 256 tokens. FAST supplies action-sequence supervision to the backbone, while the flow-matching action expert generates continuous controls at deployment.

▶ *Continuous candidates and scores.* Complementing discrete sequence learning, a set of parallel action queries along with a confidence estimator output continuous trajectory candidates directly from the transformer representation. The query heads decode N prospective trajectory candidates $\hat{A}^{(n)}$ alongside scalar predicted error margins $\hat{e}_n$. The discrepancy of each candidate is quantified through $e_n = \mathrm{MAE}_M(\hat{A}^{(n)}, A)$, in which the valid mask M excludes unsupported joints and invalid padding steps. Training employs a winner-takes-all paradigm paired with detached error regression via

$$n^* = \arg\min_n e_n, \qquad L_{\mathrm{AQ}} = e_{n^*} + \frac{\lambda_{\mathrm{score}}}{N} \sum_{n=1}^{N} (\hat{e}_n - \mathrm{sg}(e_n))^2. \tag{12}$$

Selecting a solitary winning candidate across the complete time horizon preserves distinct trajectory modes, discouraging the multi-hypothesis regression from averaging mutually incompatible paths into unsafe intermediate trajectories. Detaching the target error e_n prevents the score-regression loss from updating trajectory predictions through that target. Gradients through the predicted score $\hat{e}_n$ can still update the score head and any shared representations on its branch.

▶ *Embodied question answering and local goals.* To ground physical affordances and spatial relationships directly into linguistic tokens, Stage 2 incorporates visual question answering across scene layout, task progress, and upcoming local milestones. The contextual sequence integrates multiview frames, the task instruction, and textual question prompts, whereas target answers formulate intermediate milestones, including repositioning an object or orienting toward a target receptacle. These localized goals are processed as standard linguistic answers derived from semantic demonstrations without necessitating dedicated hierarchical goal-decoding heads. The ground-truth answer sequences are withheld from the conditioning prompt and introduced strictly as teacher-forcing targets, preventing information leaks during multimodal feature extraction.

3.4.3 Joint policy optimization

Stage 3 jointly trains the VLM backbone, future predictor, action expert, and enabled auxiliary heads. Flow matching supplies the main continuous-action objective. Action-query supervision continues on samples with valid trajectories, and auxiliary losses constrain predicted features, action representations, geometry, and task information. FAST token prediction is disabled during this stage.

▶ **Conditional flow matching.** The continuous action expert models whole-body trajectories by learning a time-dependent velocity field along a probability path connecting pure Gaussian noise to demonstration segments. For a demonstrated trajectory A, we construct the intermediate noisy segment

$$A^{\tau} = (1-\tau)A + \tau\varepsilon, \qquad \varepsilon \sim \mathcal{N}(0, I), \tag{13}$$

where $\tau \in [0,1]$ denotes continuous flow time and I represents the identity covariance. This linear interpolation between demonstration actions and Gaussian noise has target velocity $\varepsilon - A$. The action expert network v_θ is supervised to regress this velocity conditioned on the noisy segment, proprioceptive state s, causal context embeddings C, and predicted prospective visual features C^+ through

$$L_{\mathrm{FM}} = \mathbb{E}_{\tau,\varepsilon,A}\left[\mathrm{MSE}_M\left(v_\theta(A^{\tau}, \tau \mid s, C, C^+), \varepsilon - A\right)\right]. \tag{14}$$

The expectation uses demonstrated action chunks, standard Gaussian noise, and uniformly sampled $\tau \in [0,1]$. The mask M excludes padded steps and inactive control dimensions. Since the target is the derivative with respect to increasing τ, inference integrates the learned field with negative time increments from one to zero. This matches the noise-to-action convention in Section 3.3.

▶ **Prospective feature consistency.** To retain predictive visual information during supervised policy updates, joint optimization aligns causal world predictions with observed future features through

$$L_{\mathrm{future}} = \frac{\sum_{v=1}^{V} m_v \|\hat{F}_v^+ - F_v^+\|_F^2}{\sum_{v=1}^{V} m_v}, \tag{15}$$

where the squared Frobenius norm sums feature errors within a view. Here $m_v = 1$ requires a valid current–future feature pair, and samples without one are excluded. This equation expresses the feature-consistency objective at a conceptual level. The training recipe records separate distillation and perceptual components for this purpose, as distinguished below.

▶ **Action-chunk representation alignment.** We pool the action expert's tokens over the prediction horizon, project them, and normalize the resulting vector to obtain $\hat{z}_a$. A fixed linear projection of the flattened target chunk, followed by the same normalization, produces z_a. The alignment objective is

$$L_{\mathrm{align}} = \mathrm{MSE}(\hat{z}_a, \mathrm{sg}(z_a)). \tag{16}$$

The target z_a summarizes the current sample's complete action chunk, rather than the chunk from a later policy call. It is used only for supervision and is not supplied to the deployed policy. The objective encourages chunk-level representation consistency, while flow matching determines the individual control values.

▶ **End-effector geometry.** Joint-space errors can have different Cartesian consequences across poses. We therefore compare predicted and target end-effector motion through a common whole-body kinematic mapping K_r. Let $\hat{A}$ denote the predicted clean action chunk supplied to this auxiliary objective. Both chunks are converted to the same physical units and evaluated from the same initial state s

$$L_r = \mathrm{MSE}_{M_r}\left(K_r(s, \hat{A}), K_r(s, A)\right), \qquad r \in \{\mathrm{pos}, \mathrm{rot}\}, \tag{17}$$

where r selects position or rotation increments of the active end-effectors. The mask M_r selects valid end-effectors, timesteps, and geometric components. Both branches use the same reference frame and rotation convention. These losses encourage agreement with demonstrated motion. They do not test collision avoidance, contact stability, or dynamic feasibility.

▶ **Semantic identity and temporal progress.** For samples with a valid task identifier, an auxiliary classification head averages the final-layer action representations and predicts task identity through cross-entropy $L_{\text{task}} = -\log p_{\text{task}}(y_{\text{task}})$, where y_{task} is the task label. This objective preserves task information in the action features without replacing the language instruction. It is separate from the local-phase and progress objectives grouped in L_{status}.

A separate linear head with sigmoid activation predicts relative skill-phase progress $\hat{p}_{t,j}$ at each action position. For the annotated skill phase $[t_0, t_1)$ active at the anchor step t, the target is the fraction of the interval elapsed after the corresponding action step

$$p_{t,j} = \text{clip}\left(\frac{t+j-t_0+1}{t_1-t_0}, 0, 1\right). \tag{18}$$

Only positions satisfying $t_0 \le t+j < t_1$ contribute to the masked mean squared progress loss. Progress masks are defined separately from action-validity masks. The status objective L_{status} aggregates the enabled local-phase and progress objectives and excludes the task-identity loss L_{task}.

Progress is learned from relative positions within demonstrated skill phases and is not a probability of physical completion. The predicted curve describes a proposed action chunk, including its unexecuted suffix. Feedback to MetaBrain refers to the observed local phase and is interpreted together with the executed prefix and observed outcomes. Whole-episode progress is not substituted for skill-phase progress. A value near one does not independently establish physical completion, which requires verification of the physical completion conditions.

The total optimization objective summarizes the individual primary and auxiliary objectives through

$$\begin{aligned} L_{\text{train}} &= L_{\text{FM}} + L_{\text{prior}} + \lambda_{\text{AQ}} L_{\text{AQ}} + L_{\text{aux}} + 0.1(L_{\text{distill}} + L_{\text{perc}}), \\ L_{\text{aux}} &= L_{\text{task}} + L_{\text{status}} + L_{\text{align}} + 5\times 10^{-6} L_{\text{pos}} + 10^{-3} L_{\text{rot}}, \end{aligned} \tag{19}$$

where L_{distill} and L_{perc} implement the future-feature consistency objective in equation (15). The conceptual L_{future} is not added again. The Gaussian-prior loss L_{prior}, task-identity loss L_{task}, and aggregate status loss L_{status} each enter the total objective with unit weight. End-effector position and rotation losses have weights 5×10^{-6} and 10^{-3}, respectively. Each objective is evaluated only where its required observations and labels are valid.

Knowledge insulation [19] controls gradient flow through the current-condition token path from the VLM to the action expert. For a representation h on this path, we apply

$$\text{KI}(h) = \gamma h + (1-\gamma)\,\text{sg}(h). \tag{20}$$

This operator preserves the forward activation and scales gradients on this path by $\gamma \in [0,1]$. We apply it to current-context tokens supplied to the action expert. It does not freeze the VLM or scale every gradient entering it. Future-context prediction and auxiliary supervision remain separate paths through the training graph.

3.4.4 Sampling schedules, optimization, and hyperparameters

The objectives above specify supervision. The following schedules specify how training data, flow evaluations, and parameter updates are allocated.

Table 3 Recorded schedules for the three base-model stages. The correction schedule is given in Section 2.5. Training configuration and systems throughput measurements have different hardware scales and are reported separately.

Setting	World model	VLM	Continuous action
Global batch	4,608	2,048	2,048
Per-GPU batch	72	32	32
Training plan	Up to 10 epochs	150,000 steps	500,000 steps
Save interval	5,000 steps	20,000 steps	20,000 steps
Initial learning rate	3×10^{-4}	7.5×10^{-5}	7.5×10^{-5}
Warm-up	10,000 steps	2,000 steps	2,000 steps
Later schedule	Constant	Cosine to 2.5×10^{-6}	Cosine to 2.5×10^{-6}
Optimizer	AdamW	AdamW	Local Muon and AdamW
Weight decay	0.01	0.001	0.001
Gradient clipping	1.0	1.0	1.0
Precision	BF16	BF16	BF16
Image resolution	256×256	224×224	224×224
Updates	Inverse dynamics model and future predictor	VLM and enabled heads	VLM, future predictor, action expert and enabled heads

► **Data mixture and adaptive flow sampling.** Training batches sample heterogeneous datasets according to configured mixture probabilities. For each demonstration i, the action expert first evaluates $N_0 = 2$ noise-time pairs. Their masked flow losses provide a difficulty score

$$r_i = \mathrm{Mean}_{1 \le r \le N_0}(L_{i,r}) + \beta_{\mathrm{sample}} \, \mathrm{Std}_{1 \le r \le N_0}(L_{i,r}), \tag{21}$$

where β_{sample} controls the contribution of loss variation. More difficult demonstrations receive additional flow evaluations, with at most eight pairs per demonstration and a target batch average of four.

To separate the sampling budget from each demonstration's explicit loss weight, we average flow losses within each demonstration and then across the batch

$$L_{\mathrm{batch}} = \frac{1}{B} \sum_{i=1}^{B} \left(\frac{1}{N_i} \sum_{r=1}^{N_i} L_{i,r} \right), \tag{22}$$

where B is the batch size, $N_i \in \{2, \ldots, 8\}$ is the number of flow evaluations for demonstration i, and $L_{i,r}$ is its masked flow loss at sample r. This reduction gives every demonstration the same explicit outer weight while assigning more computation to difficult examples. The multimodal backbone runs once per demonstration, and its representations are shared across flow branches. Backbone objectives independent of flow time are evaluated once. Auxiliary objectives that depend on action-suffix states use one designated branch, so their effective weights do not grow with N_i.

► **Optimization schedules.** Table 3 summarizes the three base-model stages. Each uses 64 GPUs. The world-model checkpoint transferred to later stages is taken at step 45,000. The final 1% of recorded sequence intervals forms an internal validation partition for monitoring world-model training, separate from the downstream benchmark evaluation.

Optimizer dynamics are specialized according to layer types across training phases. Stage 1 applies the AdamW optimizer with hyperparameter settings $\beta = (0.9, 0.999)$, numerical stabilization constant $\varepsilon_{\mathrm{opt}} = 10^{-8}$, and unit gradient accumulation, excluding normalization gains and linear biases from weight decay regularization. Stage 2 combines FAST and VQA cross-entropy, continuous action-query regression, and latent-action distillation. The continuous action expert is not evaluated in this stage. During Stage 3

continuous-action training, structured weight matrices within attention projections and feed-forward layers are optimized via Local Muon, while remaining embedding and auxiliary layers are updated via AdamW. Muon configurations maintain a momentum factor of 0.95, Nesterov momentum acceleration, and five internal Newton–Schulz orthogonalization iterations.

► **Loss weights.** Stage 2 uses $\lambda_{\text{AQ}} = 1.0$, $\lambda_{\text{LA}} = 0.1$, and $\lambda_{\text{VQA}} = 1.0$. Stage 3 reduces the action-query weight to $\lambda_{\text{AQ}} = 0.1$ and uses knowledge-insulation scale $\gamma = 0.1$ on the current-context path. Task and status supervision follow Eq. (19). The phase-classification component has an implementation default of 0.1 and must be explicitly configured for the reported status-supervision recipe.

4 Infrastructure for Efficient Training and Deployment

Long-horizon embodied learning is limited by the cost of collecting, processing, and evaluating extended interaction sequences. For A^2-WLA, multiview history encoding and repeated flow evaluations make training expensive. In BEHAVIOR, simulation, rendering, policy inference, and variable episode lengths also make full-suite evaluation costly. Our infrastructure addresses these costs through efficient data access, shared model computation, distributed optimization, and parallel simulation scheduling.

We report training and evaluation measurements separately. Training comparisons measure demonstration throughput under the stated hardware and batch configurations. Evaluation comparisons measure the complete runtime of the optimized worker pool against an extrapolated serial reference. This distinction separates gains in model-training efficiency from the combined effects of simulation optimization and parallel hardware.

4.1 Training Optimization and Distributed Scaling



Figure 8 Data processing and distributed execution performance before and after optimization. **(a)** single-GPU data processing time, **(b)** single-GPU step time, **(c)** eight-GPU step time, **(d)** eight-GPU throughput, and **(e)** eight-GPU time to first step. Approximate values are marked with ∼. Percentages below the panels indicate relative decreases (↓) or increases (↑), calculated from the reported values. Single-GPU and eight-GPU comparisons use their respective fixed configurations and do not form one continuous ablation sequence.

► *I/O and Data Ingestion.* Continuous action optimization via flow matching constitutes the primary computational bottleneck within the multi-stage training pipeline. In the baseline single-device implementation, each optimization step requires approximately 3.03 seconds, with input processing alone accounting for 1.30 seconds. This delay stems from redundant visual decoding, where identical temporal video frames

are repeatedly decompressed across overlapping observation windows. To eliminate this bottleneck, we consolidate frame extraction through batch JPEG decompression, map demonstration datasets into Apache Arrow shared-memory caches, and streamline inter-dataset indexing. These adjustments reduce per-step input preparation time from 1.30 seconds to 28 milliseconds. Together with asynchronous background data prefetching, single-GPU step latency drops to 1.13 seconds, representing a 2.7$\times$ training acceleration. Furthermore, expanding dataset diversity from ten to 100 manipulation tasks incurs only a 3% throughput penalty, confirming that data routing scales with task coverage without introducing proportional preprocessing overhead. Figure 8 summarizes how each of these targeted improvements progressively reduces both startup overhead and step synchronization latency.

▶ *Distributed Startup and Synchronization.* Distributed training across multi-GPU clusters frequently suffers from slow initial startup and hidden communication stalls. During job initialization, dozens of worker processes often attempt to parse the same raw dataset files simultaneously, causing severe storage contention and prolonged idle waiting. We parallelize dataset preparation, share sampler weights from rank zero, and delay parameter initialization on non-primary ranks to reduce repeated loading. During active training steps, device synchronization is further streamlined by locking the backward communication order into a fixed static schedule. This configuration groups scattered parameter gradients into contiguous memory buffers for unified all-reduce synchronization, while eliminating redundant broadcast transfers for static model buffers that do not change during training.

▶ *Prefix Computation Sharing.* A substantial computational redundancy in continuous flow matching arises from sampling multiple noise-time pairs (τ, ε) for each demonstration trajectory. Although these stochastic pairs evaluate distinct flow targets, they share identical visual histories, language instructions, and proprioceptive states. Rather than evaluating the complete model repeatedly, our implementation computes the multimodal prefix once through the vision-language backbone. The resulting representations are shared across the action expert's noise-time evaluations, which are batched instead of run serially. The reference configuration uses four evaluations per demonstration on average, while the adaptive schedule varies the number by sample. Each flow sample processes its own noisy continuous action and time coordinate, whereas resulting backpropagation gradients accumulate into the shared prefix representation. For the same samples and masks, shared-prefix execution preserves the per-demonstration reduction in Eq. (22). Gradients from the action branches accumulate into the shared prefix. This is distinct from claiming bitwise equivalence of complete training runs. Together, shared-prefix execution and Arrow caching achieve 261.9 samples per second on eight GPUs.

▶ *Kernel Stabilization and Optimizer Sharding.* Additional latency in deep transformer training arises from dynamic sequence lengths and kernel launch overhead. We mitigate these delays by caching static tokenizer outputs, rotary position embeddings, and task metadata whenever input sequences permit reuse. Stable sequence-length buckets and padding upper bounds that increase only when necessary reduce repeated Triton compilation and autotuning. These optimizations reduce static host-side overhead from 33 milliseconds to 0.8 milliseconds and forward latency from 243.7 to 210.7 milliseconds. At the optimization boundary, we coordinate AdamW with the matrix-oriented Local Muon optimizer. We distribute 126 independent matrix updates across eight local ranks according to their computational cost. Each update uses the configured Newton–Schulz iterations, and the results are gathered in BF16. Sharded Local Muon reduces optimizer latency from 67.0 to 19.7 milliseconds. Bitwise equivalence was verified for the compared sharded optimizer updates, not for the complete training trajectory.

The final SDPA-based implementation reaches 427.1 demonstration samples per second on eight GPUs with global batch size 256. Multiple flow samples from one demonstration count as one demonstration sample. The $\pi_{0.5}$ reference reaches 106 demonstration samples per second on the same GPU hardware with matching image

resolution and action horizon. Each implementation uses a batch size chosen to utilize the available resources. The resulting 4.03× ratio is an implementation-throughput comparison under these conditions, rather than a matched-batch architectural ablation. When scaling to a cluster of 64 Pro6000 GPUs, the framework retains approximately 98% of theoretical linear scaling efficiency, demonstrating minimal communication overhead across distributed compute nodes. Figure 9 illustrates the aforementioned optimization gains.

Figure 9 Throughput gains from **(a)** dedicated computation paths and scheduling, **(b)** static token, rotary-index and metadata caches, and **(c)** Sharded Local Muon. Each panel compares its own fixed configuration. Gains from different panels cannot be added.

4.2 Heterogeneous Model Serving and Robot Execution

The reported BEHAVIOR deployment separates high-level reasoning from action generation. The Qwen3.8 27B model used by MetaBrain runs in BF16 with tensor parallelism across two GPUs. The complete A^2-WLA policy, including its 2B vision-language backbone, world-model components, action expert, and correction adapter, runs in BF16 on a separate GPU. Base and corrected action generation both use ten flow-integration steps.

The simulator and policy service communicate through synchronous WebSocket requests. After executing up to 32 controls from a 50-step chunk, the runtime acquires fresh observations and requests the next chunk. At 30 Hz, an uninterrupted 32-step prefix spans approximately 1.07 seconds. The policy-call interval also includes inference and communication time. Observation buffers and execution records are cleared at each episode boundary to prevent information from carrying over between episodes.

4.3 Scalable Simulation Infrastructure for Long-Horizon Benchmarks

The complete BEHAVIOR 2026 evaluation comprises 100 tasks with ten evaluation instances per task, yielding 1,000 episodes across the benchmark's seven scenes. The measured run contains 15,113,902 simulator control steps. At 30 Hz, this is approximately 140 hours of simulated manipulation, averaging 8.40 minutes per episode. This rollout duration differs from the approximately six-minute mean of the training demonstrations reported in Section 3.4.1. When factoring in photorealistic rendering, rigid-body contact dynamics, and neural network inference, sequential execution on a single worker requires an estimated 1,275 wall-clock hours, or roughly 53.1 days of continuous computation. This cost makes repeated full-suite evaluation difficult. Episode lengths also vary, so efficient scheduling must allow workers to take on new instances as they finish their current tasks.

Table 4 Cost of the complete 2026 evaluation. The serial value is an estimate from recorded unoptimized worker costs. The optimized value is a measured complete run. Their ratio combines system changes and additional hardware.

Setting	Serial reference	Optimized evaluation
Hardware	One RTX 4090 or Pro6000	Eight Pro6000 GPUs
Concurrent workers	1	24
Coverage	100 tasks, 1,000 episodes	100 tasks, 1,000 episodes
Simulated duration	$\approx$ 140 hours	$\approx$ 140 hours
Wall-clock duration	$\approx 1,275$ hours	$\approx$ 18.1 hours
Episode throughput	$\approx$ 0.78 per hour	$\approx$ 55.2 per hour
Measurement basis	Extrapolated worker costs	Full-suite measurement

Our evaluation infrastructure combines cache reuse, faster simulator startup, and coordinated CPU and GPU resource allocation. These changes reduce repeated work in the evaluation pipeline while keeping task definitions, simulation settings, and model execution logic unchanged. The optimized configuration supports three concurrent workers per Pro6000 GPU, including simulation and policy inference. On an eight-GPU node, this arrangement sustains 24 active simulation workers in parallel. A dynamic scheduler assigns the next task to each available worker, reducing idle time between unequal-length episodes.

The optimized evaluation node completes the 1,000 episodes in 18.1 hours, corresponding to approximately 55.2 episodes per hour and an aggregate throughput of 7.7$\times$ simulated real time. The eight-GPU allocation in Table 4 describes the simulation and policy workers. The separately hosted reasoning service is described in Section 4.2, so this node allocation should not be read as the total hardware requirement of every full-system deployment. Relative to the estimated unoptimized single-worker runtime, this is a 70.4$\times$ end-to-end speedup. The ratio combines software changes with increased parallel hardware and does not measure a software-only improvement on fixed hardware. The distributed scheduler further supports multi-node deployment, supporting up to 96 concurrent simulator workers across a four-machine cluster. This infrastructure makes a complete evaluation practical within a day under the measured configuration, supporting more frequent model and system comparisons.

5 Experimental Evaluation

We evaluate A^2-MEAS across long-horizon household activities, bimanual manipulation, and physical robot tasks. The experiments examine how model specialization and agent coordination affect task completion, whether the learned action policy transfers across scene variations, and how the complete system executes sequential manipulation in the real world.

5.1 Experimental Setup

BEHAVIOR 2026 evaluates long-horizon whole-body control over 100 household tasks spanning multiple scenes, with demonstration trajectories averaging approximately six minutes (revision needed to add the longest task duration and clarify the long-horizon demands of the benchmark). Our public-set analysis uses records selected from evaluation batches, with ten instances per task and 1,000 episodes per configuration. The single-model baseline uses one A^2-WLA checkpoint across all tasks. The multi-model baseline selects an action model and execution configuration for each task. Building on this action capability, A^2-MEAS coordinates MetaBrain, grounding agents, and A^2-WLA through learned correction codes that connect task reasoning and spatial evidence to continuous action generation. Official hidden-set results are reported separately in Section 5.2.3.

The reference action interface uses six frames per view, 23-dimensional actions, and a 50-step prediction horizon, with the first 32 steps executed before the next observation. Integration steps and executed prefixes follow the corresponding configuration. All model parameters remain fixed at test time, and human takeover, timeouts, and exhausted episode budgets count as failures.

We report task-macro Q-score, complete-task success rate (SR), and successful task coverage. Q-score measures the fraction of goal conditions satisfied, while SR requires completion of the entire task. Let Q_i and S_i denote the mean goal-satisfaction score and success fraction for task i. Over K tasks,

$$Q = \frac{1}{K}\sum_{i=1}^{K} Q_i, \qquad \mathrm{SR} = \frac{100}{K}\sum_{i=1}^{K} S_i. \tag{23}$$

Successful task coverage counts tasks with at least one complete success among their ten evaluation instances. Equal episode counts per task make task-macro and episode-micro success rates coincide in these benchmark evaluations.

5.2 Long-Horizon Household Manipulation on BEHAVIOR

5.2.1 Overall Performance

In our public-set evaluation records (Table 5), A^2-MEAS obtains a Q-score of 0.6411 and a complete-task success rate of 45.40%, with 454 successes in 1,000 recorded episodes and at least one success on 88 tasks. The corresponding multi-model and single-model results achieve 0.6040 and 0.4597 Q-score, respectively. The recorded task coverage increases from 70 to 80 to 88 tasks across the three configurations, while the number of tasks with mean Q-score of at least 0.8 rises from 17 to 30 to 34. These patterns motivate the task-level analysis below.

Table 5 Public-set evaluation results for BEHAVIOR 2026, with 100 tasks and 1,000 recorded episodes per configuration. Coverage counts tasks with at least one complete success.

Configuration	Q-score	Success (%)	Successes	Coverage
A^2-WLA single model	0.4597	27.20	272/1,000	70/100
A^2-WLA multiple models	<u>0.6040</u>	<u>40.60</u>	406/1,000	80/100
A^2-MEAS complete system	**0.6411**	**45.40**	454/1,000	88/100

5.2.2 Task-Level Performance and Completion Reliability

Figure 10 shows the performance of all 100 tasks in the public-set records. Eleven tasks are completed in every recorded instance, spanning activities such as turning on a radio, cooking hot dogs, installing a modem, and laying tile floors. At the other end of the distribution, eight tasks have Q-scores below 0.2, including pizza preparation and patio cleaning, both with zero goal satisfaction. This spread shows that broad benchmark coverage coexists with sharply concentrated weaknesses.

Performance varies substantially even within familiar activity families. Cooking hot dogs and making microwave popcorn both achieve 100.00% success, whereas cooking bacon reaches 20.00% and making pizza has no successful instances. Installation tasks exhibit a similar spread. Smoke-detector and modem installation succeed in all ten instances, while scanner installation succeeds in three. Success on one activity therefore does not establish reliable coverage of its broader task family.



Figure 10 Task-level performance in the public-set evaluation records, ordered by decreasing mean Q-score, with ties resolved by task ID. Blue dots show Q-score, with labels rounded to three decimals for display. The final column reports complete successes out of ten recorded instances. The two panels show ranks 1–50 and 51–100. Task names are shortened for display. IDs identify the benchmark tasks.

Table 6 Public-set results for BEHAVIOR 2026. We include our self-reported result and the 15 highest-scoring entries in the published self-report list, ordered by increasing Q-score. These records follow the participating teams' reported protocols. Institution names follow leaderboard and archived participant records. Scores were accessed 31 October 2026 [20, 21].

Team or submission	Institution	Q-score	SR (%)
George Albrecht	CAU / GMU / EWHA	0.3862	20.00
Mirua	Xiaomi Robotics	0.3971	19.80
VERA	AXXX	0.4000	25.00
Newbie	morphic & 4dvlab	0.4040	21.70
Huawei AI Algorithm Dept	Huawei Technologies	0.4076	25.20
Lion	Lionrock AI Lab	0.4082	21.80
The Southern Cross	Independent	0.4099	23.00
MXI	Beijing 1011 Technology	0.4187	22.70
Sora	Independent	0.4195	22.50
Multi	mor	0.4302	19.80
Anyverse A2R	Anyverse-A2R	0.4321	24.70
VGI-SKT	SNU / SKT	0.4449	22.30
Robot Learning Collective	Independent	0.4458	27.30
tasman3001	Ambarella, Inc.	0.4808	30.40
asteroid	CLab	0.5143	30.80
A^2-MEAS (ours)	Anyverse–AutoLab	**0.6411**	**45.40**

High goal satisfaction also does not guarantee reliable completion. Of the 34 tasks with Q-score at least 0.8, five have complete-task success rates of 40.00% or lower. Food storage is a pronounced example, with a Q-score of 0.8375 but only one successful instance out of ten. Moreover, ten of the twelve tasks with no complete successes still achieve positive Q-scores. Gift-basket assembly and boxing books for storage reach 0.6500 and 0.5500, respectively. These results expose a gap between satisfying a substantial subset of goal conditions and consistently satisfying the entire task specification.

The task-wise profile identifies two complementary targets for improvement. For tasks with substantial goal satisfaction but few complete successes, the target is reliable satisfaction of all required conditions within the same episode. For tasks with near-zero scores, the target is to establish effective execution of the activity itself. Reporting Q-score together with complete-success counts makes these distinct performance regimes visible and provides a concrete basis for selecting tasks for further model and system development.

5.2.3 Comparison with Public Results

Table 6 compares public-set results. Our public evaluation used a remotely hosted Qwen3.8 27B MetaBrain. For the official hidden-set submission, limited bandwidth between the organizers' evaluation site and our server in China required a self-contained Docker deployment. The 24 GB GPU-memory limit forced us to replace the 27B coordinator with Qwen3.5 2B. This substantial reduction in coordinator capacity limits the submitted system, so the hidden-set results do not fully represent the capability of the 27B-based system.

On the official hidden set, A^2-MEAS obtains a verified Q-score of 0.4975 and 32.05% complete-task success [22], compared with 0.4951 and 30.95% for the separate A^2-WLA submission. The 2B coordinator thus provides a small gain. However, our tests show that it is substantially less accurate than Qwen3.8 27B at deciding when to intervene and sometimes interrupts execution unnecessarily. Its weaker recognition and intervention decisions reduce the benefit of system feedback. These limitations help explain the performance gap, although the different evaluation instances prevent attributing it to model size alone. We will release the Qwen3.8 27B version of MetaBrain for further evaluation and development.

Table 7 Public-set results on task IDs 0–49 of BEHAVIOR 2026, with 500 recorded episodes per configuration, and BEHAVIOR 2025 public-dataset results grouped by evaluation setting. A dash denotes an unreported success rate.

Method	Q-score	SR (%)	Evaluation context
Competition public-dataset evaluation [11]			
RLC	0.2605	11.20	4 checkpoints
Comet	0.1830	14.40	Competition submission
SimpleAI Robot	0.1943	14.00	Competition submission
The North Star	0.1702	12.80	Competition submission
Post-competition and subsequent reports			
Openpi Comet[23]	0.3450	—	2 checkpoints, reinforcement fine-tuning
$\pi_{0.5}$[7]	0.2626	—	4 epochs, single checkpoint
G0.5[7]	0.2904	—	1 epoch, single checkpoint
G0.5[7]	0.3136	—	4 epochs, single checkpoint
Our 2026 public-set subset, 50 tasks and 500 episodes			
A^2-WLA single model	0.4522	25.60	4 epochs, single checkpoint
A^2-WLA multiple models	0.5755	37.40	25 checkpoints
A^2-MEAS complete system	0.6191	41.40	Including the full system

Table 7 places our public-set results on the 50-task BEHAVIOR 2026 subset alongside methods evaluated on the public dataset of BEHAVIOR 2025, including RLC, Comet, Openpi Comet, $\pi_{0.5}$, and G0.5. The BEHAVIOR 2025 entries report public-dataset tests and are grouped by their reported evaluation settings. On task IDs 0–49, A^2-MEAS achieves 0.6191 Q-score and 41.40% success across 500 recorded episodes.

5.3 Bimanual Manipulation on RoboTwin 2.0

RoboTwin 2.0 evaluates 50 bimanual tasks under Clean and Randomized settings [24]. The randomized scenes vary background, clutter, lighting, table height, and language. Table 8 summarizes public reference results alongside our configurations, which use A^2-WLA as the action policy and add agent-guided correction in the complete system. The A^2-WLA configuration completes 100 episodes per task in each setting, for 10,000 episodes in total. Public references retain the evaluation protocols reported by their respective sources. We report complete-task success for both settings, with Average defined as their arithmetic mean.

A^2-WLA achieves 94.26% success in Clean scenes and 93.70% under randomization, averaging 93.98%. This is 14.23 percentage points above the reported $\pi_{0.5}$ result of 79.75% and 0.73 points above G0.5 at 93.25%. Agent coordination raises the average to 94.93%, a further 0.95-point gain, while MotuBrain reports 95.95% under its own protocol. Our simple A^2-WLA architecture is thus competitive with leading bimanual policies without requiring a separate large-scale pretraining strategy tailored to this benchmark. At the same time, success rates near 95.00% leave limited room to distinguish systems on these short tasks. We include RoboTwin as a reference for local manipulation competence, while the longer BEHAVIOR and real-robot tasks more directly test sustained coordination and recovery.

5.4 Real-World Manipulation

5.4.1 Short-Horizon Tasks

We define 18 tabletop tasks across five household settings, comprising *the study, bedroom, living room, kitchen, and entryway*, and report available results for 16 tasks. The tasks include storage and retrieval in

Table 8 Public references and our results on RoboTwin 2.0. Public entries follow their respective source protocols. Average is the arithmetic mean of Clean and Randomized success rates.

Method or configuration	Clean (%)	Randomized (%)	Average (%)
$\pi_{0.5}$ [9, 25]	82.74	76.76	79.75
LingBot-VLA (without depth) [25]	86.50	85.34	85.92
LingBot-VLA (with depth) [25]	88.56	86.68	87.62
Motus [26]	88.70	87.00	87.85
StarVLA [27]	88.70	87.80	88.25
LingBot-VA [28]	92.90	91.50	92.20
Fast-WAM [29]	91.90	91.80	91.85
G0.5 [7]	93.70	92.80	93.25
LingBot-VLA 2.0 [30]	93.52	92.80	93.16
MotuBrain [31]	95.80	96.10	95.95
Our configurations			
A^2-WLA	94.26	93.70	93.98
A^2-MEAS	**95.15**	**94.71**	**94.93**

confined spaces, plug insertion, food preparation, and parcel handling, testing grasping, placement, action sequencing, and contact control under varied object sizes, spatial constraints, and contact conditions. We use $\pi_{0.5}$ as the principal generalist baseline because of its strong manipulation performance across diverse real-world environments [9], and compare it with four fine-tuned A^2-WLA configurations. For a fair real-robot comparison, high-level feedback and test-time correction are disabled.

Each task uses 200 training trajectories, and a separate policy is trained for each task and configuration for 60,000 steps from the specified initialization. The A^2-WLA configurations include base fine-tuning, the

Table 9a Base-policy configurations and results. "+" highlights an added component. ✓ and × denote enabled and disabled options. "—" in the settings columns denotes an unrecorded setting. FAST initialization applies to the vision-language backbone and history encoder. Evaluation conditions and qualifications are given in Table 9b.

Configuration	History frames	Latent world model	FAST init.	Macro SR (%)
$\pi_{0.5}$ (baseline)	—	—	—	20.31
A^2-WLA configurations				
Config. 1 (base fine-tuning)	2	×	×	27.81
Config. 2 (+ latent world model)	2	✓	×	32.50
Config. 3 (+ six-frame history)	6	✓	×	37.81
A^2-WLA (full configuration)	6	✓	✓	41.88

Figure 11 Placeholder for real-robot execution sequences comparing A^2-WLA and $\pi_{0.5}$.

Table 9b Per-task successes / attempts. "—" denotes unavailable results excluded from the aggregate. 0/20 counts as 20 failures. Success is defined as whole-task completion. The Configuration 3 medicine and full-configuration cucumber counts remain provisional because their correspondence to the evaluated checkpoints is unresolved.

Context	Task	Evaluation focus	$\pi_{0.5}$	Cfg. 1	Cfg. 2	Cfg. 3	Full
Study	USB drive storage	Small-object grasping, opening, closing, and storage	6/20	8/20	11/20	13/20	15/20
	Keyboard pushback with obstacle avoidance	Action sequencing, pushing with obstacle avoidance	6/20	15/20	17/20	15/20	17/20
	Bookshelf organization	Placement in confined spaces, pose alignment	6/20	7/20	9/20	12/20	13/20
	Study supplies organization	Small-object storage, action sequencing	0/20	0/20	0/20	0/20	0/20
Bedroom	Skincare and cosmetics organization	Pose adjustment, stable placement	12/20	14/20	14/20	15/20	16/20
	Jewelry-box sorting	Small-object grasping, storage in compartments	0/20	0/20	0/20	0/20	0/20
	Eye-drop/medicine retrieval and return	Retrieval and placement in confined spaces, delivery and return	0/20	3/20	4/20	5/20	6/20
	Bedtime item preparation	Multi-object manipulation, action sequencing	7/20	8/20	10/20	13/20	14/20
	Object retrieval from a drawer	Target selection, retrieval and placement in confined spaces	2/20	4/20	5/20	8/20	9/20
Living room	Watch/wristband and earbud placement for charging	Target alignment, stable placement	12/20	8/20	11/20	12/20	13/20
	Plug insertion into a power strip	Insertion alignment, contact control	0/20	0/20	0/20	0/20	0/20
Kitchen	Container–lid matching	Object matching, alignment and closure	2/20	0/20	0/20	0/20	0/20
	Meatball transfer	Small-object sorting, placement into compartments	0/20	0/20	0/20	0/20	0/20
	Food-waste sorting	Transfer by pouring, sorted disposal	2/20	13/20	13/20	15/20	16/20
	Cucumber preparation	Tool manipulation, cutting contact	10/20	9/20	10/20	12/20	13/20
Entryway	Label attachment with a glue stick	Target alignment, attachment and pressing	0/20	0/20	0/20	1/20	2/20
	Parcel unpacking	Tool manipulation, cutting and box opening	—	—	—	—	—
	Parcel packing and sealing	Ordered packing, sequencing lid closure	—	—	—	—	—

multiview latent world model, a six-frame history window, and FAST action-token initialization (Table 9a). For the full configuration, the vision-language backbone and motion-aware history encoder are initialized from weights jointly trained with FAST on 18 tasks for 60,000 steps, while the action expert is initialized from pretrained action-policy weights. The FAST classification loss is disabled during subsequent A^2-WLA training. Sections 3 and 6.1 describe the model components and simulation ablations. These configurations use different complete training recipes. We evaluate each task and configuration over 20 trials and compute macro success as the mean of the available per-task success rates (Table 9b).

Table 9a summarizes the recorded results across the 16 tasks with available measurements. The full A^2-WLA configuration achieves 41.88% macro success, compared with 27.81% for base fine-tuning and 20.31% for $\pi_{0.5}$. The full configuration exceeds base fine-tuning by 14.06 percentage points, computed from the underlying counts. Configuration 3 and full-configuration aggregates remain provisional because of the two checkpoint-association issues identified in Table 9b.

The per-task results in Table 9b reveal both progress and remaining limitations. The full configuration completes 17/20 keyboard-pushback trials, 16/20 food-waste-sorting trials, and 15/20 USB-storage trials. At the same time, all four fine-tuned configurations achieve 0/20 successes on study supplies organization, jewelry-box sorting, plug insertion, container–lid matching, and meatball transfer. We report these results to provide a more complete picture of the evaluated embodied systems. Such tasks require small-object localization, placement into compartments, or precise alignment. Limited visibility, occlusion, and constraints imposed by the robot configuration may contribute to these failures alongside model errors. Figure 11 reserves

space for a visual comparison of A^2-WLA and $\pi_{0.5}$ execution. The following coffee-preparation experiment extends this evaluation to recovery during a longer task.

5.4.2 Long-Horizon Pour-Over Coffee Preparation

Pour-over coffee preparation requires the robot to handle objects, position a filter, and complete a sequence of operations under changing contact and support conditions. In deployment, A^2-MEAS completes the drink in approximately four minutes per run, with more than one hundred cups completed across deployment. To examine recovery within this longer activity, we evaluate two steps where a failed grasp can interrupt progress. Step 2 retrieves the filter from the rack and places it stably on the cup rim. Step 7 removes the filter from the cup and transfers it to a designated container.

For each step, we conduct 20 trials of direct base-policy execution from the original start, 20 trials of base-policy retry after a failed grasp and rollback, and 20 trials of Adapter recovery after rollback. Direct execution starts before the initial attempt, while both recovery conditions start after a failed grasp and rollback. These conditions are reported separately. A trial succeeds when the robot completes the placement or transfer, releases the filter, and withdraws the gripper. Step 2 also requires stable support on the cup rim. Step 7 with a used filter requires removal of the grounds.

During recovery, the runtime pauses pending actions after an anomaly and updates the images and robot state. Using execution history and diagnostic evidence, MetaBrain proposes an adjustment, and A^2-WLA generates corrective actions under Adapter modulation. After a short execution segment, the system observes the scene again and checks the recovery condition before deciding whether to continue. For a missed filter grasp, the correction aims to adjust the grasp position, regrasp, and lift the filter clear. Subsequent step completion measures whether execution can continue (Fig. 12).

The real-robot experiments use a failure-history-conditioned Adapter. It takes current observations and up to 64 historical state transitions, reads the history through cross-attention, and adds a gated residual before the action output head. This variant conditions its residual on observations and failure history. The full interface in Fig. 3 instead encodes all four CorrectionContext inputs and injects its residual at an intermediate action layer. The real-robot recovery results therefore evaluate the history-conditioned variant, not the complete four-input interface. We freeze the base model and train approximately 860,000 Adapter parameters with a flow-matching objective, using measured state sequences from correction segments as supervision. The gate is initialized to zero, and all parameters remain fixed at deployment. After rollback, the Adapter completes Step 2 in 19/20 trials (95.00%) and Step 7 in 16/20 trials (80.00%), while base-policy retry succeeds in 3/20 (15.00%) and 1/20 (5.00%), respectively.

6 Ablation Studies and Long-Horizon Execution Analysis

We analyze how action-model design and grounded correction contribute to long-horizon manipulation, then compare full-task conditioning with subtask scheduling and examine whether local recovery leads to continued progress and task completion. To make repeated training and evaluation feasible, we use two 12-task subsets with different purposes. Selected12 covers object transport, storage, cleaning, cooking, and assembly, and supports the action-model and task-conditioning studies. A separate Adapter subset tests how corrective context changes execution, including button pressing in turning on a radio, object alignment in hanging pictures and attaching a camera to a tripod, and successive object-handling operations in bringing water and washing a baseball cap. These activities require control to account for target-relative position, object orientation, and the current manipulation stage, allowing us to examine the contributions of corrective language, spatial grounding, and execution history. Adapter comparisons keep the same action model frozen



Figure 12 Grasp correction and step completion during pour-over coffee preparation. (a) Rack pickup in Step 2. (b) cup-rim pickup in Step 7. Each row shows a missed grasp, gripper opening and adjustment, regrasping, and lifting. Timestamps are playback positions in the respective clips. Stages are labeled from visible actions. (c) Direct execution and combined completion from the original start. (d) base-policy retry and the failure-history-conditioned Adapter after rollback. Each measured condition has 20 trials per step. Measured bars show completions / attempts. Combined completion is an estimate computed as direct success plus the direct-failure fraction times the separately measured Adapter recovery rate. It is not an additional observed set of 20 trials.

to hold its underlying control capability fixed, and a disjoint set of instances tests whether correction gains extend beyond the instances used in the ablations. Each evaluation round covers ten instances per task, or 120 episodes, and reports task-macro Q-score and complete-task success. The full 100-task system evaluation is reported separately in Section 5.

Table 10 Base-model ablations on Selected12, averaged over three evaluation rounds of 120 episodes each. The upper block compares observation inputs and initialization. The lower block adds model and data components cumulatively to the action-pretrained baseline. Check marks denote enabled components and dashes denote their absence. History-input configurations retain conventional history encoding when motion-aware encoding is disabled.

Setting	Model components		Training data		Performance	
	World model	Motion encoding	Skill sampling	Successful rollouts	Q-score	SR (%)
Observation and initialization baselines						
Current frame only	–	–	–	–	0.1582	8.33
Six-frame history	–	–	–	–	0.2167	13.33
FAST pretraining	–	–	–	–	0.3453	20.83
Action-policy initialization	–	–	–	–	0.4846	39.72
Cumulative additions to action-policy initialization						
Configuration A	✓	–	–	–	0.5183	42.50
Configuration B	✓	✓	–	–	0.5279	45.56
Configuration C	✓	✓	✓	–	0.5546	46.67
Full A^2-WLA	✓	✓	✓	✓	**0.5905**	**50.28**

6.1 Base Action Model Ablations

Table 10 shows that the full A^2-WLA achieves a Q-score of 0.5905 and a complete-task success rate of 50.28% on Selected12, exceeding the action-pretrained baseline by 0.1059 and 10.56 percentage points, respectively. All variants use a single policy without high-level correction or the correction Adapter.

▶ *Action Pretraining and Initialization.* The pretraining stages in Section 3.4.2 introduce action supervision before continuous-policy optimization. We compare how much of this learned capability is transferred into the Selected12 policy. A six-frame model initialized from a general-purpose VLM reaches 0.2167 Q-score and 13.33% success. FAST initialization first teaches the backbone to predict discrete action tokens, raising these scores to 0.3453 and 20.83%. Action-policy initialization additionally transfers the action expert together with the vision-language backbone pretrained on all 100 tasks, reaching 0.4846 and 39.72% after downstream training. We therefore use action-policy initialization as the starting point for all subsequent cumulative ablations.

▶ *Temporal and Predictive Context.* A^2-WLA uses visual history to interpret recent interaction and a latent world model to anticipate scene changes (Sections 3.1 and 3.2). We first test whether the historical observations themselves help. With the same weights trained on six-frame inputs, replacing the current frame alone with the full history raises Q-score from 0.1582 to 0.2167 and success from 8.33% to 13.33%. This measures sensitivity to history removal at inference, including the change from the model's six-frame training input. We then add predictive and motion representations to the action-pretrained baseline. Conditioning the action expert on predicted future features raises Q-score from 0.4846 to 0.5183 and success from 39.72% to 42.50% (A). Adding the motion-aware history encoder over the same six-frame window further improves these results to 0.5279 and 45.56% (B). Thus, retaining past observations and learning explicit representations of motion and future change provide complementary gains. Actual future observations remain offline training targets, and inference uses only current and past observations.

▶ *Training-Data Composition.* The sampling design in Section 3.4.1 gives additional weight to skill transitions, where the policy must change its behavior as an operation ends. With the architecture and auxiliary objectives fixed, we jointly apply skill-boundary oversampling and primitive balancing. This raises Q-score from 0.5279

to 0.5546 and success from 45.56% to 46.67% (C), using the same trajectories and adaptive flow-sampling settings. We then broaden the training experience by perturbing initial robot and target-object positions within fixed training-scene layouts and retaining rollouts with terminal Q-score equal to one. Mixing these 2,400 successful trajectories, 200 per task, with the expert demonstrations brings the full model to 0.5905 Q-score and 50.28% success. The final comparison measures the combined effect of position perturbation, success filtering, and additional data. Together, the results show gains from both redistributing training toward skill transitions and expanding the successful execution examples. We next examine what task specialization reveals about the design of generalist action models.

6.2 Task Specialization and Model Design

A generalist action model must share knowledge across activities while retaining the control precision needed for specific interactions. In our development experiments, a model trained specifically on a 12-task subset outperformed the shared model trained on all 100 tasks when evaluated on that subset. This observation raises a model-design question about how to preserve the benefits of broad training without diluting the representations needed for particular scene layouts, object interactions, and action sequences.

We examine one form of specialization using a bank of A^2-WLA policies trained on task subsets. Prior evaluations determine the task-to-model mapping and execution configuration, both fixed before the reported evaluation. Each episode uses one selected policy conditioned on the complete task instruction. Across all 100 tasks, this configuration reaches 0.6040 Q-score and 40.60% success, compared with 0.4597 and 27.20% for the shared model (Section 5). The gains combine specialization, checkpoint selection, and execution configuration, so they do not isolate the effect of specialization alone.

These results motivate architectures that combine shared representations with specialized control capacity. One direction is to share the visual, temporal, and world-model backbone while allowing smaller action experts to adapt to different interaction patterns. A learned router conditioned on observations and task language could choose the appropriate action expert without a fixed mapping from benchmark task IDs. Another direction is to distill the specialized policies into one model, retaining their complementary skills while simplifying deployment. These possibilities remain to be tested under matched parameter and compute budgets. Grounded correction is complementary to this architectural question, and the following experiments isolate its contribution by keeping A^2-WLA fixed.

6.3 Grounded Action Correction

The correction experiments use the 12-task Adapter evaluation subset described above and keep the A^2-WLA weights fixed. The first ten instances per task form the condition-ablation set, and the last ten form a disjoint generalization set, each containing 120 episodes. Missing episode results contribute zero Q-score and count as failures. We first examine the information supplied to the Adapter, then compare correction interfaces and test additional instances.

6.3.1 Contribution of Correction Conditions

The condition encoder combines correction language u_t, spatial evidence G_t, executed history R_t, and the current base proposal $\hat{A}_t^{\text{base}}$ into c_t (Eq. 2). We remove these inputs to evaluate their contribution while retaining the same action model and upstream reasoning modules. The language–grounding variant removes correction language, task text, and structured grounding together. It is therefore a joint semantic ablation rather than an isolated test of the recovery instruction. The history variant retains only the latest state–action record. Table 11 reports the resulting task performance.

Table 11 Adapter condition ablation on the 12-task correction subset, with 120 episodes per configuration. All variants share the A^2-WLA weights.

Model	Condition change	Mean Q	Success (%)
A^2-WLA (w/o Adapter)	No Adapter	0.5310	41.67
Adapter w/o Language & Grounding	Remove correction language, task text and structured grounding	0.5344	43.33
Adapter w/o Long History	Retain only the latest state–action record	0.5356	44.17
Adapter w/o Candidate	Remove base-action candidate encoding	0.5542	47.50
Adapter w/o Grounding	Remove structured grounding input	0.5570	49.17
Full Adapter	All conditions retained	**0.6108**	**52.50**

The full Adapter achieves 0.6108 Q-score and 52.50% success, improving over the no-Adapter baseline by 0.0798 and 10.83 percentage points. Joint removal of language and grounding reduces performance to 0.5344 and 43.33%. Restricting history to one record yields 0.5356 and 44.17%. Both ablations bring performance close to the base policy, demonstrating the importance of semantic–spatial context and extended execution history for correction.

Removing the base candidate lowers Q-score by 0.0566 and success by 5.00 percentage points. Removing structured grounding lowers them by 0.0538 and 3.33 percentage points. Every tested deletion reduces performance relative to the complete condition set. The candidate anchors the adjustment to the action currently proposed by the policy, while grounding locates the correction in the physical scene.

6.3.2 Comparison of Correction Interfaces

We compare instruction restatement, end-effector geometric correction, and the latent residual Adapter on the 12-task Adapter evaluation subset (Table 12). Each interface uses high-level advice, spatial evidence, executed history, and a fresh base proposal. Trainable correction components use the same correction examples and source-trajectory split. These comparisons evaluate different intervention mechanisms and do not establish a parameter- or compute-matched architectural ablation. Physical recovery measures whether the required physical condition is re-established. Effective continuation additionally requires the next predefined meaningful task advance within a fixed window, while final completion records whether the original task goal is achieved within the remaining episode budget. For each method, the three recovery rates use episodes with at least one correction trigger, counting each episode once from its first trigger and including cases where no correction is executed. Q-score uses all 120 evaluation episodes. Triggered-episode cohorts can differ across interfaces. Effective continuation is measured within a fixed window, whereas final completion uses the remaining episode budget, so final completion need not be lower than the time-limited continuation rate.

Compared with VLM+IK, the Adapter achieves a higher physical recovery rate, 54.93% versus 52.05%, and a slightly higher Q-score, 0.6108 versus 0.6083. Its final completion rate among triggered episodes is 43.66%, compared with 45.21% for VLM+IK. VLM+IK applies geometric corrections through inverse kinematics, whereas the Adapter injects a correction code into the action expert's hidden states during trajectory generation. Conditioned on the recovery instruction, scene evidence, execution history, and base proposal, the Adapter can coordinate the adjustment with the policy's learned whole-body behavior across the action chunk. The observed improvement in physical recovery therefore does not translate into higher final task completion in this comparison.

The condition ablations vary the evidence supplied to one Adapter, whereas the interface comparison varies

Table 12 Recovery and continuation with three correction interfaces on the 12-task Adapter evaluation subset.

Interface	Q-score	Physical recovery rate	Effective continuation rate	Final task completion rate
Instruction restatement (frozen A^2-WLA)	0.5668	46.27%	25.37%	38.81%
End-effector geometric correction (VLM + IK)	0.6083	52.05%	28.77%	45.21%
Latent-space residual adapter	0.6108	54.93%	33.80%	43.66%

how the same corrective evidence changes behavior. The execution cases in Section 6.5 illustrate the distinction between local recovery and completing the original task.

6.3.3 Instance Generalization and Execution Cases

On the disjoint set of ten additional instances per task, the full Adapter reaches 0.6782 Q-score and 58.33% success, compared with 0.6185 and 50.83% for the base policy (Fig. 13). The gains of 0.0597 and 7.50 percentage points correspond to nine additional completed episodes, increasing the success count from 61 to 70. The improvement therefore holds on both disjoint instance sets of the 12 correction tasks.



Figure 13 Adapter generalization on the last ten instances of each of the 12 correction tasks, with 120 episodes per configuration. Both axes start at zero.

The correction-language ablation retains task text and structured grounding but removes corrective instructions and direction. It obtains 0.6336 Q-score and 52.50% success, below the full Adapter by 0.0446 and 5.83 percentage points. These results establish the contribution of correction language alongside spatial evidence and history on additional task instances.

Figure 14 relates the quantitative gains to hanging pictures, bringing water, and washing a baseball cap. Each column uses the same task instance and base-action checkpoint, with ten denoising steps and six input frames. Blue trajectories show A^2-WLA-only motion, and orange trajectories show Adapter-controlled intervals. The outcome insets show subsequent observations and terminal task completion. In hanging pictures, the base rollout drops the frame after approaching the wall, while the Adapter-enabled rollout completes hanging. In bringing water, the correction occurs during bottle acquisition and is followed by task completion. In cap washing, repeated baseline grasp attempts end in a dropped cap, whereas the corrected rollout finishes the task.



Figure 14 Local correction and complete-episode outcomes for hanging pictures, bringing water, and washing a baseball cap. Blue trajectories show A^2-WLA-only execution. Orange trajectories show Adapter-controlled intervals. Later insets are subsequent observations from failed A^2-WLA-only rollouts, and Final insets are terminal observations from successful Adapter-enabled rollouts. Each pair comprises independently executed rollouts on the same task instance.



Figure 15 Task-level changes from complete-task conditioning to Focus on Selected12. The left panel shows Q-score differences and the right panel shows success-rate differences in percentage points.

Across these examples, local alignment and object acquisition form the link between corrective intervention and continued execution.

We next compare execution with explicit subtask prompts and different scheduling strategies.

6.4 Full-Task Conditioning and Subtask Scheduling

6.4.1 Full-Task Conditioning versus Focus

Table 13 compares two training-and-execution configurations on Selected12. Both use the same pretrained initialization and demonstrations from the same 12 tasks. The baseline row is the first round of the action-pretrained configuration in Table 10, whose reported result averages three rounds. The baseline uses the complete task instruction. Focus retains that goal and adds a `Current focus:` instruction selected by an asynchronous VLM.

Table 13 Complete-task conditioning (B) and VLM-selected Focus (F) on Selected12, both trained for 180k steps. Each configuration reports one round of ten instances per task. The baseline results are from its first evaluation round.

Task	Task name	B: Q	F: Q	B: success	F: success
000	Turn on radio	0.7000	0.7000	7/10	7/10
001	Pick up trash	0.6000	0.4667	5/10	3/10
006	Hide Easter eggs	0.3667	0.3778	3/10	3/10
017	Bring water	0.8333	0.3000	8/10	3/10
018	Tidy bedroom	0.7000	0.7333	5/10	3/10
022	Put shoes on rack	0.8500	0.7900	7/10	5/10
030	Set the fire	0.5000	0.4750	2/10	0/10
032	Wash baseball caps	0.1000	0.1000	0/10	0/10
034	Hang pictures	0.3000	0.0000	3/10	0/10
035	Attach camera to tripod	0.1000	0.0000	1/10	0/10
040	Make microwave popcorn	0.5000	0.6000	5/10	6/10
045	Cook hot dogs	0.9500	0.7500	9/10	7/10
Overall (task-macro Q)		**0.5417**	**0.4411**	**55/120**	**37/120**

On Selected12, the baseline achieves a task-macro Q-score of 0.5417 and a complete-task success rate of 45.83%, while Focus reaches 0.4411 and 30.83%, respectively. The corresponding differences are 0.1006 Q-score and 15.00 percentage points in favor of the baseline. As shown in Fig. 15, this aggregate gap masks variation across tasks. Focus improves Q-score on three tasks, decreases it on seven, and ties on two. The largest gain is 0.1000 on making microwave popcorn, whereas the largest declines are 0.5333 on bringing water, 0.3000 on hanging pictures, and 0.2000 on cooking hot dogs. These results show that the task-specific gains do not translate into an overall improvement for the evaluated Focus configuration. This result motivates our full-task-conditioned training and execution.

The comparison evaluates the two training-and-execution configurations as a whole. To examine scheduling itself, the following control fixes the action model across all modes.

6.4.2 Scheduling with a Fixed Action Model

We use the same frozen Focus action model to compare four scheduling modes on the same 120 episodes (Table 14). All modes share observation history, action prefixes, and task budgets. Focus dropout during training supports input without a Focus prompt in F-Global. F-Linear and F-Adaptive use the same simulator-assisted completion and executability tests. The former enforces a fixed order, while the latter permits reordering and revisitation.

Table 14 Scheduling ablation with one frozen Focus action model and 120 scheduled episodes per mode. Q-score is reported on a 0–1 scale. Missing or failed evaluation runs are assigned zero Q-score and counted as unsuccessful. Valid incomplete trajectories retain their measured partial Q-score.

Mode	Conditioning and scheduling	Q-score	SR (%)
F-VLM	Full task and online VLM-selected Focus	0.4411	30.83
F-Global	Full task only	0.4201	30.00
F-Linear	Simulator-assisted assessment, fixed order	0.4115	25.00
F-Adaptive	Same assessment, reordering and revisitation	0.3785	27.50

F-VLM achieves the highest Q-score and complete-task success rate among the four modes, reaching 0.4411 and 30.83%, respectively. Compared with F-Global, it gains 0.0210 Q-score and completes one additional episode out of 120, corresponding to a 0.83 percentage-point difference in success rate. This comparison evaluates explicit Focus conditioning together with online scheduling. The simulator-assisted modes show a different pattern. Under the same completion and executability tests, F-Adaptive achieves a higher success rate than F-Linear, 27.50% versus 25.00%, but a lower Q-score, 0.3785 versus 0.4115. Thus, flexible ordering and revisitation do not improve both measures in this diagnostic comparison.

6.4.3 Task Transitions and Demonstration Coverage

The scheduling comparisons highlight the need to determine whether the physical state at the end of one operation is suitable for the next. Retrieving a bottle establishes possession, but pouring or placement also requires an appropriate grasp and orientation. Closing a door depends on whether retrieval is complete and a hand is available. A direct handoff therefore requires both completion of the preceding operation and satisfaction of the next operation's physical preconditions. The relevant state includes the objects and contacts in the scene, beyond the robot proprioception denoted by s_t.

This dependence on preceding interactions is also visible in demonstration coverage. We analyze 20,000 original demonstrations across 100 BEHAVIOR tasks, with 200 demonstrations per task. The analysis uses the original `skill_annotation`, removes navigation, normalizes object categories, and counts support by independent demonstration. Workflow variation appears even within a single task. For toolbox organization, 161 demonstrations open the lid before collecting tools. The other 39 pick up and replace a tool before opening the lid. Fixing tool categories, actions, and repetition counts still leaves 67 distinct orders among 126 demonstrations. In art-supply organization, 199 demonstrations with the same four items and pick-and-place counts contain 70 workflows, including interleaved operations on different objects.

These variations change the history preceding an otherwise identical transition. Picking up a drill and placing it in the toolbox occurs in 30 demonstrations. Distinguishing the two preceding operations divides these examples into 16 history combinations, each supported by only one to five demonstrations. Histories involving a screwdriver and then the drill have five examples, while flashlight-and-drill histories have four. The next operation therefore encounters different preceding actions and held-object states. Across all 100 tasks, reordered identical operations occur in 31 tasks, changes in operation composition or repetition in 57, and interleaved picking and placing in 41. Their union covers 75 tasks (Fig. 16). The first two categories require at least ten demonstrations of each alternative. Interleaving requires at least ten demonstrations containing pick A, pick B, place A, place B. Categories overlap.

Across 97 tasks with sufficient history and the same 203,245 operation windows, task-wise counting yields



Figure 16 Workflow variation and sparse transition histories. Common variation covers 75 of 100 tasks. The 30 drill-placement demonstrations cover 16 preceding-history combinations, with 1–5 examples per combination.



Figure 17 Base-policy recovery without the Adapter, beyond the corresponding task demonstrations. Bottle reorientation and corn regrasping occur in episodes that ultimately fail. Glove retrieval is followed by continued washing and task completion. Each row follows one episode chronologically.

2,851 adjacent transition combinations. Conditioning on the two preceding operations increases this number to 6,849. Of these history-conditioned combinations, 62.8% have support from at most five demonstrations, while accounting for only 3.7% of window occurrences. Repeated individual operations coexist with sparse coverage of the long tail of preceding contexts. These statistics characterize variation in workflow and coverage of preceding contexts. Together with the physical handoff requirements, they identify the unfinished

goals, available support and grasp relations, and required physical states that a scheduler must represent.

6.5 Qualitative Analysis of Recovery and Task Continuation

Recovering an object or a grasp does not always restore a path to the task goal. We examine execution sequences to determine whether, after a disruption, the robot resumes the original activity, stalls at the next operation, or moves away from the unfinished goal.

6.5.1 Base-Policy Recovery and Task Continuation

Figure 17 shows three recovery sequences produced by the base action policy without the Adapter, beyond the corresponding task demonstrations. During water fetching, the robot adjusts its grasp on an inverted bottle and completes a handover. During vegetable sorting, it regrasps a fallen ear of corn and resumes transport. Both episodes ultimately fail to complete the task. In contrast, retrieving a dropped boxing glove is followed by continued execution toward the washing machine and successful task completion.

These cases are consistent with reuse of grasping and object-handling behaviors in states absent from the corresponding task demonstrations. The videos alone do not identify which training activities supplied those behaviors, so they do not establish a specific cross-task transfer mechanism. Their different outcomes nevertheless show why local recovery and complete-task success must be evaluated separately. Reorienting the bottle and regrasping the corn do not complete the activity, whereas glove retrieval supports the remaining washing sequence.

6.5.2 Failure Modes in Long-Horizon Execution

Failed executions reveal different obstacles to continuation (Fig. 18). During camera installation, the robot reaches the tripod but fails to establish attachment and drops the camera. During book shelving, it retrieves the book but remains holding it without completing insertion. The first case fails at contact establishment. The second achieves possession but stalls before the required placement. Approaching a target and holding an object therefore leave different physical requirements unresolved.

A food-storage episode illustrates a different failure. After dropping the food, the robot moves the empty plate toward a sink, leaving the storage goal unfinished. Motion continues, but it no longer advances the intended activity. Across these examples, useful recovery requires both a physical state suitable for the next operation and subsequent actions that remain directed toward the original goal.

The base-model study evaluates a cumulative representation and training recipe, and the fixed-policy Adapter experiments show gains from corrective context on two instance sets. Scheduling comparisons and demonstration statistics expose the demands of task transitions. The execution cases illustrate both local recovery by the base policy and its limits. Together, these studies distinguish improvements in action generation, intervention, and continued progress toward the task goal.

7 Discussion and Conclusion

We treat long-horizon execution as a capability to be learned by the action model, with the agent system providing verification and correction at critical points. The experiments in Sections 5 and 6 examine this division of roles through task performance, action-model design, and grounded correction.

a Camera approaches the tripod but installation fails

02:27 02:56 03:06

b Book recovery does not lead to successful shelving

02:47 04:22 07:33

Figure 18 Contact failure and stalled continuation. The upper sequence shows unsuccessful camera attachment followed by a drop. The lower sequence shows book retrieval without subsequent shelving. Each row contains chronological observations from one failed episode.

7.1 Simple Action Models and Room for Improvement

A striking result is how far a relatively simple action architecture can go. A^2-WLA augments a vision-language-action policy with motion-aware history and a latent world model that predicts future visual features. Before adding agent-driven correction, its task-specialized configuration reaches 0.5755 Q-score on the 50-task BEHAVIOR 2026 public subset, approximately 2.21$\times$ the 0.2605 public score of RLC, the 2025 competition winner (Table 7). This is a comparison across benchmark editions and training configurations, including 25 specialized checkpoints for A^2-WLA and four for RLC, so the ratio should not be attributed to architecture alone. Even the shared A^2-WLA policy reaches 0.4522. Together, these results suggest that substantial long-horizon competence can emerge from improving the action model itself.

The useful lesson is to strengthen a small set of complementary capabilities by retaining recent interaction history, predicting how the scene will change, and translating that context into continuous control. The component study on Selected12 supports this direction. Adding the latent world model to the action-pretrained baseline raises Q-score from 0.4846 to 0.5183, while motion-aware history and the subsequent data improvements bring the full recipe to 0.5905. The remaining gap between partial progress and complete-task success indicates considerable room to improve temporal representations, predictive objectives, demonstration coverage, and training efficiency within this compact design. Better action policies would also give the multi-agent framework a stronger foundation for targeted correction and reliable task continuation.

7.2 Learning Long-Horizon Capability in the Action Model

Long-horizon tasks involve nonlinear composition because the feasibility of a later operation depends on the physical state and interaction history produced by earlier operations. A bottle grasp that completes retrieval may be unsuitable for pouring, and retrieving one object can change hand availability for the next operation. As

analyzed in Section 6.4.3, independently successful subtasks do not automatically compose into a successful activity. Their ordering and transition conditions must be represented by the policy, the scheduler, or both.

This motivates training the action policy directly on long-horizon task trajectories, rather than relying on a scheduler to assemble independently learned subtasks. The policy can learn recurring dependencies between operations from these trajectories. Its online decisions still depend on a finite observation window, so long-horizon training does not give it complete memory of the episode. The shared execution record and task-level reasoning supply complementary context. The sparse coverage of preceding contexts in the demonstration analysis further emphasizes the need for training data that preserve cross-step dependencies and cover different ways of reaching a task transition.

The agent system supports this learned capability through verification and correction at critical execution points. It checks progress and physical feasibility, diagnoses deviations, and supplies grounded corrective context through the Adapter. The action model continues to generate the actions needed for the remaining activity. The fixed-policy Adapter experiments demonstrate the value of this complementary role. System-level feedback adjusts execution while the underlying model weights remain unchanged. Recovery is useful when the corrected state allows the policy to continue the unfinished activity.

The 100-task analysis identifies where this division of roles must improve reliability. The system succeeds at least once on 88 tasks, but only 11 tasks succeed in all ten evaluated instances. High Q-scores also coexist with low complete-task success, as in food storage. Further development therefore requires both broader long-horizon competence in the action model and effective verification and correction at points where execution departs from the task goal.

7.3 Limitations and Future Directions

The current correction process pauses execution for diagnosis, which limits its use for events that demand immediate reactions. We prioritize scaling and diversifying interaction data so that the action model learns how contact states evolve and how to respond to deviations from visual observations and execution history. Training trajectories should cover varied object properties, contact configurations, and both successful and failed attempts, including recovery and subsequent task continuation. Together with faster interaction between reasoning and control, this data-driven approach aims to strengthen timely responses within the learned policy.

Correction training uses deviations generated at demonstration states, whereas deployed policies encounter failures that alter object arrangements and grasp configurations. Collecting these execution states and their subsequent outcomes would extend supervision to the situations in which correction is actually needed. This calls for a data pipeline that links failure detection, corrective instructions, and the success or failure of the remaining task.

The present quantitative evidence centers on household simulation. The additional Adapter instances test variation within the same tasks, while the real-robot studies cover short-horizon manipulation and sequential coffee preparation. Establishing broader generalization requires evaluation on new task families, robot embodiments, and physical environments. Such evaluation should retain both goal satisfaction and complete-task success, so that improvements in individual operations can be assessed against reliable end-to-end execution.

7.4 Conclusion

We present A^2-MEAS, an embodied multi-agent framework that connects MetaBrain, grounding agents, and A^2-WLA through learned correction codes. This interface converts language-based corrective intent and spatial evidence into action adjustments while keeping model parameters fixed during deployment. On 100 BEHAVIOR 2026 tasks, the system achieves a Q-score of 0.6411 and a complete-task success rate of 45.40%,

with at least one successful episode on 88 tasks. The accompanying training and evaluation infrastructure supports iteration across this broad task set, and coffee preparation tests a history-conditioned recovery variant on a real robot. Our approach combines long-horizon capability learned within the action model with system-level verification and correction at critical points. Further progress depends on strengthening both the learned continuity of execution and the effectiveness of targeted intervention. We will release models, training scripts, and evaluation tools to support research on this approach.

Data availability

The BEHAVIOR-1K challenge demonstrations used in this work are publicly available from the official benchmark project[17]. Correction supervision is constructed from these demonstrations using the procedure in Section 2.5. The planned code release includes scripts for constructing correction supervision and training the models on these data. The source dataset remains available through its official distribution.

Code availability

We will progressively open-source the complete A^2-MEAS solution at https://github.com/AutoLab-SAI-SJTU/A2MEAS. The planned releases cover multi-agent orchestration, the A^2-WLA model and trained checkpoints, training scripts for the action model and correction interface, data-processing code for the official BEHAVIOR demonstrations, and the optimized training, execution and evaluation infrastructure. Each release will specify its version, configuration and dependencies.

Authors and contributions

Core Contributors. Chao Liang, Xiaoxiao Feng Li, Ke Chen, and Shibo Huang.

Other Contributors. Zhaokai Yin and Chenghuan Jia.

Project Leaders. Chao Liang and Zhipeng Zhang.

Corresponding Author. Zhipeng Zhang (zhipengzhang@sjtu.edu.cn).

References

[1] Wenbo Zhang, Kaixuan Wang, Yutao Ouyang, et al. An unexpected robot policy: Early evaluations of GPT-6 Astra on RoboDojo and beyond. *arXiv preprint arXiv:2609.24170*, 2026. URL https://arxiv.org/abs/2609.24170.

[2] Fangcheng Liu, Yeqing Shen, Anda Cheng, et al. RoboICL: Embodied in-context learning with GPT-6 Astra. *arXiv preprint arXiv:2609.34261*, 2026. URL https://arxiv.org/abs/2609.34261.

[3] Michael Ahn, Anthony Brohan, Noah Brown, et al. Do as i can, not as i say: Grounding language in robotic affordances. In *Conference on Robot Learning*, 2022. URL https://arxiv.org/abs/2204.01691.

[4] Wenlong Huang, Fei Xia, Ted Xiao, et al. Inner monologue: Embodied reasoning through planning with language models. *arXiv preprint arXiv:2207.05608*, 2022. URL https://arxiv.org/abs/2207.05608.

[5] Zeyi Liu, Arpit Bahety, and Shuran Song. REFLECT: Summarizing robot experiences for failure explanation and correction. *arXiv preprint arXiv:2306.15724*, 2023. URL https://arxiv.org/abs/2306.15724.

[6] Wenlong Huang, Chen Wang, Ruohan Zhang, Yunzhu Li, Jiajun Wu, and Li Fei-Fei. VoxPoser: Composable 3D value maps for robotic manipulation with language models. *arXiv preprint arXiv:2307.05973*, 2023. URL https://arxiv.org/abs/2307.05973.

[7] Yicheng Liu, Zibin Dong, Baijun Ye, et al. G0.5: One autoregressive stream for robot reasoning and action. *arXiv preprint arXiv:2608.11739v1*, 2026. URL https://arxiv.org/abs/2608.11739v1.

[8] Ganlong Zhao, Zijia Tang, Xingping Chen, Zhanghui Kuang, Ye Tian, and Guanbin Li. FLARE: A failure-aware framework for autonomous correction and recovery in visual-language robotic manipulation. *arXiv preprint arXiv:2608.26645*, 2026. URL https://arxiv.org/abs/2608.26645.

[9] Physical Intelligence. $\pi_{0.5}$ a vision-language-action model with open-world generalization. *arXiv preprint arXiv:2504.16054*, 2025. URL https://arxiv.org/abs/2504.16054.

[10] Jialei Chen, Kai Wang, Kang Chen, et al. LaWAM: Latent world action models for efficient dynamics-aware robot policies. *arXiv preprint arXiv:2606.15768*, 2026. URL https://arxiv.org/abs/2606.15768.

[11] Stanford Vision and Learning Lab. 2025 BEHAVIOR Challenge archived leaderboard, 2025. URL https://behavior.stanford.edu/challenge/archive/2025/leaderboard.html. Public validation results. Accessed 1 October 2026.

[12] Maxime Oquab, Timothée Darcet, Théo Moutakanni, et al. DINOv2: Learning robust visual features without supervision. *arXiv preprint arXiv:2304.07193*, 2023. URL https://arxiv.org/abs/2304.07193.

[13] Alexander Kirillov, Eric Mintun, Nikhila Ravi, et al. Segment anything. *arXiv preprint arXiv:2304.02643*, 2023. URL https://arxiv.org/abs/2304.02643.

[14] Qwen Team. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*, 2025. URL https://arxiv.org/abs/2511.21631.

[15] Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling. *arXiv preprint arXiv:2210.02747*, 2022. URL https://arxiv.org/abs/2210.02747.

[16] Stanford Vision and Learning Lab. 2026 BEHAVIOR Challenge, 2026. URL https://behavior.stanford.edu/challenge/index.html. Accessed 1 October 2026.

[17] Stanford Vision and Learning Lab. 2026 BEHAVIOR Challenge dataset, 2026. URL https://behavior.stanford.edu/challenge/dataset.html. Accessed 1 October 2026.

[18] Karl Pertsch, Kyle Stachowicz, Brian Ichter, et al. FAST: Efficient action tokenization for vision-language-action models. *arXiv preprint arXiv:2501.09747*, 2025. URL https://arxiv.org/abs/2501.09747.

[19] Danny Driess, Jost Tobias Springenberg, Brian Ichter, et al. Knowledge insulating vision-language-action models: Train fast, run fast, generalize better. *arXiv preprint arXiv:2505.23705*, 2025. URL https://arxiv.org/abs/2505.23705.

[20] BEHAVIOR-1K Team. 2026 BEHAVIOR Challenge: Published self-reported results, 2026. URL https://huggingface.co/spaces/behavior-1k/2026-challenge-leaderboard/blob/main/data/published_self_reported_results.jsonl. Accessed 31 October 2026.

[21] BEHAVIOR-1K Team. 2026 BEHAVIOR Challenge: Leaderboard, 2026. URL https://huggingface.co/spaces/behavior-1k/2026-challenge-leaderboard. Accessed 31 October 2026.

[22] BEHAVIOR-1K Team. 2026 BEHAVIOR Challenge: Verified leaderboard results, 2026. URL https://huggingface.co/spaces/behavior-1k/2026-challenge-leaderboard/blob/main/data/results.jsonl. Accessed 31 October 2026.

[23] Junjie Bai, Yu-Wei Chao, Qizhi Chen, et al. Openpi comet: Competition solution for 2025 BEHAVIOR Challenge. *arXiv preprint arXiv:2512.10071*, 2025. URL https://arxiv.org/abs/2512.10071.

[24] Tianxing Chen, Zanxin Chen, Baijun Chen, et al. RoboTwin 2.0: A scalable data generator and benchmark with strong domain randomization for robust bimanual robotic manipulation. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pages 13673–13699. PMLR, 2026. URL https://proceedings.mlr.press/v306/chen26j.html.

[25] Wei Wu, Fan Lu, Yunnan Wang, et al. A pragmatic VLA foundation model. *arXiv preprint arXiv:2601.18692*, 2026. URL https://arxiv.org/abs/2601.18692.

[26] Hongzhe Bi, Hengkai Tan, Shenghao Xie, et al. Motus: A unified latent action world model. *arXiv preprint arXiv:2512.13030*, 2025. URL https://arxiv.org/abs/2512.13030.

[27] StarVLA Community. StarVLA: A lego-like codebase for vision-language-action model developing. *arXiv preprint arXiv:2604.05014*, 2026. URL https://arxiv.org/abs/2604.05014.

[28] Lin Li, Qihang Zhang, Yiming Luo, et al. Causal world modeling for robot control. *arXiv preprint arXiv:2601.21998*, 2026. URL https://arxiv.org/abs/2601.21998.

[29] Tianyuan Yuan, Zibin Dong, Yicheng Liu, and Hang Zhao. Fast-WAM: Do world action models need test-time future imagination? *arXiv preprint arXiv:2603.16666*, 2026. URL https://arxiv.org/abs/2603.16666.

[30] Wei Wu, Fangjing Wang, Fan Lu, et al. From foundation to application: Improving VLA models in practice. *arXiv preprint arXiv:2607.06403*, 2026. URL https://arxiv.org/abs/2607.06403.

[31] MotuBrain Team. MotuBrain: An advanced world action model for robot control. *arXiv preprint arXiv:2604.27792*, 2026. URL https://arxiv.org/abs/2604.27792.