

Camgaze.js: A JavaScript Library for Eye Tracking and Gaze Prediction

Alex Wallar ¹ Christian Poellabauer ² Aleksejs Sazonovs ¹
 Patrick Flynn ²

¹University of St Andrews

²University of Notre Dame

March 27, 2014

Table of contents

1 Introduction

- Review
- Motivation
- Camgaze.js

2 Implementation

- Overview
- Determining Gaze Direction
- Calibration
- Process

3 Conclusions

- Results
- Future Work
- Questions

What is it?

- Eye tracking is a problem which tries to determine where a user is looking on the screen

What is it?

- Eye tracking is a problem which tries to determine where a user is looking on the screen
- Usually done using IR or 3D cameras

What is it?

- Eye tracking is a problem which tries to determine where a user is looking on the screen
- Usually done using IR or 3D cameras
- Some web-cam technologies have emerged

What is it?

- Eye tracking is a problem which tries to determine where a user is looking on the screen
- Usually done using IR or 3D cameras
- Some web-cam technologies have emerged
- However, no in-browser solutions have been presented solely using HTML5

What is it?

- Eye tracking is a problem which tries to determine where a user is looking on the screen
- Usually done using IR or 3D cameras
- Some web-cam technologies have emerged
- However, no in-browser solutions have been presented solely using HTML5
- Until now :)

Motivation

- Eye tracking can provide vital data about what is important on the screen

Motivation

- Eye tracking can provide vital data about what is important on the screen
- We can create more intuitive user interfaces

Motivation

- Eye tracking can provide vital data about what is important on the screen
- We can create more intuitive user interfaces
- Using the web, we can crowd source where people are looking at on the website

Motivation

- Eye tracking can provide vital data about what is important on the screen
- We can create more intuitive user interfaces
- Using the web, we can crowd source where people are looking at on the website
- Also, since all of the eye tracking is done on the client side, we can preserve user privacy

Camgaze.js

- A library for eye tracking that is done inside a web browser using JavaScript

Camgaze.js

- A library for eye tracking that is done inside a web browser using JavaScript
- Uses only commodity camera (i.e. a web-cam)

Camgaze.js

- A library for eye tracking that is done inside a web browser using JavaScript
- Uses only commodity camera (i.e. a web-cam)
- Anybody can use the library without downloading any external program besides a web browser

Camgaze.js

- A library for eye tracking that is done inside a web browser using JavaScript
- Uses only commodity camera (i.e. a web-cam)
- Anybody can use the library without downloading any external program besides a web browser
- It is possible to determine where the user is looking on the screen whilst preserving user privacy and limiting server load

Overview

- 1 Obtain video using Web RTC (Real Time Communication) library

Overview

- 1 Obtain video using Web RTC (Real Time Communication) library
- 2 Determine the positions of the pupil centroids

Overview

- 1 Obtain video using Web RTC (Real Time Communication) library
- 2 Determine the positions of the pupil centroids
- 3 Use a steady point on the face as a reference point to determine gaze





Overview

- 1 Obtain video using Web RTC (Real Time Communication) library
- 2 Determine the positions of the pupil centroids
- 3 Use a steady point on the face as a reference point to determine gaze
- 4 Add face position and head orientation vectors to the predicted gaze in order to get a result gaze vector

Overview

- 1 Obtain video using Web RTC (Real Time Communication) library
- 2 Determine the positions of the pupil centroids
- 3 Use a steady point on the face as a reference point to determine gaze
- 4 Add face position and head orientation vectors to the predicted gaze in order to get a result gaze vector
- 5 The gaze vector is mapped onto the screen using the gaze mapping from the calibration stage

Determining Gaze Direction



Calibration

- 1 Four circles appear at the corners of the screen in sequence

Calibration

- 1 Four circles appear at the corners of the screen in sequence
- 2 The user is asked to look at each circle in order for a matter of time


Calibration

- 1 Four circles appear at the corners of the screen in sequence
- 2 The user is asked to look at each circle in order for a matter of time
- 3 Data about the gaze vector is stored and averaged in order to create a mapping

Calibration

- 1 Four circles appear at the corners of the screen in sequence
- 2 The user is asked to look at each circle in order for a matter of time
- 3 Data about the gaze vector is stored and averaged in order to create a mapping
- 4 The mapping is returned such that new gaze input will correlate with a position on the screen within a window of error

Process



Results

- We can determine the point of gaze within a $2.1in(\pm 0.1)$ radius

Results

- We can determine the point of gaze within a $2.1in(\pm 0.1)$ radius
- This means that we are within $0.6in$ of the results *Holland et al.* which used a native iPad application.

Future Work

- Use an Active Appearance Model instead of Haar Classifiers to determine the reference points and eye rectangles

Future Work

- Use an Active Appearance Model instead of Haar Classifiers to determine the reference points and eye rectangles
- Use a neural network for calibration instead of linear mapping

Future Work

- Use an Active Appearance Model instead of Haar Classifiers to determine the reference points and eye rectangles
- Use a neural network for calibration instead of linear mapping
- Undergo large scale, crowd sourced user testing

Questions

