

## Table of Contents

|                                                |    |                                                                  |    |
|------------------------------------------------|----|------------------------------------------------------------------|----|
| <b>1 特性</b> .....                              | 1  | 8.2 Functional Block Diagram.....                                | 17 |
| <b>2 应用</b> .....                              | 1  | 8.3 Feature Description.....                                     | 18 |
| <b>3 说明</b> .....                              | 1  | 8.4 Device Functional Modes.....                                 | 28 |
| <b>4 Revision History</b> .....                | 2  | 8.5 Register Maps.....                                           | 30 |
| <b>5 Device Comparison Table</b> .....         | 3  | <b>9 Application and Implementation</b> .....                    | 40 |
| <b>6 Pin Configuration and Functions</b> ..... | 3  | 9.1 Application Information.....                                 | 40 |
| 6.1 Versions.....                              | 3  | 9.2 Typical Applications .....                                   | 43 |
| 6.2 BQ76920 Pin Diagram.....                   | 4  | <b>10 Power Supply Recommendations</b> .....                     | 48 |
| 6.3 BQ76930 Pin Diagram.....                   | 5  | <b>11 Layout</b> .....                                           | 50 |
| 6.4 BQ76940 Pin Diagram.....                   | 6  | 11.1 Layout Guidelines.....                                      | 50 |
| <b>7 Specifications</b> .....                  | 8  | 11.2 Layout Example.....                                         | 50 |
| 7.1 Absolute Maximum Ratings.....              | 8  | <b>12 Device and Documentation Support</b> .....                 | 52 |
| 7.2 ESD Ratings.....                           | 8  | 12.1 第三方产品免责声明.....                                              | 52 |
| 7.3 Recommended Operating Conditions.....      | 9  | 12.2 Documentation Support.....                                  | 52 |
| 7.4 Thermal Information.....                   | 10 | 12.3 Related Links.....                                          | 52 |
| 7.5 Electrical Characteristics.....            | 10 | 12.4 Receiving Notification of Documentation Updates..           | 52 |
| 7.6 Timing Requirements.....                   | 14 | 12.5 Trademarks.....                                             | 52 |
| 7.7 Typical Characteristics.....               | 15 | <b>13 Mechanical, Packaging, and Orderable Information</b> ..... | 52 |
| <b>8 Detailed Description</b> .....            | 17 |                                                                  |    |
| 8.1 Overview.....                              | 17 |                                                                  |    |

## 4 Revision History

注：以前版本的页码可能与当前版本的页码不同

| <b>Changes from Revision H (March 2019) to Revision I (March 2022)</b>              | <b>Page</b> |
|-------------------------------------------------------------------------------------|-------------|
| • 通篇更改了格式.....                                                                      | 1           |
| • Added VCn rows in <i>Absolute Maximum Ratings</i> table.....                      | 8           |
| • Changed tablenote for POR and referenced entries.....                             | 10          |
| • Changed the scale in the VCx and OV Protection plots .....                        | 15          |
| • Updated <a href="#">16-Bit Pack Voltage</a> .....                                 | 22          |
| • Changed "OV Trip" to "UV Trip" in the description of undervoltage protection..... | 22          |
| • Changed the LSB bit count from 2 to 4 for the OV_TRIP register.....               | 31          |
| • Updated <a href="#">Application Information</a> .....                             | 40          |
| • Added <a href="#">Device Timing</a> .....                                         | 40          |
| • Added <a href="#">Random Cell Connection</a> .....                                | 40          |
| • Added <a href="#">Power Pin Diodes</a> .....                                      | 40          |
| • Added <a href="#">Alert Pin</a> .....                                             | 40          |
| • Added <a href="#">Sense Inputs</a> .....                                          | 40          |
| • Added <a href="#">TSn Pins</a> .....                                              | 40          |
| • Updated <a href="#">Unused Pins</a> .....                                         | 41          |
| • Updated <a href="#">Step-by-Step Design Procedure</a> .....                       | 47          |

| <b>Changes from Revision G (April 2016) to Revision H (March 2019)</b>                           | <b>Page</b> |
|--------------------------------------------------------------------------------------------------|-------------|
| • 更改了 <a href="#">应用</a> .....                                                                   | 1           |
| • 更改了 <a href="#">说明</a> .....                                                                   | 1           |
| • Added <a href="#">High-Side FET Driving</a> .....                                              | 24          |
| • Added the link to the <i>BQ769x0 Boot Switch Alternatives Application Report</i> .....         | 28          |
| • Added the link to the <i>BQ769x0 Family Top Design Considerations Application Report</i> ..... | 40          |
| • Added <a href="#">图 9-4</a> to provide an example of a high-side FET configuration.....        | 43          |
| • Added <i>BQ769x0 Family Top Design Considerations Application Report</i> link.....             | 48          |