

REVE Systems Ltd

Core Service API



11-17-2020

<http://esb.beta.doptor.gov.bd>

Part-1

Serial Number – 001

Name – Get employee details by username

Description -- This API provides the employee name, employee id, office name, office id, employee designation.

URL: <http://esb.beta.doptor.gov.bd:8280/employee/details/{username}>

Method: GET

Headers

Authorization -- BearerXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --  
request GET 'http://esb.beta.doptor.gov.bd:8280/employee/details/xxxxxxxxx  
x \  
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php  
require_once 'HTTP/Request2.php';  
$request = new HTTP_Request2();  
$request->  
>setUrl('http://esb.beta.doptor.gov.bd:8280/employee/details/xxxxxxxxx?');  
$request->setMethod(HTTP_Request2::METHOD_GET);  
$request->setConfig(array(  
    'follow_redirects' => TRUE  
));  
$request->setHeader(array(  
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'  
));  
try {  
    $response = $request->send();  
    if ($response->getStatus() == 200) {  
        echo $response->getBody();  
    }  
    else {  
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .  
            $response->getReasonPhrase();  
    }  
}  
catch(HTTP_Request2_Exception $e) {  
    echo 'Error: ' . $e->getMessage();  
}
```

Sample Request (Java - OkHttpClient)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/employee/details/xxxxxxx?")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
{
  "upazilaBbsCode": xxxxxx,
  "office_id": xxxxx,
  "office_name_eng": "xxxxxxx"
  "designation_bng": "xxxxxxx",
  "districtBbsCode": xxxxx,
  "layer_sequence": x,
  "employee_record_id": xxxxxxx,
  "name_bng": "xxxxxxxxx",
  "officeUnitOrganogramId": xxxxxxxxx,
  "unit_name_bng": "xxxxxxxxx",
  "personal_email": "xxxxxxxxx"
}
```

Serial Number – 002

Name – Get employee details by organogram

Description -- This API provides the employee record id, identification number, user id and employee designation.

URL:

<http://esb.beta.doptor.gov.bd:8280/employee/organogram/{organogram}>

Method: GET

Headers

Authorization -- Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/employee/organogram/xxxxx\
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/employee/organogram/239550');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/employee/organogram/239550")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "record_id": xxxxxx,
    "identification_number": "xxxxxxx",
    "id": xxxxxxx,
    "designation": "xxxxxxxxx"
  }
]
```

Serial Number – 003

Name – Get employee details by employee record id

Description -- This API provides the employee Nid, name, occupation, gender, father's name, mother's name, religion etc.

URL: <http://esb.beta.doptor.gov.bd:8280/employee/record/{id}>

Method: GET

Headers

Authorization -- Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/employee/record/4397' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/employee/record/xxxxxx');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/employee/record/xxxxxxx")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
{
  "occupation": "xxxxxx",
  "gender": "xxxx",
  "father_name_bng": "xxxxxx",
  "mother_name_eng": "xxxxxx",
  "nid": "xxxxxxxxxxxxxx",
  "permanent_address": "xxxxxxxx",
  "bcn": "xxxx",
  "mother_name_bng": "xxxxxx",
  "ppn": "xxxxxx",
  "religion": "xxxxxx",
  "place_of_birth": "xxxxxx",
  "marital_status": "xxxxxxxx",
  "name_eng": "xxxxxxxxxx",
  "nationality": "xxxxxx",
  "blood_group": "xxxxxx",
  "spouse_name_eng": "xxxxxxxx",
  "id": xxxxxx,
  "name_bng": "xxxxxxxxxx",
  "spouse_name_bng": "xxxxxx"
}
```


Serial Number – 004

Name – Get employee details by ID

Description -- This API provides the employee name, employee id, office name, office id, employee designation, role type, joining date, last office date etc.

URL: <http://esb.beta.doptor.gov.bd:8280/employee/{id}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/employee/xxxx \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXX
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/employee/xxxxxx');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXX
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/employee/xxxxxx")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
{
  "joining_date": xxxxxxxx,
  "identification_number": "xxxxxxx",
  "role_type": xxx,
  "office_unit_id": xxxxxxxx,
  "designation_sequence": xxx,
  "office_unit_organogram_id": xxxxxx,
  "main_role_id": xxx,
  "office_id": xxxxx,
  "record_id": xxxx,
  "designation_level": xx,
  "summary_nothi_post_type": xxx,
  "office_head": xxxx,
  "incharge_label": "xxxxxx",
  "last_office_date": xxxxx,
  "id": xxxxxx,
  "designation": "xxxxxxxxxx"
}
```

Serial Number – 005

Name – Get employee details by employee record id

Description -- This API provides the employee name, employee id, office name, office id, employee designation, Father's name, Mother's name, date of birth etc.

URL:

<http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeRecord/{employeeRecordId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeRecord/xxx \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeRecord/xxxx')
;
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doctor.gov.bd:8280/coredata/getEmployeeRecord/xxxx")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
{
  "motherEn": "নাছিমা খাতুন",
  "gender": "Male",
  "fatherBn": "মোঃ রফিকুল ইসলাম",
  "nid": "19832611293228300",
  "joiningDate": null,
  "office": "9751",
  "ministryName": "Demo Ministry",
  "idNumber": "20000002986",
  "reference": "০১",
  "empRecordId": 4397,
  "empName": "Md. Hasanuzzaman",
  "ministryNameBn": "ডেমো মন্ত্রণালয়",
  "email": "tushar@tappware.com",
  "ministryId": "63",
  "empNameBn": "মোঃ হাসানুজ্জামান",
  "mobile": "01723922458",
  "fatherEn": "MD. Rafiqul Islam",
  "ministryNameShort": "DM",
  "religion": "Islam",
  "unit": "50061",
  "nationality": "NID",
  "dob": "1983-11-22 00:00:00.0",
  "designation": "সিনিয়র সফটওয়্যার ইঞ্জিনিয়ার",
  "organogram": "239550"
},
```

Serial Number – 006

Name – Get office details by office origin unit organogram id

Description -- This API provides the Unit name, unit name in bangla, office origin, office id, and designation name in English, designation name in bangla, ministry id, and layer id.

URL:

<http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeOriginUnitOrg/{originOrganogramId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeOriginUnit
Org/xxxx \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request-
>setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeOriginUnitOrg/
xxxx');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
```

```
    echo 'Error: ' . $e->getMessage()  
  }
```

Sample Request (JAVA- OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()  
    .build();  
Request request = new Request.Builder()  
    .url("http://esb.beta.doctor.gov.bd:8280/coredata/getOfficeOriginUnitOrg/xxx")  
    .method("GET", null)  
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")  
    .build();  
Response response = client.newCall(request).execute();
```

Sample Response

```
[  
  {  
    "unitName": "",  
    "unitNameBng": "শাখা-২",  
    "officeOrigin": "669",  
    "id": 90842,  
    "designationNameEn": "Senior Software Enigneer",  
    "designationNameBn": "সিনিয়র সফটওয়্যার ইঞ্জিনিয়ার",  
    "ministry": "63",  
    "layer": "225"  
  }  
]
```

Serial Number – 007

Name – Get office details by organogram id

Description -- This API provides the office unit organogram name in English, office unit organogram name in bangla, office unit name in English, office unit name in bangla, office origin unit id, and office unit organogram.

URL: <http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrg/{organogramId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrg/xxx\
xxx\'
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrg/xxxx');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (JAVA- OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrg/xxxxxx"
    )
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "officeUnitOrgNameEng": "xxxxx",
    "officeUnitNameEn": "xxxxxxx",
    "officeUnitNameBn": "শাখা-২",
    "officeOriginUnitId": "20220",
    "officeUnitOrgId": 239550,
    "officeUnitOrgNameBn": "সিনিয়র সফটওয়্যার ইঞ্জিনিয়ার",
    "office": "9751",
    "ministry": "63",
    "layer": "225"
  }
]
```


Serial Number – 008

Name – Get office details with record id

Description -- This API provides the office origin unit organogram id, office unit origin id and ministry id

URL:

<http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeOrgMinistryId/{employeeRecordId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeOrgMinistryId/4397' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeOrgMinistryId/xxxx');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' . $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (JAVA- OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeOrgMinistryId/4397")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "officeOrgnUnitOrgId": 10532,
    "officeUnitOrgId": 22164,
    "ministry": 14
  },
  {
    "officeOrgnUnitOrgId": 10532,
    "officeUnitOrgId": 22164,
    "ministry": 14
  },
  {
    "officeOrgnUnitOrgId": 10532,
    "officeUnitOrgId": 22164,
    "ministry": 14
  },
  {
    "officeOrgnUnitOrgId": 10515,
    "officeUnitOrgId": 22438,
    "ministry": 14
  },
  {
    "officeOrgnUnitOrgId": 37226,
    "officeUnitOrgId": 162008,
    "ministry": 46
  },
  {
    "officeOrgnUnitOrgId": 10532,
    "officeUnitOrgId": 22164,
    "ministry": 14
  }
]
```

Serial Number – 009

Name – Get office details with office id

Description -- This API provides Unit name in bangla, Unit name in English, office unit id, office unit organogram id, office origin unit id, designation name in English and designation name in bangla.

URL: <http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgUnitOrgn/{officeId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgUnitOrgn/9751' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgUnitOrgn/9751');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (JAVA- OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgUnitOrgn/9751")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgUnitOrgn/9751")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "unitNameBn": "শাখা-১",
    "unitNameEn": "",
    "officeUnitId": 50060,
    "officeUnitOrganogramId": 90840,
    "officeOriginUnitId": 20219,
    "designationNameEn": "",
    "designationNameBn": "পরিচালক"
  },
  {
    "unitNameBn": "শাখা-২",
    "unitNameEn": "",
    "officeUnitId": 50061,
    "officeUnitOrganogramId": 90842,
    "officeOriginUnitId": 20220,
    "designationNameEn": "",
    "designationNameBn": "সিনিয়র সফটওয়্যার ইঞ্জিনিয়ার"
  }
]
```

Serial Number – 010

Name – Get office unit organogram details with office origin id

Description -- This API provides Designation in Bangla, Designation in English, office unit name in english, office unit name in bangla, office unit organogram id, employee email, employee record id, employee name english etc.

URL: <http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgnUnitOrg/{officeId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgnUnitOrg/343' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgnUnitOrg/343');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (JAVA- OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgnUnitOrg
/343")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "designationBng": "উপজেলা নির্বাহী অফিসার",
    "designationEng": "UNO Officer",
    "officeUnitNameEn": "UNO Office",
    "officeUnitNameBn": "উপজেলা নির্বাহী অফিসারের কার্যালয়, বরিশাল",
    "officeUnitOrganogramId": 18376,
    "employeeEmail": "",
    "employeeRecordId": 31956,
    "employeeNameEng": "",
    "officeUnitId": 7213,
    "officeId": 343,
    "employeeNameBng": "মোঃ মনিবুর রহমান",
    "employeeMobile": "01719458921",
    "username": "100000017209"
  },
  {
    "designationBng": "অফিস সহকারী",
    "designationEng": "Office Assistant",
    "officeUnitNameEn": "UNO Office",
    "officeUnitNameBn": "উপজেলা নির্বাহী অফিসারের কার্যালয়, বরিশাল",
    "officeUnitOrganogramId": 18379,
    "employeeEmail": "nasirbarisal1973@gmail.com",
    "employeeRecordId": 5041,
    "employeeNameEng": "",
    "officeUnitId": 7213,
    "officeId": 343,
    "employeeNameBng": "মো: নাসির সরদার",
    "employeeMobile": "১৭১২৭০০৩৩৮",
    "username": "200000003424"
  }
]
```

Serial Number – 012

Name – Get employee details with office id

Description -- This API provides office unit organogram id, employee name in bangla, employee name in English, username, employee record id.

URL: <http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeInfoByOfficeId/{officeId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeInfoByOf
ficeId/343' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeInfoByOffice
Id/343');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (JAVA- OkHttpClient)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeInfoByOfficeId/343")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "officeUnitOrganogramId": 18379,
    "employeeNameBn": "মো: নাসির সরদার",
    "employeeNameEn": "",
    "userName": "20000003424",
    "employeeRecordId": 5041
  },
  {
    "officeUnitOrganogramId": 18380,
    "employeeNameBn": "আবুল নাসের",
    "employeeNameEn": "",
    "userName": "20000003425",
    "employeeRecordId": 5042
  },
  {
    "officeUnitOrganogramId": 243387,
    "employeeNameBn": "আল ফারহান আজমী",
    "employeeNameEn": "",
    "userName": "20000052039",
    "employeeRecordId": 60626
  },
  {
    "officeUnitOrganogramId": 18376,
    "employeeNameBn": "মোঃ মনিবুর রহমান",
    "employeeNameEn": "",
    "userName": "10000017209",
    "employeeRecordId": 31956
  }
]
```


Serial Number – 013

Name – Get office unit employee information details with office unit organogram id

Description -- This API provides office unit id, office unit name in bangla, office unit name in English, mobile number, office unit origin id, employee name in bangla, employee name in english, email and employee username.

URL:

<http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitEmployeeInfo/{officeUnitOrgId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitEmployeeInfo/18379' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitEmployeeInfo/18379');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

```

        .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doctor.gov.bd:8280/coredata/getOfficeUnitEmployeeInfo/18379")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();

```

Sample Request (PHP-HTTP_Request2)

```

OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doctor.gov.bd:8280/coredata/getOfficeUnitEmployeeInfo/18379")
    .method("GET", null)
    .addHeader("Authorization", "Bearer MjRkR64EjrmuSbs9Q4a8qeJWIjMbT0ux")
    .build();
Response response = client.newCall(request).execute();

```

Sample Response

```

[
  {
    "officeUnitId": 7213,
    "officeUnitNameEn": "UNO Office",
    "officeUnitNameBn": "উপজেলা নির্বাহী অফিসারের কার্যালয়, বরিশাল",
    "mobile": "১৭১২৭০০৩৩৮",
    "officeUnitOrgId": 18379,
    "employeeNameBn": "মো: নাসির সরদার",
    "employeeNameEn": "",
    "email": "nasirbarisal1973@gmail.com",
    "username": "20000003424"
  }
]

```

Serial Number – 014

Name – Get employee information by office unit origin id

Description -- This API provides employee name in bangla, employee name in English, mobile number, id, office unit organogram id, email address and username

URL:

<http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeInfoByOfficeUnitOrgId/{officeUnitOrgId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeInfoByOfficeUnitOrgId/18379' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeInfoByOfficeUnitOrgId/18379');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (PHP-HTTP_Request2)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getEmployeeInfoByOfficeUnitOrgId/18379")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "nameBng": "মো: নাসির সরদার",
    "name": "",
    "mobile": "১৭১২৭০০৩৩৮",
    "id": 5041,
    "office_unit_organogram_id": 18379,
    "email": "nasirbarisal1973@gmail.com",
    "username": "20000003424"
  }
]
```

Serial Number – 015

Name – Get office unit organogram with office unit organogram id

Description -- This API provides Designation in Bangla, Designation in English, office unit id, office id, office origin unit id, office unit organogram id and office origin unit id.

URL:

<http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgById/{officeUnitOrganogramId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgById/18379' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgById/18379');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (PHP-HTTP_Request2)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgById/18379")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "designationBng": "অফিস সহকারী",
    "designationEng": "Office Assistant",
    "officeUnitId": 7213,
    "officeId": 343,
    "officeOrgnUnitOrgId": 83,
    "officeUnitOrganogramId": 18379,
    "officeOrgnUnitId": 27
  }
]
```

Serial Number – 016

Name – Get office unit origin by origin unit organogram id with office unit organogram id

Description -- This API provides designation name in bangla, designation name in english, office unit id, office id, office organogram unit origin id, office unit organogram id and office organogram unit id.

URL:

<http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgByOrgUnitOrgnId/{officeOrgUnitOrgnId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgByOrgUnitOrgnId/831' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgByOrgUnitOrgnId/831');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

```
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeUnitOrgByOrgUnitOrgnId/831")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "designationBng": "প্রশাসনিক কর্মকর্তা",
    "designationEng": "Admin Officer",
    "officeUnitId": 742,
    "officeId": 53,
    "officeOrgnUnitOrgId": 831,
    "officeUnitOrganogramId": 1620,
    "officeOrgnUnitId": 277
  }
]
```


Serial Number – 017

Name – Get office information with employee record id

Description -- This API provides office Ministry id, office unit organogram id and reference origin unit organogram id.

URL:

<http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeInfoByEmployeeId/{employeeRecordId}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeInfoByEmployeeId/5041' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeInfoByEmployeeId/5041');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/coredata/getOfficeInfoByEmployeeId/5041")
    .method("GET", null)
    .addHeader("Authorization", "Bearer ixKWAXZoRnFF4n0kKggwag0BmnBLL21D")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "officeMinistryId": 5,
    "officeUnitOrganogramId": 18379,
    "refOriginUnitOrganogramId": 83
  }
]
```

Serial Number – 018

Name – Get division information with division id

Description -- This API provides division bbs code, division english name, division bangla name, division id.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/division?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/division?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/division?id=1' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/division?id=1');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/division?id=1")
    .method("GET", null)
    .addHeader("Authorization", "Bearer ixKWAXZoRnFF4n0kKggwag0BmnBLL21D")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "bbsCode": "10",
    "name": "Barisal",
    "nameBn": "বরিশাল",
    "id": 1
  }
]
```

Serial Number – 019

Name – Get district information with district id

Description -- This API provides division bbs code, district bbs code, district english name, district bangla name, district id.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/division?{id=\[value\]}](http://esb.beta.doptor.gov.bd:8280/gen/division?{id=[value]})

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/district?id=1' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/district?id=1');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/district?id=1")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 1,
    "divisionBbsCode": "10",
    "bbsCode": "4",
    "name": "BARGUNA",
    "nameBn": "বরগুনা",
    "id": 1
  }
]
```

Serial Number – 020

Name – Get upazila information with upazila id

Description -- This API provides division code, bbscode, district, upazila name in english, upazila name in bangla, upazila id.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/upazila?{id=\[value\]}](http://esb.beta.doptor.gov.bd:8280/gen/upazila?{id=[value]})

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/upazila?id=1' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/upazila?id=1');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/upazila?id=1")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 1,
    "bbsCode": "09",
    "district": 1,
    "name": "AMTALI",
    "nameBn": "আমতলী ",
    "id": 1
  }
]
```


Serial Number – 021

Name – Get union information with union id

Description -- This API provides division id , union bbs code, district id, union name in english, union name in bangla, union id Upazila code.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/union?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/union?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/union?id=1' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/union?id=1');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/union?id=1")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 5,
    "bbsCode": "13",
    "district": 45,
    "name": "ADAM DIGHI",
    "nameBn": "আদমদিঘি",
    "id": 1,
    "upazila": 329
  }
]
```

Serial Number – 022

Name – Get city corporation information with city corporation id

Description -- This API provides Division code, city corporation bbs code, district code, city corporation name in bangla, city corporation name in english city corporation id.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/citycorporation?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/citycorporation?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/citycorporation?id=5' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/gen/citycorporation?id=5');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/citycorporation?id=5")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 18,
    "bbsCode": "25",
    "district": 18,
    "name": "DHAKA UTTAR CITY CORP.",
    "nameBn": "ঢাকা সিটি কর্পোরেশন",
    "id": 5
  }
]
```

Serial Number – 023

Name – Get municipality information with municipality id

Description -- This API provides division id, municipality bbs code, district id, municipality name in bangla, municipality name in english, municipality id, Upazila code.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/municipality?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/municipality?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/municipality?id=4' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/gen/municipality?id=4');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/municipality?id=4")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 2,
    "bbsCode": "50",
    "district": 7,
    "name": "BANDARBAN PAURASHAVA",
    "nameBn": "বান্দরবান পৌরসভা",
    "id": 4,
    "upazila": 41
  }
]
```

Serial Number – 024

Name – Get Thana information with thana id

Description -- This API provides division code, thana bbs code, district code, thana name in bangla, thana name in english, thana id.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/thana?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/thana?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/thana?id=1' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/thana?id=1');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/thana?id=1")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 2,
    "bbsCode": "50",
    "district": 7,
    "name": "BANDARBAN PAURASHAVA",
    "nameBn": "বান্দরবান পৌরসভা",
    "id": 4,
    "upazila": 41
  }
]
```


Serial Number – 025

Name – Get post office information with post office id

Description -- This API provides division code, post office bbs code, district code, post office name in english, post office name in bangla, post office id, Upazilla id

URL: [http://esb.beta.doptor.gov.bd:8280/gen/postoffice?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/postoffice?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/postoffice?id=1' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/postoffice?id=1');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/postoffice?id=1")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 1,
    "bbsCode": "8223",
    "district": 0,
    "name": "Borakotha",
    "nameBn": "",
    "id": 1,
    "upazila": 16
  }
]
```

Serial Number – 026

Name – Get office information with office id

Description -- This API provides office website, office code, office origin id, office name in bangla, office mobile number, digital nothi code, upazila code, office layer, division code, office phone number, district code, custom layer , office name, office id, office fax number, ministry id, office email address.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/office?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/office?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/office?id=55' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/office?id=55');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/office?id=55")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "website": "http://www.publiclibrary.gov.bd/",
    "code": "",
    "origin": 44,
    "nameBn": "গণগ্রন্থাগার অধিদপ্তর",
    "mobile": "",
    "digitalNothiCode": "৪৩.২৬.০০০০",
    "upazila": ০,
    "layer": 46,
    "division": 3,
    "phone": "০২-৯৬৭১২৩৪",
    "district": 18,
    "customLayer": ০,
    "name": "Department of public libraries, Shahbag, Dhaka",
    "id": 55,
    "fax": "০২-৮৬২৮২০৫",
    "ministry": 43,
    "email": "dg.dpl.2012@gmail.com"
  }
]
```

Serial Number – 027

Name – Get office front desk information with office front desk id

Description -- This API provides office name in bangla, office address, office unit id, office id, office unit organogram id, officer name, office id, office unit name , designation label, officer id.

URL: <http://esb.beta.doptor.gov.bd:8280/gen/officefrontdesk?id={value}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/officefrontdesk?id=55' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/gen/officefrontdesk?id=55');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/officefrontdesk?id=55")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "officeName": "জেলা প্রশাসকের কার্যালয়, মুন্সিগঞ্জ",
    "address": "জেলা প্রশাসকের কার্যালয়, মুন্সিগঞ্জ",
    "officeUnitId": 6388,
    "officeId": 176,
    "officeUnitOrganogramId": 16067,
    "officerName": "মোঃ মুনছুর হেলাজ",
    "id": 55,
    "officeUnitName": "ফ্রন্ট ডেস্ক শাখা",
    "designationLabel": "অফিস সহকারী ",
    "officerId": 4750
  }
]
```

Serial Number – 028

Name – Get office unit information with office unit id

Description -- This API provides office parent, office sarok id, office level, office name in bangla, office , office layer, office phone number, office nothi

URL: [http://esb.beta.doptor.gov.bd:8280/gen/officeunit?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/officeunit?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/officeunit?id=7213' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/gen/officeunit?id=7213');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/officeunit?id=7213")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "parent": 0,
    "sarok": 0,
    "level": 0,
    "nameBn": "উপজেলা নির্বাহী অফিসারের কার্যালয়, বরিশাল",
    "office": 343,
    "layer": 5,
    "phone": null,
    "nothi": "000",
    "name": "UNO Office",
    "officeoriginunitid": 27,
    "id": 7213,
    "category": "দপ্তর",
    "fax": null,
    "email": null
  }
]
```


Serial Number – 029

Name – Get office unit organogram information with office unit organogram id

Description -- This API provides unit id, is admin, designation sequence, name in bangla, name in english, office id, id, designation level.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/officefrontdesk?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/officefrontdesk?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/officeunitorganogram?id=
7213' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
setUrl('http://esb.beta.doptor.gov.bd:8280/gen/officeunitorganogram?id=7213
');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX
'));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/officeunitorganogram?id=7213"
    )
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "unit": 3614,
    "isadmin": false,
    "designationSequence": 0,
    "nameBn": "উপ পরিচালক",
    "name": "Deputy Director (Local Government)",
    "office": 85,
    "id": 7213,
    "designationLevel": 2
  }
]
```

Serial Number – 030

Name – Get office incharge type with office interchange type id

Description -- This API provides unit id, is admin, designation sequence, name in bangla, name in english, office id, id, designation level.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/officeincharge?{id=\[value\]}](http://esb.beta.doptor.gov.bd:8280/gen/officeincharge?{id=[value]})

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/officeunitorganogram?id=
7213' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/gen/officeunitorganogram?id=7213
');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/officeunitorganogram?id=7213"
    )
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "unit": 3614,
    "isadmin": false,
    "designationSequence": 0,
    "nameBn": "উপ পরিচালক",
    "name": "Deputy Director (Local Government)",
    "office": 85,
    "id": 7213,
    "designationLevel": 2
  }
]
```

Serial Number – 031

Name – Get office ministry with office ministry id

Description -- This API provides Reference id, office name in english, office name in bangla, office id, office type id, office short name.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/officeministry?id=\[value\]}](http://esb.beta.doptor.gov.bd:8280/gen/officeministry?id=[value]})

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/officeministry?id=55' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/gen/officeministry?id=55');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/officeministry?id=55")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "reference": "০১",
    "name": "Public Division, President Office",
    "nameBn": "জন বিভাগ, রাষ্ট্রপতির কার্যালয়",
    "id": 55,
    "type": 2,
    "nameShort": "Bangabhaban"
  }
]
```

Serial Number – 032

Name – Get office unit category with office unit category id

Description -- This API provides office unit category name in english, office unit category name in bangla, office unit category id.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/officeunitcategory?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/officeunitcategory?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/officeunitcategory?id=3'
\
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/gen/officeunitcategory?id=3');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/officeunitcategory?id=3")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "name": "Section",
    "nameBn": "শ্রীক্ষণ",
    "id": 3
  }
]
```


Serial Number – 033

Name – Get employee office details with employee office id

Description -- This API provides unit id, employee record id, employee joining date, employee id, employee designation, office id, organogram id and employee last working day date.

URL: <http://esb.beta.doptor.gov.bd:8280/gen/emooffice?id={value}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/empoffice?id=3' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/empoffice?id=3');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/empoffice?id=3")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "unit": 289,
    "employeeRecord": 5,
    "joiningDate": null,
    "id": 3,
    "designation": "জেলা প্রশাসক",
    "office": 3,
    "organogram": 558,
    "lastDate": null
  }
]
```

Serial Number – 034

Name – Get employee records with employee record id

Description -- This API provides cadre or non cadre id, gender, father name, employee name in bangla, nid number, mobile number, employee joining date, current office , religion, ppn, mother name, employee blood group, nationality, date of birth, grade, name in english, employee id, employee marital status, email address .

URL: [http://esb.beta.doptor.gov.bd:8280/gen/emprecord?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/emprecord?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/emprecord?id=3' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/emprecord?id=3');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doctor.gov.bd:8280/gen/emprecord?id=3")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "pob": "",
    "cadreNonCadre": 1,
    "gender": "1",
    "father": "",
    "nameBn": "মনির হোসাইন চৌধুরী ",
    "nid": "",
    "mobile": "+88-02-9514377",
    "joiningDate": null,
    "currentOffice": 0,
    "religion": "Islam",
    "ppn": "",
    "mother": "",
    "bloodGroup": "",
    "nationality": null,
    "dob": null,
    "grade": 0,
    "name": "Monir Hossain Chowdhury",
    "id": 3,
    "maritalStatus": "",
    "email": "pssec@mopa.gov.bd\t"
  }
]
```

Serial Number – 035

Name – Get employee batch with employee batch id

Description -- This API provides number of the batch, batch year, batch id.

URL: <http://esb.beta.doptor.gov.bd:8280/gen/empbatch?id={value}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/empbatch?id=3' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/empbatch?id=3');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/empbatch?id=3")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "number": "৮৩",
    "year": "১৯৮৩",
    "id": 3
  }
]
```

Serial Number – 036

Name – Get employee cadre information with employee cadre id

Description -- This API provides cadre name in bangla, name in english, cadre id.

URL: <http://esb.beta.doptor.gov.bd:8280/gen/empcadre?id={value}>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'http://esb.beta.doptor.gov.bd:8280/gen/empcadre?id=3' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/empcadre?id=3');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/empcadre?id=3")
    .method("GET", null)
    .addHeader("Authorization", "Bearer VgnFuPR6VLWgpt2bR3U8DykmP6xLjz1w")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "number": "৮৩",
    "year": "১৯৮৩",
    "id": 3
  }
]
```


Serial Number – 037

Name – Get employee grade information with employee grade id

Description -- This API provides employee rank, employee grade name in english, employee grade name in bangla, employee grade id, employee cadre id.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/empgrade?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/empgrade?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/empgrade?id=1' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('http://esb.beta.doptor.gov.bd:8280/gen/empgrade?id=1');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/empgrade?id=1")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "employeeRank": 1,
    "name": "Grade 1",
    "nameBn": "গ্রেড ১",
    "id": 1,
    "employeeCadre": 3
  }
]
```

Serial Number – 038

Name – Get employee policy role information with employee policy role id

Description -- This API provides employee role name in bangla, employee role name in english, policy role id.

URL: [http://esb.beta.doptor.gov.bd:8280/gen/emppolicyrole?id=\[value\]](http://esb.beta.doptor.gov.bd:8280/gen/emppolicyrole?id=[value])

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --
request GET 'http://esb.beta.doptor.gov.bd:8280/gen/emppolicyrole?id=1' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->
>setUrl('http://esb.beta.doptor.gov.bd:8280/gen/emppolicyrole?id=1');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
        $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java -OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("http://esb.beta.doptor.gov.bd:8280/gen/emppolicyrole?id=1")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "name": "main role",
    "nameBn": "মূল দায়িত্ব",
    "id": 1
  }
]
```

<https://api-doptor.nothi.gov.bd>

Serial Number – 0039

Name – Get division details

Description -- This API provides the division name in Bangla, division name in English, Division BBS code and division id

URL: <https://api-doptor.nothi.gov.bd/g/division>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/division' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/division');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttpClient)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/division")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "bbsCode": "10",
    "name": "Barisal",
    "nameBn": "বরিশাল",
    "id": 1
  },
  {
    "bbsCode": "20",
    "name": "Chittagong",
    "nameBn": "চট্টগ্রাম",
    "id": 2
  },
  {
    "bbsCode": "30",
    "name": "Dhaka",
    "nameBn": "ঢাকা",
    "id": 3
  },
  {
    "bbsCode": "40",
    "name": "Khulna",
    "nameBn": "খুলনা",
    "id": 4
  }
]
```

```
    },  
    {  
      "bbsCode": "50",  
      "name": "Rajshahi",  
      "nameBn": "রাজশাহী",  
      "id": 5  
    },  
    {  
      "bbsCode": "55",  
      "name": "Rangpur",  
      "nameBn": "রংপুর",  
      "id": 6  
    },  
    {  
      "bbsCode": "70",  
      "name": "Sylhet",  
      "nameBn": "সিলেট",  
      "id": 7  
    },  
    {  
      "bbsCode": "45",  
      "name": "Mymensingh",  
      "nameBn": "ময়মনসিংহ",  
      "id": 9  
    }  
  ]  
}
```


Serial Number – 040

Name – Get district details

Description -- This API provides the division id, division bbs code, district bbs code, district name in English, district name in bangla, district id.

URL: <https://api-doptor.noithi.gov.bd/g/district>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.noithi.gov.bd/g/district' \
--header 'Authorization: Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.noithi.gov.bd/g/district');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttpClient)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/district")
    .method("GET", null)
    .addHeader("Authorization", "Bearer XXXXXXXXXXXXXXXXXXXXXXXX ")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 1,
    "divisionBbsCode": "10",
    "bbsCode": "04",
    "name": "BARGUNA",
    "nameBn": "বরগুনা",
    "id": 1
  },
  {
    "division": 1,
    "divisionBbsCode": "10",
    "bbsCode": "06",
    "name": "BARISAL",
    "nameBn": "বরিশাল",
    "id": 2
  },
]
```

Serial Number – 041

Name – Get union details

Description -- This API provides the division id , union bbs code, district id, union name in bangla, union name in english, union id, and Upazila id.

URL: <https://api-doptor.nothi.gov.bd/g/union>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/union' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/union');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/union")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 5,
    "bbsCode": "13",
    "district": 45,
    "name": "ADAM DIGHI",
    "nameBn": "আদমদিঘি",
    "id": 1,
    "upazila": 329
  },
  {
    "division": 5,
    "bbsCode": "27",
    "district": 45,
    "name": "CHAMPAPUR",
    "nameBn": "চাঁপাপুর",
    "id": 2,
    "upazila": 329
  },
]
```

Serial Number – 042

Name – Get City corporation details

Description -- This API provides the division id, city corporation bbs code, district id , city corporation name in bangla, city corporation name in english and city corporation id.

URL: <https://api-doptor.nothi.gov.bd/g/citycorporation>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/citycorporation' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/citycorporation');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/citycorporation")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 2,
    "bbsCode": "50",
    "district": 2,
    "name": "BARISAL CITY CORP.",
    "nameBn": "বরিশাল সিটি কর্পোরেশন",
    "id": 1
  },
  {
    "division": 10,
    "bbsCode": "16",
    "district": 10,
    "name": "CHITTAGONG CITY CORP.",
    "nameBn": "চট্টগ্রাম সিটি কর্পোরেশন",
    "id": 2
  }
]
```

Serial Number – 043

Name – Get municipality details

Description -- This API provides the division id , municipality bbs code, district id, municipality name in bangla, municipality name in english, municipality id and Upazila id.

URL: <https://api-doptor.nothi.gov.bd/g/municipality>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/municipality' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/municipality');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/municipality")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 4,
    "bbsCode": "25",
    "district": 35,
    "name": "BAGERHAT PAURASAVA",
    "nameBn": "বাগেরহাট পৌরসভা",
    "id": 1,
    "upazila": 0
  },
  {
    "division": 4,
    "bbsCode": "501",
    "district": 35,
    "name": "MONGLA PORT PAURASAVA",
    "nameBn": "মোংলা পোর্ট পৌরসভা",
    "id": 2,
    "upazila": 275
  }
]
```


Serial Number – 044

Name – Get Thana details

Description -- This API provides the division id, thana bbs code, district id, thana name in bangla, thana name in english and thana id.

URL: <https://api-doptor.nothi.gov.bd/g/thana>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/thana' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/thana');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/thana")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "division": 4,
    "bbsCode": "08",
    "district": 35,
    "name": "BAGERHAT SADAR",
    "nameBn": "বাগেরহাট সদর",
    "id": 1
  },
  {
    "division": 4,
    "bbsCode": "14",
    "district": 35,
    "name": "CHITALMARI",
    "nameBn": "চিতলমারী",
    "id": 2
  }
]
```

Serial Number – 045

Name – Get employee office details

Description -- This API provides the office unit id, employee record id , employee joining date, employee id, employee designation , employee office, office organogram id, employee last working date.

URL: <https://api-doptor.nothi.gov.bd/g/empoffice>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/empoffice' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/empoffice');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/empoffice")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "unit": 23312,
    "employeeRecord": 989056,
    "joiningDate": 1611619200000,
    "id": 104582,
    "designation": "মাননীয় প্রতিমন্ত্রী",
    "office": 14,
    "organogram": 84615,
    "lastDate": 1614038400000
  },
  {
    "unit": 4612,
    "employeeRecord": 989056,
    "joiningDate": 1611705600000,
    "id": 104583,
    "designation": "সিনিয়র সহকারী সচিব",
    "office": 8,
    "organogram": 10034,
    "lastDate": 1612915200000
  }
]
```

Serial Number – 046

Name – Get employee batch details

Description -- This API provides the batch number, batch year and batch id

URL: <https://api-doptor.nothi.gov.bd/g/empbatch>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/empbatch' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/empbatch');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/empbatch")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "number": "০০",
    "year": "২০০০",
    "id": 254
  },
  {
    "number": "০১",
    "year": "২০০১",
    "id": 255
  }
]
```

Serial Number – 047

Name – Get employee cadre details

Description -- This API provides the cadre name in bangla, cadre name in English and cadre id.

URL: <https://api-doptor.nothi.gov.bd/g/empcadre>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/empcadre' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/empcadre');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/empcadre")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "name": "Bangladesh Civil Service (Telecommunication)",
    "nameBn": "বাংলাদেশ সিভিস সার্ভিস (টেলিযোগাযোগ)",
    "id": 31
  },
  {
    "name": "Bangladesh Civil Service (Police)",
    "nameBn": "বাংলাদেশ সিভিল সার্ভিস (পুলিশ)",
    "id": 32
  },
  {
    "name": "Bangladesh Civil Service (Administration)",
    "nameBn": "বাংলাদেশ সিভিল সার্ভিস (প্রশাসন)",
    "id": 33
  }
]
```


Serial Number – 048

Name – Get office details

Description -- This API provides the office website, office code, office origin id, office name in bangla, office mobile number, office digital nothi code, Upazila id, office layer, division id, office phone number, district id , office custom layer, office name in english, office id, office fax number, ministry id and office email.

URL: <https://api-doptor.nothi.gov.bd/g/office>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/office' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/office');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/office")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "website": "www.chittagong.gov.bd",
    "code": "৪২",
    "origin": 16,
    "nameBn": "জেলা প্রশাসকের কার্যালয়, চট্টগ্রাম",
    "mobile": "০১৭১৩১০৪৩৩২",
    "digitalNothiCode": "০৫.৪২.১৫০০",
    "upazila": ০,
    "layer": 375,
    "division": 2,
    "phone": "০৩১- ৬১৯৯৯৬",
    "district": 10,
    "customLayer": 1,
    "name": "Office of the Deputy Commissioner, Chittagong",
    "id": 3,
    "fax": "৮৮-০৩১-৬২০৫৭০, ৮৮-০৩১-৬৩৫২৭২",
    "ministry": 5,
    "email": "dcchittagong@mopa.gov.bd"
  },
]
```

Serial Number – 049

Name – Get office layer details

Description -- This API provides the custom layer id, level id, layer name in bangla, layer name in English, layer id.

URL: <https://api-doptor.nothi.gov.bd/g/officelayer>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officelayer' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officelayer');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officelayer")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "customlayerid": 19,
    "level": 1,
    "name": "Ministry",
    "nameBn": "মন্ত্রণালয়",
    "id": 19
  },
  {
    "customlayerid": 21,
    "level": 2,
    "name": "Directorate",
    "nameBn": "অধিদপ্তর",
    "id": 20
  }
]
```

Serial Number – 050

Name – Get office unit organogram details

Description -- This API provides the office unit id, admin, designation sequence, name in bangla, name in English, office id, office unit organogram id, office unit organogram designation level.

URL: <https://api-doptor.nothi.gov.bd/g/officeunitorganogram>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officeunitorganogram' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officeunitorganogram');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttpClient)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officeunitorganogram")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "unit": 1,
    "isadmin": true,
    "designationSequence": 1,
    "nameBn": "সুপার অ্যাডমিন",
    "name": "super admin",
    "office": -1,
    "id": -1,
    "designationLevel": 1
  },
  {
    "unit": 210,
    "isadmin": false,
    "designationSequence": 0,
    "nameBn": "উপজেলা নির্বাহী অফিসার ",
    "name": "UNO Officer",
    "office": 9,
    "id": 534,
    "designationLevel": 0
  }
]
```

Serial Number – 051

Name – Get office front desk details

Description -- This API provides the office name in bangla, office name in english, office address, office unit id, office unit organogram id, officer name in bangla, office id, office unit name in bangla, office id and designation label at office.

URL: <https://api-doptor.nothi.gov.bd/g/officeforntdesk>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officefrontdesk' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officefrontdesk');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officefrontdesk")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "officeName": "জেলা প্রশাসকের কার্যালয়, জামালপুর",
    "address": "জেলা প্রশাসকের কার্যালয়\nজামালপুর, বাংলাদেশ",
    "officeUnitId": 785,
    "officeId": 11,
    "officeUnitOrganogramId": 1860,
    "officerName": "মোছাঃ জেসমিন সুলতানা",
    "id": 1,
    "officeUnitName": "জেলা ই-সেবা কেন্দ্র",
    "designationLabel": "অফিস সহকারী কাম কম্পিউটার অপারেটর",
    "officerId": 458
  }
]
```


Serial Number – 052

Name – Get office inchange type details

Description -- This API provides the office type name in bangla, office type name in english and id

URL: <https://api-doptor.nothi.gov.bd/g/officeinchangetype>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officeinchangetype' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officeinchangetype');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officeinchargetype")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
{
  "name": "Incharge",
  "nameBn": "ভারপ্রাপ্ত",
  "id": 1
},
{
  "name": "Current",
  "nameBn": "চলতি দায়িত্ব",
  "id": 2
},
{
  "name": "Additional",
  "nameBn": "অতিরিক্ত দায়িত্ব",
  "id": 3
},
{
  "name": "Substitute",
  "nameBn": "রুটিন দায়িত্ব",
  "id": 4
}
]
```

Serial Number – 053

Name – Get office ministry details

Description -- This API provides the office name in bangla, office name in english, office reference code, office id , office type and office short name.

URL: <https://api-doptor.nothi.gov.bd/g/officeministry>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officeministry' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officeministry');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officeministry")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "reference": "০৩",
    "name": "Prime Minister's Office",
    "nameBn": "প্রধানমন্ত্রীর কার্যালয়",
    "id": 3,
    "type": 1,
    "nameShort": "PMO"
  },
  {
    "reference": "০৪",
    "name": "Cabinet Division",
    "nameBn": "মন্ত্রিপরিষদ বিভাগ",
    "id": 4,
    "type": 2,
    "nameShort": "CABINET"
  }
]
```

Serial Number – 053

Name – Get office unit category details

Description -- This API provides the office category name in bangla, office category name in english, office category id

URL: <https://api-doptor.nothi.gov.bd/g/officeunitcategory>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officeunitcategory' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officeunitcategory');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officeunitcategory")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "name": "Institution",
    "nameBn": "সংস্থা",
    "id": 0
  },
  {
    "name": "Office",
    "nameBn": "দপ্তর",
    "id": 2
  },
  {
    "name": "Section",
    "nameBn": "শাখা",
    "id": 3
  }
]
```

Serial Number – 054

Name – Get office unit details

Description -- This API provides the office unit parent id, office sharok id, office level, unit office name in bangla, and office unit name in English, office id, office layer id, office phone number, office nothi code, and officer name

URL: <https://api-doptor.nothi.gov.bd/g/officeunitcategory>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-  
doptor.nothi.gov.bd/g/officeunit' \  
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php  
require_once 'HTTP/Request2.php';  
$request = new HTTP_Request2();  
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officeunit');  
$request->setMethod(HTTP_Request2::METHOD_GET);  
$request->setConfig(array(  
    'follow_redirects' => TRUE  
));  
$request->setHeader(array(  
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'  
));  
try {  
    $response = $request->send();  
    if ($response->getStatus() == 200) {  
        echo $response->getBody();  
    }  
    else {  
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .  
            $response->getReasonPhrase();  
    }  
}  
catch(HTTP_Request2_Exception $e) {  
    echo 'Error: ' . $e->getMessage();  
}
```

Sample Request (Java - OkHttpClient)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officeunit")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
{
  "parent": 300,
  "sarok": 0,
  "level": 0,
  "nameBn": "জেনারেল সার্টিফিকেট শাখা",
  "office": 11,
  "layer": 5,
  "phone": null,
  "nothi": "০২২",
  "name": "General Certificate Section",
  "officeoriginunitid": 15,
  "id": 301,
  "category": "শাখা",
  "fax": null,
  "email": null
},
{
  "parent": 300,
  "sarok": 0,
  "level": 0,
  "nameBn": "রাজস্ব মুন্সিখানা শাখা",
  "office": 11,
  "layer": 5,
```



```
    "phone": null,  
    "nothi": "୦୧୬",  
    "name": "Revenue Munshikhana Section",  
    "officeoriginunitid": 16,  
    "id": 302,  
    "category": "ଆଦାଲତ",  
    "fax": null,  
    "email": null  
  }  
]
```

Serial Number – 055

Name – Get office origin details

Description -- This API provides the office parent id, office sequence, office level, office name in bangla, office name in english, office id, office ministry, office layer,

URL: <https://api-doptor.nothi.gov.bd/g/officeorigin>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officeorigin' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officeorigin');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officeorigin")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "parent": 0,
    "sequence": 1,
    "level": 1,
    "nameBn": "প্রধানমন্ত্রীর কার্যালয়",
    "name": "Prime Ministry office",
    "id": 1,
    "ministry": 3,
    "layer": 44
  },
  {
    "parent": 0,
    "sequence": 0,
    "level": 0,
    "nameBn": "মন্ত্রণালয়ের কার্যালয়",
    "name": "Ministry Office",
    "id": 12,
    "ministry": 5,
    "layer": 19
  },
]
```

Serial Number – 056

Name – Get office origin unit details

Description -- This API provides the office parent id , office level , office origin unit name in bangla, office origin unit name in english, office origin id, office id, ministry id and office layer.

URL: <https://api-doctor.nothi.gov.bd/g/officeoriginunit>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doctor.nothi.gov.bd/g/officeoriginunit' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doctor.nothi.gov.bd/g/officeoriginunit');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officeoriginunit")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "parent": 9,
    "level": 0,
    "nameBn": "শিক্ষা ও কল্যাণ শাখা",
    "name": "Education & welfare Section",
    "officeOrigin": 16,
    "id": 1,
    "ministry": 5,
    "layer": 22
  },
  {
    "parent": 0,
    "level": 0,
    "nameBn": "জেলা প্রশাসকের কার্যালয়",
    "name": "Deputy Commissioner Office",
    "officeOrigin": 16,
    "id": 4,
    "ministry": 5,
    "layer": 22
  },
]
```

Serial Number – 057

Name – Get office origin unit organogram details

Description -- This API provides the sequence, superior unit, superior designation, level, office origin unit organogram name in bangla, office origin unit organogram name in english, short name in bangla, office origin unit organogram id, origin unit id and short name.

URL: <https://api-doptor.nothi.gov.bd/g/officeoriginunitorganogram>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officeoriginunitorganogram' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officeoriginunitorganogram');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officeoriginunitorganogram")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "sequence": 1,
    "superiorUnit": 0,
    "superiorDesignation": 0,
    "level": 1,
    "nameBn": "জেলা প্রশাসক",
    "name": "DC",
    "shortNameBn": "",
    "id": 51,
    "originUnit": 4,
    "shortName": ""
  },
  {
    "sequence": 0,
    "superiorUnit": 0,
    "superiorDesignation": 51,
    "level": 0,
    "nameBn": "অতিরিক্ত জেলা প্রশাসক",
    "name": "ADC",
    "shortNameBn": "",
    "id": 64,
    "originUnit": 7,
    "shortName": ""
  }
]
```

```
},  
]
```


Serial Number – 058

Name – Get office custom layer details

Description -- This API provides the layer level , custom layer name in bangla, custom layer id.

URL: <https://api-doptor.nothi.gov.bd/g/officecustomlayers>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officecustomlayers' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officecustomlayers');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officecustomlayers")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "layerlevel": 1,
    "name": "ডেমো কাস্টম লেয়ার",
    "id": 1
  },
  {
    "layerlevel": 3,
    "name": "কর্তৃপক্ষ / অথোরিটি",
    "id": 2
  },
]
```

Serial Number – 059

Name – Get office custom layer details

Description -- This API provides the layer level, custom layer name in bangla, custom layer id.

URL: <https://api-doptor.nothi.gov.bd/g/officecustomlayers>

Method: GET

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request GET 'https://api-doptor.nothi.gov.bd/g/officecustomlayers' \
--header 'Authorization: Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://api-doptor.nothi.gov.bd/g/officecustomlayers');
$request->setMethod(HTTP_Request2::METHOD_GET);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
$request->setHeader(array(
    'Authorization' => 'Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP'
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' .
            $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
Request request = new Request.Builder()
    .url("https://api-doctor.nothi.gov.bd/g/officecustomlayers")
    .method("GET", null)
    .addHeader("Authorization", "Bearer EvDxUspC1KeYW4nqwyEmFdJh3CxZ4UUP")
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
[
  {
    "layerlevel": 1,
    "name": "ডেমো কাস্টম লেয়ার",
    "id": 1
  },
  {
    "layerlevel": 3,
    "name": "কর্তৃপক্ষ / অথোরিটি",
    "id": 2
  },
]
```

<https://esb-trainingv2.doptor.gov.bd/coredatacustomv1>

Part – 2

Serial Number – 01

Name – Get designation from office unit

Description -- This API provides office id, office unit id, designation level, designation sequence, short name in bangla, short name in english, id, superior designation id, designation id

URL: <https://esb-trainingv2.doptor.gov.bd/coredatacustomv1/office/unit/designations?unitIds=XXXXXXX>

Method: POST

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request POST 'https://esb-trainingv2.doptor.gov.bd/coredatacustomv1/office/unit/designations?unitIds=XXXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://esb-trainingv2.doptor.gov.bd/coredatacustomv1/office/unit/designations?unitIds=XXXXXXX');
$request->setMethod(HTTP_Request2::METHOD_POST);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' . $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```

Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
MediaType mediaType = MediaType.parse("text/plain");
RequestBody body = RequestBody.create(mediaType, "");
Request request = new Request.Builder()
    .url("https://esb-
trainingv2.doptor.gov.bd/coredatacustomv1/office/unit/designations?unitIds=XXXXXXX")
    .method("POST", body)
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
"data": [
  {
    "office_id": 28,
    "office_unit_id": 410,
    "designation_level": 1,
    "designation_sequence": "1",
    "short_name_bng": "",
    "id": 850,
    "superior_designation_id": 850,
    "designation_eng": "Cabinet Secretary",
    "short_name_eng": ""
  },
  {
    "office_id": 28,
    "office_unit_id": 410,
    "designation_level": 11,
    "designation_sequence": "1",
    "short_name_bng": "",
    "id": 851,
    "superior_designation_id": 850,
    "designation_eng": " PS to Secretary",
    "short_name_eng": ""
  }
]
```

Serial Number – 02

Name – Get details from designation id

Description -- This API provides cadre, joining date, name in english, employee batch id, date of birth, employee cadre id, appointment memo number, id, identity number, name in bangla, personal email

URL: <https://esb-trainingv2.doptor.gov.bd/coredatacustomv1/employee/information/designation?designationIds=XXXXXX>

Method: POST

Headers

Authorization – Bearer XXXXXXXXXXXXXXXXXXXXXXXXXX

Example:

Sample Request (cURL)

```
curl --location --request POST 'https://esb-trainingv2.doptor.gov.bd/coredatacustomv1/employee/information/designation?designationIds=XXXXXX,XXXXXX'
```

Sample Request (PHP-HTTP_Request2)

```
<?php
require_once 'HTTP/Request2.php';
$request = new HTTP_Request2();
$request->setUrl('https://esb-trainingv2.doptor.gov.bd/coredatacustomv1/employee/information/designation?designationIds=XXXXXX,XXXXXX');
$request->setMethod(HTTP_Request2::METHOD_POST);
$request->setConfig(array(
    'follow_redirects' => TRUE
));
try {
    $response = $request->send();
    if ($response->getStatus() == 200) {
        echo $response->getBody();
    }
    else {
        echo 'Unexpected HTTP status: ' . $response->getStatus() . ' ' . $response->getReasonPhrase();
    }
}
catch(HTTP_Request2_Exception $e) {
    echo 'Error: ' . $e->getMessage();
}
```


Sample Request (Java - OkHttp)

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();
MediaType mediaType = MediaType.parse("text/plain");
RequestBody body = RequestBody.create(mediaType, "");
Request request = new Request.Builder()
    .url("https://esb-
trainingv2.doctor.gov.bd/coredatacustomv1/employee/information/designation?d
esignationIds=XXXX,XXXXX")
    .method("POST", body)
    .build();
Response response = client.newCall(request).execute();
```

Sample Response

```
{
  "data": [
    {
      "is_cadre": true,
      "joining_date": "0",
      "name_eng": "",
      "employee_batch_id": 0,
      "date_of_birth": "0",
      "employee_cadre_id": 0,
      "appointment_memo_no": "",
      "id": 1096,
      "identity_no": "5785",
      "name_bng": "এ এফ এম হায়াতুল্লাহ",
      "personal_email": "hayatullahafm@yahoo.com"
    }
  ],
  "status": "success"
}
```