

Chado Contact Module

From GMOD

Contents

- 1 Introduction
- 2 Tables
 - 2.1 Table: contact
 - 2.2 Table: contact_relationship

Introduction

The contact module is used to store information about people, groups, and organizations.

Tables

Table: contact

Model persons, institutes, groups, organizations, etc.

contact Structure

F-Key	Name	Type	Description
	contact_id	serial	<i>PRIMARY KEY</i>
cvterm	type_id	integer	What type of contact is this? E.g. "person", "lab".
	name	character varying(255)	<i>UNIQUE NOT NULL</i>
	description	character varying(255)	

Tables referencing this one via Foreign Key Constraints:

- arraydesign
- assay
- biomaterial
- contact_relationship
- quantification
- stockcollection
- study

Table: contact_relationship

Model relationships between contacts

contact_relationship Structure

F-Key	Name	Type	Description
	contact_relationship_id	serial	<i>PRIMARY KEY</i>
cvterm	type_id	integer	<i>UNIQUE#1 NOT NULL</i> Relationship type between subject and object. This is a cvterm, typically from the OBO relationship ontology, although other relationship types are allowed.
contact	subject_id	integer	<i>UNIQUE#1 NOT NULL</i> The subject of the subj-predicate-obj sentence. In a DAG, this corresponds to the child node.
contact	object_id	integer	<i>UNIQUE#1 NOT NULL</i> The object of the subj-predicate-obj sentence. In a DAG, this corresponds to the parent node.

Retrieved from "http://gmod.org/mediawiki/index.php?title=Chado_Contact_Module&oldid=26559"
Categories: Chado Modules | !Lacking ERD

- Last updated at 04:34 on 18 February 2015.
- 28,299 page views.
- Content is available under a GNU Free Documentation License unless otherwise noted.