

Baseline Approach



Train/Test Split

We'll try to detect the component state by learning an autoencoder

- We'll train a model on the earlier data
- ...And then use the reconstruction error as a proxy for component wear

We start as usual by splitting the training and test set

```
In [2]: tr_sep = int(0.5 * len(data_b))  
data_b_tr = data_b.iloc[:tr_sep]  
data_b_ts = data_b.iloc[tr_sep:]
```

...And then by standardizing our data


```
In [3]: scaler = StandardScaler()  
data_b_s_tr = scaler.fit_transform(data_b_tr)  
data_b_s_ts = scaler.transform(data_b_ts)  
data_b_s = pd.DataFrame(columns=data_b.columns, data=np.vstack([data_b_s_tr, data_b_s_ts]))
```



Training and Autoencoder

Now we can build and train the autoencoder

```
In [4]: nn = util.build_nn_model(input_shape=len(data_b.columns), output_shape=len(data_b.columns),  
                                hidden=[len(data_b.columns)//2])  
history = util.train_nn_model(nn, data_b_s_tr, data_b_s_tr, loss='mse', validation_split=0.0,  
                              batch_size=32, epochs=400)  
util.plot_training_history(history, figsize=figsize)
```



Final loss: 0.0347 (training)




We need many epochs to compensate for the small number of samples

Evaluation

Let's check the reconstruction error

```
In [5]: pred = nn.predict(data_b_s, verbose=0)
se = (data_b_s - pred)**2
sse = pd.Series(index=data_b.index, data=np.sum(se, axis=1))
util.plot_series(sse, figsize=figsize)
```




- Since we have a single run, we will limit ourselves to a visual inspection

✎ And the signal does not look very clear

Evaluation

We can gain more information by checking the individual errors

```
In [6]: util.plot_dataframe(se, figsize=figsize)
```



- Reconstruction errors are large for different features over time



Do you think we can improve these results? How?



Altering the Training Distribution




Distribution Discrepancy

A major problem is related to the distribution balance

The modes of operation are **not used equally often**

```
In [8]: data_b['mode'].hist(figsize=figsize, bins=np.arange(1, 10));
```



- Moreover, the mode of operation is a **controlled variable**
- ...Hence its distribution might change a lot based on the workload

Distribution Discrepancy

In fact, there is a difference between the training and test distribution

```
In [9]: data_b_tr['mode'].hist(figsize=(figsize[0], figsize[1]/2), bins=np.arange(1, 10)); plt.title  
data_b_ts['mode'].hist(figsize=(figsize[0], figsize[1]/2), bins=np.arange(1, 10)); plt.title
```



Maximum Likelihood

This matters because we are **training for maximum likelihood**

...Ideally we would like to solve:

$$\operatorname{argmax}_{\theta} \mathbb{E}_{x,y \sim P} \left[\prod_{i=1}^m f_{\theta}(y_i \mid x_i) \right]$$

- P represents the real (joint) distribution
- $f_{\theta}(\cdot \mid \cdot)$ is our estimated probability, with parameter vector θ
- I.e. an estimator for a conditional distribution
- We distinguish \mathbf{x} (input) and \mathbf{y} (output) to cover generic supervised learning
- ...Even if for an autoencoder they are the same



...And Empirical Risk

...But in practice we don't have access to the full distribution

So usually we employ a Monte-Carlo approximation:

$$\operatorname{argmax}_{\theta} \prod_{i=1}^m f_{\theta}(y_i \mid x_i)$$

- Typically, we consider a single sample \mathbf{x}, \mathbf{y} (i.e. the training set)
- The resulting objective (i.e. the big product) is sometimes called empirical risk



...And Empirical Risk

...But in practice we don't have access to the full distribution

So usually we employ a Monte-Carlo approximation:

$$\operatorname{argmax}_{\theta} \prod_{i=1}^m f_{\theta}(y_i \mid x_i)$$

- Typically, we consider a single sample \mathbf{x}, \mathbf{y} (i.e. the training set)
- The resulting objective (i.e. the big product) is sometimes called empirical risk

Problems arise when our sample is biased. E.g. because:

- We can collect data only under certain circumstances
- The dataset is the result of a selection process
- ...Or perhaps due to pure sampling noise



Handling Sampling Noise

So, let's recap

- Our issue is that the training sample is biased
- ...So that it is **not representative** of the true distribution

How can we deal with this problem?



Handling Sampling Noise

So, let's recap

- Our issue is that the training sample is biased
- ...So that it is **not representative** of the true distribution

How can we deal with this problem?

- A possible solution would be to **alter the training distribution**
- ...So that it **matches more closely** the test distribution

...And this is actually something we can do!

- E.g. we can use data augmentation, or subsampling
- ...Or we can use **sample weights**



Virtual Alterations to the Training Distribution

Let our training set consist of $\{(x_1, y_1), (x_2, y_2)\}$

The corresponding optimization problem would be:

$$\operatorname{argmax}_{\theta} f_{\theta}(y_1 \mid x_1) f_{\theta}(y_2 \mid x_2)$$

If sample #2 occurred twice in the training data, we would have

$$\operatorname{argmax}_{\theta} f_{\theta}(y_1 \mid x_1) f_{\theta}(y_2 \mid x_2)^2$$

Normalizing over the number of samples does not change the minima:

$$\operatorname{argmax}_{\theta} f_{\theta}(y_1 \mid x_1)^{\frac{1}{3}} f_{\theta}(y_2 \mid x_2)^{\frac{2}{3}}$$



Virtual Alterations to the Training Distribution

Let's generalize these considerations:

A general training problem based on Empirical Risk Minimization is the form:

$$\operatorname{argmax}_{\theta} \prod_{i=1}^m f_{\theta}(y_i \mid x_i)$$

We can virtually **alter the training distribution** via exponents:

$$\operatorname{argmax}_{\theta} \prod_{i=1}^m f_{\theta}(y_i \mid x_i)^{w_i}$$

- We can do this to make the training distribution **more representative**
- E.g. when we expect a discrepancy between the training and test distribution



Virtual Distribution and Sample Weights

When we switch to log-likelihood minimization

...The exponents become **sample weights**

$$\operatorname{argmin}_{\theta} - \sum_{i=1}^m w_i \log f_{\theta}(y_i \mid x_i)$$

We can **always** view the weights as the ratio of two probabilities:

$$w_i = \frac{p_i^*}{p_i}$$

- p_i is the sampling bias that we want to **cancel**
- p_i^* is the distribution we wish to **emulate**

This approach is known as **importance sampling**



Canceling Sampling Bias in Our Problem

Let's apply the approach to our skinwrapper example

We know there's an unwanted sampling bias for some modes of operation

- Let $m(x_i)$ be the mode of operation for the i -th sample
- Then we can estimate p_i as a frequency of occurrence:

$$p_i = \frac{1}{n} |\{k : m(x_k) = m(x_i), k = 1..n\}|$$

We don't want our anomaly detector to be sensitive to the mode

- So we can assume a uniform distribution for p_i^* :

$$p_i = \frac{1}{n}$$



Canceling Sampling Bias in Our Problem

By combining the two we get:

$$w_i = \frac{1}{|\{k : m(x_k) = m(x_i), k = 1..n\}|}$$

- I.e. the weight is just the inverse of the corresponding mode count

We can compute the weights by first obtaining inverse counts for all modes

```
In [23]: vcounts = data_b_tr['mode', 'first'].value_counts()  
mode_weight = 1 / vcounts
```

Then by associating the respective value to every sample:


```
In [24]: sample_weight = mode_weight[data_b_tr['mode', 'first']]
```



Training with Sample Weights

Now we can pass training weights to the training algorithm

```
In [25]: nn2 = util.build_nn_model(input_shape=len(data_b.columns), output_shape=len(data_b.columns),  
history = util.train_nn_model(nn2, data_b_s_tr, data_b_s_tr, loss='mse', validation_split=0.  
util.plot_training_history(history, figsize=figsize)
```




Final loss: 0.0002 (training)



Evaluation

Let's check the new reconstruction error

```
In [26]: pred2 = nn2.predict(data_b_s, verbose=0)
se2 = (data_b_s - pred2)**2
sse2 = pd.Series(index=data_b.index, data=np.sum(se2, axis=1))
util.plot_series(sse2, figsize=figsize)
```




At a first glance, the change is not dramatic



Evaluation

...But the individual error components are very different

```
In [27]: util.plot_dataframe(se2, figsize=figsize)
```



- Suspected anomalies in the middle sequence have almost disappeared
- ...And there is a much clearer plateau at the end of the signal



Applications of Importance Sampling



Despite its simplicity, importance sampling has many applications

Can you identify a few?



Class Rebalancing

The usual **class rebalancing trick** is a subcase of importance sampling

In this situation, we assume that some classes are over/under sampled

- Therefore, we estimate p_i using the class frequency
- We make a neutral (uniform) assumption on p_i^*
- ...And we define the sample weights for (x_i, y_i) as:

$$w_i = \frac{1}{n} \frac{n}{|\{k : y_k = y_i, k = 1..n\}|}$$

Watch out during evaluation!

- Evaluating via (e.g.) accuracy on the unmodified test set **might be a mistake**
- ...Since the weights alter the training distribution

Use a **cost model** instead, or just a confusion matrix



Removing Sampling Bias based on Continuous Attribute

The p_i and p_i^* values can be probability **densities**

...Meaning we can remove sampling bias over **continuous attributes**, e.g.:

- Continuous control variables (position, speed, etc.) in industrial machines
- Income or age in socio-economic applications
- Number of reviews in online rating systems

In this case:

We can first apply any **density estimation** approach

- The discrete attribute/class case is the same (we just use a histogram)

Then, it's a good idea to apply some **clipping**, i.e. $p_i = \max(l, \min(u, f(x_i, y_i)))$

- Densities can be very high/low, causing numerical instability



Removing Sampling Bias due to External Attributes

It is possible to remove sampling bias due to an "external" process

Consider an organ transplant program

- Candidate recipients are described by attribute \mathbf{x}_i and wait in a queue
- ...from which they may be selected ($y_i = 1$) or not ($y_i = 0$) for surgery
- ...Surgery may then have a positive ($z_i = 1$) or negative ($z_i = 0$) outcome

Say we want to improve the outcome estimation using ML

...And possibly use to adjust the selection criterion

- The historical data will be **subject to bias** due to existing criteria
- ...But if we can estimate the **current selection probability** $P(Y | X)$
- ...We can use it as p_i for mitigating the bias!

Any classifier with probabilistic output can be used on this purpose



Sample-specific Variance

With an **MSE loss**, sample weights have also an alternative interpretation

In this case we have proved the training problem is equivalent to:

$$\operatorname{argmin}_{\theta} - \sum_{i=1}^m \log k \exp\left(-\frac{1}{2}(y_i - h_{\theta}(x_i))^2\right)$$

- We have simply replaced the generic PDF with a Normal one
- We have $k = 1/\sqrt{2\pi}$ to simplify the notation

Let's now introduce sample weights, in the form as $1/\hat{\sigma}_i^2$

By doing so we get:

$$\operatorname{argmin}_{\theta} - \sum_{i=1}^m \frac{1}{\sigma_i^2} \log k \exp\left(-\frac{1}{2}(y_i - h_{\theta}(x_i))^2\right)$$



Sample-specific Variance

Which can be rewritten as:

$$\operatorname{argmin}_{\theta} - \sum_{i=1}^m \log k \exp \left(-\frac{1}{2} \left(\frac{y_i - h_{\theta}(x_i)}{\sigma_i} \right)^2 \right)$$

- This means that sample weights with an MSE loss
- ...Can be interpreted as **inverse sample variances**



Sample-specific Variance

Which can be rewritten as:

$$\operatorname{argmin}_{\theta} - \sum_{i=1}^m \log k \exp \left(-\frac{1}{2} \left(\frac{y_i - h_{\theta}(x_i)}{\sigma_i} \right)^2 \right)$$

- This means that sample weights with an MSE loss
- ...Can be interpreted as **inverse sample variances**

This gives us a way to account for non-uniform measurement errors

- If we know that there is a measurement error with stdev σ_i on example i
- ...We can account for that by using $1/\sigma_i^2$ as a weight

The result is analogous to using a separate variance model



Stochastic Differentiation in Reinforcement Learning

Importance sampling finds applications also in **Reinforcement Learning**

While the goal of **statistical ML** is usually maximize a likelihood, e.g.:

$$\operatorname{argmax}_{\theta} \mathbb{E}_{x, y \sim P} [f_{\theta}(y \mid x)]$$

...The goal of RL is to **learn how to optimize** a reward, e.g.:

$$\operatorname{argmax}_{\theta} \mathbb{E}_{x \sim P} [f(x, \pi_{\theta}(x))]$$

Where the presented formulation focuses on **a single step** (for simplicity)

- x represents an observable **state**
- $\pi_{\theta} : x \mapsto a$ is a parameterized policy outputting an **action**
- $f : x, a \mapsto r$ is a **reward function**



Stochastic Differentiation in Reinforcement Learning

In typical RL settings, the reward function is **non-differentiable**

- In AlphaGo Zero, the ultimate reward is winning a game of Go
- For OpenAI Five the goal is winning a game of Dota 2
- In this research the goal is for a robot not to fall

If we still want to use a gradient method, we need to overcome this issue

- One way is approximating f via a **differentiable critic** (e.g. a NN)
- ...Another is using a **stochastic policy**

In the latter case, π_θ defines a probability distribution $\pi_\theta(a \mid x)$

- Given a state x , we might obtain different actions a
- ...Usually according to a Normal distribution (with fixed σ)



Stochastic Differentiation in Reinforcement Learning

With a stochastic policy, the training problem becomes:

$$\operatorname{argmax}_{\theta} \mathbb{E}_{x \sim P, a \sim \pi_{\theta}(a|x)} [f(x, a)]$$

- The semantic is not the same as the original, but the goal is similar
- The problem contains now a **double expectation**

We could try to use a Monte Carlo approach with both

- There are well established techniques for sampling \mathbf{x}
- ...And we could sample actions $\{a_k\}_{k=1}^m$ directly from $\pi_{\theta}(a \mid \mathbf{x})$, obtaining:

$$\mathbb{E}_{a \sim \pi_{\theta}(a|x)} [f(x, a)] \simeq \frac{1}{m} \sum_{k=1}^m f(x, a_k)$$



...But unfortunately this expression is again non-differentiable

Stochastic Differentiation in Reinforcement Learning

It is possible to circumvent the issue via importance sampling

We sample the actions **uniformly at random**, but then we alter their distribution

- All p_i are identical, due to the uniform assumption
- The p_i^* are given by the policy itself, leading to:

$$\mathbb{E}_{a \sim \pi_{\theta}(a|x)} [f(x, a)] \simeq \frac{1}{m} \sum_{k=1}^m \pi_{\theta}(a_k | x) f(x, a_k)$$

- While the $f(x, a_k)$ is still just a constant
- ...The probability $\pi_{\theta}(a_k | x)$ is now **differentiable in θ**

Intuitively: we train to increase the probability of good actions



Stochastic Differentiation in Reinforcement Learning

This differentiation trick via importance sampling is a bit crude

- Uniform sampling might generate actions with very low probability
- ...Leading to noisy estimates and numerical issues

In practice, it's not a good idea to use it directly

...But it is the basis for some famous RL methods!

- It is used to derive the original REINFORCE algorithm
- It is central to the TRPO method
- ...And to the state-of-the-art Proximal Policy Optimization method

