Power-State Variance in One WGPU Vector-Search Kernel: A Low-Cost Case Study with Qenlo

Akshat Singh Kushwaha
akshatsingh14372@outlook.com

Abstract. GPUs lower their clocks under light load, which is why careful kernel benchmarks lock clocks before timing. We measure what this does to a comparison between two GPU paths of one exact filtered vector-search engine, Qenlo, that return identical top-k results. A *light* path does device work proportional to the E eligible rows; a deliberately naive *heavy* path scans all N rows and keeps the GPU at boost. Across fresh processes on an RTX 4050 Laptop GPU, RTX 4090s (one archived host and five cloud pods) and an H100, the heavy kernel's device time varied by at most 1% between processes on one machine and 7% across the five pods. The light kernel's varied up to $4.2\times$ on the laptop and $4.6\times$ across the pods, including at $E = 10{,}000$, where the light path is faster than our CPU scan. Telemetry shows the driver running the light path at low clocks. On the laptop, in an experiment whose protocol was committed before its data, locking the clocks removed the variation ($2.8\times$ to $1.00\times$ across blocks) and a low lock reproduced the slow mode. Clocks could not be locked on the cloud hosts. There, a separate light GPU load made slow light-kernel runs rarer on all three GPU types, but it also loaded the host and its planned end-to-end prediction failed, so the cross-host account is weaker. The magnitudes belong to this engine and these machines. The study ran on one laptop and about US$6 of cloud time; protocols, raw data and telemetry are released.

1 Introduction

GPUs drop to lower clocks when they are lightly loaded. Kernel benchmarking practice knows this, and locks clocks or warms the device up before timing (Oliaro et al., 2026; Chu and Li, 2026). Application-level benchmarks usually do neither. They compare implementations at the driver's default clocks, and the implementations being compared can load the GPU very differently. A work-efficient kernel that leaves the GPU mostly idle can be clocked down; a wasteful one that keeps it busy is not. The measured gap between them then partly reflects the power state each one induced. We report one case of this and test it.

The case comes from Qenlo, an embedded vector store with two GPU paths for exact filtered top-k search that return identical results. A *light* path uploads the list of E eligible rows and does device work proportional to E. A *heavy* path evaluates the filter inside the kernel and scans all N rows; its selection kernel makes k passes over all N scores in one workgroup. The heavy path is not a competitive baseline. We keep it because it computes the same answer while holding the GPU at boost, which makes it a load contrast and a negative control. At $E = 10{,}000$ eligible rows out of $N = 100{,}000$, the light path is faster than both the heavy path and our CPU scan on the laptop and the RTX 4090 pods (Appendix Table 7), so this is a regime where an application would choose it. There its kernel time varied $1.4\times$ between fresh processes on the laptop and $4.6\times$ across five RTX 4090 cloud pods, while the heavy kernel's varied by at most 1% on one machine and 7% across the pods (Section 4). At smaller E the CPU wins and the light path's spread matters less in practice, although it is as large.

The direct test is to lock the clock. That needs administrator rights, which we had on the laptop. There, in an experiment whose protocol and predictions were committed to version control before its first run (Section 7), locking the SM and memory clocks at boost removed the light kernel's spread across processes, and locking them at the light path's observed low state reproduced its slow mode. One of its five predictions failed: locked at boost, the light kernel took 32–50% less time than the best unlocked median, outside the 15% we had predicted.

Inside the cloud containers clocks could not be locked, so there we tried to raise the clock instead. A separate process, the *heater*, keeps the GPU lightly busy. If the variation came only from contention, the heater could only slow every path down; if it came from power state, it should speed up work that was running below its attainable clock. At the device level that is what we saw on all three GPU types: the share of light-kernel runs more than $1.5\times$ slower than their best fell from 52% to 0% on the laptop, 28% to 16% on the RTX 4090 pods and 11% to 0% on the H100, and the heavy kernel never got faster (Figure 1c, Section 6). The heater is a crude instrument. It also uses host CPU, it slowed host-side work by 40–48% on the H100 pod, and the end-to-end speed-up we had planned to see did not appear on any GPU. Its protocols were written before the data but committed only afterwards (Appendix A). We treat the cross-host account as supported by telemetry and the heater, not as tested.

Why a small engine. Everything here ran on one laptop plus about US$6 of rented GPU time. That was possible because Qenlo is small enough to instrument end to end: device timestamps on every call, a fresh process per measurement, continuous clock telemetry, and two code paths with identical outputs that load the GPU differently. With those in place,




Figure 1: **The light kernel's speed tracks the GPU clock.** (a) Device time of the top-k kernel for one query cell ($N = 100$K, $E = 10{,}000$, $D = 384$, $k = 10$, batch 1), one point per fresh process. At this E the light path is faster than the CPU scan. The heavy path does $10\times$ more work and reproduces within 1% on a machine and 7% across the five RTX 4090 pods; the light path varies up to $1.5\times$ on a machine and $4.6\times$ across the pods. (b) SM clock sampled every 50 ms during one laptop process per condition ($E = 10{,}000$), including data loading. The heavy path stays at boost and the light path drops to about 500 MHz; a separate light GPU load (the *heater*) raises it. (c) Light (squares) and heavy (triangles) device time relative to the best value observed for that GPU and E, heater off (hollow) and on (filled), one point per block and E. With the heater, the light kernel's slow runs become rarer on every GPU and the heavy kernel never gets faster.

finding the effect, testing it by locking clocks and releasing every sample took days. We think small, fully instrumented engines are a cheap way to do this kind of systems measurement, and we offer Qenlo as one.

Contributions.

- **An observation in one engine.** For identical results, Qenlo's work-efficient GPU path is the less reproducible one. Its kernel time varies up to $4.2\times$ between fresh processes on one machine and $4.6\times$ across five same-model cloud hosts, while the heavy path's varies by at most 1% on one machine and 7% across those hosts (Section 4).
- **A locked-clock test on one laptop.** With its protocol committed before the data, locking the clocks removed the light kernel's variation and a low lock reproduced the slow mode (Section 7).
- **Weaker evidence across hosts.** Telemetry and the heater are consistent with the same account on RTX 4090 and H100 hosts; the planned end-to-end prediction failed, and we report it as failed (Sections 5–6).
- **Reporting rules and data.** We give rules for benchmarking latency-bound GPU work (Section 8) and release protocols, raw samples and telemetry.

2 The query paths and why their load differs

We study Qenlo, an embedded Rust vector store that answers exact (exhaustive) filtered cosine top-k queries over a canonical collection of N normalized FP32 vectors of dimension D with per-row metadata. A predicate selects E eligible rows; the query returns the k eligible rows nearest to the query. Every execution path below returns the same result set (all runs pass an FP64-oracle recall@10 gate of 0.99; observed recall is 1.0 except where noted), so the choice of path affects only latency.

CPU scan. A single-threaded AVX2 scan over the eligible rows. For $E \leq 4{,}096$ it scores in FP32 and rescores boundary candidates in FP64; above that it accumulates in FP64 throughout. The kernel switch is part of the implementation and applies equally to every condition we compare.

GPU paths (WGPU/WGSL). Vectors, identifiers and metadata are resident on the device. Each query uploads the query vector and an eligibility description, runs a scoring kernel and a top-k selection kernel, and blocks on a readback of k candidates, which the host merges. The paths differ only in how eligibility reaches the device:

- *Compact rows (the light path).* The host materializes the sorted list of E eligible row ids and uploads $4E$ bytes.

Scoring and selection touch only those E rows, so device work is proportional to E.

- *Shader predicate (the heavy path).* The host uploads per-row liveness ($4N$ bytes) and the predicate bounds; the kernels run over all N rows and evaluate the predicate in the shader. Selection scans all N scores k times in one workgroup, so device work is proportional to N regardless of E.

The heavy path therefore does up to N/E times more device work for the same answer (1,000× at $E = 100$, $N = 10^5$). This selection kernel is deliberately simple and far from the best available; a tuned top-k would narrow the gap. We use the heavy path as a load contrast and a negative control, not as a baseline: the two paths put very different loads on the GPU while computing identical results.

Timing boundary. Latency is measured from the host search call to host-visible ordered results, including eligibility preparation, upload, dispatch, synchronization, readback and merge. Device-side scoring and selection times come from GPU timestamp queries in the same calls; they overlap host phases and are not additive. Host row materialization is timed separately on the CPU.

3 Experimental design

Workload. 100,000 AG News sentence embeddings (all-MiniLM-L12-v2, $D = 384$; Nielsen, 2023) form the corpus; 5,000 disjoint held-out embeddings are the queries. Synthetic unique timestamps are attached to rows and a timestamp range selects exactly $E \in \{100, 1\text{K}, 3\text{K}, 10\text{K}, 30\text{K}\}$ eligible rows (0.1%–30%). Batch size is 1 and $k = 10$, the regime of an interactive retrieval or agent-memory lookup.

Unit of replication. Every condition runs in a fresh process: dataset load, 200 warm-up queries, then three passes over the 5,000 queries (15,000 timed calls). The per-process statistic is the lower median of the three per-pass percentiles. A *block* runs every condition once in a shuffled order; blocks are the independent replicates. Paired effects are computed within a block and summarized by the median over blocks of per-block log-ratios, with 95% percentile-bootstrap intervals over blocks (20,000 draws). With three to five blocks these intervals are coarse and we read them descriptively. The 15,000 calls within a process are repeated measurements and are never treated as independent.

Telemetry. `nvidia-smi` samples SM clock, memory clock, performance state (P-state), utilization and power every 50 ms for the whole life of each process. `nvidia-smi` itself observes the GPU only part of the time (Yang et al., 2023), so short kernels can fall between samples; we use the clocks to identify states, not to time kernels.

Intervention: a GPU heater. To move the GPU's power state without touching the measured process, a separate process (the *heater*) repeatedly dispatches a small compute kernel (64 workgroups × 256 threads, 500 dependent FMAs each), waits for it, and sleeps 1 ms. Its own reported utilization is a few percent. On the GPU the heater can only compete with the measured process, so a speed-up it produces suggests that the measured process was held back by its power state and not by a lack of capacity. The heavy path, which already holds a high P-state, is the negative control. If contention were the only effect, the heater would slow both paths; if power state matters, it should speed up the light path and slow only the heavy one. The heater also uses host CPU, so it is not a clean GPU-only perturbation; its host cost shows up in end-to-end latency much more than in device timestamps (Section 6).

Hosts and protocols. (i) A Windows 11 laptop (Intel i5-13420H, RTX 4050 Laptop GPU, driver 616.56, Vulkan, AC power, "Balanced" power plan). It uses hybrid graphics (Optimus); the display is driven by the Intel iGPU. (ii) RTX 4090s on Linux with Vulkan: *host A*, an archive of five blocks on one host from September 24, and *pods B*, five pods on five different hosts from September 25 with one block each. The pods use two driver branches (570.195 and 580.126–580.173). Because each pod ran one block, host and process variance are confounded on the pods. (iii) One H100 SXM pod (Linux, Vulkan) running a reduced design. A pod whose host CPU was about 14× slower than the others was replaced before any of its results were inspected (Appendix A). The laptop, pod and H100 experiments (D1, D1R, H100) follow written protocols with predictions, but those were committed to version control only after the data; we call them planned analyses. The locked-clock protocol was committed and hashed before its first run. Clock locking (`nvidia-smi -lgc`) requires administrator rights; it was available on the laptop (Section 7) and refused inside the cloud containers.

4 The heavy kernel reproduces; the light kernel does not

Table 1 reports the median device time of the top-k selection kernel per fresh process, for both paths at three selectivities on four GPUs. We use device timestamps rather than end-to-end latency because they isolate the GPU from host-side effects; Section 6 returns to end-to-end latency.

The heavy kernel reproduces within 1% between processes on each single machine (the laptop, 4090 host A and the H100), and within 7% across the five pod hosts, which span two driver branches (570 and 580). The light kernel does not. Its spread between processes reaches 2.6× on 4090 host A, 4.2× on the laptop and 4.3–4.6× across the five 4090 pods. The per-process values look bimodal (Figure 1a), so a median of three to five processes mostly reports which mode most of them landed in. Host A's and the pods' ranges overlap at every E; we read the difference between their medians as a

Table 1: Top-k kernel device time per query (ms): median over fresh heater-off processes (min–max), and max/min across processes. Heavy = shader predicate over all $N = 100$K rows; light = compact eligible rows. RTX 4090 host A is the retained September 24 archive (one host, 5 blocks); pods B are five September 25 pods on five different hosts, one block each. Identical binary source, dataset bytes and queries.

E	GPU	n	Heavy (ms)	max/min	Light (ms)	max/min
1,000	RTX 4050 Laptop	5	0.950 (0.949–0.954)	1.01	0.030 (0.030–0.030)	1.00
1,000	RTX 4090 host A	5	0.711 (0.711–0.711)	1.00	0.053 (0.051–0.065)	1.27
1,000	RTX 4090 pods B	5	0.681 (0.650–0.695)	1.07	0.028 (0.027–0.056)	2.08
1,000	H100 SXM	3	0.987 (0.982–0.987)	1.00	0.039 (0.039–0.039)	1.02
3,000	RTX 4050 Laptop	5	0.952 (0.951–0.956)	1.01	0.106 (0.055–0.230)	4.16
3,000	RTX 4090 host A	5	0.711 (0.711–0.711)	1.00	0.210 (0.098–0.251)	2.56
3,000	RTX 4090 pods B	5	0.685 (0.652–0.700)	1.07	0.055 (0.050–0.216)	4.30
3,000	H100 SXM	3	0.988 (0.988–0.988)	1.00	0.094 (0.088–0.104)	1.18
10,000	RTX 4050 Laptop	5	0.941 (0.940–0.941)	1.00	0.461 (0.425–0.595)	1.40
10,000	RTX 4090 host A	5	0.703 (0.703–0.703)	1.00	0.440 (0.337–0.512)	1.52
10,000	RTX 4090 pods B	5	0.673 (0.643–0.687)	1.07	0.142 (0.128–0.589)	4.61
10,000	H100 SXM	3	0.977 (0.972–0.977)	1.01	0.205 (0.188–0.206)	1.10

difference in how often each landed in the slow mode, not as a stable property of the host. The light path is faster than the heavy path in every cell.

The retained archive shows the same pattern within one host over time. Across ten identical blocks, the light path's selection time spans $2.44\times$ and correlates with the GPU clock recorded at process end (Spearman $\rho = -0.83$, $p = 0.003$). The heavy kernels in the same archive vary by at most 0.1% wherever their clock was at boost.

5 Which power state each path gets

Table 2 reports the median SM and memory clocks while the GPU was active (samples with non-zero utilization) for each path. On every GPU the heavy path holds boost SM clocks: 2,670–2,820 MHz on the consumer GPUs and 1,980 MHz on the H100. The light path runs lower. At $E = 10{,}000$ the driver also cuts the memory clock to 810 MHz on the laptop (from 8,201 MHz; performance state P5) and on the 4090 pods (from 10,501 MHz). Here both clocks fall together, so telemetry alone cannot say which of them slows the kernels. On the H100 the light path's SM clock falls from 1,605 to 645 MHz between $E = 1{,}000$ and $10{,}000$.

The governor's inputs are undocumented, and we do not try to model them; we report what we observe. The heavy path spends 52–84% of each call inside its two kernels and always holds boost. The light path spends 13–43% and does not. Within the light path, however, the clock *falls* as E grows on the laptop and the H100, even though per-call device work grows. A simple busy-fraction account does not explain this. The busy fraction is also endogenous, because a lower clock lengthens the kernels that define it. The NVIDIA policy is undocumented (Spaan et al., 2026), and our claims concern its observable consequences.

6 Raising the load where clocks could not be locked

Each experiment ran every condition (engine $\times$ E $\times$ heater on/off) once per block, in shuffled order and fresh processes (Section 3). Table 3 gives the most direct test. For every block and E, it divides each path's device time by the best value observed for that GPU and E in either arm. Both arms share the same reference, so a heater-off run that happened to be slow cannot flatter the heater through regression to the mean.

Device time: the planned interaction appears on every GPU. Without the heater, the light kernel runs a median 1.15–$1.59\times$ slower than its best, with a tail reaching $3.3\times$. With the heater, its median is 1.00–1.07; runs more than $1.5\times$ slow disappear on the laptop and the H100 and fall from 28% to 16% on the 4090 pods. The heavy kernel has no tail to remove. With the heater it becomes uniformly slower on the laptop ($1.19\times$) and the H100 ($1.36\times$), the cost of sharing the GPU, and stays unchanged on the 4090 pods. Paired ratios with block-bootstrap intervals are in Appendix Table 6.

End to end: small and host-dependent. The heater also competes for GPU submission and readback, and on some hosts for the CPU: on the H100 pod it slowed host row materialization by 40–48%. End to end, the light path's median call latency with the heater was 0.94–0.96 of its heater-off value on the 4090 pods at $E = 3{,}000$–$10{,}000$ (1.07 at 30,000) and 0.95–0.97 on the laptop at $E \geq 3{,}000$, with intervals that mostly include 1. On the H100 it was 1.10–1.24. Heavy calls were 6–9% slower on the consumer GPUs and 25–27% slower on the H100. Under the same added load the light path fared better than the heavy path in 10 of 13 cells, but whether it gained or lost overall depends on how much contention the host adds. The $1.9\times$ end-to-end speed-up in our laptop pilot

Table 2: Median SM / memory clock (MHz) while the GPU is active, pooled over blocks. Clocks are sampled by `nvidia-smi` every 50 ms, which is itself a partial sampler (Yang et al., 2023).

GPU	E	Heavy path	Light path	Light path + heater
RTX 4050 Laptop	1,000	2670 / 8201	2130 / 8201	2130 / 8201
RTX 4050 Laptop	3,000	2670 / 7001	1080 / 7001	1912 / 8201
RTX 4050 Laptop	10,000	2670 / 8201	585 / 810	1215 / 8201
RTX 4090 pods B	1,000	2820 / 10501	2520 / 10501	2550 / 10501
RTX 4090 pods B	3,000	2820 / 10501	2505 / 10501	2550 / 10501
RTX 4090 pods B	10,000	2820 / 10501	2235 / 810	2520 / 10501
H100 SXM	1,000	1980 / 2619	1605 / 2619	1980 / 2619
H100 SXM	3,000	1980 / 2619	1275 / 2619	1980 / 2619
H100 SXM	10,000	1980 / 2619	645 / 2619	1980 / 2619

Table 3: Device time relative to the best observed for that GPU and E: median, 90th percentile, and share of runs more than $1.5\times$ slower than best, heater off versus on. One observation per block and E.

			Heater off			Heater on		
Path	GPU	n	median	p90	$> 1.5\times$	median	p90	$> 1.5\times$
Light	RTX 4050 Laptop	25	1.59	2.61	52%	1.07	1.27	0%
Light	RTX 4090 pods	25	1.15	3.29	28%	1.06	1.59	16%
Light	H100 SXM	9	1.24	1.41	11%	1.00	1.01	0%
Heavy	RTX 4050 Laptop	25	1.00	1.00	0%	1.19	1.20	0%
Heavy	RTX 4090 pods	25	1.05	1.07	0%	1.05	1.07	0%
Heavy	H100 SXM	9	1.00	1.01	0%	1.36	1.37	0%

did not replicate reliably across blocks.

Scorecard against the planned predictions (Appendix Table 5).

- P1 predicted a light-path end-to-end speed-up of at least 10% at $E \leq 3{,}000$. It *failed* on every GPU.
- P2 predicted no heavy-path speed-up. It held in every cell.
- P3 predicted that the light path's ratio would fall below the heavy path's. It held in every cell for device time and in 10 of 13 cells end to end.
- P4 predicted that light device time falls while host materialization stays within 10%. It held in 6 of 13 cells and failed where the heater also slowed the host.

The device-level predictions held. P1, the end-to-end prediction and the one that mattered most for an application, did not.

7 Locking the clock

On the laptop we ran the direct test. Each condition ran in a fresh process with the driver's default clocks (U), with SM and memory locked at the heavy path's boost (2,670 and 8,001 MHz; Lhi), or locked at the light path's low state (585 and 810 MHz; Llo). The heater was crossed with U and Lhi. The design was 6 cells $\times$ 5 conditions $\times$ 5 blocks $=$ 150 processes, with its protocol committed and hashed before the first run (Appendix A). No run was excluded, the observed SM clock matched the lock in every locked run, and the GPU never exceeded 50 °C.

The variation disappears at fixed clocks. Unlocked, the light kernel's device time varied by $2.84\times$, $2.11\times$ and $1.51\times$ across blocks at $E = 1{,}000$, $3{,}000$ and $10{,}000$. Locked at boost, it varied by $1.00\times$ in all three cells (prediction K1, ≤ 1.15). The heater had cut unlocked light time to 0.57, 0.37 and 0.40 of its heater-off value; with the clock locked it changed nothing (ratio 1.00 in every cell; K4). The heavy kernel was already stable and unchanged by the lock (Lhi/U $= 1.000, 1.000, 1.002$; K5).

The low state alone reproduces the slow mode. Locked at 585/810 MHz, the light kernel at $E = 10{,}000$ took 0.444 ms, within 4% of the 0.461 ms that D1 measured on the same laptop without locking (K3). The same lock slowed the heavy kernel by $3.8\times$ (0.95 to 3.6 ms), so the slow state is costly for both paths. The driver put the light path there and kept the heavy path out of it.

One prediction failed. K2 predicted that locking high would match the best unlocked speed to within 15%. Locked-high light time was 0.50–0.68 of the best unlocked median (0.63–0.81 of the best single unlocked run), outside that tol-

Table 4: Locked-clock experiment on the laptop: median top-k device time per query (ms) over five blocks, and max/min across blocks. Light = compact rows, heavy = shader predicate; heater off. U = unlocked, Lhi = locked at 2,670/8,001 MHz, Llo = locked at 585/810 MHz.

	Light						Heavy, Lhi	
	U		Lhi		Llo			
E	ms	max/min	ms	max/min	ms	max/min	ms	max/min
1,000	0.069	2.84	0.024	1.00	0.096	1.00	0.948	1.00
3,000	0.176	2.11	0.045	1.00	0.177	1.00	0.951	1.00
10,000	0.567	1.51	0.113	1.00	0.444	1.00	0.941	1.00

erance, so K2 fails. After the fact, we note that the lock beat every unlocked configuration, including unlocked with the heater. That suggests the driver's best unlocked state for light work is still below boost, but we did not predict it.

What this does and does not show. On this laptop, fixing the clocks removes the light kernel's process-to-process variation and sets its level, so the clock the driver chooses accounts for the variation we measured. Locking fixes the SM and memory clocks together, and we did not vary them separately. We could not repeat the test on the cloud hosts, so the cross-host spread there is attributed to power state by the heater and telemetry evidence only.

8 Consequences

Unlocked-clock benchmarks can understate the efficient implementation. On the laptop, the light kernel at fixed boost ran 2.9–5.0× faster than with default clocks, so the unlocked number understates it. A benchmark that compares a work-efficient GPU kernel with a less efficient one at low load runs the efficient one at a lower clock. Here the light path won every cell regardless. But at $E = 10{,}000$ its device-time advantage over the heavy path is $1.6\times$ on 4090 host A, $2.0\times$ on the laptop, $4.7\times$ on the 4090 pods and $4.8\times$ on the H100 (medians of three to five processes, from Table 1), for identical code. On the laptop with both paths locked at boost it is $8.3\times$ (Table 4). Optimizations that remove GPU work (tighter filtering, smaller kernels, early exit) can be measured at a discount the benchmark does not show, and the discount differs between machines.

Kernel-level results did not transfer between machines with the same GPU. On RTX 4090s (host A and the five pods), light-kernel times for the same cell at $E = 10{,}000$ ran from 0.128 to 0.589 ms across processes, a $4.6\times$ span. Any threshold or cost model calibrated on one of them, for example a CPU/GPU router, partly encodes that host's power behavior. The study that preceded this one fitted a scalar CPU/GPU routing threshold with zero errors on 31 development pairs. On a held-out suite it chose the slower route in 8 of 16 workloads, several of them within the process-to-process variation measured here (Appendix C). In our data the heater never changed a CPU/GPU winner (Appendix Table 7). We therefore do not claim that power state moves this system's crossover, only that it moves the margins a router is calibrated on.

Isolated benchmarks may misstate co-located latency. In deployment a retrieval kernel often shares the GPU with a model; our heater is a crude stand-in for that load. On an idle GPU the light path is exposed to deep power states; under load, to contention. The heavy path is exposed only to contention. Latency measured on an idle GPU is therefore a poor proxy for latency under co-location, and the error can differ between implementations. We did not test co-location with a real model.

What to report. For latency-bound GPU work:

(i) Replicate across fresh processes and report the spread between them; repetitions inside one process share its power state.

(ii) Log clocks and performance state continuously, not just before and after a run.

(iii) Report device-timestamp kernel time alongside end-to-end latency, to separate power-state effects from host effects.

(iv) Lock clocks where possible, and report results at the locked clock alongside the default. Where clocks cannot be locked, add a load-raising control such as the heater, together with a heavy negative control.

(v) When comparing implementations, state whether they ran in the same power state.

9 Related work

Power management versus latency. On servers, low-power states and slow frequency governors are known to inflate the latency of latency-critical services at low load (Meisner et al., 2011; Kanev et al., 2014), motivating latency-aware controllers (Lo et al., 2014; Kasture et al., 2015; Hsu et al., 2015; Chou et al., 2019). Mobile GPU governors mispredict bursty and concurrent work (Pathania et al., 2014; Lin et al., 2023; Zhang et al., 2025), and at low locked clocks desktop GPUs can drop into idle-like states (Adamek et al., 2021). GPU DVFS work for machine learning treats frequency as

a knob to *lower* for energy (Tang et al., 2019; You et al., 2023; Chung et al., 2024; Qiu et al., 2024; Stojkovic et al., 2025; Kakolyris et al., 2025; Maliakel et al., 2025; Spaan et al., 2026). We study the opposite case, in which the default policy under-clocks latency-bound work that the application would prefer to run fast. We have not found a report that this changes the measured margin between two implementations of the same GPU operation, or that an unrelated co-running GPU load speeds up a latency-bound GPU kernel.

Benchmark validity. Innocuous setup details bias measured speed-ups (Mytkowicz et al., 2009); variation across executions must be sampled and reported (Kalibera and Jones, 2013; Maricq et al., 2018). For GPUs, power management causes 8–22% variation across same-model devices under load (Sinha et al., 2022) and 1–14% in GEMM timings (Golden et al., 2025); kernel benchmarking practice therefore often locks clocks (Oliaro et al., 2026; Chu and Li, 2026), and `nvidia-smi` telemetry itself is sampled only part-time (Yang et al., 2023). The variation we measure is much larger (up to $4.6\times$ rather than tens of percent), and it makes the less efficient implementation look relatively better.

Filtered vector search and CPU/GPU placement. Filtered nearest-neighbor search is an active area (Gollapudi et al., 2023; Patel et al., 2024; Iff et al., 2026; Shi et al., 2025; Li et al., 2025; Amanbayev et al., 2026), including GPU systems (Johnson et al., 2021; Xi et al., 2025). Whether to run vector search on a GPU at all depends on data movement and batch size (Gregg and Hazelwood, 2011; Mageirakos et al., 2026), and cost-model-based CPU/GPU operator placement is known to be fragile (Breß et al., 2016). The choice between an eligible-id list and a full-width filter mirrors selection vectors versus bitmaps in vectorized databases (Ngom et al., 2021). We add that the measured margins between such alternatives can depend on the GPU's power state, which the alternatives themselves influence.

10 Limitations

One engine, one kernel pair. Both paths come from Qenlo, with a simple hand-written WGSL selection kernel, and the heavy path is deliberately naive. Tuned library kernels such as FAISS or cuVS may load the GPU differently and run in different states; testing them, and more hosts per GPU model, needs compute we did not have. We do not expect these magnitudes to carry over. *Clock locking on one machine.* Locking was possible only on the laptop and was refused in the cloud containers, so the cross-host account rests on telemetry and the heater, which also loads the host. The locked-clock test covers one GPU, one driver and one operating system. *Laptop platform.* The laptop uses hybrid graphics (Optimus): the display runs on the Intel iGPU and the RTX 4050 renders nothing else during the runs. It ran on AC power under the Windows "Balanced" plan; we did not test other plans. *Telemetry.* `nvidia-smi` samples every 50 ms and only part of the time (Yang et al., 2023); clocks are reported for active samples of a whole process, including warm-up. *Small n and confounding.* Five blocks on the laptop, five RTX 4090 pods with one block each on five different hosts, and three H100 blocks. On the pods, host and process variance cannot be separated, and with three to five blocks the bootstrap intervals are descriptive at best. The pods also span two driver branches. One pod was replaced before analysis because its host CPU was about $14\times$ slower on a single-threaded test; its partial block is archived but excluded. *Host coupling.* On the laptop and the H100 the heater also changed host-side timings, so end-to-end effects there cannot be attributed to the GPU clock alone. *API.* All runs use Vulkan through WGPU; CUDA runtimes may be managed differently. *Driver versions.* 616.56 (Windows) and 570.195–580.173 (Linux).

11 Conclusion

In Qenlo, the faster GPU path for a light query was also the one whose kernel time varied most between processes and machines, and the variation tracked the clock the driver chose. On the laptop, fixing the clock removed it. On the cloud hosts we could only raise the GPU's load, which made the light kernel's slow runs rarer at the device level but did not make calls faster end to end. The heavy path holds a high clock, so it looks more stable than it would at equal clocks, and its gap to the light path looks smaller. For benchmarks of light GPU work, we would record the power state, replicate across fresh processes, and report device time separately from end-to-end latency. A small engine with this much instrumentation should find similar effects in other kernels for little money, which is the use we have in mind for it.

Reproducibility

Each experiment's protocol and predictions were written before its data were collected, but only the locked-clock protocol was committed to version control before its data; the others were committed the same evening, after collection (Appendix A). Raw per-call samples, 50 ms telemetry, analysis scripts and the heater are in the repository: `research/data/raw/2026-09-25-dvfs-*`, `research/scripts/analyze_dvfs_d1.py`, `research/scripts/cross_host.py`, `research/scripts/pool_hosts.py` and `crates/qenlo/examples/gpu_heater.rs`. The scripts in `paper/v2/scripts/` regenerate all tables and figures. Cloud compute for the new runs cost about US$6.

References

Karel Adamek, Jan Novotny, Jeyarajan Thiyagalingam, and Wesley Armour. Efficiency near the edge: Increasing the energy efficiency of FFTs on GPUs for real-time edge computing. *IEEE Access*, 9:18167–18182, 2021. ISSN 2169-

3536. doi: 10.1109/access.2021.3053409. URL http://dx.doi.org/10.1109/ACCESS.2021.3053409.

Abylay Amanbayev, Brian Tsan, Tri Dang, and Florin Rusu. Filtered approximate nearest neighbor search in vector databases: System design and performance analysis. *arXiv preprint arXiv:2602.11443*, 2026. URL https://arxiv.org/abs/2602.11443.

Sebastian Breß, Henning Funke, and Jens Teubner. Robust query processing in co-processor-accelerated databases. In *Proceedings of the 2016 International Conference on Management of Data*, SIGMOD/PODS'16, pages 1891–1906. ACM, June 2016. doi: 10.1145/2882903.2882936. URL http://dx.doi.org/10.1145/2882903.2882936.

Chih-Hsun Chou, Laxmi N. Bhuyan, and Daniel Wong. μDPM: Dynamic power management for the microsecond era. In *2019 IEEE International Symposium on High Performance Computer Architecture (HPCA)*, pages 120–132. IEEE, February 2019. doi: 10.1109/hpca.2019.00032. URL http://dx.doi.org/10.1109/HPCA.2019.00032.

Logan Chu and Dong Li. Hardware-attributed operator profiling for PyTorch, 2026. URL https://arxiv.org/abs/2609.11938.

Jae-Won Chung, Yile Gu, Insu Jang, Luoxi Meng, Nikhil Bansal, and Mosharaf Chowdhury. Reducing energy bloat in large model training. In *Proceedings of the ACM SIGOPS 30th Symposium on Operating Systems Principles*, SOSP '24, pages 144–159. ACM, November 2024. doi: 10.1145/3694715.3695970. URL http://dx.doi.org/10.1145/3694715.3695970.

Alicia Golden, Michael Kuchnik, Samuel Hsia, Zachary DeVito, Gu-Yeon Wei, David Brooks, and Carole-Jean Wu. PRISM: Probabilistic runtime insights and scalable performance modeling for large-scale distributed training, 2025. URL https://arxiv.org/abs/2510.15596.

Siddharth Gollapudi, Neel Karia, Varun Sivashankar, Ravishankar Krishnaswamy, Nikit Begwani, Swapnil Raz, Yiyong Lin, Yin Zhang, Neelam Mahapatro, Premkumar Srinivasan, Amit Singh, and Harsha Vardhan Simhadri. Filtered-DiskANN: Graph algorithms for approximate nearest neighbor search with filters. In *Proceedings of the ACM Web Conference 2023*, pages 3406–3416. Association for Computing Machinery, 2023. doi: 10.1145/3543507.3583552. URL https://doi.org/10.1145/3543507.3583552.

Chris Gregg and Kim Hazelwood. Where is the data? why you cannot debate CPU vs. GPU performance without the answer. In *(IEEE ISPASS) IEEE INTERNATIONAL SYMPOSIUM ON PERFORMANCE ANALYSIS OF SYSTEMS AND SOFTWARE*, pages 134–144. IEEE, April 2011. doi: 10.1109/ispass.2011.5762730. URL http://dx.doi.org/10.1109/ISPASS.2011.5762730.

Chang-Hong Hsu, Yunqi Zhang, Michael A. Laurenzano, David Meisner, Thomas Wenisch, Jason Mars, Lingjia Tang, and Ronald G. Dreslinski. Adrenaline: Pinpointing and reining in tail queries with quick voltage boosting. In *2015 IEEE 21st International Symposium on High Performance Computer Architecture (HPCA)*, pages 271–282. IEEE, February 2015. doi: 10.1109/hpca.2015.7056039. URL http://dx.doi.org/10.1109/HPCA.2015.7056039.

Patrick Iff, Paul Brügger, Marcin Chrapek, David Kochergin, Maciej Besta, and Torsten Hoefler. Benchmarking filtered approximate nearest neighbor search algorithms on transformer-based embedding vectors. In *Proceedings of the 49th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 610–622, 2026. doi: 10.1145/3805712.3809731. URL https://doi.org/10.1145/3805712.3809731.

Jeff Johnson, Matthijs Douze, and Hervé Jégou. Billion-scale similarity search with GPUs. *IEEE Transactions on Big Data*, 7(3):535–547, 2021. doi: 10.1109/TBDATA.2019.2921572. URL https://doi.org/10.1109/TBDATA.2019.2921572.

Andreas Kosmas Kakolyris, Dimosthenis Masouros, Petros Vavaroutsos, Sotirios Xydis, and Dimitrios Soudris. throttLL'eM: Predictive GPU throttling for energy efficient LLM inference serving. In *2025 IEEE International Symposium on High Performance Computer Architecture (HPCA)*, pages 1363–1378. IEEE, March 2025. doi: 10.1109/hpca61900.2025.00103. URL http://dx.doi.org/10.1109/HPCA61900.2025.00103.

Tomas Kalibera and Richard Jones. Rigorous benchmarking in reasonable time. In *Proceedings of the 2013 international symposium on memory management*, ISMM '13, pages 63–74. ACM, June 2013. doi: 10.1145/2464157.2464160. URL http://dx.doi.org/10.1145/2464157.2464160.

Svilen Kanev, Kim Hazelwood, Gu-Yeon Wei, and David Brooks. Tradeoffs between power management and tail latency in warehouse-scale applications. In *2014 IEEE International Symposium on Workload Characterization (IISWC)*, pages 31–40. IEEE, October 2014. doi: 10.1109/iiswc.2014.6983037. URL http://dx.doi.org/10.1109/IISWC.2014.6983037.

Harshad Kasture, Davide B. Bartolini, Nathan Beckmann, and Daniel Sanchez. Rubik: fast analytical power management for latency-critical systems. In *Proceedings of the 48th International Symposium on Microarchitecture*, MICRO-48, pages 598–610. ACM, December 2015. doi: 10.1145/2830772.2830797. URL http://dx.doi.org/10.1145/2830772.2830797.

Mocheng Li, Xiao Yan, Baotong Lu, Yue Zhang, James Cheng, and Chenhao Ma. Attribute filtering in approxi-

mate nearest neighbor search: An in-depth experimental study. *Proceedings of the ACM on Management of Data*, 3(6):298:1–298:26, 2025. doi: 10.1145/3769763. URL https://doi.org/10.1145/3769763.

Chengdong Lin, Kun Wang, Zhenjiang Li, and Yu Pu. A workload-aware DVFS robust to concurrent tasks for mobile devices. In *Proceedings of the 29th Annual International Conference on Mobile Computing and Networking*, MobiCom '23, pages 1–16. ACM, July 2023. doi: 10.1145/3570361.3592524. URL http://dx.doi.org/10.1145/3570361.3592524.

David Lo, Liqun Cheng, Rama Govindaraju, Luiz Andre Barroso, and Christos Kozyrakis. Towards energy proportionality for large-scale latency-critical workloads. In *2014 ACM/IEEE 41st International Symposium on Computer Architecture (ISCA)*, pages 301–312. IEEE, June 2014. doi: 10.1109/isca.2014.6853237. URL http://dx.doi.org/10.1109/ISCA.2014.6853237.

Vasilis Mageirakos, Joel André, Marko Kabić, Bowen Wu, Yannis Chronis, and Gustavo Alonso. To GPU or not to GPU: Vector search in relational engines, 2026. URL https://arxiv.org/abs/2605.15957.

Paul Joe Maliakel, Shashikant Ilager, and Ivona Brandic. Characterizing LLM inference energy-performance tradeoffs across workloads and GPU scaling, 2025. URL https://arxiv.org/abs/2501.08219.

Aleksander Maricq, Dmitry Duplyakin, Ivo Jimenez, Carlos Maltzahn, Ryan Stutsman, and Robert Ricci. Taming performance variability. In *13th USENIX Symposium on Operating Systems Design and Implementation (OSDI 18)*, pages 409–425, Carlsbad, CA, October 2018. USENIX Association. ISBN 978-1-939133-08-3. URL https://www.usenix.org/conference/osdi18/presentation/maricq.

David Meisner, Christopher M. Sadler, Luiz André Barroso, Wolf-Dietrich Weber, and Thomas F. Wenisch. Power management of online data-intensive services. In *Proceedings of the 38th annual international symposium on Computer architecture*, ISCA '11, pages 319–330. ACM, June 2011. doi: 10.1145/2000064.2000103. URL http://dx.doi.org/10.1145/2000064.2000103.

Todd Mytkowicz, Amer Diwan, Matthias Hauswirth, and Peter F. Sweeney. Producing wrong data without doing anything obviously wrong! In *Proceedings of the 14th international conference on Architectural support for programming languages and operating systems*, ASPLOS09, pages 265–276. ACM, March 2009. doi: 10.1145/1508244.1508275. URL http://dx.doi.org/10.1145/1508244.1508275.

Amadou Ngom, Prashanth Menon, Matthew Butrovich, Lin Ma, Wan Shen Lim, Todd C. Mowry, and Andrew Pavlo. Filter representation in vectorized query execution. In *Proceedings of the 17th International Workshop on Data Management on New Hardware (DaMoN 2021)*, SIGMOD/PODS '21, pages 1–7. ACM, June 2021. doi: 10.1145/3465998.3466009. URL http://dx.doi.org/10.1145/3465998.3466009.

Beatrix Miranda Ginn Nielsen. DTU pretrained sentence BERT AG News embeddings, 2023. URL https://doi.org/10.11583/DTU.21286923.v1.

Gabriele Oliaro, Yichao Fu, May Jiang, Owen Lu, Junli Wang, Zhihao Jia, Hao Zhang, and Samyam Rajbhandari. FastKernels: Benchmarking GPU kernel generation in production, 2026. URL https://arxiv.org/abs/2605.23215.

Liana Patel, Peter Kraft, Carlos Guestrin, and Matei Zaharia. ACORN: Performant and predicate-agnostic search over vector embeddings and structured data. *Proceedings of the ACM on Management of Data*, 2(3):120:1–120:27, 2024. doi: 10.1145/3654923. URL https://doi.org/10.1145/3654923.

Anuj Pathania, Qing Jiao, Alok Prakash, and Tulika Mitra. Integrated CPU-GPU power management for 3d mobile games. In *Proceedings of the 51st Annual Design Automation Conference*, DAC '14, pages 1–6. ACM, June 2014. doi: 10.1145/2593069.2593151. URL http://dx.doi.org/10.1145/2593069.2593151.

Haoran Qiu, Weichao Mao, Archit Patke, Shengkun Cui, Saurabh Jha, Chen Wang, Hubertus Franke, Zbigniew Kalbarczyk, Tamer Başar, and Ravishankar K. Iyer. Power-aware deep learning model serving with μ-Serve. In *2024 USENIX Annual Technical Conference (USENIX ATC 24)*, pages 75–93, Santa Clara, CA, July 2024. USENIX Association. ISBN 978-1-939133-41-0. URL https://www.usenix.org/conference/atc24/presentation/qiu.

Jiayang Shi, Yuzheng Cai, and Weiguo Zheng. Filtered approximate nearest neighbor search: A unified benchmark and systematic experimental study. *arXiv preprint arXiv:2509.07789*, 2025. URL https://arxiv.org/abs/2509.07789.

Prasoon Sinha, Akhil Guliani, Rutwik Jain, Brandon Tran, Matthew D. Sinclair, and Shivaram Venkataraman. Not all GPUs are created equal: Characterizing variability in large-scale, accelerator-rich systems. In *SC22: International Conference for High Performance Computing, Networking, Storage and Analysis*, pages 01–15. IEEE, November 2022. doi: 10.1109/sc41404.2022.00070. URL http://dx.doi.org/10.1109/SC41404.2022.00070.

Jeffrey Spaan, Kuan-Hsun Chen, and Ana-Lucia Varbanescu. Reducing compute waste in LLMs through kernel-level DVFS, 2026. URL https://arxiv.org/abs/2601.08539.

Jovan Stojkovic, Chaojie Zhang, Íñigo Goiri, Josep Torrellas, and Esha Choukse. DynamoLLM: Designing LLM inference clusters for performance and energy efficiency. In *2025 IEEE International Symposium on High Performance Computer Architecture (HPCA)*, pages 1348–1362. IEEE, March 2025. doi: 10.1109/hpca61900.2025.00102. URL http://dx.doi.org/10.1109/HPCA61900.2025.00102.

Zhenheng Tang, Yuxin Wang, Qiang Wang, and Xiaowen Chu. The impact of GPU DVFS on the energy and performance of deep learning: an empirical study. In *Proceedings of the Tenth ACM International Conference on Future Energy Systems*, e-Energy '19, pages 315–325. ACM, June 2019. doi: 10.1145/3307772.3328315. URL http://dx.doi.org/10.1145/3307772.3328315.

Jingyi Xi, Chenghao Mo, Benjamin Karsin, Artem Chirkin, Mingqin Li, and Minjia Zhang. VecFlow: A high-performance vector data management system for filtered-search on GPUs, 2025. URL https://arxiv.org/abs/2506.00812.

Zeyu Yang, Karel Adamek, and Wesley Armour. Part-time power measurements: nvidia-smi's lack of attention, 2023. URL https://arxiv.org/abs/2312.02741.

Jie You, Jae-Won Chung, and Mosharaf Chowdhury. Zeus: Understanding and optimizing GPU energy consumption of DNN training. In *20th USENIX Symposium on Networked Systems Design and Implementation (NSDI 23)*, pages 119–139, Boston, MA, April 2023. USENIX Association. ISBN 978-1-939133-33-5. URL https://www.usenix.org/conference/nsdi23/presentation/you.

Zongpu Zhang, Pranab Dash, Y. Charlie Hu, Qiang Xu, Jian Li, and Haibing Guan. Dissecting the impact of mobile DVFS governors on LLM inference performance and energy efficiency, 2025. URL https://arxiv.org/abs/2507.02135.

A Protocols, predictions and deviations

Three protocols were written, according to our records, before their data existed, but they were committed to version control and hashed only after the data for D1, D1R and the H100 arm had been collected (same evening, 2026-09-25), so no independent timestamp shows the order. We therefore call their predictions planned, not pre-registered. Their timing rests on the protocol files' own statements and the run logs. The protocols are: the laptop experiment D1 (research/experiments/dvfs-d1/protocol.md), the RTX 4090 pod replication D1R (dvfs-d1r/) and the H100 arm (dvfs-h100/). A protocol for an API and batch-size follow-up (D2, dvfs-d2/) was written but not run and is not part of this paper. The locked-clock experiment E-LOCK (research/experiments/dvfs-lock/), was committed and hashed on 2026-10-19, 12 minutes before its first run, and ran on the laptop only. Only E-LOCK's ordering is therefore verifiable from the repository history, and only E-LOCK's predictions are called pre-registered here. One exploratory pilot preceded them (research/data/raw/2026-09-25-dvfs-pilot/) and is used only to motivate the design. D1 predicted, for batch-1 queries: P1, the heater lowers light-path end-to-end P50 by at least 10% (ratio < 0.9, interval excluding 1) at $E \leq 3{,}000$; P2, the heater does not speed up the heavy path (ratio ≥ 0.95); P3, the light path's ratio is below the heavy path's; P4, the heater lowers light-path device time while host row materialization stays within $\pm 10\%$. The same rules were applied unchanged to every host.

P1 fails everywhere at the block level; the pilot's $1.9\times$ end-to-end speed-up on the laptop did not replicate reliably across blocks. P2 and the device-time half of P3 hold in every cell. P4 fails where the heater also slowed host-side work. On the H100 pod, host row materialization became 40–48% slower with the heater running, which shows that the heater process took host CPU time as well as GPU time. The end-to-end slowdowns on that host therefore say little about the power-state account; they show that our heater is not a clean GPU-only perturbation.

Deviations. (i) The clock summary in the planned analysis script took the median over the whole process, including data loading; we added a GPU-active median (utilization > 0) before inspecting any cross-host comparison and report both in the released CSVs. (ii) Two pod setup attempts failed because of script bugs (a missing dataset copy, a mis-specified pod) and were re-run before any cell completed; no completed cell was discarded. (iii) The pod first assigned to block 3 ran host-side benchmark work roughly $10\times$ slower than the others (about $14\times$ on a single-threaded Python test). Before any of its results were inspected, we re-ran block 3 from scratch on a new pod (Ryzen 9 7950X). The 14 cells the slow pod completed are retained (d1r-b3-partial.tar.gz) and excluded from the tables. A stray setup process ran for about 30 s on the block 4 pod during three cells; dropping those cells changes the affected light-path ratio from 0.967 to 0.966. (iv) The cross-host table (Table 1) and the device-time framing were not planned; they were suggested by the retained September 24 archive and are therefore partly exploratory, although the pods and H100 supplied new data for them.

E-LOCK predictions. K1 (light max/min ≤ 1.15 locked high), K3 (locked-low light time within 25% of D1's slow mode at $E = 10{,}000$), K4 (no heater effect locked high) and K5 (heavy within 3% of unlocked) held in every tested cell. K2 (locked-high light time within 15% of the best unlocked) failed: locked-high light time was 32–50% *lower* than the best unlocked median. No run was excluded and the run followed the protocol, with memory clocks locked

Table 5: Planned predictions by GPU and E. P3 is shown for end-to-end P50 / device time. "n/a": P1 was registered only for $E \leq 3{,}000$.

GPU	E	P1 call < 0.9	P2 heavy ≥ 0.95	P3 light $<$ heavy	P4 device $\downarrow$, host flat
RTX 4050 Laptop	100	**no**	yes	**no** / yes	**no**
RTX 4050 Laptop	1,000	**no**	yes	**no** / yes	**no**
RTX 4050 Laptop	3,000	**no**	yes	yes / yes	**no**
RTX 4050 Laptop	10,000	n/a	yes	yes / yes	**no**
RTX 4050 Laptop	30,000	n/a	yes	yes / yes	yes
RTX 4090 pods B	100	**no**	yes	yes / yes	**no**
RTX 4090 pods B	1,000	**no**	yes	yes / yes	yes
RTX 4090 pods B	3,000	**no**	yes	yes / yes	yes
RTX 4090 pods B	10,000	n/a	yes	yes / yes	yes
RTX 4090 pods B	30,000	n/a	yes	**no** / yes	yes
H100 SXM	1,000	**no**	yes	yes / yes	**no**
H100 SXM	3,000	**no**	yes	yes / yes	**no**
H100 SXM	10,000	n/a	yes	yes / yes	yes

Table 6: Paired heater-on / heater-off ratios (median over blocks of per-block ratios, 95% block-bootstrap interval; with $n \leq 5$ the intervals are descriptive, and with the H100's $n = 3$ there are only ten distinct resamples). Below 1 = faster with the heater. Device = top-k kernel time; call = end-to-end P50. n = blocks.

GPU	E	n	Light device	Heavy device	Light call	Heavy call
RTX 4050 Laptop	100	5	0.91 [0.90, 1.12]	1.19 [1.00, 1.20]	1.11 [0.78, 1.80]	1.09 [1.02, 1.12]
RTX 4050 Laptop	1,000	5	1.00 [0.98, 1.01]	1.18 [1.18, 1.19]	1.13 [1.05, 1.64]	1.06 [1.04, 1.09]
RTX 4050 Laptop	3,000	5	0.65 [0.26, 1.25]	1.19 [1.18, 1.19]	0.96 [0.48, 1.56]	1.07 [1.02, 1.09]
RTX 4050 Laptop	10,000	5	0.46 [0.39, 0.54]	1.19 [1.19, 1.20]	0.97 [0.79, 1.10]	1.08 [1.06, 1.17]
RTX 4050 Laptop	30,000	5	0.59 [0.57, 0.68]	1.00 [1.00, 1.00]	0.95 [0.92, 1.01]	1.07 [1.02, 1.11]
RTX 4090 pods B	100	5	0.92 [0.91, 1.01]	1.00 [1.00, 1.00]	0.97 [0.95, 1.11]	1.07 [0.95, 1.08]
RTX 4090 pods B	1,000	5	0.90 [0.70, 0.92]	1.00 [1.00, 1.00]	0.97 [0.94, 1.03]	1.07 [1.06, 1.28]
RTX 4090 pods B	3,000	5	0.87 [0.35, 0.94]	1.00 [1.00, 1.00]	0.96 [0.54, 0.99]	1.07 [1.02, 1.07]
RTX 4090 pods B	10,000	5	0.82 [0.34, 0.91]	1.00 [1.00, 1.01]	0.94 [0.64, 1.00]	1.07 [1.07, 1.37]
RTX 4090 pods B	30,000	5	1.00 [0.46, 1.00]	1.00 [1.00, 1.00]	1.07 [0.57, 1.09]	1.07 [1.03, 1.16]
H100 SXM	1,000	3	0.86 [0.86, 0.88]	1.36 [1.35, 1.36]	1.24 [1.21, 1.25]	1.26 [1.26, 1.28]
H100 SXM	3,000	3	0.71 [0.65, 0.77]	1.35 [1.35, 1.35]	1.10 [1.03, 1.17]	1.27 [1.26, 1.28]
H100 SXM	10,000	3	0.81 [0.80, 0.88]	1.36 [1.36, 1.37]	1.18 [1.14, 1.48]	1.25 [1.19, 1.26]

as planned. Analysis: `research/scripts/analyze_dvfs_lock.py`.

B CPU/GPU crossover

C The held-out router failure that motivated this study

The system's earlier research campaign (preserved unchanged in `paper/paper.tex`) selected a scalar routing rule, GPU if $E \cdot D \cdot B \geq 10^6$, with zero errors on 31 development CPU/GPU pairs. On a held-out suite of 16 workloads on an RTX 4050 laptop it chose the slower route in 8, with median regret 0.4% and maximum regret 235.7%. Each route was measured in a single process with five in-process runs. An audit of that archive found that the automatic arm differed from the forced arm of the same backend by more than 25% in 9 of 16 cells, and that two of the eight "wrong" labels were within 3.2% regret. In light of Section 4, labels near parity in such a suite partly measure the GPU's power state during each process, and the per-workload count is not a stable statistic. The maximum-regret rejection survives: a $3.36\times$ ratio exceeds every within-host spread we measured except the laptop light path's $4.2\times$. The earlier manuscript also documents representation, preparation and harness findings that are not repeated here.

D Cost and resources

New cloud runs used five RTX 4090 pods (one block each), one H100 SXM pod and a 4-minute H100 probe, at $0.74 and $3.49 per hour. The operator's ledger totals about US$6 (`research/experiments/dvfs-d1r/campaign-log.md`). All pods were deleted after their data were downloaded and hash-checked. A container-level Vulkan fix (pointing the loader at `libEGL_nvidia.so.0` rather than the toolkit's GLX ICD) was required on every pod and is documented in the log; it may explain an earlier "no Vulkan" failure on an A6000.

Table 7: Median-block end-to-end P50 (ms) for the single-threaded CPU scan, the light GPU path with the heater off and on (winner against CPU in parentheses), and the heavy GPU path. The heater never changed a winner.

GPU	E	CPU	Light, heater off	Light, heater on	Heavy
RTX 4050 Laptop	100	0.010	0.172 (CPU)	0.253 (CPU)	1.999
RTX 4050 Laptop	1,000	0.083	0.230 (CPU)	0.374 (CPU)	2.050
RTX 4050 Laptop	3,000	0.308	0.548 (CPU)	0.559 (CPU)	2.109
RTX 4050 Laptop	10,000	3.332	1.682 (GPU)	1.685 (GPU)	2.204
RTX 4050 Laptop	30,000	9.187	2.265 (GPU)	2.138 (GPU)	2.791
RTX 4090 pods B	100	0.008	0.103 (CPU)	0.100 (CPU)	0.828
RTX 4090 pods B	1,000	0.048	0.123 (CPU)	0.123 (CPU)	0.835
RTX 4090 pods B	3,000	0.133	0.178 (CPU)	0.175 (CPU)	0.849
RTX 4090 pods B	10,000	1.495	0.430 (GPU)	0.405 (GPU)	0.860
RTX 4090 pods B	30,000	4.907	0.779 (GPU)	0.833 (GPU)	0.894