

FLR IN 10 SLIDES OR LESS

Ernesto Jardim

October 8, 2013



WHAT IS FLR ?

FLR ??

FLQUANT

FLSTOCK

FLINDEX


FLSR

FLR LISTS

EXAMPLE

- ▶ FLR = Fisheries Libraries in R
- ▶ FLR is a set of R packages
- ▶ FLR is developed and maintained by a group of fisheries scientists

PACKAGES



FLQUANT

FLR ??

FLQUANT

FLSTOCK

FLINDEX

FLSR

FLR LISTS

EXAMPLE

Stands for "FL quantity" and it's the smallest component of FLR classes.

Six dimensional array used to store data of a particular type (e.g. catch numbers), with the following dimensions:

```
[1] "quant" "year" "unit" "season" "area" "iter"
```

FLStock

Represents a fish stock and comprises a number of slots.

```
> showClass("FLStock")
```

```
Class "FLStock" [package "FLCore"]
```

```
Slots:
```

Name:	catch	catch.n	catch.wt	discards	discards.n
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	discards.wt	landings	landings.n	landings.wt	stock
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	stock.n	stock.wt	m	mat	harvest
Class:	FLQuant	FLQuant	FLQuant	FLQuant	FLQuant

Name:	harvest.spwn	m.spwn	name	desc	range
Class:	FLQuant	FLQuant	character	character	numeric

```
Extends:
```

```
Class "FLS", directly
```

```
Class "FLComp", by class "FLS", distance 2
```

FLINDEX

Represents a index (e.g. index of abundance from a survey)

```
> showClass("FLIndex")
```

```
Class "FLIndex" [package "FLCore"]
```

Slots:

Name:	type	distribution	index	index.var	catch.n
Class:	character	character	FLQuant	FLQuant	FLQuant

Name:	catch.wt	effort	sel.pattern	index.q	name
Class:	FLQuant	FLQuant	FLQuant	FLQuant	character

Name:	desc	range
Class:	character	numeric

Extends: "FLComp"

FLSR

Represents a stock-recruitment relationship and allows the estimation of its parameters.

```
> showClass("FLSR")
```

```
Class "FLSR" [package "FLCore"]
```

```
Slots:
```

Name:	rec	ssb	covar	logerror	model
Class:	FLQuant	FLQuant	FLQuants	logical	formula

Name:	logl	gr	distribution	initial	params
Class:	function	function	factor	function	FLPar

Name:	logLik	vcov	hessian	details	residuals
Class:	logLik	array	array	list	FLArray

Name:	fitted	name	desc	range
Class:	FLArray	character	character	numeric

```
Extends:
```

```
Class "FLModel", directly
```

```
Class "FLComp", by class "FLModel", distance 2
```

A list of other classes

```
> showClass("FLlst")
```

```
Class "FLlst" [package "FLCore"]
```

```
Slots:
```

Name:	.Data	names	desc	lock
Class:	list	character	character	logical

```
Extends:
```

```
Class "list", from data part
```

```
Class "vector", by class "list", distance 2
```

```
Known Subclasses:
```

```
Class "FLQuants", directly
```

```
Class "FLCohorts", directly
```

```
Class "FLComps", directly
```

```
Class "FLPars", directly
```

```
Class "FLModelSims", directly
```

```
Class "FLStocks", by class "FLComps", distance 2
```

```
Class "FLIndices", by class "FLComps", distance 2
```

```
Class "FLBiols", by class "FLComps", distance 2
```

```
Class "FLSRs", by class "FLComps", distance 2
```


EXAMPLE I

FLR ??

FLQUANT

FLSTOCK

FLINDEX

FLSR

FLR LISTS

EXAMPLE

```
> # load -----  
> library(FLCore)  
> data(ple4.index)  
> data(ple4)  
> # FLStock -----  
> plot(ple4)  
> summary(ple4)  
> # FLQuant -----  
> cth <- catch(ple4)  
> plot(cth)  
> summary(cth)
```

EXAMPLE II

FLR ??

FLQUANT

FLSTOCK

FLINDEX

FLSR

FLR LISTS

EXAMPLE

```
> # FLIndex -----  
> plot(ple4.index)  
> summary(ple4.index)  
> # FLSR -----  
> ple4.sr <- as.FLSR(ple4, model="bevholt")  
> ple4.sr <- fmle(ple4.sr)  
> plot(ple4.sr)  
> # FLlst -----  
> flqs <- FLQuants(c=catch(ple4), b=stock(ple4))  
> xyplot(data~year, groups=qname, data=flqs,  
+         type="l")
```