# Table 1

CREATE table orders(O\_Id INT(5),Orderno INT(5),P\_Id INT(3));

DESC orders;

INSERT INTO orders VALUES(1,77895,3);

INSERT INTO orders VALUES(2,44678,3);

INSERT into orders values(3,22456,1);

INSERT into orders values(4,24562,1);

INSERT into orders values(5,34764,15);

```
mysql> SELECT * FROM orders;
 0_Id | Orderno | P_Id |
     1
           77695
                       3
     2
           44678
                       3
     3
           22456
                       1
           24562
                       1
           34764
                      15 |
5 rows in set (0.01 sec)
```

## Table 2

CREATE table persons(p\_Id INT(5),LASTNAME varchar(10),Firstname varchar(15), Address varchar(20),city varchar(10));

```
mysql> desc persons;
  Field
                            | Null | Key | Default | Extra
             | Type
  p_Id
               int(5)
                                           NULL
                             YES
              varchar(10)
  LASTNAME
                             YES
                                           NULL
  Firstname
               varchar(15)
                             YES
                                           NULL
  Address
               varchar(20)
                             YES
                                           NULL
               varchar(10)
  city
                             YES
                                           NULL
  rows in set (0.00 sec)
```

INSERT into persons values(1,'Hansen','Ola','Timoteivn 10','sadnes');

INSERT into persons values(2,'Svendson','Tove','Borgn 23','Sandnes');

INSERT into persons values(3, 'Pettersen', 'Kari', 'Storgt 20', 'Stavanger');

```
mysql> SELECT * FROM persons;
                                                city
 p_Id | LASTNAME
                     Firstname | Address
         Hansen
                     0la
                                  Timoteivn 10
                                                 sadnes
         Svendson
                                  Borgn 23
     2
                     Tove
                                                 Sandnes
                                  Storgt 20
         Pettersen
                     Kari
                                                 Stavanger
 rows in set (0.01 sec)
```

## Left Join

SELECT persons.lastname,persons.firstname,orders.orderno

FROM persons

**LEFT JOIN orders** 

ON persons.p Id = orders.p Id

ORDER BY persons.lastname;

```
-> ON persons.p_Id = orders.p_Id
  ->
  -> ORDER BY persons.lastname;
           | firstname |
lastname
                         orderno
            0la
                           22456
Hansen
                           24562
            0la
Hansen
                           77695
Pettersen
            Kari
                           44678
Pettersen
            Kari
Svendson
                            NULL
            Tove
```

#### Full outer Join

SELECT persons.lastname,persons.firstname,orders.orderno FROM persons
FULL OUTER JOIN orders
ON persons.p\_Id = orders.p\_Id
ORDER BY persons.lastname;

# Right/Right Outter Join

SELECT persons.lastname,persons.firstname,orders.orderno FROM persons
RIGHT OUTER JOIN orders
ON persons.p\_Id = orders.p\_Id
ORDER BY persons.lastname;

#### Inner Join

SELECT persons.lastname,persons.firstname,orders.orderno 2 FROM persons 3 INNER JOIN orders

- 4 ON persons.p\_Id = orders.p\_Id 5 ORDER BY persons.lastname;

<pre>mysql&gt; SELECT persons.lastname,persons.first BY persons.lastname;</pre>			
lastname	firstname	orderno	i
Hansen	0la	22456	i
Hansen	0la	24562	İ
Pettersen	Kari	77695	İ
Pettersen	Kari	44678	İ
+			
4 rows in set (0.00 sec)			