

# Application of learning algorithms to nonlinear filtering and MCMC

PhD Dissertation defense

Nov 6, 2019

Anand Radhakrishnan



Department of Electrical and Computer Engineering — University of Florida

Committee chair: Prof. Sean Meyn

Committee members : Prof. José Principe, Prof. Kamran Mohseni, Prof. James Hobert

Thanks to the National Science Foundation and Army Research Office

Thanks to friends & family

# Outline

- 1 PhD Proposal - Recap
- 2 Poisson's Equation
- 3 Differential LSTD learning
- 4 Applications to Nonlinear filtering
- 5 Applications to MCMC
- 6 Conclusions and Future Work

# PhD Proposal - Recap

Work till then

- Presented the **feedback particle filter (FPF)** - an approximation of the nonlinear filter that requires computing a gain function by solving a *Poisson's equation*.
- Proposed a **differential TD-learning** algorithm to approximate the gradient of the solution to Poisson's equation. [R et al. 16]

# PhD Proposal - Recap

Work till then

- Presented the **feedback particle filter (FPF)** - an approximation of the nonlinear filter that requires computing a gain function by solving a *Poisson's equation*.
- Proposed a **differential TD-learning** algorithm to approximate the gradient of the solution to Poisson's equation. [R et al. 16]
- Presented numerical examples for gain approximation and state estimation for scalar systems.

# PhD Proposal - Recap

## Tasks promised and accomplished

- Extend the algorithm to a multidimensional setting.

# PhD Proposal - Recap

## Tasks promised and accomplished

- Extend the algorithm to a multidimensional setting. - ✓ [R et al. 18]
- Explore appropriate basis selection for these algorithms.

# PhD Proposal - Recap

## Tasks promised and accomplished

- Extend the algorithm to a multidimensional setting. - ✓ [R et al. 18]
- Explore appropriate basis selection for these algorithms. - ✓
- Impact of gain approximation error on filtering performance.

# PhD Proposal - Recap

## Tasks promised and accomplished

- Extend the algorithm to a multidimensional setting. - ✓ [R et al. 18]
- Explore appropriate basis selection for these algorithms. - ✓
- Impact of gain approximation error on filtering performance. - ✗  
[Taghvaei et al. 18]

### New direction

- Simplified version of the algorithm for Langevin diffusion. [R et al. 18]
- Improvements for online gain estimation. [R et al. 19]
- Explored the application to MCMC algorithms. [Brosse et al. 19]



## Poisson's Equation

$$0 = \tilde{c} + \mathcal{D}h$$

$$h(x) = \mathbb{E} \left[ \int_0^\tau \tilde{c}(X(t)) dt \right]$$

with  $X(0) = x$

## Optimal FPF Gain

$$\mathbf{K} = \nabla h$$

$$\left\{ (x)^n \mathcal{U}^n \mathcal{C} + (n^+ x)^n \right\} \lim_{n \rightarrow \infty} = (x)^{1+n} \phi$$

## Optimal Control

$$\|_{\mathcal{Z}} \|\theta^{\mathcal{U}} \Delta\|_{\mathcal{Z}} =$$

$$\langle \theta^{\mathcal{Z}}, \theta^{\mathcal{U}} \rangle_{\mathcal{Z}} = \frac{\theta^{\mathcal{U}}}{\mathcal{Z}}$$

$$\langle \mathcal{Z}^{\mathcal{U}} \Delta h, \mathcal{Z} \rangle = \frac{\mathcal{U} \mathcal{C} \mathcal{U}}{\mathcal{Z}}$$

## Optimal MCMC CV

# Poisson's Equation

# Poisson's Equation

- Second order partial differential equation with applications in various fields.
- General form in stochastic systems

$$\mathcal{D}h := -f$$

$\mathcal{D}$  - differential operator

$f$  - forcing function, usually centered

$h$  - solution to Poisson's equation

# Poisson's Equation

## Stochastic optimal control

**Example:** In average cost optimal control problems,

$$\min_u \{c(x, u) + P_u h^*(x)\} = h^*(x) + \eta^*$$

$c(x, u)$  - Cost function associated with state  $x$  and action  $u$ .

$P_u$  - Transition kernel of the controlled Markov chain.

$\eta^*$  - Optimal average cost.

$h^*(x)$  - **Relative value function**

# Poisson's Equation

## Stochastic optimal control

**Example:** In average cost optimal control problems,

$$\min_u \{c(x, u) + P_u h^*(x)\} = h^*(x) + \eta^*$$

$c(x, u)$  - Cost function associated with state  $x$  and action  $u$ .

$P_u$  - Transition kernel of the controlled Markov chain.

$\eta^*$  - Optimal average cost.

$h^*(x)$  - **Relative value function**

Poisson's equation is the dynamic programming equation.

# Poisson's Equation

## Langevin Diffusion

Langevin diffusion is given by the SDE,

$$d\Phi_t = \underbrace{-\nabla U(\Phi_t) dt}_{\text{Drift term}} + \underbrace{\sqrt{2} dW_t}_{\text{Diffusion term}}, \quad \Phi \in \mathbb{R}^d$$

$U \in C^1$  is called the *Potential function*.

$W = \{W_t : t \geq 0\}$  is a standard Brownian motion on  $\mathbb{R}^d$ .

# Poisson's Equation

## Langevin Diffusion

Langevin diffusion is given by the SDE,

$$d\Phi_t = \underbrace{-\nabla U(\Phi_t) dt}_{\text{Drift term}} + \underbrace{\sqrt{2} dW_t}_{\text{Diffusion term}}, \quad \Phi \in \mathbb{R}^d$$

$U \in C^1$  is called the *Potential function*.

$W = \{W_t : t \geq 0\}$  is a standard Brownian motion on  $\mathbb{R}^d$ .

- May be regarded as a  $d$ -dimensional gradient flow with “noise”.

# Poisson's Equation

## Langevin Diffusion

Langevin diffusion is given by the SDE,

$$d\Phi_t = \underbrace{-\nabla U(\Phi_t) dt}_{\text{Drift term}} + \underbrace{\sqrt{2} dW_t}_{\text{Diffusion term}}, \quad \Phi \in \mathbb{R}^d$$

$U \in C^1$  is called the *Potential function*.

$W = \{W_t : t \geq 0\}$  is a standard Brownian motion on  $\mathbb{R}^d$ .

- May be regarded as a  $d$ -dimensional gradient flow with “noise”.
- Diffusion is reversible, with unique *invariant density*  $\rho = e^{-U+\Lambda}$ , where  $\Lambda$  is a normalizing constant.

# Poisson's Equation

## Langevin Diffusion

Differential generator  $\mathcal{D}$ ,

$$\mathcal{D}f := \lim_{t \rightarrow 0} \frac{\mathbb{E}[f(\Phi_t) | \Phi_0 = x] - f(x)}{t}$$



# Poisson's Equation

## Langevin Diffusion

Differential generator  $\mathcal{D}$ ,

$$\begin{aligned}\mathcal{D}f &:= \lim_{t \rightarrow 0} \frac{\mathbb{E}[f(\Phi_t) | \Phi_0 = x] - f(x)}{t} \\ &= -\nabla U \cdot \nabla f + \Delta f, \quad f \in C^2,\end{aligned}$$

where  $\nabla$  is the gradient and  $\Delta$  is the Laplacian.

# Poisson's Equation

## Langevin Diffusion

Differential generator  $\mathcal{D}$ ,

$$\begin{aligned}\mathcal{D}f &:= \lim_{t \rightarrow 0} \frac{\mathbb{E}[f(\Phi_t) | \Phi_0 = x] - f(x)}{t} \\ &= -\nabla U \cdot \nabla f + \Delta f, \quad f \in C^2,\end{aligned}$$

where  $\nabla$  is the gradient and  $\Delta$  is the Laplacian.

Let  $c: \mathbb{R}^d \rightarrow \mathbb{R}$  be a function of interest, and

$$\eta = \int c(x) \rho(x) dx = \langle c, 1 \rangle_{L^2}.$$

# Poisson's Equation

## Langevin Diffusion

Differential generator  $\mathcal{D}$ ,

$$\begin{aligned}\mathcal{D}f &:= \lim_{t \rightarrow 0} \frac{\mathbb{E}[f(\Phi_t) | \Phi_0 = x] - f(x)}{t} \\ &= -\nabla U \cdot \nabla f + \Delta f, \quad f \in C^2,\end{aligned}$$

where  $\nabla$  is the gradient and  $\Delta$  is the Laplacian.

Let  $c: \mathbb{R}^d \rightarrow \mathbb{R}$  be a function of interest, and

$$\eta = \int c(x) \rho(x) dx = \langle c, 1 \rangle_{L^2}.$$

Function  $h \in C^2$  solves **Poisson's equation** with forcing function  $c$  if

$$\mathcal{D}h := -\tilde{c}, \quad \tilde{c} = c - \eta.$$

$$h := \int_0^\infty \mathbb{E}[\tilde{c}(\Phi_t)] dt$$

# Poisson's Equation

## Existence of a solution

- A solution exists under weak assumptions on  $U$  and  $c$  [Glynn 96, Kontoyiannis 12].
- Representations for the gradient of  $h$  and bounds are obtained in [Laugesen 15, Devraj 18].
- A smooth solution  $h \in C^2$  exists under stronger conditions in [Pardoux 01], subject to growth conditions on  $c$  similar to [Glynn 96].

# Poisson's Equation

## Approximate solution to Poisson's equation

Obtaining an analytical solution for  $h$  is difficult outside special cases.  
Hence approximation.

# Poisson's Equation

## Approximate solution to Poisson's equation

Obtaining an analytical solution for  $h$  is difficult outside special cases. Hence approximation.

Goal: For a given function class  $\mathcal{H}$ , find the minimizer of

$$g^* := \arg \min_{g \in \mathcal{H}} \|h - g\|_{L^2}^2$$

Such minimum norm optimization problems can be solved using *TD learning* [Tsitsiklis 99, CTCN].

# Poisson's Equation

## Approximate solution to Poisson's equation

Obtaining an analytical solution for  $h$  is difficult outside special cases. Hence approximation.

Goal: For a given function class  $\mathcal{H}$ , find the minimizer of

$$g^* := \arg \min_{g \in \mathcal{H}} \|h - g\|_{L^2}^2$$

Such minimum norm optimization problems can be solved using *TD learning* [Tsitsiklis 99, CTCN].

Challenge - No algorithm exists for state spaces of dimension  $> 1$ .

# LSTD learning

## Discounted cost case

Discounted-cost value function:

$$h^\gamma(x) := \int_0^\infty e^{-\gamma t} \mathbb{E}_x[c(\Phi_t)] dt, \quad \gamma > 0 \text{ - discount factor}$$

Discounted-cost optimality equation:

$$\gamma h^\gamma = c + \mathcal{D}h^\gamma$$



# LSTD learning

## Discounted cost case

Discounted-cost value function:

$$h^\gamma(x) := \int_0^\infty e^{-\gamma t} \mathbb{E}_x[c(\Phi_t)] dt, \quad \gamma > 0 - \text{discount factor}$$

Discounted-cost optimality equation:

$$\gamma h^\gamma = c + \mathcal{D}h^\gamma$$

$$\text{LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|h^\gamma - g\|_{L^2}^2$$

# LSTD learning

## Discounted cost case

$$\text{LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|h^\gamma - g\|_{L^2}^2$$

For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i$$

$$\theta^* = M^{-1}b$$

$$M_{ij} = \langle \psi_i, \psi_j \rangle_{L^2}, \quad b_i = \langle \psi_i, h^\gamma \rangle_{L^2}$$

# LSTD learning

## Discounted cost case

$$\text{LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|h^\gamma - g\|_{L^2}^2$$

For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i$$

$$\theta^* = M^{-1}b$$

$$M_{ij} = \langle \psi_i, \psi_j \rangle_{L^2}, \quad b_i = \langle \psi_i, h^\gamma \rangle_{L^2}$$

# LSTD learning

## Discounted cost case

$$\text{LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|h^\gamma - g\|_{L^2}^2$$

For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i$$

$$\theta^* = M^{-1}b$$

$$\begin{aligned} M_{ij} &= \langle \psi_i, \psi_j \rangle_{L^2}, & b_i &= \langle \psi_i, h^\gamma \rangle_{L^2} \\ & & &= \langle \psi_i, R_\gamma c \rangle_{L^2} \end{aligned}$$

$$\text{Resolvent kernel} - R_\gamma c(x) := \int_0^\infty \mathbb{E}_x \left[ e^{-\gamma t} c(\Phi_t) \right] dt$$

$$R_\gamma c = (I_\gamma - \mathcal{D})^{-1}c$$

# LSTD learning

Discounted cost case

$$\text{LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|h^\gamma - g\|_{L^2}^2$$

For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i$$

$$\theta^* = M^{-1}b$$

$$M_{ij} = \langle \psi_i, \psi_j \rangle_{L^2}, \quad b_i = \langle \psi_i, R_\gamma c \rangle_{L^2}$$

$$= \langle R_\gamma^\dagger \psi_i, c \rangle_{L^2}$$

Using an adjoint operation and applying the stationarity of  $\Phi$ .

# LSTD learning

## Discounted cost case

$$\text{LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|h^\gamma - g\|_{L^2}^2$$

For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i$$

$$\theta^* = M^{-1}b$$

$$M_{ij} = \langle \psi_i, \psi_j \rangle_{L^2}, \quad b_i = \langle R_\gamma^\dagger \psi_i, c \rangle_{L^2}$$

$$\text{Eligibility vector} - \varphi_\psi(t) := \int_0^\infty e^{-\gamma r} \psi(\Phi_{t-r}) dr$$

$$R_\gamma^\dagger \psi_i(x) = \mathbb{E}[\varphi_{\psi_i}(t) | \Phi_t = x]$$

# LSTD learning

## Discounted cost case

$$\text{LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|h^\gamma - g\|_{L^2}^2$$

For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i$$

$$\theta^* = M^{-1}b$$

$$\begin{aligned} M_{ij} &= \langle \psi_i, \psi_j \rangle_{L^2}, & b_i &= \langle R_\gamma^\dagger \psi_i, c \rangle_{L^2} \\ & & &= \mathbb{E}[\varphi_{\psi_i}(t)c(\Phi_t)] \end{aligned}$$

# LSTD learning

## Discounted cost case

ODE formulation of the LSTD algorithm:

$$\frac{d}{dt}M(t) = \psi(\Phi_t)\psi^T(\Phi_t)$$

$$\frac{d}{dt}\varphi_\psi(t) = -\gamma \varphi_\psi(t) + \psi(\Phi_t)$$

$$\frac{d}{dt}b(t) = \varphi_\psi(t)c(\Phi_t)$$

$$\theta(t) := M(t)^{-1}b(t)$$



# LSTD learning

## Discounted cost case

ODE formulation of the LSTD algorithm:

$$\begin{aligned}\frac{d}{dt}M(t) &= \psi(\Phi_t)\psi^T(\Phi_t) \\ \frac{d}{dt}\varphi_\psi(t) &= -\gamma\varphi_\psi(t) + \psi(\Phi_t) \\ \frac{d}{dt}b(t) &= \varphi_\psi(t)c(\Phi_t) \\ \theta(t) &:= M(t)^{-1}b(t)\end{aligned}$$

By law of large numbers,

$$\lim_{t \rightarrow \infty} \theta(t) = \theta^*$$

Drawback: For average-cost, LSTD requires the existence of a regenerating state.

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

Idea: Approximate the gradient of  $h$  directly [R et al. 16, Devraj et al. 16]:

$$g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

Idea: Approximate the gradient of  $h$  directly [R et al. 16, Devraj et al. 16]:

$$g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

Need to choose a function class  $\mathcal{H}$  for  $g$  (or  $\nabla g$ )

- A finitely parameterized family of functions.
- A reproducing kernel Hilbert space (RKHS).

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

Idea: Approximate the gradient of  $h$  directly [R et al. 16, Devraj et al. 16]:

$$g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

Need to choose a function class  $\mathcal{H}$  for  $g$  (or  $\nabla g$ )

- A finitely parameterized family of functions.
- A reproducing kernel Hilbert space (RKHS).

Choice of basis is not an easy task

$\implies$  RKHS framework is far easier to implement.

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

**Challenge:** the function  $h$  is not known,  
and hence the objective function is not observable

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

**Challenge:** the function  $h$  is not known,  
and hence the objective function is not observable

**$\nabla$ -LSTD:** For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i \implies \nabla g = \sum_{i=1}^{\ell} \theta_i \nabla \psi_i$$

$$\theta^* = M^{-1}b$$

$$M_{ij} = \langle \nabla \psi_i, \nabla \psi_j \rangle_{L^2}, \quad b_i = \langle \nabla \psi_i, \nabla h \rangle_{L^2}$$

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

**Challenge:** the function  $h$  is not known,  
and hence the objective function is not observable

**$\nabla$ -LSTD:** For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i \implies \nabla g = \sum_{i=1}^{\ell} \theta_i \nabla \psi_i$$

$$\theta^* = M^{-1}b$$

$$M_{ij} = \langle \nabla \psi_i, \nabla \psi_j \rangle_{L^2}, \quad b_i = \langle \nabla \psi_i, \nabla h \rangle_{L^2}$$

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

**Challenge:** the function  $h$  is not known,  
and hence the objective function is not observable

**$\nabla$ -LSTD:** For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i \implies \nabla g = \sum_{i=1}^{\ell} \theta_i \nabla \psi_i$$

$$\theta^* = M^{-1}b$$

$$M_{ij} = \langle \nabla \psi_i, \nabla \psi_j \rangle_{L^2}, \quad b_i = \langle \nabla \psi_i, \nabla h \rangle_{L^2} \\ = \langle \nabla \psi_i, R_{U''} \nabla c \rangle_{L^2}$$

Resolvent kernel -  $R_{U''} \nabla c(x) := \int_0^\infty \mathbb{E}_x \left[ \exp \left( - \int_0^t U''(\Phi_s) ds \right) \nabla c(\Phi_t) \right] dt$



# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

**Challenge:** the function  $h$  is not known,  
and hence the objective function is not observable

**$\nabla$ -LSTD:** For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i \implies \nabla g = \sum_{i=1}^{\ell} \theta_i \nabla \psi_i$$

$$\theta^* = M^{-1}b$$

$$\begin{aligned} M_{ij} &= \langle \nabla \psi_i, \nabla \psi_j \rangle_{L^2}, & b_i &= \langle \nabla \psi_i, R_{U''} \nabla c \rangle_{L^2} \\ & & &= \langle R_{U''}^\dagger \nabla \psi_i, \nabla c \rangle_{L^2} \end{aligned}$$

Using an adjoint operation and applying the stationarity of  $\Phi$ .

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

**Challenge:** the function  $h$  is not known,  
and hence the objective function is not observable

**$\nabla$ -LSTD-L:** For Langevin diffusion, if  $f, g \in L^2(\rho)$

$$\langle \nabla f, \nabla g \rangle_{L^2} = -\langle f, \mathcal{D}g \rangle_{L^2} = -\langle \mathcal{D}f, g \rangle_{L^2}.$$

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

**Challenge:** the function  $h$  is not known,  
and hence the objective function is not observable

**$\nabla$ -LSTD-L:** For Langevin diffusion, if  $f, g \in L^2(\rho)$

$$\langle \nabla f, \nabla g \rangle_{L^2} = -\langle f, \mathcal{D}g \rangle_{L^2} = -\langle \mathcal{D}f, g \rangle_{L^2}.$$

Applying this and Poisson's equation  $\mathcal{D}h = -\tilde{c}$ :

$$\begin{aligned} \|\nabla h - \nabla g\|_{L^2}^2 &= \|\nabla h\|_{L^2}^2 + \|\nabla g\|_{L^2}^2 - 2\langle \nabla h, \nabla g \rangle_{L^2} \\ &= \|\nabla h\|_{L^2}^2 + \|\nabla g\|_{L^2}^2 + 2\langle \mathcal{D}h, g \rangle_{L^2} \end{aligned}$$

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD goal} - g^* := \arg \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

**Challenge:** the function  $h$  is not known,  
and hence the objective function is not observable

**$\nabla$ -LSTD-L:** For Langevin diffusion, if  $f, g \in L^2(\rho)$

$$\langle \nabla f, \nabla g \rangle_{L^2} = -\langle f, \mathcal{D}g \rangle_{L^2} = -\langle \mathcal{D}f, g \rangle_{L^2}.$$

Applying this and Poisson's equation  $\mathcal{D}h = -\tilde{c}$ :

$$\begin{aligned} \|\nabla h - \nabla g\|_{L^2}^2 &= \|\nabla h\|_{L^2}^2 + \|\nabla g\|_{L^2}^2 - 2\langle \nabla h, \nabla g \rangle_{L^2} \\ &= \|\nabla h\|_{L^2}^2 + \|\nabla g\|_{L^2}^2 - 2\langle \tilde{c}, g \rangle_{L^2} \end{aligned}$$

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD-L goal} - g^* := \arg \min_{g \in \mathcal{H}} \left\{ \|\nabla g\|_{L^2}^2 - 2\langle \tilde{c}, g \rangle_{L^2} \right\}$$

$\nabla$ -LSTD-L: For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i \implies \nabla g = \sum_{i=1}^{\ell} \theta_i \nabla \psi_i$$

$$\theta^* = M^{-1}b$$

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD-L goal} - g^* := \arg \min_{g \in \mathcal{H}} \left\{ \|\nabla g\|_{L^2}^2 - 2\langle \tilde{c}, g \rangle_{L^2} \right\}$$

$\nabla$ -LSTD-L: For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i \implies \nabla g = \sum_{i=1}^{\ell} \theta_i \nabla \psi_i$$

$$\theta^* = M^{-1}b$$

$$M_{ij} = \langle \nabla \psi_i, \nabla \psi_j \rangle_{L^2}$$

$$b_i = \langle \nabla \psi_i, \nabla h \rangle_{L^2} = \langle \psi_i, \tilde{c} \rangle_{L^2}$$

# Differential LSTD learning ( $\nabla$ -LSTD)

Poisson's equation

$$\nabla\text{-LSTD-L goal} - g^* := \arg \min_{g \in \mathcal{H}} \left\{ \|\nabla g\|_{L^2}^2 - 2\langle \tilde{c}, g \rangle_{L^2} \right\}$$

$\nabla$ -LSTD-L: For a linear parameterization

$$g = h^\theta := \sum_{i=1}^{\ell} \theta_i \psi_i \implies \nabla g = \sum_{i=1}^{\ell} \theta_i \nabla \psi_i$$

$$\theta^* = M^{-1}b$$

$$\begin{aligned} M_{ij} &= \langle \nabla \psi_i, \nabla \psi_j \rangle_{L^2} \\ &\approx \frac{1}{t} \int_0^t \nabla \psi(\Phi_s) \nabla \psi^T(\Phi_s) ds \end{aligned}$$

$$\begin{aligned} b_i &= \langle \nabla \psi_i, \nabla h \rangle_{L^2} = \langle \psi_i, \tilde{c} \rangle_{L^2} \\ &\approx \frac{1}{t} \int_0^t \psi_i(\Phi_s) \tilde{c}(\Phi_s) ds \end{aligned}$$

# Differential LSTD learning on RKHS ( $\nabla$ -LSTD-RKHS)

## Basics of RKHS

Choose a kernel function  $K(x, y)$  that is

- *Symmetric*:  $K(x, y) = K(y, x)$  for any  $x, y \in \mathbb{R}^d$
- *Positive definite*: For any finite subset  $\{x^i\} \subset \mathbb{R}^d$ , the matrix  $\{M_{ij} := K(x^i, x^j)\}$  is positive definite.
- *Smooth*:  $K \in C^2$

$K$  defines a unique reproducing kernel Hilbert space (RKHS)  $\mathcal{H}$  [Moore-Aronszajn theorem].

**Inner product:** If  $g_\alpha = \sum_i \alpha_i K(x^i, \cdot)$  and  $g_\beta = \sum_j \beta_j K(y^j, \cdot)$ ,

$$\langle g_\alpha, g_\beta \rangle_{\mathcal{H}} := \sum_{i,j} \alpha_i \beta_j K(x^i, y^j)$$

**Reproducing property:**  $g_\alpha(x) = \langle g_\alpha, K(x, \cdot) \rangle_{\mathcal{H}}$ ,  $x \in \mathbb{R}^d$ .



# Differential LSTD learning on RKHS

## Empirical risk minimization (ERM)

Recall  $\nabla$ -LSTD goal:

$$g^* = \arg \min_{g \in \mathcal{H}} \left\{ \|\nabla g\|_{L^2}^2 - 2\langle \tilde{c}, g \rangle_{L^2} \right\}$$

Approximation via **empirical risk minimization (ERM)**:

$$\arg \min_{g \in \mathcal{H}} \underbrace{\frac{1}{N} \sum_{i=1}^N \left[ \|\nabla g(x^i)\|^2 - 2\tilde{c}_N(x^i)g(x^i) \right]}_{\text{Empirical risk}} + \underbrace{\lambda \|g\|_{\mathcal{H}}^2}_{\text{Regularization}}$$

where  $\tilde{c}_N(x) = c(x) - \frac{1}{N} \sum_{i=1}^N c(x^i)$ ,  $x \in \mathbb{R}^d$

# Differential LSTD learning on RKHS

Empirical risk minimization (ERM)

## Extended Representer Theorem [Zhou 08]

If loss function  $L(x, \cdot, \cdot)$  is convex on  $\mathbb{R}^{d+1}$  for each  $x \in \mathbb{R}^d$ , then the optimizer  $g^*$  over  $g \in \mathcal{H}$  exists:

$$g^*(\cdot) = \sum_{i=1}^N \left[ \beta_i^{0*} K(x^i, \cdot) + \sum_{k=1}^d \beta_i^{k*} \frac{\partial}{\partial x_k} K(x^i, \cdot) \right]$$

# Differential LSTD learning on RKHS

Empirical risk minimization (ERM)

## Extended Representer Theorem [Zhou 08]

If loss function  $L(x, \cdot, \cdot)$  is convex on  $\mathbb{R}^{d+1}$  for each  $x \in \mathbb{R}^d$ , then the optimizer  $g^*$  over  $g \in \mathcal{H}$  exists:

$$g^*(\cdot) = \sum_{i=1}^N \left[ \beta_i^{0*} K(x^i, \cdot) + \sum_{k=1}^d \beta_i^{k*} \frac{\partial}{\partial x_k} K(x^i, \cdot) \right]$$

Our loss function is convex:  $L(x, g, \nabla g) = \|\nabla g(x)\|^2 - 2\tilde{c}(x)g(x)$

# Differential LSTD learning on RKHS

Optimal solution in one dimension

$\nabla$ -LSTD-RKHS ERM:

$$g^* = \arg \min_{g \in \mathcal{H}} \frac{1}{N} \sum_{i=1}^N \left\{ (g'(x^i))^2 - 2\tilde{c}_N(x^i)g(x^i) \right\} + \lambda \|g\|_{\mathcal{H}}^2$$

$$\text{Solution: } g^*(y) = \sum_{i=1}^N \left\{ \beta_i^{0*} K(x^i, y) + \beta_i^{1*} \partial_x K(x^i, y) \right\}, \quad y \in \mathbb{R}$$

# Differential LSTD learning on RKHS

Optimal solution in one dimension

$\nabla$ -LSTD-RKHS ERM:

$$g^* = \arg \min_{g \in \mathcal{H}} \frac{1}{N} \sum_{i=1}^N \left\{ (g'(x^i))^2 - 2\tilde{c}_N(x^i)g(x^i) \right\} + \lambda \|g\|_{\mathcal{H}}^2$$

$$\text{Solution: } g^*(y) = \sum_{i=1}^N \left\{ \beta_i^{0*} K(x^i, y) + \beta_i^{1*} \partial_x K(x^i, y) \right\}, \quad y \in \mathbb{R}$$

Notation:

$$\begin{aligned} M_{00}(i, j) &:= K(x^i, x^j), & M_{10}(i, j) &:= \frac{\partial K}{\partial x}(x^i, x^j) \\ M_{01}(i, j) &:= \frac{\partial K}{\partial y}(x^i, x^j), & M_{11}(i, j) &:= \frac{\partial^2 K}{\partial x \partial y}(x^i, x^j) \\ \tilde{\zeta}_j &:= \tilde{c}_N(x^j), & \beta^T &= [\beta_1^0, \dots, \beta_N^0, \beta_1^1, \dots, \beta_N^1] \end{aligned}$$

# Differential LSTD learning on RKHS

Optimal solution in one dimension

$\nabla$ -LSTD-RKHS ERM:

$$g^* = \arg \min_{g \in \mathcal{H}} \frac{1}{N} \sum_{i=1}^N \left\{ (g'(x^i))^2 - 2\tilde{c}_N(x^i)g(x^i) \right\} + \lambda \|g\|_{\mathcal{H}}^2$$

$$\text{Solution: } g^*(y) = \sum_{i=1}^N \left\{ \beta_i^{0*} K(x^i, y) + \beta_i^{1*} \partial_x K(x^i, y) \right\}, \quad y \in \mathbb{R}$$

Computation:  $\beta^* = M^{-1}b$

$$M = \frac{1}{N} \begin{bmatrix} \frac{M_{01}}{M_{11}} \end{bmatrix} [M_{10} \mid M_{11}] + \lambda \begin{bmatrix} \frac{M_{00}}{M_{10}} \mid \frac{M_{01}}{M_{11}} \end{bmatrix}$$

$$b = \frac{1}{N} \begin{bmatrix} \frac{M_{00}}{M_{10}} \end{bmatrix}$$

# Differential LSTD learning on RKHS

## Simplified solution

Drawback : Complexity grows linearly with  $d$ , since  $\beta^* \in \mathbb{R}^{(d+1) \times N}$

**Simplified solution** : By considering the finite-dimensional function class -  
 $\mathcal{H}_N := \text{span}\{K_{x^j} : 1 \leq j \leq N\}$

$$g^*(y) = \sum_{j=1}^N \beta_j^* K(x^j, y)$$

$$\beta^* = M^{-1}b$$

$$\text{where, } M := N^{-1}M_{01}M_{10} + \lambda M_{00}, \quad b := N^{-1}M_{00}\tilde{\zeta}$$

**Surprising empirical observation** : Simplified solution does as good as the optimal solution for  $d \leq 5$ .

# Applications to Nonlinear filtering

## Feedback Particle Filter

Goal : To obtain estimates of the state of a stochastic dynamical system based on noisy partial observations.

Kalman filter is optimal for a linear Gaussian system.

For nonlinear systems, conditional distribution fails to be Gaussian, cannot be captured by a finite set of parameters.

Particle filters are Monte-Carlo approximations of the nonlinear filter.



# Applications to Nonlinear filtering

## Feedback Particle Filter

Problem:

**Signal:** 
$$dX_t = a(X_t)dt + dB_t, \quad X_0 \sim \rho_0^*,$$

**Observation:** 
$$dZ_t = c(X_t)dt + dW_t,$$

- $X_t \in \mathbb{R}^d$  is the state at time  $t$ .
- $\{Z_t : t \geq 0\}$  is the observation process.
- $a(\cdot), c(\cdot)$  are  $C^1$  functions.
- $\{B_t\}, \{W_t\}$  are mutually independent Wiener processes.

# Applications to Nonlinear filtering

## Feedback Particle Filter

Problem:

**Signal:** 
$$dX_t = a(X_t)dt + dB_t, \quad X_0 \sim \rho_0^*,$$

**Observation:** 
$$dZ_t = c(X_t)dt + dW_t,$$

- $X_t \in \mathbb{R}^d$  is the state at time  $t$ .
- $\{Z_t : t \geq 0\}$  is the observation process.
- $a(\cdot), c(\cdot)$  are  $C^1$  functions.
- $\{B_t\}, \{W_t\}$  are mutually independent Wiener processes.
- $\rho_t^* := P(X_t | \{Z_s : s \leq t\})$  is the posterior distribution.

# Applications to Nonlinear filtering

## Feedback Particle Filter

Feedback particle filter (FPF) [Yang 13] is motivated by techniques from mean-field optimal control.

# Applications to Nonlinear filtering

## Feedback Particle Filter

Feedback particle filter (FPF) [Yang 13] is motivated by techniques from mean-field optimal control.

$N$  *particles* are propagated in the form of a controlled system.

$$dX_t^i = \underbrace{a(X_t^i)dt + dB_t^i}_{\text{Propagation}} + \underbrace{dU_t^i}_{\text{Update}}, \quad i = 1 \text{ to } N$$

- $X_t^i \in \mathbb{R}$  is the state of the  $i^{th}$  particle at time  $t$
- $U_t^i$  is the control input applied to  $i^{th}$  particle
- $\{B_t^i\}$  are mutually independent standard Wiener processes.

# Applications to Nonlinear filtering

## Feedback Particle Filter

Feedback particle filter (FPF) [Yang 13] is motivated by techniques from mean-field optimal control.

$N$  *particles* are propagated in the form of a controlled system.

$$dX_t^i = \underbrace{a(X_t^i)dt + dB_t^i}_{\text{Propagation}} + \underbrace{dU_t^i}_{\text{Update}}, \quad i = 1 \text{ to } N$$

- $X_t^i \in \mathbb{R}$  is the state of the  $i^{th}$  particle at time  $t$
- $U_t^i$  is the control input applied to  $i^{th}$  particle
- $\{B_t^i\}$  are mutually independent standard Wiener processes.

Approximation of  $\rho_t^*$  :

$$\rho_t^* \approx \rho_t^{(N)}(A) = \frac{1}{N} \sum_{i=1}^N \mathbb{I}\{X_t^i \in A\}, \quad A \subset \mathbb{R}.$$

# Applications to Nonlinear filtering

## Feedback Particle Filter

Asymptotically exact filter obtained by minimizing the KL divergence between  $\rho_t^*$  and  $\rho_t$  (see [Yang 13]):

$$dU_t^i = K_t(X_t^i) \circ \overbrace{(dZ_t - \frac{1}{2}[c(X_t^i) + \hat{c}_t]dt)}^{dI_t^i},$$

$I_t^i$  : Innovations process.

$K_t$  : FPF gain, similar in nature to the Kalman gain.

# Applications to Nonlinear filtering

## Feedback Particle Filter

Asymptotically exact filter obtained by minimizing the KL divergence between  $\rho_t^*$  and  $\rho_t$  (see [Yang 13]):

$$dU_t^i = K_t(X_t^i) \circ \overbrace{(dZ_t - \frac{1}{2}[c(X_t^i) + \hat{c}_t]dt)}^{dI_t^i},$$

$I_t^i$  : Innovations process.

$K_t$  : FPF gain, similar in nature to the Kalman gain.





Figure: Finite- $N$  implementation

# Applications to Nonlinear filtering

## Feedback Particle Filter

KF: 
$$d\mu_t = a(\mu_t)dt + \underbrace{K_{\text{kal}}(dZ_t - c(\mu_t)dt)}_{\text{update}}$$



Kalman filter




# Applications to Nonlinear filtering


## Feedback Particle Filter

KF: 
$$d\mu_t = a(\mu_t)dt + \underbrace{K_{\text{kal}}(dZ_t - c(\mu_t)dt)}_{\text{update}}$$

FPF: 
$$dX_t^i = a(X_t^i)dt + dB_t^i + \underbrace{K_t(X_t^i) \circ (dZ_t - \frac{1}{2}[c(X_t^i) + \hat{c}_t]dt)}_{\text{update}}$$



Kalman filter



Feedback particle filter (FPF)

# Applications to Nonlinear filtering

## FPF Gain function

Representation:  $K_t = \nabla h$

$h$  solves Poisson's equation:  $\mathcal{D}h = -\nabla U \cdot \nabla h + \Delta h = -\tilde{c}$ .

# Applications to Nonlinear filtering

## FPF Gain function

Representation:  $K_t = \nabla h$

$h$  solves **Poisson's equation**:  $\mathcal{D}h = -\nabla U \cdot \nabla h + \Delta h = -\tilde{c}$ .

Approximations to  $K$  can be obtained by

$$\min_{g \in \mathcal{H}} \|K - \hat{K}\|_{L^2}^2 = \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

# Applications to Nonlinear filtering

## FPF Gain function

Representation:  $\mathbf{K}_t = \nabla h$

$h$  solves **Poisson's equation**:  $\mathcal{D}h = -\nabla U \cdot \nabla h + \Delta h = -\tilde{c}$ .

Approximations to  $\mathbf{K}$  can be obtained by

$$\min_{g \in \mathcal{H}} \|\mathbf{K} - \hat{\mathbf{K}}\|_{L^2}^2 = \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

Can be solved using  $\nabla$ -LSTD learning

# Applications to Nonlinear filtering

## FPF Gain function

Representation:  $K_t = \nabla h$

$h$  solves **Poisson's equation**:  $\mathcal{D}h = -\nabla U \cdot \nabla h + \Delta h = -\tilde{c}$ .

Approximations to  $K$  can be obtained by

$$\min_{g \in \mathcal{H}} \|K - \hat{K}\|_{L^2}^2 = \min_{g \in \mathcal{H}} \|\nabla h - \nabla g\|_{L^2}^2$$

FPF implementation requires online gain estimation for each  $t$ .

- $\nabla$ -LSTD-RKHS with optimal mean
- $\nabla$ -LSTD-RKHS with memory

# Applications to Nonlinear filtering

▽-LSTD-RKHS-OM

**Constant gain approximation** for  $K$  is the minimizer obtained over all deterministic vectors:

$$\hat{K}^* := \arg \min_{\hat{K} \in \mathbb{R}^d} \|K - \hat{K}\|_{L^2}^2$$

# Applications to Nonlinear filtering

▽-LSTD-RKHS-OM

**Constant gain approximation** for  $K$  is the minimizer obtained over all deterministic vectors:

$$\hat{K}^* := \arg \min_{\hat{K} \in \mathbb{R}^d} \|K - \hat{K}\|_{L^2}^2$$

Solution is evidently the mean,  $\hat{K}^* = E[K]$ .

$$\hat{K}_k^* = \langle K, e_k \rangle_{L^2}$$

# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-OM

**Constant gain approximation** for  $K$  is the minimizer obtained over all deterministic vectors:

$$\hat{K}^* := \arg \min_{\hat{K} \in \mathbb{R}^d} \|K - \hat{K}\|_{L^2}^2$$

Solution is evidently the mean,  $\hat{K}^* = E[K]$ .

$$\begin{aligned} \hat{K}_k^* &= \langle K, e_k \rangle_{L^2} \\ &= \langle \nabla h, e_k \rangle_{L^2} \end{aligned}$$



# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-OM

**Constant gain approximation** for  $K$  is the minimizer obtained over all deterministic vectors:

$$\hat{K}^* := \arg \min_{\hat{K} \in \mathbb{R}^d} \|K - \hat{K}\|_{L^2}^2$$

Solution is evidently the mean,  $\hat{K}^* = E[K]$ .

$$\begin{aligned} \hat{K}_k^* &= \langle K, e_k \rangle_{L^2} \\ &= \langle \nabla h, e_k \rangle_{L^2} \\ &= -\langle \mathcal{D}h, x_k \rangle_{L^2} = \langle \tilde{c}, x_k \rangle_{L^2} \end{aligned}$$

# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-OM

**Constant gain approximation** for  $K$  is the minimizer obtained over all deterministic vectors:

$$\hat{K}^* := \arg \min_{\hat{K} \in \mathbb{R}^d} \|K - \hat{K}\|_{L^2}^2$$

Solution is evidently the mean,  $\hat{K}^* = E[K]$ .

$$\begin{aligned} \hat{K}_k^* &= \langle K, e_k \rangle_{L^2} \\ &= \langle \nabla h, e_k \rangle_{L^2} \\ &= -\langle \mathcal{D}h, x_k \rangle_{L^2} = \langle \tilde{c}, x_k \rangle_{L^2} \end{aligned}$$

Empirical approximation:

$$\hat{K}_k^* \approx \frac{1}{N} \sum_{i=1}^N [c(x^i) - \hat{c}] x_k^i$$

# Applications to Nonlinear filtering

$\nabla$ -LSTD-RKHS-OM

Redefine the approximation to  $K$  as,

$$\nabla g = \widehat{K}^* + \nabla \tilde{g}$$

Modified ERM with constraints is:

$$\begin{aligned} \tilde{g}^* &:= \arg \min_{\tilde{g} \in \mathcal{H}} \|\nabla h - \widehat{K}^* - \nabla \tilde{g}\|_{L_2}^2 \\ \text{s.t.} \quad &\langle \partial_{x_k} \tilde{g}, 1 \rangle_{L_2} = 0, \quad 1 \leq k \leq d \end{aligned}$$

# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-OM

Redefine the approximation to  $K$  as,

$$\nabla g = \widehat{K}^* + \nabla \tilde{g}$$

Modified ERM with constraints is:

$$\begin{aligned} \tilde{g}^* &:= \arg \min_{\tilde{g} \in \mathcal{H}} \|\nabla h - \widehat{K}^* - \nabla \tilde{g}\|_{L_2}^2 \\ \text{s.t. } &\langle \partial_{x_k} \tilde{g}, 1 \rangle_{L_2} = 0, \quad 1 \leq k \leq d \end{aligned}$$

Solution obtained by finding a saddle point for the Lagrangian

$$L(\tilde{g}, \mu) := \|\nabla h - \widehat{K}^* - \nabla \tilde{g}\|_{L_2}^2 + \langle \mu, \nabla \tilde{g} \rangle_{L_2}$$

where  $\mu \in \mathbb{R}^d$  are the Lagrange multipliers.

# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-OM

Redefine the approximation to  $K$  as,

$$\nabla g = \widehat{K}^* + \nabla \tilde{g}$$

Modified ERM with constraints is:

$$\begin{aligned} \tilde{g}^* &:= \arg \min_{\tilde{g} \in \mathcal{H}} \|\nabla h - \widehat{K}^* - \nabla \tilde{g}\|_{L_2}^2 \\ \text{s.t.} \quad &\langle \partial_{x_k} \tilde{g}, 1 \rangle_{L_2} = 0, \quad 1 \leq k \leq d \end{aligned}$$

Using  $\mathcal{H}_N := \text{span}\{K_{x^j} : 1 \leq j \leq N\}$ ,  $\beta$  and  $\mu$  can be obtained by solving  $N + d$  linear equations

$$K = \widehat{K}^* + \nabla \tilde{g}^*$$

# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-memory

Gain updates are done at  $t = n\delta$ , where  $\delta$  is the inter-sampling time.

Continuity :  $K_n = K_{t_n} \approx K_{t_{n-1}}$  if  $\delta \approx 0$ .

# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-memory

Gain updates are done at  $t = n\delta$ , where  $\delta$  is the inter-sampling time.

Continuity :  $K_n = K_{t_n} \approx K_{t_{n-1}}$  if  $\delta \approx 0$ .

Adding a regularizer term to the loss function:

$$g_n^* := \arg \min_{g \in \mathcal{H}} \frac{1}{N} \sum_{j=1}^N L_n(x_n^j, g, \nabla g) + \lambda \|g\|_{\mathcal{H}}^2$$

$$L_n(x, g, \nabla g) := \|\nabla g(x)\|^2 - 2\tilde{c}_N(x)g(x) + \underbrace{\lambda_{mem} \|\nabla g(x) - \nabla g_{n-1}(x)\|^2}_{\text{continuity penalty}}$$

# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-memory

Gain updates are done at  $t = n\delta$ , where  $\delta$  is the inter-sampling time.  
 Continuity :  $K_n = K_{t_n} \approx K_{t_{n-1}}$  if  $\delta \approx 0$ .

$$\beta_n^* = M^{-1}b$$

where,

$$M = (1 + \lambda_{mem}) \sum_{k=1}^d M_{10}^T M_{10} + \lambda N M_{00}$$

$$b = M_{00} \tilde{\zeta} + \lambda_{mem} \sum_{k=1}^d M_{10}^T K_{n-1,k}$$



# Applications to Nonlinear filtering

## $\nabla$ -LSTD-RKHS-memory

Gain updates are done at  $t = n\delta$ , where  $\delta$  is the inter-sampling time.

Continuity :  $K_n = K_{t_n} \approx K_{t_{n-1}}$  if  $\delta \approx 0$ .

$$\beta_n^* = M^{-1}b$$

$$\text{where,} \quad M = (1 + \lambda_{mem}) \sum_{k=1}^d M_{10}^T M_{10} + \lambda N M_{00}$$

$$b = M_{00} \tilde{\zeta} + \lambda_{mem} \sum_{k=1}^d M_{10}^T K_{n-1,k}$$

Both these improvements can be applied independently or simultaneously.

# Applications to Nonlinear filtering

Markov kernel approximation [Taghvaei 16]

Approximates the transition kernel of the Langevin diffusion:

$$h = P_\epsilon h + \int_0^\epsilon P_s(c - \hat{c})ds,$$

Give the expression for kernel approx. Empirical approximation on particle locations  $x^i$ :

$$h_i = \sum_{j=1}^N T_{ij} h_j + \epsilon(c - \hat{c}), \text{ for } i = 1 \text{ to } N$$

Gain K is then obtained by approximating the gradient  $\nabla h_i$ .

# Application to nonlinear filtering

## Numerical example - Gain approximation for a fixed $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$$T = 10^4, 10^5, 10^6 \text{ with } \delta = 0.01, N = 1000$$


# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$$T = 10^4, 10^5, 10^6 \text{ with } \delta = 0.01, N = 1000$$



$\nabla$ -LSTD with  $\psi_i = x^i \rho_1(x)$ ,  $\psi_{i+1} = x^i \rho_2(x)$  with  $1 \leq i \leq 5$ .


# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$$N = 100, 500, 1000$$



$\nabla$ -LSTD-L with  $\psi_i = x^i \rho_1(x)$ ,  $\psi_{i+1} = x^i \rho_2(x)$  with  $1 \leq i \leq 5$ .


# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$$N = 100, 500, 1000$$



Grid-search using  $K_\varepsilon := e^{-\frac{\|x-x'\|^2}{4\varepsilon}}$ , yields and  $\varepsilon = 0.1$  and  $\lambda = 10^{-2}$ .


# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$N = 100, 500, 1000$



$\nabla$ -LSTD-RKHS-N with Gaussian kernel,  $\varepsilon = 0.1$  and  $\lambda = 10^{-2}$


# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$N = 100, 500, 1000$



$\nabla$ -LSTD-RKHS-2N with Gaussian kernel,  $\varepsilon = 0.1$  and  $\lambda = 10^{-2}$




# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$N = 100, 500, 1000$




$\nabla$ -LSTD-RKHS-OM with Gaussian kernel,  $\varepsilon = 0.1$  and  $\lambda = 10^{-2}$

# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture  
 $c(x) \equiv x$   
 $N = 100, 500, 1000$



Markov kernel approximation with  $\epsilon = 0.1$

# Application to nonlinear filtering


Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$$N = 100, 500, 1000$$

Parameters  $\{\beta_i\}$  from RKHS simplified, optimal and OM methods




# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:** For a fixed  $t$ ,  $\rho_t$  a Gaussian mixture

$$c(x) \equiv x$$

$$N = 100, 500, 1000$$






Histogram of MSEs obtained from 100 independent trials

# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:**  $\rho(x) = \prod_{k=1}^d \rho_k(x_k)$   
 $c(x) = C^T x$ , where  $C = \mathbb{I}_d$   
 $d = 2, 5, 10, \quad N = 1000$






$\nabla$ -LSTD-RKHS-OM

# Application to nonlinear filtering

Numerical example - Gain approximation for a fixed  $t$

**Example:**  $\rho(x) = \prod_{k=1}^d \rho_k(x_k)$   
 $c(x) = C^T x$ , where  $C = \mathbb{I}_d$   
 $d = 2, 5, 10, \quad N = 1000$



Markov kernel approximation

# Application to nonlinear filtering

## Numerical example - Gain for a nonlinear oscillator model

**Example:**  $\rho(x)$  is a mixture of von Mises densities on a circle  
$$d\vartheta = \omega dt + \sigma_B dB_t \mod 2\pi,$$
$$dZ_t = c(\vartheta)dt + \sigma_W dW_t, \quad c(\vartheta) = \frac{1}{2}[1 + \cos(\vartheta)]$$


# Application to nonlinear filtering

## Numerical example - Gain for a nonlinear oscillator model

**Example:**  $\rho(x)$  is a mixture of von Mises densities on a circle

$$d\vartheta = \omega dt + \sigma_B dB_t \mod 2\pi,$$

$$dZ_t = c(\vartheta)dt + \sigma_W dW_t, \quad c(\vartheta) = \frac{1}{2}[1 + \cos(\vartheta)]$$




$\nabla$ -LSTD-L with  $\psi_i = \sin(ix)$ ,  $\psi_{i+1} = \cos(ix)$  with  $1 \leq i \leq \ell/2$ ,  
 $\ell = 4, 6, 8$ .



# Applications to Nonlinear filtering

## Numerical example - Parameter estimation


**Example:** Parameter estimation with bimodal prior  
Observations: parameter plus additive noise with  $\sigma_W = 1$ .



# Applications to Nonlinear filtering

## Numerical example - Parameter estimation


**Example:** Parameter estimation with bimodal prior  
Observations: parameter plus additive noise with  $\sigma_W = 1$ .



# Applications to Nonlinear filtering

## Numerical example - Parameter estimation


**Example:** Parameter estimation with bimodal prior  
Observations: parameter plus additive noise with  $\sigma_W = 1$ .



# Applications to Nonlinear filtering

## Numerical example - Parameter estimation


**Example:** Parameter estimation with bimodal prior  
 Observations: parameter plus additive noise with  $\sigma_W = 1$ .



# Applications to Nonlinear filtering

## Numerical example - Parameter estimation


**Example:** Parameter estimation with bimodal prior  
 Observations: parameter plus additive noise with  $\sigma_W = 1$ .



# Applications to Nonlinear filtering

## Numerical example - Nonlinear 2d ship dynamics model


**Example:** Nonlinear ship dynamics model in 2d.  
 Observations:  $c(x) = \arctan(x_1/x_2)$  with std. deviation  $\approx 18^\circ$ .



# Applications to Nonlinear filtering

## Numerical example - Nonlinear 2d ship dynamics model


**Example:** Nonlinear ship dynamics model in 2d.  
 Observations:  $c(x) = \arctan(x_1/x_2)$  with std. deviation  $\approx 18^\circ$ .



# Applications to Nonlinear filtering

## Numerical example - Nonlinear 2d ship dynamics model

**Example:** Nonlinear ship dynamics model in 2d.  
 Observations:  $c(x) = \arctan(x_1/x_2)$  with std. deviation  $\approx 18^\circ$ .






# Applications to Nonlinear filtering

## Numerical example - Nonlinear 2d ship dynamics model

**Example:** Nonlinear ship dynamics model in 2d.  
 Observations:  $c(x) = \arctan(x_1/x_2)$  with std. deviation  $\approx 18^\circ$ .



# Applications to Nonlinear filtering

Numerical example - Nonlinear 2d ship dynamics model

Summary table of RMSEs from 100 trials

Type of filter	$\Sigma_1 = I_{2 \times 2}$	$\Sigma_2 = 5I_{2 \times 2}$	Lost track ( $\Sigma_2$ )
FPF RKHS-OM	0.9023	1.6254	4 times
FPF RKHS mem.	0.9162	1.9408	7 times
FPF const. gain	1.3060	2.3231	14 times
SIR PF	3.1481	4.2648	57 times
EKF	6.5203	18.441	93 times

# Applications to MCMC

## Introduction to MCMC

In many applications, we need to compute

$$\eta = \int c(x) \rho(x) \, dx$$

- $c: \mathbb{R}^\ell \rightarrow \mathbb{R}$  is a measurable function.
- $\rho$  is a target probability density in  $\mathbb{R}^\ell$ .

Markov-Chain Monte Carlo (MCMC) methods provide numerical algorithms to obtain estimates:

$$\eta_t = \frac{1}{t} \int_0^t c(\Phi(s)) \, ds$$

$\Phi$  is a Markov process with steady state distribution  $\rho$ .

# Applications to MCMC

## Asymptotic Variance

Estimates  $\eta_t$  obey a Central Limit Theorem,

$$\sqrt{t}(\eta_t - \eta) \xrightarrow{d} N(0, \gamma^2)$$

Rate of convergence captured by **asymptotic variance**

$$\gamma^2 = \lim_{t \rightarrow \infty} \mathbb{E} \left[ \left( \frac{1}{\sqrt{t}} \int_0^t (c(\Phi(s)) - \eta) ds \right)^2 \right]$$

Alternate representation in terms of covariance

$$\gamma^2 := \int_{-\infty}^{\infty} R(s) ds, \quad R(s) = \mathbb{E}[\tilde{c}(\Phi_0) \tilde{c}(\Phi_s)]$$

# Applications to MCMC

## Asymptotic Variance

Representation in terms of  $h$  [Glynn 96]:

$$\gamma^2 = 2\langle h, \tilde{c} \rangle$$

# Applications to MCMC

## Asymptotic Variance

Representation in terms of  $h$  [Glynn 96]:

$$\begin{aligned}\gamma^2 &= 2\langle h, \tilde{c} \rangle \\ &= 2\|\nabla h\|_{L^2}^2 \\ &\text{(For Langevin diffusion)}\end{aligned}$$

# Applications to MCMC

## Control Variates

**Goal:** To minimize asymptotic variance.

# Applications to MCMC

## Control Variates

**Goal:** To minimize asymptotic variance.

**Idea:** Modify the estimator using control variates [Henderson 01, CTCN]

$$c_g = c + \underbrace{\mathcal{D}g}_{\text{Control variate}}, \quad \text{where } g \in \mathcal{H}$$

$$\eta_t^g = \frac{1}{t} \int_0^t c_g(\Phi_s) ds$$

For asymptotically unbiased estimates, control variate needs to have zero-mean with respect to  $\rho$ .



# Applications to MCMC

## Control Variates

**Goal:** To minimize asymptotic variance.

**Idea:** Modify the estimator using control variates [Henderson 01, CTCN]

$$c_g = c + \underbrace{\mathcal{D}g}_{\text{Control variate}}, \quad \text{where } g \in \mathcal{H}$$

$$\eta_t^g = \frac{1}{t} \int_0^t c_g(\Phi_s) ds$$

For asymptotically unbiased estimates, control variate needs to have zero-mean with respect to  $\rho$ .

For any  $g \in C^2$ ,  $Pg$  is invariant with  $\rho \implies \langle \mathcal{D}g, 1 \rangle_{L^2} = 0$ .

# Applications to MCMC

## Optimal control variates

Let  $\tilde{h}_g = h - g$ ,

$$\begin{aligned}\mathcal{D}\tilde{h}_g &= \mathcal{D}h - \mathcal{D}g \\ &= -c_g + \eta\end{aligned}$$

Thus  $\tilde{h}_g$  is the solution to Poisson's equation with forcing function  $c_g$ .

# Applications to MCMC

## Optimal control variates

Let  $\tilde{h}_g = h - g$ ,

$$\begin{aligned}\mathcal{D}\tilde{h}_g &= \mathcal{D}h - \mathcal{D}g \\ &= -c_g + \eta\end{aligned}$$

Thus  $\tilde{h}_g$  is the solution to Poisson's equation with forcing function  $c_g$ .

Asymptotic variance of the new estimator:

$$\gamma_g^2 = 2\langle \tilde{h}_g, \tilde{c}_g \rangle_{L^2}$$

# Applications to MCMC

## Optimal control variates

Let  $\tilde{h}_g = h - g$ ,

$$\begin{aligned}\mathcal{D}\tilde{h}_g &= \mathcal{D}h - \mathcal{D}g \\ &= -c_g + \eta\end{aligned}$$

Thus  $\tilde{h}_g$  is the solution to Poisson's equation with forcing function  $c_g$ .

Asymptotic variance of the new estimator:

$$\begin{aligned}\gamma_g^2 &= 2\langle \tilde{h}_g, \tilde{c}_g \rangle_{L^2} \\ &= 2\|\nabla h - \nabla g\|_{L^2}^2 \\ &\quad \text{(For Langevin diffusion)}\end{aligned}$$

# Applications to MCMC

## Optimal control variates

Let  $\tilde{h}_g = h - g$ ,

$$\begin{aligned}\mathcal{D}\tilde{h}_g &= \mathcal{D}h - \mathcal{D}g \\ &= -c_g + \eta\end{aligned}$$

Thus  $\tilde{h}_g$  is the solution to Poisson's equation with forcing function  $c_g$ .

Asymptotic variance of the new estimator:



$$\begin{aligned}\gamma_g^2 &= 2\langle \tilde{h}_g, \tilde{c}_g \rangle_{L^2} \\ &= 2\|\nabla h - \nabla g\|_{L^2}^2 \\ &\quad \text{(For Langevin diffusion)}\end{aligned}$$

Can be minimized using  $\nabla$ -LSTD algorithms.

# Applications to MCMC

## Numerical Examples - ULA



**Example:** Unadjusted Langevin algorithm (ULA)



# Applications to MCMC

## Numerical Examples - RWM


**Example:** Random walk Metropolis (RWM)



# Applications to MCMC

## Numerical Examples - ULA v RWM

Unadjusted Langevin algorithm (ULA) vs Random walk Metropolis (RWM)





# Applications to MCMC

## Numerical Examples - Sample variance v Asymptotic variance

### Sample variance v Asymptotic variance

$$\sigma^2 = \langle \tilde{c}, \tilde{c} \rangle_{L^2} = R(0)$$

- Sample variance

# Applications to MCMC

## Numerical Examples - Sample variance v Asymptotic variance

### Sample variance v Asymptotic variance

$$\sigma^2 = \langle \tilde{c}, \tilde{c} \rangle_{L^2} = R(0) \quad - \text{Sample variance}$$

$$\gamma^2 = 2 \langle h, \tilde{c} \rangle_{L^2} = \int_{-\infty}^{\infty} R(s) ds \quad - \text{Asymptotic variance}$$

# Applications to MCMC

## Numerical Examples - Sample variance v Asymptotic variance

### Sample variance v Asymptotic variance

$$\sigma^2 = \langle \tilde{c}, \tilde{c} \rangle_{L^2} = R(0) \quad - \text{Sample variance}$$

$$\gamma^2 = 2 \langle h, \tilde{c} \rangle_{L^2} = \int_{-\infty}^{\infty} R(s) ds \quad - \text{Asymptotic variance}$$

Minimizing  $\sigma^2$  is easier than minimizing  $\gamma^2$  [Oates 14, Papamarkou 14]

Appropriate only if samples are i.i.d.

Minimizing  $\sigma^2$  also minimizes  $\gamma^2$  ?

# Applications to MCMC

## Numerical Examples - Sample variance v Asymptotic variance

### Sample variance v Asymptotic variance

$$\sigma^2 = \langle \tilde{c}, \tilde{c} \rangle_{L^2} = R(0) \quad - \text{Sample variance}$$

$$\gamma^2 = 2 \langle h, \tilde{c} \rangle_{L^2} = \int_{-\infty}^{\infty} R(s) ds \quad - \text{Asymptotic variance}$$

Minimizing  $\sigma^2$  is easier than minimizing  $\gamma^2$  [Oates 14, Papamarkou 14]

Appropriate only if samples are i.i.d.



Minimizing  $\sigma^2$  also minimizes  $\gamma^2$  ? NO !

# Applications to MCMC

## Numerical Examples - Sample variance vs Asymptotic variance

**Example:** Unadjusted Langevin algorithm (ULA)

$$c(x) \equiv x$$



# Applications to MCMC

## Numerical Examples - Logistic regression with RWM sampling

**Example:** Logistic Regression for Swiss bank notes

$X \in \mathbb{R}^{200 \times 4}$  - Covariates measurements of four features of 200 bank notes.

$\{Y_i \in \{0, 1\}, 1 \leq i \leq 200\}$  - Binary response variables.


$\Theta \in \mathbb{R}^4$  - Regression coefficients for classification.

$$\rho(\Theta | \{X_i, Y_i\}_1^N) \propto \exp \left( \underbrace{\sum_{i=1}^N \{Y_i \Theta^T X_i - \log(1 + e^{\Theta^T X_i})\}}_{\text{Likelihood}} - \underbrace{\frac{\Theta^T \Sigma^{-1} \Theta}{2}}_{\text{Prior}} \right)$$

# Applications to MCMC

## Numerical Examples - Logistic Regression with RWM sampling

**Example:** Logistic Regression for Swiss bank notes



Box plots of estimates of  $\Theta_4$ .

# Conclusions

- Differential LSTD learning based approaches to approximate solution to Poisson's equation for the Langevin diffusion.
  - Finite dimensional basis.
  - RKHS.
- Two interesting applications
  - Asymptotic variance reduction in MCMC algorithms.
  - Gain function approximation in Feedback particle filter.
- Extended the approach to include reversible Markov chains.



# References



A. Radhakrishnan, A. Devraj and S. Meyn, "Learning techniques for feedback particle filter design," *2016 IEEE 55th Conference on Decision and Control (CDC)*, Las Vegas, NV, 2016.



A. Radhakrishnan, S. Meyn, "Feedback particle filter design using a differential-loss reproducing kernel Hilbert space," *2018 American Control Conference (ACC)*, Milwaukee, WI, 2018.



S.P.Meyn, "Control Techniques for Complex Networks", *Cambridge University Press*, Dec 2007.



S. Henderson. *Variance Reduction Via an Approximating Markov Process*. PhD thesis, Stanford University, Stanford, California, 1997.



T. Yang, P. G. Mehta and S. P. Meyn, "Feedback Particle Filter," in *IEEE Transactions on Automatic Control*, vol. 58, no. 10, pp. 2465-2480, Oct. 2013.



A. M. Devraj and S. P. Meyn, "Differential LSTD learning for value function approximation," *2016 IEEE 55th Conference on Decision and Control (CDC)*, Las Vegas, NV, 2016.



D.X. Zhou, "Derivative reproducing properties for kernel methods in learning theory," *Journal of Computational and Applied Mathematics*, Vol. 220, Issues 1?2, 2008.

# Thank You!

## Questions?