



HABIB UNIVERSITY

Data Structures & Algorithms

CS/CE 102/171 Spring 2025

Instructor: Maria Samad

Quiz # 3 Solution

QUESTION 1: HASHING (15 marks)

- a. A hash table contains player IDs (integers) as keys, and their names as values. Write an algorithm using Hashing that gets the value, i.e., name of the player from the Hash table when the key, i.e., player ID is provided. The key will be taken as input from the user. Assume N to be the size of existing hash table. Hash function to be used is Divide Modulo, and collisions must be handled using Key Offset Rehashing with the Secondary Hash function defined as: $(id * 2) + 2 \text{ mod size}$. If they key is not found, return a message stating “Not Found”, otherwise return the value. You may use two separate lists to represent keys and values just like you did in the labs. **YOU ARE NOT ALLOWED TO USE ANY ADDITIONAL DATA STRUCTURES, APART FROM THE ONES SPECIFIED IN THE QUESTION.**

Solution:

- $N \rightarrow$ given size of the hashtable
 - Keys $\rightarrow$ a list of keys given for the hashtable
 - Values $\rightarrow$ a list of values given for the hashtable
 - player_id $\rightarrow$ Take input from the user
 - slot_index = student_id mod N
 - if Keys [slot_index] == player_id, this means we have found the ID we were looking for so return its value, i.e., the name of the player as follows:
 - return Values [slot_index]
 - Otherwise, it needs to probe further to find the required ID using Key Offset Rehashing, as follows:
 - iteration = 1
 - new_index = slot_index
 - $h2 = (player_id * 2) + 2 \text{ mod } N$
 - while (Keys [new_index] != player_id or iteration <= N), keep probing as follows:
 - new_index = (slot_index + (iteration * h2)) mod N
 - if Keys [new_index] == player_id, then we have found the player, so return its name as follows:
 - ❖ return Values [new_index]
 - Otherwise, continue probing as follows:
 - ❖ iteration += 1
 - return “Not Found”
- b. For the given hash table, dry run the algorithm from part (a), to get the values for the player ID = 85. Don't just write down the answer by looking at the hash table. Show each step to get the value. Assume size of hash table is 9.
Keys = [99, None, 24, None, 49, 40, 15, 33, 85]
Values = [“Faiz”, None, “Bilal”, None, “Dania”, “Zecana”, “Ariana”, “Emaad”, “Abdul Ahad”]

Solution:

- slot_index = $85 \text{ mod } 9 = 4$
 - Keys [4] = $49 \neq 85$, so continue probing
- $h2 = ((85 * 2) + 2) \text{ mod } 9 = 1$
 - new_index = $(4 + (1 * 1)) \text{ mod } 9 = 5$
 - Keys [5] = $40 \neq 85$, so continue probing
- new_index = $(4 + (2 * 1)) \text{ mod } 9 = 6$
 - Keys [6] = $15 \neq 85$, so continue probing
- new_index = $(4 + (3 * 1)) \text{ mod } 9 = 7$
 - Keys [7] = $33 \neq 85$, so continue probing
- new_index = $(4 + (4 * 1)) \text{ mod } 9 = 8$
 - Keys [8] = 85, which is the desired player_id so return the player's name, i.e., Abdul Ahad

QUESTION 2: GRAPH TRAVERSAL (10 marks)



For the given graph, apply the Breadth-First Search Traversal Algorithm with the starting vertex = 2. Show all the working for each step. Construct the corresponding BFS graph, by showing all the tree edges and non-tree edges. Use different notation to represent each edge, and specify a legend for it. Follow ascending order in choosing vertices. Calculate the total cost of traversal in the end.

IF YOU ARE MISSING ANY INTERIM CALCULATIONS, YOU WILL NOT GET ANY MARKS

Solution:

Date:

BFS Start vertex = 2



Legend: $\rightarrow$ Tree Edge
 $---\rightarrow$ Back Edge
 $\rightsquigarrow$ Cross Edge

Queue	Visited List	Path
[3, 4]	[2*]	
[4, 1, 2, 5]	[2*, 3]	2 $\rightarrow$ 3? $\checkmark$
[3, 2, 5, 2, 5]	[2*, 3, 4]	2 $\rightarrow$ 4? $\checkmark$
[2, 5, 2, 5, 3, 6]	[2, 3*, 4, 1]	3 $\rightarrow$ 1? $\checkmark$
[5, 2, 5, 3, 6]	"	3 $\rightarrow$ 2? $\times$
[5, 3, 6, 3, 4, 6, 7]	[2, 3*, 4, 1, 5]	3 $\rightarrow$ 5? $\checkmark$
[5, 3, 6, 3, 4, 6, 7]	[2, 3, 4*, 1, 5]	4 $\rightarrow$ 2? $\times$
[3, 6, 3, 4, 6, 7]	"	4 $\rightarrow$ 5? $\times$
[6, 3, 4, 6, 7]	[2, 3, 4, 1*, 5]	1 $\rightarrow$ 3? $\times$
[3, 4, 6, 7, 1, 5]	[2, 3, 4, 1*, 5, 6]	1 $\rightarrow$ 6? $\checkmark$
[4, 6, 7, 1, 5]	[2, 3, 4, 1, 5*, 6]	5 $\rightarrow$ 3? $\times$
[6, 7, 1, 5]	"	5 $\rightarrow$ 4? $\times$
[7, 1, 5]	"	5 $\rightarrow$ 6? $\times$
[1, 5, 5]	[2, 3, 4, 1, 5*, 6, 7]	5 $\rightarrow$ 7? $\checkmark$
[5, 5]	[2, 3, 4, 1, 5, 6*, 7]	6 $\rightarrow$ 1? $\times$
[5]	"	6 $\rightarrow$ 5? $\times$
[]	[2, 3, 4, 1, 5, 6, 7*]	7 $\rightarrow$ 5? $\times$


Path = 2 $\rightarrow$ 3, 2 $\rightarrow$ 4, 3 $\rightarrow$ 1, 3 $\rightarrow$ 5, 1 $\rightarrow$ 6, 5 $\rightarrow$ 7
Cost = 1 + 1 + 1 + 1 + 1 + 1 = 6

QUESTION 3: SHORTEST PATH (15 marks)

- a. Run the Dijkstra's Algorithm on the following directed, weighted graph, to get the shortest path of every vertex from the starting vertex, P. Specify shortest path of every vertex from the starting vertex, and calculate the cost of this shortest path. Draw the reduced graph after Dijkstra's algorithm has successfully been implemented, showing the shortest paths between all the vertices. Show your complete working. **IF YOU DO NOT SHOW ANY WORKING, YOU WILL NOT GET MARKS FOR IT**

Solution:**Date:**


Dijkstra starting vertex = P



Visited	P	Q	R	S	T	U	V
P	0	∞	∞	∞	∞	∞	∞
Q		3	10	∞	∞	∞	∞
T			10	8	5	∞	∞
S			10	8		13	∞
R			10			10	14
U						10	14
V							14

Src → Dest	Shortest Path	Cost
P → Q	Q, P ⇒ P → Q	3
P → R	R, P ⇒ P → R	10
P → S	S, Q, P ⇒ P → Q → S	3 + 5 = 8
P → T	T, Q, P ⇒ P → Q → T	3 + 2 = 5
P → U	U, S, Q, P ⇒ P → Q → S → U	3 + 5 + 2 = 10
P → V	V, S, Q, P ⇒ P → Q → S → V	3 + 5 + 6 = 14

Reduced graph for shortest path:



b. For the same graph, as given in part (a), define the Graph using Adjacency Map Representation

Solution:

$$G(V, E) = \{ \begin{array}{l} P : [(Q, 3), (R, 10)], \\ Q : [(S, 5), (T, 2)], \\ R : [(T, 1)], \\ S : [(U, 2), (V, 6)], \\ T : [(S, 7), (U, 8)], \\ U : [(V, 4)], \\ V : [] \end{array} \}$$