



HIT Academy
Heliopolis Institute of Technology
Information Technology Department

AI Brain Tumor Detection

Prepared by

Abdelhalim Gamal Abdelhalim
Ahmed Khaled Soliman
Nader Adel Asham
Tarik Mohamed Sobhi
Aya Mohamed Ibrahim
Hasnaa Ahmed Abdullah
Juman Hussein Mohamed
Mariem Alaa Mohamed

Supervised by

Dr. Hala Ahmed Ali
Information Technology Department
Faculty of Computers and Information
Mansoura University

(2026)

Acknowledgment

In the name of Allah, the Most Merciful, the Most Compassionate. All praise is due to Allah, the Lord of the Worlds, and Prophet Mohammed - peace and blessings be upon him.

First and foremost, we would like to thank Allah for supporting us in completing this project.

Many people contributed to this project in one way or another, and we offer our regards and blessings to all those who supported us during the completion of this work.

We would like to express our deep appreciation and gratitude to our supervisor, Dr. Hala Ahmed Ali, for her meticulous supervision, constructive criticism, expertise, constant professional guidance, fruitful comments, and continuous unlimited help. We would not have been able to start and finish this work without her guidance.

We are also grateful to the faculty members of the Information Technology Department at HIT Academy and for their support and encouragement throughout this project.

Finally, we would like to thank our families and friends for their unwavering support and patience during the completion of this work.

Summary

Brain tumors are one of the most aggressive forms of cancer and a leading cause of death worldwide. Early and accurate diagnosis is critical for improving patient outcomes and treatment planning. However, traditional manual interpretation of MRI scans by radiologists can be time-consuming and subject to inter-reader variability. This project aims to develop an integrated AI-based system for brain tumor detection and classification using MRI images.

The proposed system consists of three main components: a CNN-based classification model for tumor detection and multi-class classification (Glioma, Meningioma, Pituitary, No Tumor), a U-Net model for tumor segmentation to delineate tumor boundaries, and a rule-based recommendation engine (chatbot) for patient consultation. A web-based interface was developed using Flask, HTML, CSS, and JavaScript, allowing users to upload MRI images, view diagnosis results, interact with the chatbot, and download bilingual PDF reports.

The classification model was trained on 16,696 balanced MRI images and achieved 98.47% accuracy, 98.25% precision, 98.75% recall, and 98.50% F1-score on the test dataset. The No Tumor class achieved perfect recall (100%), confirming that no healthy case was misdiagnosed. The U-Net segmentation model achieved a 100% detection rate but limited IoU (9.14%) due to the small dataset size.

The system supports three user roles (Patient, Doctor, Admin) with JWT-based authentication and complete data persistence using SQLite. The results demonstrate that the proposed system is effective and reliable for brain tumor diagnosis, providing a user-friendly interface for patients and doctors.

Contents

Acknowledgment	i
Abstract	ii
List of Figures	vi
List of Tables	vii
List of Acronyms	viii
1 Introduction	1
1.1 Overview	1
1.2 Problem Statement	2
1.3 Objectives	2
2 Literature Review	4
2.1 Introduction	4
2.2 Basic Concepts	4
2.2.1 Brain Tumors	4
2.2.2 Magnetic Resonance Imaging (MRI)	5
2.2.3 Deep Learning	5
2.2.4 Data Augmentation	6
2.2.5 Performance Evaluation Metrics	7
2.3 Related Work	8
2.3.1 Brain Tumor Classification Studies	8
2.3.2 Brain Tumor Segmentation Studies	8
2.3.3 Hybrid Techniques	8
2.4 Research Gaps	8
3 System Analysis	10
3.1 Introduction	10
3.2 Classification Component Analysis	10
3.2.1 Decomposition Diagram	10
3.2.2 Use Case Diagram	12
3.2.3 Sequence Diagram	15
3.2.4 Activity Diagram	18
3.3 Segmentation Component Analysis	21
3.3.1 Decomposition Diagram	21
3.3.2 Use Case Diagram	24

3.3.3	Sequence Diagram	27
3.3.4	Activity Diagram	30
3.4	Chatbot Component Analysis	33
3.4.1	Decomposition Diagram	33
3.4.2	Use Case Diagram	36
3.4.3	Sequence Diagram	39
3.4.4	Activity Diagram	42
3.5	Project Timeline (Gantt Chart)	45
4	System Design	46
4.1	System Architecture	46
4.1.1	Architecture Diagram Walkthrough	47
4.1.2	Complete Data Flow Sequence	49
4.1.3	Role-Based Access Control Summary	50
4.2	Frontend Design	51
4.2.1	Page Layout	51
4.2.2	User Interface Components	52
4.2.3	Responsive Design	53
4.2.4	PDF Report Generation	53
4.3	Backend Design	54
4.3.1	Architecture Overview	54
4.3.2	Data Flow	56
4.3.3	API Endpoints	56
4.3.4	Request/Response Format	57
4.3.5	Port Configuration	59
4.3.6	Technologies Used	60
4.3.7	Authentication & Authorization	60
4.3.8	Error Handling	60
4.3.9	Database Schema Integration	61
4.3.10	API Documentation	61
4.4	Database Design	62
4.4.1	Entity Relationship Diagram (ERD)	62
4.4.2	Database Tables Description	62
4.4.3	Table Relationships	63
4.4.4	AI Model Integration	64
4.4.5	Recommendation Engine Integration	67
5	Implementation and Results	71
5.1	Experimental Setup	71
5.2	Dataset Description	71
5.3	Implementation Details	72
5.3.1	Libraries and Dependencies	72
5.3.2	Data Preprocessing	72
5.3.3	Model Architecture	72
5.3.4	Training Hyperparameters	73
5.3.5	Training Code Snippet	73
5.4	Classification Results	74
5.4.1	Overall Performance Metrics	74

5.4.2	Class-wise Performance	75
5.4.3	Confusion Matrix	75
5.4.4	Training Curves	76
5.4.5	Sample Predictions	77
5.5	Segmentation Results	78
5.5.1	Model Architecture	78
5.5.2	Model Parameters	78
5.5.3	Experimental Setup	79
5.5.4	Segmentation Results	79
5.5.5	Performance Comparison	79
5.5.6	Visual Example	79
5.5.7	Discussion	80
5.5.8	Limitations and Future Work	80
6	Conclusion and Future Work	81
6.1	Conclusion	81
6.2	Future Work	82

List of Figures

3.1	Decomposition Diagram of the Classification Component	10
3.2	Use Case Diagram of the Classification Component	12
3.3	Sequence Diagram of the Classification Component	15
3.4	Activity Diagram of the Classification Component	18
3.5	Decomposition Diagram of the Segmentation Component	21
3.6	Use Case Diagram of the Segmentation Component	24
3.7	Sequence Diagram of the Segmentation Component	27
3.8	Activity Diagram of the Segmentation Component	30
3.9	Decomposition Diagram of the Chatbot Component	33
3.10	Use Case Diagram of the Chatbot Component	36
3.11	Sequence Diagram of the Chatbot Component	39
3.12	Activity Diagram of the Chatbot Component	42
3.13	Gantt Chart of the Complete Project Timeline	45
4.1	Overall System Architecture of the Proposed Brain Tumor Detection System	46
4.2	Frontend Page Layout	51
4.3	Backend Architecture Overview	54
4.4	Entity Relationship Diagram	62
4.5	Recommendation Engine Architecture	67
5.1	Confusion Matrix of the Classification Model	75
5.2	Training and Validation Accuracy and Loss Curves	76
5.3	Sample Predictions for Each Tumor Class	77
5.4	LSMAtt-Net Segmentation	79

List of Tables

2.1	Properties of various MRI sequences	5
3.1	Activity Summary for Classification Workflow	20
3.2	Segmentation System Modules	23
3.3	Actors in Segmentation Use Case Diagram	25
3.4	Key Use Cases in Segmentation System	26
3.5	Sequence Steps for Segmentation Process	29
3.6	Activities in Segmentation Workflow	32
3.7	Chatbot System Modules	35
3.8	Actors in Chatbot Use Case Diagram	37
3.9	Key Use Cases in Chatbot System	38
3.10	Sequence Steps for Chatbot Process	41
3.11	Activities in Chatbot Workflow	44
4.1	User Roles and Permissions	50
4.2	Authentication API Endpoints	57
4.3	Tumor Detection API Endpoints	57
4.4	Reports API Endpoints	57
4.5	Chatbot API Endpoints	57
4.6	Port Configuration	59
4.7	Technologies Stack	60
4.8	Error Codes and Responses	60
4.9	Recommendation Engine API	67
4.10	Conversation Flow	68
4.11	Glioma Recommendations	69
4.12	Meningioma Recommendations	69
4.13	Pituitary Recommendations	69
4.14	No Tumor Recommendations	69
5.1	Experimental Environment	71
5.2	Dataset Distribution After Balancing (80/20 Split)	71
5.3	CNN Model Architecture Summary	73
5.4	Training Hyperparameters	73
5.5	Overall Classification Performance Metrics	74
5.6	Class-wise Performance Metrics	75
5.7	Training and Validation Metrics per Epoch	76
5.8	LSMAtt-Net Model Parameters	78
5.9	LSMAtt-Net Segmentation Results	79
5.10	Comparison with State-of-the-Art Methods	79

List of Acronyms

Acronym	Description
AI	Artificial Intelligence
ML	Machine Learning
DL	Deep Learning
CNN	Convolutional Neural Network
U-Net	U-shaped Convolutional Network for Biomedical Segmentation
MRI	Magnetic Resonance Imaging
CAD	Computer-Aided Diagnosis
API	Application Programming Interface
JWT	JSON Web Token
SQL	Structured Query Language
ORM	Object-Relational Mapping
TP	True Positive
TN	True Negative
FP	False Positive
FN	False Negative
IoU	Intersection over Union
DSC	Dice Similarity Coefficient
AUC	Area Under the Curve
ROC	Receiver Operating Characteristic
WHO	World Health Organization
CNS	Central Nervous System
GUI	Graphical User Interface
HTTP	Hypertext Transfer Protocol
REST	Representational State Transfer
GPU	Graphics Processing Unit
RAM	Random Access Memory
CPU	Central Processing Unit
OS	Operating System
PET	Positron Emission Tomography
CT	Computed Tomography
FLAIR	Fluid-Attenuated Inversion Recovery
DWI	Diffusion-Weighted Imaging

Chapter 1

Introduction

1.1 Overview

Brain tumors are defined as an abnormal and uncontrolled growth of cells originating from the brain tissue [1]. They are considered one of the most aggressive forms of cancer and a leading cause of death worldwide, requiring precise diagnosis and treatment planning to improve patient outcomes [2]. According to the World Health Organization (WHO), approximately 300,000 new cases of brain tumors are diagnosed annually [3], with high mortality rates especially in late-diagnosed cases. In Saudi Arabia, pediatric patients have the highest number of reported brain and central nervous system (CNS) cancers, making them the second-most common type of cancer among children after leukemia [4].

Medical imaging modalities play a crucial role in the non-invasive detection and diagnosis of brain tumors. Magnetic Resonance Imaging (MRI) is considered the clinical gold standard for diagnosing brain tumors in both adults and children due to its high spatial resolution, superior soft tissue contrast, and lack of ionizing radiation [1]. MRI provides detailed images of brain structures and can be enhanced with gadolinium to better visualize abnormal tissues. Different MRI sequences, such as T1-weighted, T2-weighted, and FLAIR, offer complementary information about tumor characteristics, with most tumors appearing hypointense on T1-weighted images and hyperintense on T2-weighted and FLAIR images [1].

However, traditional manual interpretation of MRI scans by radiologists can be challenging, time-consuming, and subject to inter-reader variability, which depends on the medical practitioner's competency [1]. This is particularly problematic in pediatric cases where tumors may be small and difficult to detect [4]. Therefore, developing automated and reliable diagnostic tools is crucial for improving the accuracy and efficiency of brain tumor detection and classification.

Artificial Intelligence (AI) and its subfields, particularly Machine Learning (ML) and Deep Learning (DL), have emerged as powerful tools in medical image analysis [1]. Computer-Aided Diagnosis (CAD) systems, which integrate AI techniques, have been developed to assist radiologists in interpreting imaging data, reducing reading time, and enhancing diagnostic accuracy and stability [1]. Deep Learning, particularly Convolutional Neural Networks (CNNs), has revolutionized the field by automatically learning relevant features from raw data without the need for manual feature engineering [2]. CNNs have demonstrated exceptional success in brain tumor classification, achieving accuracy levels that often match or exceed human expert performance [2].

1.2 Problem Statement

Despite significant advances in medical imaging and AI, several challenges remain in the accurate diagnosis of brain tumors:

- **Subjectivity of Human Interpretation:** Diagnosis accuracy heavily depends on the physician's experience. Manual analysis of MRI scans is prone to inter-reader variability and depends heavily on the radiologist's expertise, potentially leading to diagnostic errors [1].
- **Difficulty in Tumor Differentiation:** Different tumor types (e.g., Glioma, Meningioma, Pituitary) appear similar in standard MRI sequences, making accurate classification challenging even for experienced specialists [2].
- **Need for Precise Tumor Localization:** Diagnosis is not limited to identifying the presence of a tumor; accurate segmentation to determine its size, shape, and exact location is critical for surgical planning and treatment decisions [1].
- **Data Scarcity and Imbalance:** Most medical datasets suffer from class imbalance, where some tumor types are underrepresented. Deep learning models typically require large, well-annotated datasets for training, which are often difficult to obtain in the medical domain due to patient privacy concerns and the high cost of expert annotation [2].
- **Lack of Integrated Systems:** Patients face difficulties getting quick medical advice, and many existing systems focus on either classification or segmentation in isolation, often lacking the interpretability needed to build trust with clinicians [2].

1.3 Objectives

This project aims to develop an integrated and interpretable AI system for brain tumor diagnosis using MRI images. The specific objectives are:

1. **Tumor Detection:** Develop an AI model for brain tumor detection in MRI images to accurately detect the presence or absence of a brain tumor.
2. **Multi-Class Tumor Classification:** Classify tumors into four types: Glioma, Meningioma, Pituitary, and No Tumor using Deep Learning techniques [2].
3. **Tumor Segmentation:** Perform tumor segmentation by drawing boundaries around the affected area to precisely delineate tumor boundaries and visualize the affected region [1].
4. **Address Data Challenges:** Apply data augmentation techniques to artificially expand the training dataset and mitigate the effects of class imbalance, improving model generalization and robustness [2].
5. **Ensure Interpretability:** Utilize Explainable AI (XAI) techniques to provide visual explanations of model decisions, highlighting the image regions that most influence the classification. This is crucial for building trust and enabling clinical validation [2].

6. **Build a Medical Chatbot:** Develop a medical chatbot for patient consultation to provide quick medical advice and assist patients in understanding their diagnosis.
7. **Create a User-Friendly Interface:** Create a user-friendly web interface enabling users to upload images and get results quickly.

Chapter 2

Literature Review

2.1 Introduction

This chapter presents a comprehensive review of the fundamental concepts related to brain tumor diagnosis and the artificial intelligence techniques used in this field. It also surveys the related work in brain tumor classification, segmentation, and medical chatbots, identifying the research gaps that this project aims to address.

2.2 Basic Concepts

2.2.1 Brain Tumors

Brain tumors are defined as an abnormal and uncontrolled growth of cells originating from the brain tissue [1]. They can be classified based on their origin, location, growth rate, and histological characteristics. The World Health Organization (WHO) has categorized brain tumors into over 120 types, with grading systems ranging from Grade I (least malignant) to Grade IV (most malignant) [5].

Types of Brain Tumors

This project focuses on four common types of brain tumors:

- **Glioma:** A primary brain tumor that arises from glial cells. It is the most common type of primary brain tumor in adults and can be further classified into Low-Grade Gliomas (LGG) and High-Grade Gliomas (HGG). Gliomas account for a significant portion of pediatric brain tumors as well [4].
- **Meningioma:** Typically benign tumors that originate from the meninges, the protective layers surrounding the brain and spinal cord. They are often slow-growing and represent about 36% of primary brain tumors [1].
- **Pituitary Tumor:** Benign tumors mainly arising from the pituitary gland in the anterior fossa. Despite being benign, their difficult location can make them challenging to manage [4].
- **No Tumor:** Healthy brain tissue samples used as a control group for classification tasks [2].

2.2.2 Magnetic Resonance Imaging (MRI)

Magnetic Resonance Imaging (MRI) is considered the clinical gold standard for diagnosing brain tumors in both adults and children due to its high spatial resolution, superior soft tissue contrast, and lack of ionizing radiation [1]. MRI provides detailed images of brain structures and can be enhanced with gadolinium to better visualize abnormal tissues [1].

MRI Sequences

Different MRI sequences offer complementary information about tumor characteristics [1]:

- **T1-weighted (T1-w):** Most tumors appear hypointense (dark) on T1-weighted images. This sequence is useful for distinguishing between gray and white matter.
- **T2-weighted (T2-w):** Most tumors exhibit hyperintense (bright) intensity on T2-weighted images. This sequence is sensitive to water content and is therefore well-suited for conditions where water accumulates within brain tissues.
- **FLAIR (Fluid-Attenuated Inversion Recovery):** This sequence is utilized to differentiate between cerebrospinal fluid (CSF) and abnormalities in the brain. Tumors typically appear bright on FLAIR images while CSF appears dark.

Table 2.1 summarizes the properties of various MRI sequences [1].

Table 2.1: Properties of various MRI sequences

Tissue	T1-w	T2-w	FLAIR
White Matter	Bright	Dark	Dark
Gray Matter	Gray	Dark	Dark
CSF	Dark	Bright	Dark
Tumor	Dark	Bright	Bright

2.2.3 Deep Learning

Convolutional Neural Networks (CNN)

Convolutional Neural Networks (CNN) are specialized types of deep neural networks designed specifically for processing grid-structured data such as images [1]. CNN consists of several main layers:

- **Convolutional Layers:** Extract features from images using multiple filters. These layers learn to detect patterns such as edges, textures, and shapes.
- **Pooling Layers:** Reduce image dimensions while preserving important features, reducing computational complexity and preventing overfitting. Common pooling operations include max pooling and average pooling.
- **Fully Connected Layers:** Perform the final classification based on the features extracted by the convolutional and pooling layers. Every neuron in this layer is connected to every neuron in the previous layer.

Transfer Learning

Transfer Learning is a technique where a pre-trained model on a large dataset (such as ImageNet) is reused for a new task [1]. This approach offers several advantages:

- **Reduced training time:** No need to train the model from scratch.
- **Need for less data:** Suitable for limited-size medical datasets.
- **Better performance:** Benefits from features learned from large and diverse datasets.

Popular CNN Architectures

Several CNN architectures have been successfully applied to brain tumor classification [1]:

- **AlexNet:** One of the pioneering deep CNN architectures that achieved breakthrough performance on ImageNet classification.
- **VGG16 and VGG19:** Simple and regular models consisting of 16 and 19 layers respectively, characterized by their uniform structure and ease of use.
- **ResNet50:** A 50-layer deep model using skip connections (residual connections) to solve the vanishing gradient problem, allowing for training of much deeper networks.
- **GoogleNet (Inception):** Uses inception modules that capture multi-scale features through parallel convolutions of different sizes.
- **DenseNet:** Features dense connections between layers, where each layer receives inputs from all previous layers, promoting feature reuse and reducing the number of parameters.

2.2.4 Data Augmentation

Data Augmentation is a technique used to increase the size and diversity of the dataset by creating new images from existing ones through simple transformations [1]. This technique is particularly important in the medical field where obtaining new data is expensive and difficult, and it helps address issues with unequal class distribution and data scarcity.

Common types of transformations used in medical image augmentation include [2]:

- **Rotation:** Rotating the image at different angles (e.g., 20 degrees clockwise or counterclockwise).
- **Flip:** Flipping the image horizontally or vertically.
- **Zoom:** Changing the image scale (enlarging or reducing).
- **Brightness Adjustment:** Modifying image brightness to simulate varying lighting conditions.
- **Shift:** Moving the image in different directions (horizontal or vertical shifts).

- **Shear:** Slightly distorting the image along an axis.
- **Noise Injection:** Adding random noise to images to simulate real-world imperfections such as sensor noise or transmission errors.

2.2.5 Performance Evaluation Metrics

To evaluate the performance of the proposed models, several metrics are commonly used in medical image analysis [1]. These metrics are based on four fundamental elements: True Positive (TP), True Negative (TN), False Positive (FP), and False Negative (FN).

1. **True Positive (TP):** The model correctly predicts the positive class. For example, the model correctly identifies that a tumor is present and the actual label is tumor.
2. **True Negative (TN):** The model correctly predicts the negative class. For example, the model correctly identifies that no tumor is present and the actual label is no tumor.
3. **False Positive (FP) - Type I Error:** The model incorrectly predicts the positive class. For example, the model predicts that a tumor is present, but the actual image has no tumor. This is also known as a "false alarm."
4. **False Negative (FN) - Type II Error:** The model incorrectly predicts the negative class. For example, the model predicts that no tumor is present, but the actual image has a tumor. This is considered more dangerous in medical diagnosis because it misses a real disease.

The following metrics are derived from these four fundamental values:

- **Accuracy (ACC):** The ratio of correct predictions to total predictions.

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN} \quad (1)$$

- **Precision (PR):** The ratio of correct positive predictions to total positive predictions.

$$Precision = \frac{TP}{TP + FP} \quad (2)$$

- **Recall (Sensitivity):** The ratio of correct positive predictions to total actual positive cases.

$$Recall = \frac{TP}{TP + FN} \quad (3)$$

- **Specificity (SPE):** The ratio of correct negative predictions to total actual negative cases.

$$Specificity = \frac{TN}{TN + FP} \quad (4)$$

- **F1-Score:** The harmonic mean of precision and recall.

$$F1 = 2 \times \frac{Precision \times Recall}{Precision + Recall} \quad (5)$$

- **Dice Similarity Coefficient (DSC):** Measures the spatial overlap between the segmented region and the ground-truth.

$$DSC = \frac{2 \times TP}{2 \times TP + FP + FN} \quad (6)$$

- **Jaccard Index (JI) or Intersection over Union (IoU):** Calculates the overlap percentage between prediction and ground-truth.

$$Jaccard = \frac{TP}{TP + FP + FN} \quad (7)$$

2.3 Related Work

2.3.1 Brain Tumor Classification Studies

Sultan et al. (2019) proposed a CNN-based approach to classify brain tumors into three types (glioma, meningioma, and pituitary) achieving 96.13% and 98.7% accuracy on two datasets [6]. Khan et al. (2020) compared custom CNN with pre-trained models and achieved 100% accuracy using their custom CNN [7]. Ozcan et al. (2021) developed a customized CNN for glioma grade prediction achieving 97.1% accuracy [8]. Srinivas and Parvathi (2026) developed an explainable AI framework using a 4-conv-1-dense-1-dropout CNN achieving 95.86% accuracy with Grad-CAM and LIME explanations [2].

2.3.2 Brain Tumor Segmentation Studies

Pereira et al. (2016) proposed a CNN-based segmentation using small 3x3 kernels achieving Dice scores of 0.88, 0.83, and 0.77 [9]. Razzak et al. (2018) introduced a two-pathway-group CNN achieving DSC of 89.2% [10]. The U-Net architecture [11] is widely used as a foundation for many biomedical image segmentation tasks.

2.3.3 Hybrid Techniques

Ahmmed et al. (2017) combined SVM and ANN achieving 97.44% and 97.37% accuracy. Gurbina et al. (2019) combined DWT and SVM achieving 99% accuracy. Farajzadeh et al. (2023) developed a hybrid U-Net achieving 98.93% segmentation and 98.81% classification accuracy.

2.4 Research Gaps

Based on the comprehensive literature review, several research gaps have been identified:

1. **Lack of Integrated Systems:** Most systems focus on either classification or segmentation in isolation [2].

2. **Insufficient Handling of Imbalanced Data:** Many studies do not adequately address class imbalance [2].
3. **Limited Interpretability:** Few studies integrate explainable AI techniques [2].
4. **Absence of Medical Chatbot Integration:** Scarcity of systems integrating diagnostic tools with medical chatbots.
5. **Lack of User-Friendly Interfaces:** Many solutions lack interfaces for healthcare professionals and patients.

Chapter 3

System Analysis

3.1 Introduction

This chapter presents the system analysis phase of the proposed AI Brain Tumor Detection System. System analysis is a critical phase in software development that focuses on understanding the system requirements, identifying the actors and their interactions, and modeling the system's behavior and structure. This chapter includes the analysis of three main system components: Classification, Segmentation, and Chatbot. For each component, four key diagrams are presented: Decomposition Diagram, Use Case Diagram, Sequence Diagram, and Activity Diagram. Finally, a Gantt Chart is provided to illustrate the overall project timeline.

3.2 Classification Component Analysis

3.2.1 Decomposition Diagram




Figure 3.1: Decomposition Diagram of the Classification Component

1. **Data Engineering Module:** Responsible for preparing the dataset for training. This module includes:
 - **Dataset Collection:** Gathering MRI images from public sources (Kaggle).
 - **Data Augmentation:** Applying transformations (rotation, flipping, zoom) to increase dataset size and improve generalization.
 - **Normalization:** Scaling pixel values from $[0, 255]$ to $[0, 1]$ for stable model training.
 - **Data Balancing:** Addressing class imbalance to ensure equal representation of all tumor types.
2. **CNN Architecture Module:** Defines the structure of the neural network:
 - **Convolutional Layers:** Extract spatial features from input images using learnable filters.
 - **Pooling Layers:** Reduce spatial dimensions while preserving important features.
 - **Activation Functions:** Introduce non-linearity (ReLU) to enable learning complex patterns.
 - **Fully Connected Layers:** Perform final classification based on extracted features.
3. **Model Training Module:** Handles the learning process:
 - **Forward Propagation:** Pass input data through the network to generate predictions.
 - **Loss Function:** Binary Cross-Entropy measures the difference between predictions and ground truth.
 - **Optimizer (Adam):** Updates network weights to minimize the loss function.
 - **Backward Propagation:** Computes gradients and propagates errors backward through the network.
4. **Model Evaluation Module:** Assesses model performance using various metrics:
 - **Accuracy:** Overall correctness of predictions.
 - **Precision and Recall:** Measure of prediction quality and completeness.
 - **F1-Score:** Harmonic mean of precision and recall.
 - **Confusion Matrix:** Visual representation of correct and incorrect classifications per class.
 - **ROC-AUC:** Evaluates the model's ability to distinguish between classes.

These four modules work sequentially to transform raw MRI images into accurate tumor classifications, providing a clear hierarchical view of the classification system's architecture.

3.2.2 Use Case Diagram




Figure 3.2: Use Case Diagram of the Classification Component

Actors

The diagram includes three main actors:

- **Patient:** A regular user who can upload MRI images, view diagnosis results, download reports, chat with the bot, and view their history.
- **Doctor:** A medical professional who has all patient privileges plus the ability to view all patients' history, view patient details, add medical notes, and verify diagnoses.
- **Admin:** A system administrator who has all doctor privileges plus the ability to manage users, monitor system performance, backup the database, and perform system maintenance.

Authentication Use Cases

- **Register Account:** Allows new users to create an account.
- **Login:** Enables registered users to access the system.
- **Reset Password:** Allows users to recover or change their password.
- **Verify Credentials:** An <<include>> relationship from Login, responsible for validating user credentials.
- **Logout:** Allows users to securely exit the system.

Core Classification Use Cases

- **Upload MRI Image:** The primary use case where users submit MRI scans for analysis. This use case includes:
 - <<include>> **Validate Format:** Checks that the uploaded file has a supported format (JPG, PNG, JPEG).
 - <<include>> **Process Image:** Handles image preprocessing (resizing, normalization).
- **View Diagnosis Result:** Displays the classification outcome including tumor type and confidence score. This use case includes <<include>> **Classify Tumor** (the AI model inference).
- **Download Report:** Allows users to download a PDF report of their diagnosis, including <<include>> **Generate PDF**.
- **Chat with Bot:** Enables users to interact with the medical chatbot for recommendations, with <<extend>> relationships to additional information services.
- **View History:** Allows users to access their previous diagnosis records.

Doctor-Only Use Cases

- **View All Patients History:** Access to all patient records.
- **View Patient Details:** View detailed information about a specific patient.
- **Add Medical Note:** Add professional notes to a patient's diagnosis.
- **Verify Diagnosis:** Confirm or correct the AI-generated diagnosis.

Admin-Only Use Cases

- **Manage Users:** Add, edit, or delete user accounts.
- **Monitor System Performance:** Track system health and performance metrics.
- **Backup Database:** Create backups of the system database.
- **System Maintenance:** Perform routine system maintenance tasks.

Relationships

The diagram uses two types of relationships:

- **<<include>>:** Indicates that one use case requires another to complete (mandatory).
- **<<extend>>:** Indicates optional behavior that may be triggered under certain conditions.

This use case diagram provides a comprehensive view of all functionalities available to different user roles within the classification system.

3.2.3 Sequence Diagram




Figure 3.3: Sequence Diagram of the Classification Component

Step-by-Step Flow

1. Authentication (Steps 1-4):

- The Patient enters their login credentials (username and password).
- The System forwards these credentials to the Database for verification.
- Upon successful validation, the Database returns confirmation, and the System notifies the Patient of successful login.

2. Image Upload and Validation (Steps 5-7):

- The Patient uploads an MRI image to the System.
- The System validates the image format to ensure it is supported (JPG, PNG, JPEG).
- The System then processes the image (resizing to 224×224 pixels, normalization).

3. AI Model Inference (Steps 8-9):

- The preprocessed image is sent to the AI Model for classification.
- The AI Model returns the classification result, including the tumor type and confidence score.

4. Result Storage and Display (Steps 10-11):

- The System saves the diagnosis result to the Database, linking it to the user ID.
- The System displays the result to the Patient, showing the tumor type and medical recommendations.

5. Chatbot Interaction (Steps 12-13): (Optional)

- The Patient can ask questions about the tumor via the Chatbot.
- The Chatbot processes the query and returns relevant information and recommendations.

6. Report Generation (Steps 14-16):

- The Patient requests to download a report.
- The System generates a PDF report containing the diagnosis results.
- The PDF file is returned to the Patient for download.

System Components

The diagram involves four main components:

- **Patient:** The end-user initiating the interactions.
- **System:** The backend server handling requests and coordinating between components.
- **Database:** Stores user credentials and diagnosis results.
- **AI Model:** Performs tumor classification on MRI images.
- **Chatbot:** Provides additional medical information and recommendations.

Key Observations

- The authentication step is a prerequisite for all other operations.
- The AI Model is called only once per diagnosis, after image preprocessing.
- Results are persistently stored in the Database for future reference (view history).
- Chatbot interaction is optional and occurs after diagnosis results are displayed.
- PDF generation happens on-demand when the user requests a report download.

This sequence diagram provides a clear, time-ordered view of how the classification system processes a tumor diagnosis request from start to finish.

3.2.4 Activity Diagram




Figure 3.4: Activity Diagram of the Classification Component

Step-by-Step Workflow

1. User Login:

- The user enters their login credentials (username and password).
- The system verifies the credentials against the database.

2. Login Decision Node:

- **If credentials are invalid (No):** An error message "Invalid Credentials" is displayed, and the user is prompted to re-enter their credentials.
- **If credentials are valid (Yes):** The system displays "Login Successful" and proceeds to the image upload step.

3. Image Upload:

- The user uploads an MRI image for analysis.
- The system validates the file format (JPG, PNG, JPEG).

4. Format Validation Decision Node:

- **If the format is invalid (No):** An error message "Invalid Format" is displayed, and the user is prompted to upload a valid file.
- **If the format is valid (Yes):** The system proceeds to process the image.

5. Image Processing:

- The system preprocesses the image (resizing to 224×224 pixels, normalization to $[0,1]$ range).

6. AI Model Classification:

- The preprocessed image is sent to the AI Model for classification.
- The model performs inference and returns the tumor type (Glioma, Meningioma, Pituitary, or No Tumor) along with a confidence score.

7. Result Storage:

- The system saves the diagnosis result to the database, linking it to the user ID for future reference.

8. Result Display:

- The final diagnosis result (tumor type, confidence score, and recommendations) is displayed to the user.

Key Features of the Activity Diagram

- **Decision Nodes:** Two critical decision points are included:
 - Credential validation (ensures only authenticated users can proceed).
 - Format validation (ensures only supported image formats are processed).
- **Looping Behavior:**
 - Invalid credentials lead back to the login step.
 - Invalid file format leads back to the upload step.
- **Linear Flow After Validation:** Once both validations pass, the process follows a linear path through preprocessing, classification, storage, and display.
- **End-to-End Coverage:** The diagram covers the entire process from initial login to final result display, including error handling and retry mechanisms.

Summary of Activities

Table 3.1: Activity Summary for Classification Workflow

Activity	Description
Login	User authentication
Image Upload	User submits MRI image
Format Validation	Check supported file types
Image Processing	Resize and normalize image
AI Classification	Model inference for tumor type
Result Storage	Save diagnosis to database
Result Display	Show diagnosis to user

This activity diagram provides a clear, visual representation of the tumor classification workflow, including error handling and decision points, making it an essential tool for understanding the system's operational logic.

3.3 Segmentation Component Analysis

3.3.1 Decomposition Diagram




Figure 3.5: Decomposition Diagram of the Segmentation Component

Input and Preprocessing Modules

- **Input Module:** Receives the raw MRI image as input.
- **Preprocessing Module:** Prepares the image for segmentation, including resizing to 128×128 pixels, normalization, and noise reduction.

Encoder Module (Downsampling Path)

The encoder module progressively reduces the spatial dimensions while increasing the number of feature channels. It consists of four layers:

- **Layer 1 (Conv + Pool):** Applies two convolutional operations (32 filters) followed by max pooling.
- **Layer 2 (Conv + Pool):** Applies two convolutional operations (64 filters) followed by max pooling.
- **Layer 3 (Conv + Pool):** Applies two convolutional operations (128 filters) followed by max pooling.
- **Layer 4 (Conv + Pool):** Applies two convolutional operations (256 filters) followed by max pooling.

Bottleneck Module

- **Conv Layers (512×2):** The deepest part of the network, consisting of two convolutional layers with 512 filters each. This captures the most abstract features of the input image.

Decoder Module (Upsampling Path)

The decoder module progressively restores the spatial dimensions while concatenating features from the encoder via skip connections:

- **UpConv 1 + Skip Connection:** Upsampling with concatenation from Layer 4 (256 filters).
- **UpConv 2 + Skip Connection:** Upsampling with concatenation from Layer 3 (128 filters).
- **UpConv 3 + Skip Connection:** Upsampling with concatenation from Layer 2 (64 filters).
- **UpConv 4 + Skip Connection:** Upsampling with concatenation from Layer 1 (32 filters).

Output and Visualization Modules

- **Output Module:** Generates the final segmentation mask. Includes:
 - **Activation:** Sigmoid activation function to produce pixel-wise probabilities.
 - **Segmentation Mask:** Binary mask where tumor pixels are marked as 1 and background as 0.
- **Visualization Module:** Overlays the segmentation mask on the original MRI image to produce a visual representation of the tumor location.
- **Tumor Overlay on MRI:** The final visualized output showing the original MRI image with the tumor region highlighted.

Module Summary

Table 3.2: Segmentation System Modules

Module	Function
Input Module	Receives raw MRI image
Preprocessing Module	Resize and normalize image
Encoder Module (4 layers)	Downsample and extract features
Bottleneck Module	Capture abstract features (512 filters)
Decoder Module (4 UpConv)	Upsample with skip connections
Output Module	Generate binary segmentation mask
Visualization Module	Overlay mask on original MRI

This decomposition provides a clear hierarchical view of the U-Net architecture used for tumor segmentation, showing how the input MRI image is transformed through encoding, bottleneck, decoding, and visualization stages to produce the final tumor overlay.

3.3.2 Use Case Diagram




Figure 3.6: Use Case Diagram of the Segmentation Component

Actors

The diagram includes three main actors:

- **Patient:** Can upload MRI images, view segmentation results (tumor boundaries drawn on the image), download reports, chat with the bot, and view history.
- **Doctor:** Has all patient privileges plus the ability to view all patients' history, view patient details, add medical notes, and verify diagnoses.
- **Admin:** Has all doctor privileges plus the ability to manage users, monitor system performance, backup the database, and perform system maintenance.

Table 3.3: Actors in Segmentation Use Case Diagram

Actor	Description
Patient	Regular user who can upload images and view segmentation results
Doctor	Medical professional with additional patient management privileges
Admin	System administrator with full system management capabilities

Authentication Use Cases

- **Register Account:** Allows new users to create an account.
- **Login:** Enables registered users to access the system.
- **Reset Password:** Allows users to recover or change their password.
- **Verify Credentials:** An <<include>> relationship from Login, responsible for validating user credentials.
- **Logout:** Allows users to securely exit the system.

Core Segmentation Use Cases

- **Upload MRI Image:** The primary use case where users submit MRI scans for segmentation. This use case includes:
 - <<include>> **Validate Format:** Checks that the uploaded file has a supported format.
 - <<include>> **Process Image:** Handles image preprocessing for segmentation.
- **View Segmentation Result:** Displays the original MRI image with tumor boundaries overlaid. The segmentation mask is generated by the U-Net model.
- **Download Report:** Allows users to download a PDF report containing the segmentation results.
- **Chat with Bot:** Enables users to interact with the medical chatbot for additional information.
- **View History:** Allows users to access their previous segmentation records.

Doctor-Only Use Cases

- **View All Patients History:** Access to all patient segmentation records.
- **View Patient Details:** View detailed information about a specific patient.
- **Add Medical Note:** Add professional notes to a patient's segmentation result.
- **Verify Diagnosis:** Confirm or correct the AI-generated segmentation.

Admin-Only Use Cases

- **Manage Users:** Add, edit, or delete user accounts.
- **Monitor System Performance:** Track system health and performance metrics.
- **Backup Database:** Create backups of the system database.
- **System Maintenance:** Perform routine system maintenance tasks.

Relationships

The diagram uses two types of relationships:

- **<<include>>:** Indicates that one use case requires another to complete (mandatory).
- **<<extend>>:** Indicates optional behavior that may be triggered under certain conditions.

Key Use Cases Summary

Table 3.4: Key Use Cases in Segmentation System

Use Case	Actor	Description
Register Account	Patient	Create a new user account
Login	Patient, Doctor, Admin	Authenticate to access the system
Upload MRI Image	Patient, Doctor	Submit MRI image for segmentation
View Segmentation Result	Patient, Doctor, Admin	Display tumor boundaries on MRI
Download Report	Patient, Doctor, Admin	Generate and download PDF report
Chat with Bot	Patient, Doctor, Admin	Interact with medical chatbot
View All Patients History	Doctor, Admin	Access all patient segmentation records
Manage Users	Admin	Add, edit, or delete user accounts

This use case diagram provides a comprehensive view of all functionalities available to different user roles within the segmentation system. The core functionality is viewing the segmented tumor boundaries, which distinguishes this diagram from the classification use case diagram.

3.3.3 Sequence Diagram




Figure 3.7: Sequence Diagram of the Segmentation Component

Step-by-Step Flow

1. Authentication (Steps 1-4):

- The Radiologist (User) enters their login credentials.
- The Web Interface forwards these credentials to the Backend Server for validation.
- If credentials are invalid, an error message is returned.
- Upon successful validation, the user is granted access.

2. Image Upload and Validation (Steps 5-8):

- The Radiologist uploads an MRI image via HTTP/POST request.
- The Backend Server validates the image format.
- If the format is invalid, an error message is returned.

3. Segmentation Model Loading (Steps 9-10):

- The Backend Server loads the pre-trained U-Net segmentation model.
- The model confirms it is ready for inference.

4. Image Preprocessing (Step 11):

- The image is preprocessed: resized to 128×128 pixels and normalized to $[0,1]$ range.

5. Segmentation Inference (Steps 12-13):

- The preprocessed image is sent to the Segmentation Model.
- The model predicts the tumor mask (binary mask where tumor pixels = 1, background = 0).
- The binary mask is returned to the Backend Server.

6. Result Storage (Steps 14-15):

- The Backend Server saves the image, mask, and timestamp to the Database.
- The Database confirms successful storage.

7. Visualization and Display (Steps 16-17):

- The Backend Server draws the tumor boundary on the original MRI image.
- The final image (original MRI with tumor boundary overlay) is displayed to the Radiologist.

System Components

The diagram involves six main components:

- **Radiologist (User):** The end-user initiating the interactions.
- **Web Interface:** The frontend application handling user requests.
- **Backend Server:** The server coordinating between components.
- **Segmentation Model:** The U-Net model performing tumor segmentation.
- **Database:** Stores the original image, segmentation mask, and timestamp.
- **Classification:** Reference to the classification system (not actively used in this flow).

Table 3.5: Sequence Steps for Segmentation Process

Step	From	Action
1	Radiologist	Enter login credentials
2	Web Interface	Validate user credentials
3	Backend Server	Verify with database
4	Web Interface	Show result (success/error)
5	Radiologist	Upload MRI image
6	Backend Server	Validate image format
7	Backend Server	Preprocess image (resize, normalize)
8	Backend Server	Load segmentation model
9	Segmentation Model	Confirm model ready
10	Segmentation Model	Run segmentation inference
11	Segmentation Model	Return binary mask
12	Backend Server	Save image + mask + timestamp
13	Database	Confirm saved successfully
14	Backend Server	Draw boundary on image
15	Web Interface	Display MRI with tumor boundary

Key Observations

- The segmentation model is loaded once at the beginning of the process and remains in memory for subsequent requests.
- The preprocessing step (resize to 128×128, normalization) is critical for model compatibility.
- The segmentation model returns a binary mask where tumor pixels are 1 and background is 0.
- Results are persistently stored in the Database with timestamps for future reference.
- The final output is the original MRI image with the tumor boundary overlaid, not just the mask alone.

This sequence diagram provides a clear, time-ordered view of how the segmentation system processes a tumor boundary detection request from start to finish.

3.3.4 Activity Diagram




Figure 3.8: Activity Diagram of the Segmentation Component

Step-by-Step Workflow

1. **Start:** The process begins.
2. **Login:** The user enters their username and password to access the system.
3. **User Validation:**
 - The system validates the user credentials.
 - **Decision Node:** If the user is invalid, the process returns to the login step.
 - If valid, the process proceeds to image upload.
4. **Upload MRI Image:** The user submits an MRI image for segmentation.
5. **Preprocessing:** The image is preprocessed, including resizing to 128×128 pixels and normalization to $[0,1]$ range.
6. **Load Trained U-Net Model:** The pre-trained U-Net model is loaded into memory.
7. **Forward Pass (Inference):** The preprocessed image is passed through the U-Net model for inference.
8. **Generate Output Mask:** The model generates a binary segmentation mask (tumor = 1, background = 0).
9. **Postprocess (Threshold):** A threshold (typically 0.5) is applied to convert probabilities to binary values.
10. **Display Segmentation:** The segmentation result (original MRI with tumor boundary overlay) is displayed to the user.
11. **Mask Accuracy Decision Node:**
 - **If the mask is accurate (Yes):** The result is saved to the database, and the process ends.
 - **If the mask is inaccurate (No):** The system allows for manual correction or re-running the segmentation with adjusted parameters.
12. **Manual Correction / Re-run:** The user can manually correct the mask or re-run the segmentation with different settings.
13. **Save to Database:** The final (corrected or original) segmentation result is saved to the database.
14. **End:** The process terminates.

Key Features of the Activity Diagram

- **Decision Nodes:** Three critical decision points are included:
 - User validation (ensures only authenticated users can proceed).
 - Mask accuracy evaluation (allows for quality control).
- **Looping Behavior:**
 - Invalid credentials lead back to the login step.
 - Inaccurate masks lead to manual correction or re-running the segmentation.
- **Linear Flow After Validation:** Once the user is authenticated and the image is uploaded, the process follows a structured path through preprocessing, model inference, and result generation.
- **Quality Control:** The inclusion of a manual correction step is clinically significant, allowing medical professionals to verify and adjust AI-generated segmentations.

Table 3.6: Activities in Segmentation Workflow

Activity	Description
Start	Beginning of the process
Login	User enters username and password
Validate User	Check credentials against database
Upload MRI Image	User submits MRI scan
Preprocess	Resize (128×128) and normalize image
Load Trained U-Net Model	Load the pre-trained segmentation model
Forward Pass (Inference)	Run model inference on the image
Generate Output Mask	Produce binary segmentation mask
Postprocess (Threshold)	Apply threshold to convert to binary
Display Segmentation	Show tumor boundary overlay
Mask Accuracy?	Decision node for quality control
Save to Database	Store result permanently
Manual Correction	Clinician adjusts the segmentation mask
End	Process termination

Clinical Significance

The inclusion of a manual correction step is particularly important for medical applications. It acknowledges that while the AI model can produce segmentations automatically, a medical professional should have the final say on accuracy. This human-in-the-loop approach ensures higher reliability and builds trust in the system.

This activity diagram provides a clear, visual representation of the tumor segmentation workflow, including error handling, quality control, and manual correction mechanisms.

3.4 Chatbot Component Analysis

3.4.1 Decomposition Diagram




Figure 3.9: Decomposition Diagram of the Chatbot Component

Input Module

Handles all incoming user interactions:

- **MRI Upload:** Accepts MRI image uploads for analysis (triggers the classification system).
- **Text Query:** Processes user text questions about tumors, treatments, and recommendations.
- **Data Validation:** Validates input data format and content before processing.

Process Module

The core processing engine of the chatbot:

- **Risk Calculation:** Calculates risk level based on tumor type and size using the formula:
 - Base risk: Glioma = 3, Meningioma = 2, Pituitary = 2
 - Size multiplier: Small = 1, Medium = 2, Large = 3
 - Total risk: Base + Multiplier (≥ 6 = High, ≥ 4 = Medium, ...)
- **Recommendation Engine:** Generates medical recommendations based on tumor type and risk level.
- **Tumor Detection:** Interfaces with the AI classification model to detect tumor presence and type from MRI images.
- **Response Builder:** Constructs appropriate responses (text + recommendations) based on processed input.

Output Module

Delivers results to the user:

- **Final Response:** The complete response sent to the user, including tumor information, risk level, and recommendations.
- **Reports:** Generates downloadable PDF reports containing diagnosis results.
- **Statistics:** Provides statistical information about diagnoses (optional).
- **Notifications:** Sends system notifications to users (e.g., report ready).

User Management Module

Handles user account and session management:

- **Login & Logout:** Manages user authentication and session termination.
- **Verify User:** Validates user credentials and permissions.
- **Role:** Manages role-based access control (Patient, Doctor, Admin).
- **Admin:** Administrative functions including user management and system monitoring.

Table 3.7: Chatbot System Modules

Module	Sub-components / Functions
Input Module	MRI Upload, Text Query, Data Validation
Process Module	Risk Calculation, Recommendation Engine, Tumor Detection
Output Module	Final Response, Reports, Statistics, Notifications
User Management	Login & Logout, Verify User, Role, Admin

Module Interactions

- The **Input Module** receives user requests (text or image upload) and validates them.
- Valid inputs are passed to the **Process Module**, where risk is calculated, recommendations are generated, and responses are built.
- The **Output Module** delivers the final response to the user and optionally generates reports.
- The **User Management Module** operates independently, handling authentication and authorization for all users.

This decomposition provides a clear hierarchical view of the chatbot system, showing how user inputs are processed through risk calculation, recommendation generation, and response building to produce final outputs.

3.4.2 Use Case Diagram




Figure 3.10: Use Case Diagram of the Chatbot Component

Actors

The diagram includes three main actors:

- **Patient:** A regular user who can ask questions about tumor types, risk percentages, recommendations, treatment advice, lifestyle advice, and chat with a doctor.
- **Doctor:** A medical professional who can view patient data, provide treatment advice, and chat with patients.
- **Admin:** A system administrator who can manage the system and manage users.

Table 3.8: Actors in Chatbot Use Case Diagram

Actor	Description
Patient	End-user seeking medical information and recommendations
Doctor	Medical professional providing advice and reviewing patient data
Admin	System administrator managing users and system settings

Patient Use Cases

- **Upload MRI Image:** Patient uploads an MRI image for analysis. This use case includes <<include>> **Manage System** (triggering the backend processing).
- **View Diagnosis Result:** Displays the diagnosis outcome from the AI model.
- **Ask About Tumor Type:** Patient asks about the characteristics of different tumor types (Glioma, Meningioma, Pituitary).
- **Ask About Risk Percentage:** Patient inquires about the calculated risk level based on tumor type and size.
- **Ask About Recommendation:** Patient requests medical recommendations based on their diagnosis.
- **Get Treatment Advice:** Patient asks about treatment options (surgery, chemotherapy, radiation).
- **Get Lifestyle Advice:** Patient asks about lifestyle changes to support treatment or prevention.
- **Chat with Doctor:** Patient initiates a conversation with a medical professional for personalized advice.

Doctor Use Cases

- **View Patient Data:** Doctor accesses patient diagnosis history and medical records.
- **Provide Treatment Advice:** Doctor offers professional treatment recommendations to patients.
- **Chat with Patient:** Doctor engages in real-time conversation with patients to address specific concerns.

Admin Use Cases

- **Manage System:** Admin oversees system operations, monitors performance, and handles maintenance.
- **Manage Users:** Admin adds, edits, or deletes user accounts and manages role assignments.

Relationships

The diagram uses:

- **<<include>>:** Upload MRI Image includes Manage System (the backend processing is automatically triggered).

Table 3.9: Key Use Cases in Chatbot System

Use Case	Actor	Description
Upload MRI Image	Patient	Submit MRI image for analysis
View Diagnosis Result	Patient	Display AI diagnosis
Ask About Tumor Type	Patient	Request tumor type information
Ask About Risk Percentage	Patient	Request risk level calculation
Ask About Recommendation	Patient	Request medical recommendations
Get Treatment Advice	Patient	Request treatment information
Get Lifestyle Advice	Patient	Request lifestyle recommendations
Chat with Doctor	Patient, Doctor	Real-time conversation
View Patient Data	Doctor	Access patient medical records
Provide Treatment Advice	Doctor	Offer professional recommendations
Manage System	Admin	System administration and monitoring
Manage Users	Admin	User account management

This use case diagram provides a comprehensive view of all chatbot functionalities available to different user roles, distinguishing between patient inquiries, doctor interactions, and administrative tasks.

3.4.3 Sequence Diagram




Figure 3.11: Sequence Diagram of the Chatbot Component

System Components

The diagram involves seven main components:

- **User:** The end-user interacting with the chatbot.
- **Web Interface:** The frontend application handling user requests.
- **Auth Service:** Handles user authentication and token verification.
- **User DB:** Stores user credentials and profile information.
- **Chat API:** The backend API processing chat requests.
- **NLP Processor:** Performs natural language processing on user queries.

- **Intent Classifier:** Classifies the user's intent based on extracted keywords.
- **Response DB:** Stores predefined responses and medical information.

Step-by-Step Flow

1. Authentication (Steps 1-5):

- The User enters login data (username and password).
- The Web Interface sends a login request to the Auth Service.
- The Auth Service validates the credentials against the User DB.
- Upon successful validation, the Auth Service returns a verification token.
- The Web Interface confirms the result to the User.

2. Question Submission (Steps 6-7):

- The User enters a question in the chat interface.
- The Web Interface sends the question to the Chat API with the verification token.
- The Chat API verifies the token with the Auth Service.
- The Auth Service confirms the token is valid.

3. NLP Processing (Steps 8-11):

- The Chat API forwards the question to the NLP Processor.
- The NLP Processor processes the text (tokenization, part-of-speech tagging, named entity recognition).
- The processed text is sent to the Intent Classifier.
- The Intent Classifier extracts the user's intent (e.g., "ask_about_tumor", "ask_about_treatment", "ask_about_risk").

4. Response Generation (Steps 12-14):

- The Intent Classifier queries the Response DB for a matching response based on the identified intent and extracted keywords.
- The Response DB retrieves the appropriate data (e.g., tumor information, treatment options, risk levels).
- The retrieved data is returned to the Intent Classifier.

5. Response Delivery (Steps 15-16):

- The Intent Classifier generates the final response and sends it back through the Chat API.
- The Chat API returns the response to the Web Interface.
- The Web Interface displays the response to the User.

Table 3.10: Sequence Steps for Chatbot Process

Step	From	Action
1	User	Enter login data
2	Web Interface	Send login request to Auth Service
3	Auth Service	Validate with User DB
4	Auth Service	Return verification token
5	Web Interface	Confirm result to User
6	User	Enter question
7	Web Interface	Send question to Chat API with token
8	Chat API	Forward to NLP Processor
9	NLP Processor	Process text
10	NLP Processor	Send to Intent Classifier
11	Intent Classifier	Extract intent
12	Intent Classifier	Query Response DB
13	Response DB	Retrieve data
14	Response DB	Return intent data
15	Intent Classifier	Generate and return response
16	Chat API	Return response to Web Interface
17	Web Interface	Display response to User

Key Observations

- **Authentication First:** All chat interactions require a valid authentication token, ensuring only registered users can access the chatbot.
- **Separation of Concerns:** The diagram clearly separates authentication (Auth Service, User DB) from chat processing (Chat API, NLP Processor, Intent Classifier, Response DB).
- **Modular Design:** Each component has a specific responsibility:
 - Auth Service: Handles authentication
 - NLP Processor: Processes natural language
 - Intent Classifier: Identifies user intent
 - Response DB: Stores response data
- **Token-Based Authentication:** The verification token is passed with each chat request, maintaining session security.
- **Asynchronous Flow:** The user's question triggers a chain of synchronous calls through the various processing components before the response is returned.

This sequence diagram provides a clear, time-ordered view of how the chatbot processes user questions, from authentication through NLP processing to response generation and delivery.

3.4.4 Activity Diagram




Figure 3.12: Activity Diagram of the Chatbot Component

Step-by-Step Workflow

1. **Start:** The process begins.
2. **Login:** The user logs into the system to access the chatbot.
3. **User Enters Question:** The user types a question or request into the chat interface.
4. **Send to Chatbot API:** The question is transmitted to the chatbot backend API for processing.
5. **NLP Text Processing:** The system performs Natural Language Processing to understand the user's intent:
 - Tokenization (splitting text into words)
 - Part-of-speech tagging
 - Named entity recognition (e.g., identifying "glioma" as a tumor type)
6. **Extract Keywords & Features:** Key terms are extracted from the user's question, such as:
 - Tumor type (glioma, meningioma, pituitary)
 - Action keywords (treatment, risk, recommendation, symptoms)
 - Modifiers (small, medium, large, high, low)
7. **Intent Recognition Decision Node:**
 - **If intent is NOT recognized (No):** The system asks the user to rephrase their question, and the process returns to "User enters question."
 - **If intent is recognized (Yes):** The system proceeds to query the database.
8. **Query Database:** The system searches the knowledge base for matching responses based on the extracted keywords and intent.
9. **Response Found Decision Node:**
 - **If a response is found (Yes):** The system generates the appropriate response.
 - **If no response is found (No):** The system returns a default response (e.g., "I'm sorry, I didn't understand your question. Please ask about tumor types, treatments, or recommendations.").
10. **Generate Response / Default Response:** The appropriate response text is prepared.
11. **Return Response:** The response is sent back to the frontend.
12. **Display to User:** The response is shown in the chat interface.
13. **End:** The process terminates for this query. The user may ask additional questions, restarting the process from "User enters question."

Key Features of the Activity Diagram

- **Decision Nodes:** Two critical decision points are included:
 - Intent recognition (determines if the system understands the question).
 - Response found (determines if a matching answer exists in the database).
- **Looping Behavior:**
 - If intent is not recognized, the user is asked to rephrase, and the process loops back.
- **Fallback Mechanism:** If no matching response is found, a default response is returned instead of failing.
- **Linear Flow After Recognition:** Once the intent is recognized and a response is found, the process follows a straightforward path to return and display the response.

Table 3.11: Activities in Chatbot Workflow

Activity	Description
Start	Beginning of the process
Login	User authenticates to the system
User enters question	User types a query into the chat
Send to chatbot API	Transmit question to backend
NLP Text Processing	Natural language processing
Extract Keywords & Features	Identify key terms and intents
Is intent recognized?	Decision node for understanding
Query Database	Search knowledge base
Response found?	Decision node for matching answers
Generate response	Prepare custom response
Default response	Fallback response for unmatched queries
Return response	Send response to frontend
Display to user	Show response in chat interface
End	Process termination

Example Interaction Flow

1. User asks: "What is the treatment for glioma?"
2. NLP extracts keywords: "treatment" + "glioma"
3. Intent recognized: "ask_about_treatment"
4. Database query returns: "Glioma treatment options include surgery, radiation therapy, and chemotherapy depending on grade and location."
5. Response displayed to user.

This activity diagram provides a clear, visual representation of the chatbot's natural language processing workflow, including intent recognition, database querying, and fallback mechanisms for unrecognized queries.

3.5 Project Timeline (Gantt Chart)

The Gantt chart illustrates the overall project schedule, including start and end dates for each task, dependencies between tasks, and the complete project timeline. This chart covers all three components (Classification, Segmentation, and Chatbot) as well as documentation and testing phases.




Figure 3.13: Gantt Chart of the Complete Project Timeline

Chapter 4

System Design

4.1 System Architecture

Figure 4.1 presents the overall system architecture of the proposed brain tumor detection system. The diagram is organized from top to bottom, starting with the users (Patient, Doctor, Admin) and ending with the database.




Figure 4.1: Overall System Architecture of the Proposed Brain Tumor Detection System

4.1.1 Architecture Diagram Walkthrough

The diagram contains eight main components connected by arrows that represent the direction of data flow. We will examine each component and its connections in order.

1. Users (Patient, Doctor, and Admin)

The diagram starts at the top with three user icons:

- **Patient:** A regular user who seeks diagnosis. Patients can upload MRI images, view results, interact with the chatbot, and download reports.
- **Doctor:** A medical professional who has all patient privileges plus the ability to view all patients' history and add medical notes.
- **Admin:** A system administrator who has all doctor privileges plus the ability to manage users, view system logs, and update or retrain the AI model.

From the users, arrows point downward:

- Patients and Doctors point to the Web Browser ("opens website").
- The Admin points directly to the Admin API ("opens admin panel").

2. Web Browser (Frontend)

Below the users, the **Web Browser** block represents the frontend application. This component is built with HTML, CSS, and JavaScript and serves Patients and Doctors. From this block, three arrows depart to different services:

- An arrow labeled "**upload MRI image**" points to `/upload` API. This represents the Frontend sending the selected MRI image to the Backend for analysis.
- An arrow labeled "**send message**" points to `/chat` API. This represents the Frontend sending user questions to the Chatbot Service.
- An arrow labeled "**view history**" points directly to the Database. This represents the Frontend retrieving previous diagnosis records.

3. Backend API (`/upload`)

The `/upload` block represents the main backend server that handles image uploads and diagnosis requests. This Flask-based API communicates with the AI Model and Database. The diagram shows the following connections:

- **Incoming arrow from Web Browser:** Carries the MRI image to be analyzed.
- **Outgoing arrow to AI Model:** Labeled "send image for analysis". The Backend forwards the image to the CNN model.
- **Incoming arrow from AI Model:** Labeled "return tumor type + confidence". The model sends back the classification result.

- **Outgoing arrow to Database:** Labeled "save result". The Backend stores the diagnosis result.
- **Outgoing arrow back to Web Browser:** Labeled "return result". The Backend sends the result to the Frontend for display.

4. Admin API (/admin)

The `/admin` block represents the administrative backend service. This component handles administrative tasks and is only accessible by the Admin user. The diagram shows:

- **Incoming arrow from Admin:** Labeled "opens admin panel". The Admin accesses this service directly.
- **Outgoing arrow to Database:** Labeled "manage users". The Admin can add, edit, or delete user accounts.
- **Outgoing arrow to Database:** Labeled "view logs". The Admin can monitor system activities and errors.
- **Outgoing arrow to AI Model:** Labeled "update/retrain". The Admin can update or retrain the AI model when needed.

5. AI Model (CNN Classification)

The **AI Model** block represents the convolutional neural network trained for tumor classification. Built with TensorFlow/Keras, this model analyzes MRI images and classifies them into four categories: glioma, meningioma, pituitary, or no tumor. The model receives images from the Backend API and returns the classification result.

6. Chatbot Service (/chat)

The `/chat` block represents the independent chatbot service that handles all user inquiries. The diagram shows:

- **Incoming arrow from Web Browser:** Labeled "send message". Carries the user's question.
- **Outgoing arrow to Chatbot:** Labeled "process question". Forwards the question to the recommendation engine.
- **Incoming arrow from Chatbot:** Labeled "return response". Receives the generated answer.
- **Outgoing arrow back to Web Browser:** Labeled "return answer". Sends the response to the user.

7. Chatbot (Recommendations)

The **Chatbot** block represents the recommendation engine that generates responses. It operates in two modes: rule-based (using a predefined Q&A database) or Gemini API (using Google's AI). This component processes questions and returns appropriate medical recommendations.

8. Database

The **Database** block (shown as a cylinder) is the final component at the bottom of the diagram. It stores three types of data:

- **Users:** Account information (ID, name, email, password, role)
- **Images:** Uploaded MRI images metadata (image ID, user ID, path, date)
- **Results:** Diagnosis results (result ID, image ID, tumor type, confidence, risk level)

The Database receives data from:

- The Backend API ("save result")
- The Admin API ("manage users")

The Database responds to requests from:

- The Web Browser ("view history")
- The Admin API ("view logs")

4.1.2 Complete Data Flow Sequence

Reading the diagram from top to bottom, the complete data flow sequence for different user types is:

For Patient and Doctor:

1. **User → Web Browser:** The user opens the website.
2. **Web Browser → Upload API:** The user uploads an MRI image.
3. **Upload API → AI Model:** The Backend sends the image for analysis.
4. **AI Model → Upload API:** The model returns the tumor type and confidence score.
5. **Upload API → Database:** The Backend saves the result.
6. **Upload API → Web Browser:** The Backend returns the result to the user.
7. **Web Browser → Chat API:** The user sends a message to the chatbot.
8. **Chat API → Chatbot:** The service processes the question.
9. **Chatbot → Chat API:** The chatbot returns a response.
10. **Chat API → Web Browser:** The service returns the answer to the user.
11. **Web Browser → Database:** The user views their history.
12. **Database → Web Browser:** The database returns historical records.

For Admin:

1. **Admin** → **Admin API**: The Admin opens the admin panel.
2. **Admin API** → **Database**: The Admin manages users (add, edit, delete).
3. **Admin API** → **Database**: The Admin views system logs.
4. **Admin API** → **AI Model**: The Admin updates or retrains the AI model.

4.1.3 Role-Based Access Control Summary

Table 4.1: User Roles and Permissions

Feature / Permission	Patient	Doctor	Admin
Upload MRI Image	✓	✓	✗
View Diagnosis Result	✓	✓	✗
Chat with Bot	✓	✓	✗
Download Report	✓	✓	✗
View Personal History	✓	✓	✗
View All Patients History	✗	✓	✓
Add Medical Notes	✗	✓	✗
Manage Users	✗	✗	✓
View System Logs	✗	✗	✓
Update/Retrain AI Model	✗	✗	✓

4.2 Frontend Design

The frontend is a single-page web application that provides an intuitive interface for users to upload MRI images, view diagnosis results, and interact with the medical chatbot.

4.2.1 Page Layout

The interface is divided into five main sections as shown in Figure 4.2:




Figure 4.2: Frontend Page Layout

1. **Header Section:** Contains the application logo and authentication buttons (Login /Register).
2. **Upload Section:** Allows users to upload MRI images via click or drag-and-drop. Displays a preview of the uploaded image before analysis.
3. **Chatbot Section:** Enables users to interact with the medical chatbot. Displays conversation history and allows text input for questions.
4. **Result Section:** Displays the diagnosis result including tumor type, confidence score, risk level, and medical recommendations.
5. **History Section:** Shows the user's previous diagnosis records. This section is visible only after login.

4.2.2 User Interface Components

Upload Area

The upload area supports both click-to-upload and drag-and-drop functionality. It includes:

- A dashed border area with an upload icon
- Text instructions for the user
- File type restrictions (JPG, PNG, JPEG only)
- Image preview after selection

Chatbot Component

The chatbot interface consists of:

- A scrollable message container showing conversation history
- Message bubbles differentiated by sender (user in purple, bot in gray)
- A text input field for typing questions
- A send button for submitting messages
- A typing indicator showing when the bot is processing
- PDF download buttons: After the diagnosis result is displayed, two buttons appear:
 - **Download Report (Arabic):** Generates a PDF report in Arabic language containing the diagnosis result, tumor type, risk level, medical recommendations, and the uploaded MRI image.
 - **Download Report (English):** Generates the same report in English language for international users or English-speaking patients.

Result Display Component

The diagnosis result is displayed in a card-style component that includes:

- A colored header based on tumor type (purple for glioma, green for meningioma, pink for pituitary, blue for normal)
- The tumor name in Arabic
- The risk level (Low, Medium, High) with corresponding colors
- A list of medical recommendations
- A disclaimer message for educational purposes
- Download buttons for generating PDF reports (Arabic and English versions)

4.2.3 Responsive Design

The interface is fully responsive and adapts to different screen sizes:

- **Desktop (1200px and above):** Two-column grid layout with upload section on the left and chatbot on the right.
- **Tablet (768px to 1200px):** Single-column stacked layout with reduced padding.
- **Mobile (below 768px):** Single-column layout with smaller fonts and touch-friendly button sizes. The download buttons stack vertically instead of horizontally.

4.2.4 PDF Report Generation

The system includes functionality to generate PDF reports of diagnosis results. The report includes:

- Tumor type (in Arabic or English)
- Risk level
- Tumor size (if provided)
- Medical recommendations
- The uploaded MRI image
- A disclaimer for educational purposes

The PDF generation uses two external libraries:

- **html2canvas:** Converts HTML elements to canvas images
- **jsPDF:** Generates PDF files from images

4.3 Backend Design

The backend is a FastAPI-based REST API server that handles all core operations including user authentication, image uploads, tumor detection, report management, and chatbot interactions. It acts as the intermediary between the frontend, the AI model (TensorFlow), and the SQLite database.

4.3.1 Architecture Overview

As illustrated in Figure 4.3, the backend follows a modular architecture organized into four main layers: the Backend Server (Port 8000), the Database Layer, the AI Processing Layer, and the File Storage Layer.




Figure 4.3: Backend Architecture Overview

Backend Server Layer (Port 8000)

The Backend Server is built with FastAPI and serves as the entry point for all client requests. It contains a Request Router that directs incoming HTTP requests to the appropriate route handlers:

- **Auth Routes (/auth/*):** Handle user authentication operations including registration, login, logout, and user management. These routes implement JWT-based authentication and role-based access control.

- **Reports Routes (/reports/*):** Manage medical reports. Users can upload reports, view their own reports, and doctors can add diagnoses. Admins have access to all reports.
- **Detection Routes (/api/v1/*):** Handle the core tumor detection functionality. These routes receive MRI images, preprocess them, call the TensorFlow model for inference, and return classification results.
- **Chatbot Routes (/api/v1/chat):** Process user messages and interact with the recommendation engine to provide medical advice based on the tumor type.

Database Layer

The Database Layer uses SQLite with SQLAlchemy ORM for data persistence. It consists of four main tables:

- **Users Table:** Stores user information including id, username, email, hashed password, role (user/doctor/admin), and account status.
- **Reports Table:** Stores diagnosis reports including user_id, image path, prediction results, confidence score, risk level, and doctor's diagnosis.
- **Chat Sessions Table:** Manages chat conversation sessions between users and the chatbot for context preservation.
- **Token Blacklist Table:** Stores invalidated JWT tokens to support secure logout functionality.

AI Processing Layer

The AI Processing Layer is responsible for all machine learning operations:

- **Image Preprocessing:** Before feeding images to the model, they undergo:
 - Resizing to 224×224 pixels (model input size)
 - Normalization (scaling pixel values to [0, 1])
 - Adding batch dimension for model compatibility
- **TensorFlow Model:** A custom CNN model built from scratch with the following architecture:
 - 4 Convolutional layers (Conv2D)
 - 4 MaxPooling layers (MaxPooling2D)
 - Flatten layer
 - Dense layer with 512 units
 - Dropout layer (rate 0.5) to prevent overfitting
 - Output Dense layer with 4 units and Softmax activation

The model is loaded from the file `classification_model_final.keras` and performs inference on preprocessed MRI images.

- **Result Interpretation:** Converts model output probabilities into meaningful results:
 - Tumor type classification into four classes: Glioma, Meningioma, Pituitary, and No Tumor
 - Confidence score (percentage) based on prediction probability
 - Risk level calculated from tumor type and confidence

The model achieves an overall accuracy of **98.47%** on the test dataset.

File Storage Layer

The File Storage Layer handles persistent storage of image files:

- **Uploads/:** Stores original MRI images uploaded by users. Files are saved with unique timestamps to avoid naming conflicts.
- **Outputs/:** Stores processed images and segmentation results for future reference and report generation.

4.3.2 Data Flow

The data flow between layers follows this sequence:

1. Client sends a request to the Backend Server on Port 8000
2. The Request Router directs the request to the appropriate route handler
3. Detection routes load the image from the Uploads folder
4. The image is passed to the AI Processing Layer for preprocessing
5. The preprocessed image is fed to the Custom CNN TensorFlow Model for inference
6. Results are interpreted and saved to the Reports table in the Database
7. Processed images are saved to the Outputs folder
8. Reports routes fetch data from the Database when requested
9. Chatbot routes save conversation history to Chat Sessions table
10. Authentication routes validate credentials against the Users table and manage tokens in the Token Blacklist

4.3.3 API Endpoints

The backend provides the following API endpoints organized by functionality:

Authentication Endpoints

Table 4.2: Authentication API Endpoints

Endpoint	Method	Port	Description
/auth/register	POST	8000	Register a new user
/auth/login	POST	8000	Login and get JWT token
/auth/logout	POST	8000	Logout (blacklist token)
/auth/users	GET	8000	Get all users (Admin only)
/auth/doctors	GET	8000	Get all doctors (Admin only)
/auth/patients	GET	8000	Get all patients (Doctor/Admin)

Tumor Detection Endpoints

Table 4.3: Tumor Detection API Endpoints

Endpoint	Method	Port	Description
/api/v1/classification	POST	8000	Classify uploaded MRI image
/api/v1/upload-analyze	POST	8000	Upload and analyze with report saving
/api/v1/test-all	POST	8000	Test model on entire dataset

Reports Management Endpoints

Table 4.4: Reports API Endpoints

Endpoint	Method	Port	Description
/reports/upload	POST	8000	Upload a new medical report
/reports/my-reports	GET	8000	Get current user's reports
/reports/id	GET	8000	Get specific report details
/reports/id/diagnose	PUT	8000	Add doctor diagnosis
/reports/admin/all-reports	GET	8000	Get all reports (Admin only)

Chatbot Endpoints

Table 4.5: Chatbot API Endpoints

Endpoint	Method	Port	Description
/api/v1/chat	POST	8000	Send message to chatbot
/api/v1/chatbot-message	POST	8000	Advanced chatbot interaction

4.3.4 Request/Response Format

Register Endpoint (/auth/register)

Request Format:

- Method: POST

- **Content-Type:** application/json

Request Body:

```
{
  "username": "ahmed",
  "email": "ahmed@example.com",
  "password": "123456",
  "full_name": "Ahmed Mohamed",
  "phone": "01000000000"
}
```

Response (200 OK):

```
{
  "id": 1,
  "username": "ahmed",
  "email": "ahmed@example.com",
  "full_name": "Ahmed Mohamed",
  "role": "user",
  "is_active": true
}
```

Login Endpoint (/auth/login)**Request Body:**

```
{
  "email": "ahmed@example.com",
  "password": "123456"
}
```

Response (200 OK):

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIs... ",
  "token_type": "bearer",
  "role": "user",
  "user_id": 1
}
```

Upload & Analyze Endpoint (/api/v1/upload-analyze)**Request Format:**

- **Method:** POST
- **Content-Type:** multipart/form-data
- **Headers:** Authorization: Bearer {token} (optional)
- **Body:** image file (JPG, PNG, JPEG)

Processing Steps:

1. Receive the uploaded image file
2. Validate the file format
3. Convert image to RGB if needed
4. Resize image to 224x224 pixels
5. Normalize pixel values to [0, 1]
6. Add batch dimension for model input
7. Run inference using the Custom CNN TensorFlow model
8. Interpret prediction (tumor type and confidence)
9. Calculate risk level based on results
10. Save report to database (if authenticated)
11. Return results to frontend

Response (200 OK):

```
{
  "status": "success",
  "has_tumor": true,
  "prediction": "Tumor Detected",
  "confidence": 92.5,
  "tumor_type": "glioma",
  "risk_level": "High",
  "image_info": {
    "filename": "mri_scan.jpg",
    "size": [224, 224]
  }
}
```

4.3.5 Port Configuration

The system uses the following port configuration:

Table 4.6: Port Configuration

Service	Port	Description
Backend API (FastAPI)	8000	Main API server
Frontend (Streamlit - optional)	8501	Web interface
Database (SQLite)	N/A	Local file (tumor_app.db)

4.3.6 Technologies Used

The backend is built using the following technologies:

Table 4.7: Technologies Stack

Technology	Version	Purpose
FastAPI	0.115.0	Web framework for API
Uvicorn	0.30.0	ASGI server
TensorFlow	2.21.0	Custom CNN model inference
SQLAlchemy	2.0.23	Database ORM
python-jose	3.3.0	JWT token handling
passlib	1.7.4	Password hashing
Pillow	10.4.0	Image processing
NumPy	1.26.0	Numerical operations
scikit-learn	-	Model evaluation metrics

4.3.7 Authentication & Authorization

The backend implements JWT (JSON Web Token) based authentication:

- **Token Generation:** Upon successful login, a JWT token is generated with user ID and role
- **Token Expiry:** Tokens expire after 30 minutes
- **Token Blacklisting:** Logout adds tokens to blacklist table
- **Role-Based Access:**
 - **User:** Can upload images, view own reports
 - **Doctor:** Can view assigned reports, add diagnoses
 - **Admin:** Full access, can manage users and doctors

4.3.8 Error Handling

The backend implements comprehensive error handling with appropriate HTTP status codes:

Table 4.8: Error Codes and Responses

Status Code	Description	Example Response
400	Bad Request	{"detail": "Email already registered"}
401	Unauthorized	{"detail": "Could not validate credentials"}
403	Forbidden	{"detail": "Admin privileges required"}
404	Not Found	{"detail": "User not found"}
500	Internal Error	{"detail": "Error processing image"}

Example Error Response:

```
{
  "detail": "Email or username already registered"
}
```

4.3.9 Database Schema Integration

The backend uses SQLAlchemy ORM to interact with the SQLite database. Key tables include:

- **users:** Stores user information (id, username, email, hashed_password, role)
- **reports:** Stores diagnosis reports (user_id, image_path, prediction, confidence)
- **chat_sessions:** Stores chat conversation sessions
- **chat_messages:** Stores individual chat messages
- **token_blacklist:** Stores invalidated JWT tokens

4.3.10 API Documentation

FastAPI automatically generates interactive API documentation:

- **Swagger UI:** <http://127.0.0.1:8000/docs>
- **ReDoc:** <http://127.0.0.1:8000/redoc>
- **OpenAPI JSON:** <http://127.0.0.1:8000/openapi.json>

4.4 Database Design

The system uses SQLite as the database management system with SQLAlchemy ORM for data persistence. Based on the actual implementation, the database consists of seven main tables: Users, Reports, Chat Sessions, Chat Messages, Token Blacklist, DoctorPatient, and Feedback.

4.4.1 Entity Relationship Diagram (ERD)

Figure 4.4 illustrates the entity relationship diagram of the database, showing all tables, columns, primary keys, foreign keys, and relationships.




Figure 4.4: Entity Relationship Diagram

4.4.2 Database Tables Description

As shown in Figure 4.4, the database contains the following tables:

- **Users Table:** Stores all account information for patients, doctors, and administrators. Key fields include: `id` (Primary Key), `username`, `email`, `hashed_password`, `full_name`, `phone`, `role` (user/doctor/admin), `is_active`, `is_verified`, and timestamps (`created_at`, `updated_at`, `last_login`).
- **Reports Table:** Stores diagnosis results for each uploaded image. Key fields include: `id` (Primary Key), `user_id` (Foreign Key referencing Users), `doctor_id` (For-

eign Key referencing Users), `image_path`, `image_name`, `image_size`, `prediction_result` (Tumor/No Tumor), `confidence`, `tumor_type`, `tumor_location`, `tumor_size_mm`, `processed_image_path`, `segmentation_mask_path`, `doctor_diagnosis`, `doctor_notes`, `status`, `severity`, and timestamps (`created_at`, `updated_at`).

- **Chat Sessions Table:** Manages conversation sessions between users and the chatbot. Key fields include: `id` (Primary Key), `user_id` (Foreign Key referencing Users), `session_name`, and timestamps (`created_at`, `updated_at`).
- **Chat Messages Table:** Stores individual messages within each chat session. Key fields include: `id` (Primary Key), `session_id` (Foreign Key referencing Chat Sessions), `role` (user/assistant), `content`, and `created_at`.
- **Token Blacklist Table:** Stores invalidated JWT tokens to support secure logout functionality. Key fields include: `id` (Primary Key), `token`, `user_id` (Foreign Key referencing Users), `expires_at`, and `created_at`.
- **DoctorPatient Table:** Manages the relationship between doctors and their assigned patients. Key fields include: `id` (Primary Key), `doctor_id` (Foreign Key referencing Users), `patient_id` (Foreign Key referencing Users), `assigned_at`, and `is_active`.
- **Feedback Table:** Stores user feedback on diagnosis results. Key fields include: `id` (Primary Key), `report_id` (Foreign Key referencing Reports), `user_id` (Foreign Key referencing Users), `is_correct`, `user_rating`, `user_comment`, and `created_at`.

4.4.3 Table Relationships

The relationships between the tables are as follows:

- **Users to Reports:** One-to-Many relationship through `user_id`. One user can have many reports, and each report belongs to exactly one user.
- **Users to Reports (Doctor):** One-to-Many relationship through `doctor_id`. One doctor can be assigned to many reports.
- **Users to Chat Sessions:** One-to-Many relationship. One user can have many chat sessions.
- **Chat Sessions to Chat Messages:** One-to-Many relationship. One session contains many messages.
- **Users to Token Blacklist:** One-to-Many relationship. One user can have many blacklisted tokens.
- **Users to DoctorPatient:** Two relationships - one as doctor, one as patient. Many-to-Many between doctors and patients.
- **Reports to Feedback:** One-to-One relationship. Each report has at most one feedback entry.

4.4.4 AI Model Integration

This section describes how the trained CNN model is integrated into the backend to serve predictions through the API.

Model Loading

At server startup, the backend loads the pre-trained model from the filesystem. The model is loaded once and kept in memory to serve all incoming requests, avoiding redundant loading operations.

Listing 4.1: Loading the trained model

```
import tensorflow as tf
from pathlib import Path

model_path = Path("models/classification_model_final.h5")
model = tf.keras.models.load_model(model_path)
```

Image Preprocessing

Before an image can be passed to the model, the backend applies a series of preprocessing steps to ensure the input matches the format the model expects during training. These steps are critical for obtaining accurate predictions.

The preprocessing steps are performed in the following order:

1. **Color Conversion:** The uploaded image is converted to RGB format to ensure it has three color channels, regardless of the original format (e.g., grayscale, RGBA).
2. **Resizing:** The image is resized to the fixed input size required by the model, which is 224×224 pixels. This is a mandatory step as neural networks require a consistent input shape.
3. **Normalization:** Pixel values, which are originally in the range $[0, 255]$, are scaled to the range $[0, 1]$ by dividing by 255.0. This stabilizes the learning process and improves model convergence.
4. **Batch Dimension Addition:** The model expects a batch of images, even for a single prediction. Therefore, an extra dimension (batch size = 1) is added to the image array, changing its shape from $(224, 224, 3)$ to $(1, 224, 224, 3)$.

The following code implements the full preprocessing pipeline:

Listing 4.2: Helper function for preprocessing a single image

```
from PIL import Image
import numpy as np

def preprocess_image(image: Image.Image) -> np.ndarray:
    # 1. Convert to RGB
```

```

if image.mode != 'RGB':
    image = image.convert('RGB')

# 2. Resize to model's target size
image = image.resize((224, 224))

# 3. Convert to numpy array and normalize
img_array = np.array(image) / 255.0

# 4. Add batch dimension (model expects batch)
img_array = np.expand_dims(img_array, axis=0)

return img_array

```

Inference Process

Once the image is preprocessed, the model performs inference to generate predictions.

Listing 4.3: Model inference code

```

# Preprocess the image
image_array = preprocess_image(image)

# Run inference
predictions = model.predict(image_array)[0]

# Get predicted class index and confidence
class_index = np.argmax(predictions)
confidence = float(predictions[class_index])

```

Integration with Backend API

The complete integration is implemented in the `/api/v1/upload-analyze` endpoint.

Listing 4.4: Complete upload and analyze endpoint

```

@router.post("/upload-analyze")
async def upload_and_analyze(file: UploadFile = File(...)):
    try:
        # 1. Read and open image
        contents = await file.read()
        image = Image.open(BytesIO(contents))

        # 2. Preprocess
        image_array = preprocess_image(image)

        # 3. Run inference
        predictions = model.predict(image_array)[0]
        class_index = np.argmax(predictions)
        confidence = float(predictions[class_index])

        # 4. Map to tumor type
        tumor_types = ['glioma', 'meningioma', 'pituitary', 'no_tumor']

```

```
tumor_type = tumor_types[class_index]
tumor_type_ar = tumor_types_ar[class_index]
has_tumor = (class_index != 3)

# 5. Prepare response
return {
    "status": "success",
    "has_tumor": has_tumor,
    "confidence": round(confidence * 100, 2),
    "tumor_type": tumor_type,
    "tumor_type_ar": tumor_type_ar
}

except Exception as e:
    raise HTTPException(status_code=400, detail=f"Error: {str(e)}")
```

4.4.5 Recommendation Engine Integration

The recommendation engine is integrated within the main backend server as a chatbot service. It provides medical recommendations based on the tumor type and risk level calculated by the AI model.

Architecture Overview

The recommendation engine runs on the same FastAPI backend (Port 8000) and interacts with the SQLite database to save chat sessions and conversation history. Figure 4.5 illustrates the architecture.




Figure 4.5: Recommendation Engine Architecture

API Endpoint

Table 4.9: Recommendation Engine API

Property	Value
Endpoint	/api/v1/chatbot-message
Method	POST
Port	8000 (same as main backend)
Authentication	Optional (works with or without token)

Request Format**Request Body:**

```
{
  "message": "glioma"
}
```

Example Request (Python):

```
import requests

response = requests.post(
    "http://127.0.0.1:8000/api/v1/chatbot-message",
    json={"message": "glioma"}
)
```

Response Format**Case 1: Tumor Type Detected**

```
{
  "response": "glioma",
  "next_question": "What is the tumor size? (small/medium/large)"
}
```

Case 2: Tumor Size Received

```
{
  "response": "medium",
}
```

Case 3: No Tumor

```
{
  "response": "no tumor",
  "next_question": null
}
```

Case 4: Unknown Input

```
{
  "response": "unknown",
  "glioma, meningioma, pituitary, or no tumor"
}
```

Conversation Flow

The chatbot follows a two-step conversation flow:

Table 4.10: Conversation Flow

User Input	Response
"glioma"	"Glioma" + "What is the tumor size? (small/medium/large)"
"meningioma"	"Meningioma" + "What is the tumor size? (small/medium/large)"
"pituitary"	"Pituitary" + "What is the tumor size? (small/medium/large)"
"no tumor"	"No tumor detected"

Risk Level Calculation

The risk level is calculated based on tumor type and size:

```
def calculate_risk_level(tumor_type, tumor_size):
    base_risk = {'glioma': 3, 'meningioma': 2, 'pituitary': 2}
    size_multiplier = {'small': 1, 'medium': 2, 'large': 3}

    total_risk = base_risk[tumor_type] + size_multiplier[tumor_size]

    if total_risk >= 6: return "High"
    elif total_risk >= 4: return "Medium"
    else: return "Low"
```

Medical Recommendations by Tumor Type

Glioma

Table 4.11: Glioma Recommendations

Risk Level	Recommendations
Low	Regular follow-up with a neurologist, MRI every 6 months, Monitor symptoms
Medium	Visit a neurologist soon, Conduct detailed tests, Adhere to prescribed medications
High	Immediate hospital evaluation, Consult a neurosurgeon, Prepare for chemotherapy

Meningioma

Table 4.12: Meningioma Recommendations

Risk Level	Recommendations
Low	Annual check-ups only, Maintain healthy lifestyle
Medium	Consult a neurologist, Regular imaging tests (MRI)
High	Immediate neurosurgeon evaluation, Discuss surgical removal

Pituitary

Table 4.13: Pituitary Recommendations

Risk Level	Recommendations
Low	Regular endocrinologist follow-up, Check hormone levels every 6 months
Medium	Start hormone-regulating medication, Monitor headaches and vision
High	Urgent neurosurgical consultation, Specialized follow-up

No Tumor

Table 4.14: No Tumor Recommendations

Recommendations
Continue healthy lifestyle, Annual routine check-ups, Regular exercise

Integration with Diagnosis Results

When a user uploads an image for analysis, the system:

1. The AI Model detects tumor presence and type
2. The Recommendation Engine generates appropriate medical advice
3. The response combines diagnosis and recommendations

Complete Response Example:

```
{
  "status": "success",
  "has_tumor": true,
  "prediction": "Tumor Detected",
  "confidence": 92.5,
  "tumor_type": "glioma",
  "risk_level": "High",
  "recommendations": [
    "Immediate hospital evaluation",
    "Consult a neurosurgeon",
    "Prepare for chemotherapy or radiation"
  ]
}
```

Database Integration

Chat conversations are saved to the database:

```
-- Chat Sessions Table
INSERT INTO chat_sessions (user_id, session_name)
VALUES (1, 'Medical Consultation');

-- Chat Messages Table
INSERT INTO chat_messages (session_id, role, content)
VALUES (1, 'user', 'glioma');

INSERT INTO chat_messages (session_id, role, content)
VALUES (1, 'assistant', 'Glioma\nWhat is the tumor size?');
```

All components work together seamlessly to provide an integrated, user-friendly system for brain tumor diagnosis. The design supports three user roles (Patient, Doctor, Admin) with appropriate permissions, secure authentication using JWT tokens, and complete data persistence through SQLite database.

Chapter 5

Implementation and Results

5.1 Experimental Setup

The experiments were conducted using the following hardware and software configuration:

Table 5.1: Experimental Environment

Component	Specification
Operating System	Windows 11
RAM	32 GB
CPU	Intel(R) Xeon(R) E-2186M @ 2.90 GHz
GPU	NVIDIA Quadro P1000
Python Version	3.12.7

The dataset was split into 80% for training and 20% for testing. Data augmentation (rotation, flipping, rescale, brightness) was applied only to the training set to improve generalization and address class imbalance.

5.2 Dataset Description

The dataset consists of MRI images of brain tumors collected from public sources (Kaggle) [12, 13]. The images are divided into four classes: Glioma, Meningioma, Pituitary, and No Tumor. After applying data augmentation to balance all classes, each class contains 4,174 images. Table 5.2 shows the distribution of images with 80/20 split.

Table 5.2: Dataset Distribution After Balancing (80/20 Split)

Class	Training (80%)	Testing (20%)	Total
Glioma	3339	835	4174
Meningioma	3339	835	4174
Pituitary	3339	835	4174
No Tumor	3339	835	4174
Total	13356	3340	16696

5.3 Implementation Details

5.3.1 Libraries and Dependencies

The following Python libraries were used in the implementation:

- **TensorFlow/Keras:** For building and training the CNN model [14]
- **NumPy:** For numerical operations and array manipulation [15]
- **OpenCV (cv2):** For image processing and manipulation [16]
- **Matplotlib/Seaborn:** For visualization and plotting results [17]
- **Scikit-learn:** For evaluation metrics (classification report, confusion matrix) [18]
- **OS:** For file and directory path management

5.3.2 Data Preprocessing

The following preprocessing steps were applied to all images:

- **Resizing:** All images were resized to 224×224 pixels to match the input size of the CNN model.
- **Normalization:** Pixel values were scaled from the range $[0, 255]$ to $[0, 1]$ by dividing by 255.0.
- **Data Augmentation:** Applied only to the training set to address class imbalance and improve generalization:
 - Rotation range: ± 20 degrees
 - Horizontal flip: Yes
 - Brightness range: 80% to 120%

5.3.3 Model Architecture

The proposed CNN model architecture is based on a custom sequential CNN. The architecture consists of:

- **Input Layer:** $224 \times 224 \times 3$ (RGB images)
- **Convolutional Layers:** Four convolutional blocks with increasing filters
 - Conv2D + MaxPool: 32 filters, 3×3 kernel
 - Conv2D + MaxPool: 64 filters, 3×3 kernel
 - Conv2D + MaxPool: 128 filters, 3×3 kernel
 - Conv2D + MaxPool: 128 filters, 3×3 kernel
- **Fully Connected Layers:**
 - Flatten layer

- Dense layer with 512 units and ReLU activation
- Dropout layer with rate 0.5 (to prevent overfitting)
- Output Dense layer with 4 units and Softmax activation

The model summary is presented in Table 5.3.

Table 5.3: CNN Model Architecture Summary

Layer (Type)	Output Shape	Param #
conv2d	(224, 224, 32)	896
max_pooling2d	(112, 112, 32)	0
conv2d_1	(112, 112, 64)	18,496
max_pooling2d_1	(56, 56, 64)	0
conv2d_2	(56, 56, 128)	73,856
max_pooling2d_2	(28, 28, 128)	0
conv2d_3	(28, 28, 128)	147,584
max_pooling2d_3	(14, 14, 128)	0
flatten	(25088)	0
dense	(512)	12,845,568
dropout	(512)	0
dense_1	(4)	2,052
Total params:	13,088,452	
Trainable params:	13,088,452	
Non-trainable params:	0	

5.3.4 Training Hyperparameters

Table 5.4: Training Hyperparameters

Parameter	Value
Batch Size	32
Epochs	20
Learning Rate	0.001 (default Adam)
Optimizer	Adam
Loss Function	Categorical Crossentropy
Callbacks	ModelCheckpoint, EarlyStopping (patience=5)

5.3.5 Training Code Snippet

The following code shows the key implementation of the model training process using TensorFlow [14]:

Listing 5.1: CNN Model Training Implementation

```
# Build CNN Model
model = Sequential()
model.add(Input(shape=(224, 224, 3)))
model.add(Conv2D(32, (3, 3), activation='relu', padding='same'))
model.add(MaxPooling2D((2, 2)))
```

```

model.add(Conv2D(64, (3, 3), activation='relu', padding='same'))
model.add(MaxPooling2D((2, 2)))
model.add(Conv2D(128, (3, 3), activation='relu', padding='same'))
model.add(MaxPooling2D((2, 2)))
model.add(Conv2D(128, (3, 3), activation='relu', padding='same'))
model.add(MaxPooling2D((2, 2)))
model.add(Flatten())
model.add(Dense(512, activation='relu'))
model.add(Dropout(0.5))
model.add(Dense(4, activation='softmax'))

# Compile Model
model.compile(optimizer='adam',
              loss='categorical_crossentropy',
              metrics=['accuracy'])

# Callbacks
checkpoint = ModelCheckpoint('best_model.keras',
                             monitor='val_accuracy',
                             save_best_only=True)
early_stop = EarlyStopping(monitor='val_loss',
                             patience=5,
                             restore_best_weights=True)

# Train Model
history = model.fit(train_generator,
                    validation_data=test_generator,
                    epochs=20,
                    callbacks=[checkpoint, early_stop])

```

5.4 Classification Results

5.4.1 Overall Performance Metrics

The model achieved the following performance on the test dataset (3,340 images):

Table 5.5: Overall Classification Performance Metrics

Metric	Value
Accuracy	98.47%
Precision (Macro Avg)	98.25%
Recall (Macro Avg)	98.75%
F1-Score (Macro Avg)	98.50%
Loss	0.0594

5.4.2 Class-wise Performance

Table 5.6 shows the performance metrics for each tumor type individually.

Table 5.6: Class-wise Performance Metrics

Class	Precision	Recall	F1-Score	Support
Glioma	0.99	0.98	0.98	835
Meningioma	0.98	0.98	0.98	835
No Tumor	0.98	1.00	0.99	835
Pituitary	0.98	0.99	0.99	835
Accuracy	0.98 (98%)			3340

5.4.3 Confusion Matrix

Figure 5.1 shows the confusion matrix of the classification results on the test dataset. The diagonal values represent correct classifications, while off-diagonal values indicate misclassifications between different tumor types.




Figure 5.1: Confusion Matrix of the Classification Model

5.4.4 Training Curves

Figure 5.2 shows the training and validation accuracy/loss curves over 20 epochs. The curves demonstrate that the model converged well without significant overfitting.




Figure 5.2: Training and Validation Accuracy and Loss Curves

Table 5.7: Training and Validation Metrics per Epoch

Epoch	Train Accuracy	Val Accuracy	Train Loss	Val Loss
1	0.5989	0.7754	0.9439	0.5454
2	0.8122	0.8892	0.4934	0.3098
3	0.8850	0.9096	0.3223	0.2460
4	0.9210	0.9404	0.2243	0.1820
5	0.9416	0.9485	0.1730	0.1605
6	0.9522	0.9704	0.1395	0.1187
7	0.9622	0.9763	0.1170	0.0900
8	0.9653	0.9617	0.0977	0.1335
9	0.9694	0.9772	0.0916	0.0819
10	0.9750	0.9811	0.0812	0.0764
11	0.9747	0.9832	0.0749	0.0776
12	0.9794	0.9781	0.0676	0.0802
13	0.9726	0.9853	0.0775	0.0637
14	0.9827	0.9847	0.0560	0.0594
15	0.9866	0.9862	0.0425	0.0830
16	0.9838	0.9796	0.0508	0.0729
17	0.9836	0.9784	0.0488	0.0975
18	0.9848	0.9826	0.0507	0.0717
19	0.9867	0.9832	0.0401	0.0668

5.4.5 Sample Predictions

Figure 5.3 shows sample predictions from the trained model on four test images, one from each tumor class. For each image, the figure displays the original MRI scan, the true label, the model's predicted label, and the confidence score.




Figure 5.3: Sample Predictions for Each Tumor Class

5.5 Segmentation Results

For tumor segmentation, the LSMAtt-Net (Lightweight Shared Multi-Attention Network) was implemented. This model was specifically designed to address the efficiency-accuracy tradeoff in brain tumor segmentation, as proposed by Chen et al. (2025) in the journal *Biomedical Signal Processing and Control* [19].

5.5.1 Model Architecture

The LSMAtt-Net architecture consists of two key components that enable both high accuracy and computational efficiency:

LSDC (Lightweight Shared Dilation Conv)

The LSDC module employs dilated convolutions with shared weights to extract multi-scale features from MRI images [19]. This approach provides several advantages:

- Captures features at different scales without increasing the number of parameters
- Reduces parameter count by 51.6% compared to traditional convolution blocks
- Maintains high feature quality while minimizing computational cost

LMA (Lightweight Multi-Attention)

The LMA module combines two attention mechanisms to improve segmentation accuracy [19]:

- **Channel Attention:** Identifies which feature channels are most important for tumor detection
- **Spatial Attention:** Focuses on the spatial regions most relevant to the tumor

This dual-attention approach enables the model to concentrate on tumor regions while effectively ignoring background noise.

5.5.2 Model Parameters

Table 5.8: LSMAtt-Net Model Parameters

Parameter	Value
Total Parameters	1,386,612
Input Size	$128 \times 128 \times 3$
Output Size	$128 \times 128 \times 1$
Training Epochs	30
Batch Size	8
Loss Function	Dice Loss
Learning Rate	0.001

5.5.3 Experimental Setup

The LSMAtt-Net model was trained on 3,933 MRI images from the BRISC 2025 dataset [13] with corresponding ground truth masks. The dataset was split into 3,933 training images and 860 validation images.

Key training configurations include:

- Image size: 128×128 pixels (to balance memory usage and detail)
- Optimizer: Adam with ReduceLROnPlateau scheduling
- Early stopping with patience of 15 epochs to prevent overfitting
- Dice Loss function, which is specifically optimized for segmentation tasks by directly measuring overlap between predicted and ground truth masks

5.5.4 Segmentation Results

Table 5.9: LSMAtt-Net Segmentation Results

Metric	Value
Detection Rate (Tumor Present)	100% (30/30 images)
Average IoU (Intersection over Union)	51.07%
Best IoU	92.40%
Images with IoU > 0	85/100 (85%)
Validation Accuracy	99.37%

5.5.5 Performance Comparison

Table 5.10: Comparison with State-of-the-Art Methods

Model	Parameters (M)	Avg IoU	Best IoU
U-Net (Standard)	31.0	9.14%	37.00%
Attention U-Net	3.0	10.00%	50.40%
LSMAtt-Net (Ours)	1.39	51.07%	92.40%

5.5.6 Visual Example




Figure 5.4: LSMAtt-Net Segmentation

5.5.7 Discussion

The LSMAtt-Net model achieved excellent segmentation performance, demonstrating several key advantages:

- **Perfect Detection Rate:** The model successfully identified tumors in all test images (100% detection rate), confirming its reliability as a screening tool.
- **High Segmentation Accuracy:** With an average IoU of 51.07% and a best IoU of 92.40%, the model shows strong capability in delineating tumor boundaries.
- **Computational Efficiency:** The model uses only 1.39 million parameters and requires only 5.5 MB of storage, making it suitable for deployment in resource-constrained environments [19].
- **Superior Performance:** Compared to standard U-Net (avg IoU: 9.14%) and Attention U-Net (avg IoU: 10.00%), LSMAtt-Net achieves significantly higher segmentation accuracy with fewer parameters.

5.5.8 Limitations and Future Work

While the LSMAtt-Net achieved strong results, some limitations remain:

- **Resolution Constraints:** Training at 128×128 pixels limits the model's ability to capture fine spatial details. Future work could explore higher resolutions (256×256 or 512×512) if computational resources permit.
- **Dataset Diversity:** The model was trained on a single dataset. Testing on multi-center clinical data would further validate its generalizability.
- **Real-time Processing:** While the model is lightweight, optimization for real-time inference on standard hardware would enhance clinical applicability.

Future work will focus on:

- Training at higher resolutions
- Integration with the classification model for comprehensive diagnosis
- Web-based deployment for clinical use

Chapter 6

Conclusion and Future Work

6.1 Conclusion

This project successfully developed an integrated AI-based system for brain tumor detection and classification using MRI images. The main achievements of this work can be summarized as follows:

1. A comprehensive dataset of 16,696 MRI images was collected and balanced using data augmentation techniques to address class imbalance across four tumor types: Glioma, Meningioma, Pituitary, and No Tumor.
2. A custom CNN model was designed and trained for tumor classification, achieving an overall accuracy of 98.47% on the test dataset, with precision of 98.25%, recall of 98.75%, and F1-score of 98.50%.
3. The No Tumor class achieved perfect recall (100%), demonstrating the model's ability to correctly identify healthy cases without false negatives, which is clinically significant.
4. For tumor segmentation, the LSMAtt-Net (Lightweight Shared Multi-Attention Network) was implemented [19]. This state-of-the-art model achieved superior performance with a detection rate of 100%, average IoU of 51.07%, and best IoU of 92.40%, while using only 1.39 million parameters (5.5 MB), making it suitable for deployment in resource-constrained environments.
5. A web-based interface was developed using Flask, HTML, CSS, and JavaScript, allowing users to upload MRI images, view diagnosis results, interact with a medical chatbot, and download bilingual PDF reports.
6. A recommendation engine (chatbot) was integrated to provide medical advice based on the diagnosed tumor type and calculated risk level.
7. The system supports three user roles (Patient, Doctor, Admin) with appropriate permissions, secure JWT-based authentication, and complete data persistence using SQLite.
8. The project was fully documented with system analysis (UML diagrams: Use Case, Sequence, Activity, Decomposition) and system design (architecture, frontend, backend, database).

The experimental results demonstrate that the proposed system is effective and reliable for brain tumor diagnosis, achieving competitive accuracy compared to state-of-the-art approaches while maintaining robust performance on a balanced dataset.

6.2 Future Work

Several directions for future research and development can be pursued to enhance the current system:

1. **Enhanced Segmentation with Larger Datasets:** Future work should focus on:
 - Training on multi-institutional datasets (target: 10,000+ images)
 - Using higher input resolution (256×256 or 512×512 pixels)
 - Exploring advanced architectures such as Swin-UNETR or U-Net++ for further improvement
 - Implementing post-processing techniques like Conditional Random Fields (CRF) for boundary refinement
 - Multi-class segmentation to distinguish between Glioma, Meningioma, and Pituitary boundaries in the same image
2. **Larger and More Diverse Dataset:** Train the classification model on larger, multi-institutional datasets to improve generalization across different MRI machines and protocols.
3. **Multi-Modal Imaging:** Incorporate additional MRI sequences (T1, T2, FLAIR, DWI) to provide richer information for more accurate diagnosis.
4. **Real-time Deployment:** Optimize the model for real-time inference on edge devices and mobile platforms, enabling deployment in resource-limited settings.
5. **Generative AI Chatbot:** Replace the current rule-based recommendation engine with a generative AI chatbot (e.g., Gemini API or fine-tuned LLM) for more natural and flexible conversations.
6. **Patient History Tracking:** Enhance the database to track patient history over time, enabling longitudinal analysis of tumor progression and treatment response.
7. **Clinical Validation:** Validate the system with real clinical data from hospitals, including prospective studies with medical professionals.
8. **Explainable AI (XAI):** Integrate Grad-CAM and LIME visualizations to provide heatmaps showing which regions of the MRI influenced the model's decision, increasing clinician trust.

Bibliography

- [1] R. Kaifi, “A review of recent advances in brain tumor diagnosis based on ai-based classification,” *Diagnostics*, vol. 13, no. 18, p. 3007, 2023.
- [2] V. Srinivas and R. Parvathi, “Explainable ai-driven mri-based brain tumor classification: a novel deep learning approach,” *Frontiers in Artificial Intelligence*, vol. 8, p. 1700214, 2026.
- [3] W. H. Organization, “Brain tumor statistics,” 2024.
- [4] Z. Hamd, E. Osman, A. Alorainy, A. Alqahtani, N. Alshammari, O. Bajamal, S. Alruwaili, S. Almohsen, R. Almusallam, and M. Khandaker, “The role of machine learning in detecting primary brain tumors in saudi pediatric patients through mri images,” *Journal of Radiation Research and Applied Sciences*, vol. 18, no. 3, p. 101375, 2025.
- [5] D. Louis, A. Perry, P. Wesseling, D. Brat, I. Cree, D. Figarella-Branger, C. Hawkins, H. Ng, S. Pfister, G. Reifenberger, *et al.*, “The 2021 who classification of tumors of the central nervous system: a summary,” *Neuro-Oncology*, vol. 23, no. 8, pp. 1231–1251, 2021.
- [6] H. Sultan, N. Salem, and W. Al-Atabany, “Multi-classification of brain tumor images using deep neural network,” *IEEE Access*, vol. 7, pp. 69215–69225, 2019.
- [7] H. Khan, W. Jue, M. Mushtaq, and M. Mushtaq, “Brain tumor classification in mri image using convolutional neural network,” *Mathematical Biosciences and Engineering*, vol. 17, no. 5, pp. 6203–6216, 2020.
- [8] H. Ozcan, B. Emiroglu, H. Sabuncuoglu, S. Ozdogan, and T. Saygi, “A comparative study for glioma classification using deep convolutional neural networks,” *Mathematical Biosciences and Engineering*, vol. 18, no. 2, pp. 1550–1572, 2021.
- [9] S. Pereira, A. Pinto, V. Alves, and C. Silva, “Brain tumor segmentation using convolutional neural networks in mri images,” *IEEE Transactions on Medical Imaging*, vol. 35, no. 5, pp. 1240–1251, 2016.
- [10] M. Razzak, M. Imran, and G. Xu, “Efficient brain tumor segmentation with multi-scale two-pathway-group conventional neural networks,” *IEEE Journal of Biomedical and Health Informatics*, vol. 23, no. 5, pp. 1911–1919, 2018.
- [11] O. Ronneberger, P. Fischer, and T. Brox, “U-net: Convolutional networks for biomedical image segmentation,” in *International Conference on Medical Image Computing and Computer-Assisted Intervention (MICCAI)*, vol. 9351 of *LNCS*, pp. 234–241, Springer, 2015.

- [12] M. Nickparvar, “Brain tumor mri dataset.” Kaggle, 2026.
- [13] A. Fateh, Y. Rezvani, S. Moayedi, S. Rezvani, F. Fateh, M. Fateh, and V. Abolghasemi, “BRISC 2025: Annotated dataset for brain tumor image segmentation and classification.” Kaggle, 2025.
- [14] M. Abadi, A. Agarwal, P. Barham, E. Brevdo, Z. Chen, C. Citro, G. S. Corrado, A. Davis, J. Dean, M. Devin, S. Ghemawat, I. Goodfellow, A. Harp, G. Irving, M. Isard, Y. Jia, R. Jozefowicz, L. Kaiser, M. Kudlur, J. Levenberg, D. Mané, R. Monga, S. Moore, D. Murray, C. Olah, M. Schuster, J. Shlens, B. Steiner, I. Sutskever, K. Talwar, P. Tucker, V. Vanhoucke, V. Vasudevan, F. Viégas, O. Vinyals, P. Warden, M. Wattenberg, M. Wicke, Y. Yu, and X. Zheng, “TensorFlow: Large-scale machine learning on heterogeneous systems,” 2015.
- [15] C. Harris, K. Millman, S. van der Walt, *et al.*, “Array programming with numpy,” *Nature*, vol. 585, pp. 357–362, 2020.
- [16] G. Bradski, “Open source computer vision library,” 2000.
- [17] J. Hunter, “Matplotlib: Visualization with python,” 2007.
- [18] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay, “Scikit-learn: Machine learning in python,” *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.
- [19] Z. Chen, Y. Wang, X. Li, and B. Li, “Lsmatt-net: A lightweight brain tumor segmentation approach with efficiency–complexity tradeoff,” *Biomedical Signal Processing and Control*, vol. 104, p. 108930, 2025.