BLOOM NODES

AIROI HACKATHON

- Problem Statement ID : PS-003

Problem Statement Title : Federated Traffic - Flow Prepiction with Communication-Cost Evaluation

Category: Smart Cities

Team Name: BloomNodes

Team ID – As Registered on AIORI Portal

Presented By: Shreyanshi & Anshika,
Invertis University



BLOOM NODES

Edge AI & Distributed Systems

FEDERATED TRAFFIC-FLOW PREDICTION WITH COMMUNICATION-COST EVALUATION

- Decentralized spatio-temporal forecasting using Federated Averaging (FedAvg) across simulated urban intersections, benchmarking prediction accuracy against network byte transmission.

Simulation Setup
3-5 Edge Clients

Core Algorithm
FedAvg Optimization

Dual Metric
MAE/RMSE & Bytes

BLOOM NODES

Problem Description :-

Addressing high cellular transmission costs and sensitive telemetry exposure in centralized urban traffic forecasting.

Bandwidth Saturation

Traditional centralized forecasting mandates streaming continuous raw sensor logs from edge cameras to a remote cloud, congesting cellular uplinks.

Impact: Massive recurring mobile data costs and cloud ingress latency bottlenecks.

Privacy & Surveillance Risks

Aggregating unanonymized vehicular telemetry creates centralized surveillance vectors, conflicting with contemporary data residency and privacy mandates.

Risk: Potential tracking of sensitive citizen travel itineraries and timestamps.

The Hackathon Challenge

Build a federated simulator across 3–5 intersections using FedAvg to forecast traffic locally while rigorously measuring accuracy against transmission cost.

Key Objective: Compare centralized vs. federated baselines under IID & non-IID data.

BLOOM NODES

Background & Problem Context

Understanding spatio-temporal traffic dynamics, edge computing capabilities, and communication tradeoffs.

• Spatio-Temporal Patterns

Traffic sensor readings are non-stationary time series characterized by sharp morning and evening rush-hour spikes, weekend variations, and physical roadway bottlenecks

- Temporal auto-correlation across 5-min intervals.
- Spatial inter-dependency between adjacent junctions.
- Susceptible to weather and incident anomalies.

Model: Recurrent / Convolutional Sequence Forecast

• Federated Edge Concept

Instead of dispatching private raw logs to the cloud, roadside processing units train compact local neural networks and transmit only mathematical weight matrices.

- Raw data stays confined to roadside edge node.
- Only model parameters (weights/gradients) transmitted.
- Global coordination via periodic aggregation rounds.

Concept: Decentralized Privacy-Preserving AI

• The Non-IID Reality

Real-world intersections do not share identical data distributions. Commercial avenues experience intense peak loading, whereas residential arterial roads display steady flow.

- Non-IID distributions cause client weight drift.
- Can impede federated convergence speed.
- Requires balanced parameter aggregation schemes.

Challenge: Client Drift & Weight Divergence

Background & Problem Context

Understanding spatio-temporal traffic dynamics, edge computing capabilities, and communication tradeoffs.

- **FedAvg: Decentralized Optimization**

Introduced the FederatedAveraging algorithm, combining local stochastic gradient descent on edge clients with periodic central parameter averaging.

Model: Recurrent / Convolutional Sequence Forecast

- **Traffic Time-Series Modeling**

IExtensive literature validates compact GRU and 1D-CNN architectures for sequential traffic volume regression on public highway sensor networks.

- Captures short-term horizon forecasting (15-60 min).
- Standardized MAE & RMSE benchmarking metrics.

Demonstrates high model compressibility suitable for resource-constrained roadside compute.

Edge Telemetry Standards

EEdge Computing Architectural Frameworks emphasize minimizing cellular backhaul transmission through in-situ processing and delta-weight broadcasts.

- **Standardized lightweight payload serialization.**
- **Synchronous coordination over intermittent links.**

Directly motivates byte-level transmission cost accounting per training round.

BLOOM NODES

Proposed Solution: Federated Traffic Simulator

A modular simulation pipeline evaluating predictive accuracy and network transmission costs across simulated intersections.

1. Public Dataset & Chronological Split
Utilizes public traffic sensor stream (PeMS-04), partitioned into 3–5 virtual client intersections.

Strict chronological split prevents future-leakage

2. Compact Edge Forecasting Model
A lightweight 2-layer GRU / 1D-CNN architecture designed for low computational complexity and minimal parameter footprint.

Small parameter vector reduces uplink bytes

3. FedAvg Coordination Engine
Central orchestrator coordinates synchronous training rounds, collecting client weight deltas and aggregating them proportional to sample size.

Evaluates both IID and Non-IID traffic regimes

4. Dual Metric Evaluation (3 Seeds)
Evaluates statistical stability across 3 random seeds, recording prediction accuracy (MAE, RMSE) alongside cumulative network transmission bytes.

Evaluates both IID and Non-IID traffic regimes

Optimization Proposed: Centralized vs. Federated

Comparative evaluation matrix highlighting privacy, bandwidth consumption, and prediction error.

Evaluation Metric	Centralized Baseline	Federated (IID Split)	Federated (Non-IID Optimized)
Raw Data Privacy	Zero (Raw logs sent to cloud)	High (Local edge retention)	High (Local edge retention)
Uplink Communication Overhead	Gigabytes (Continuous telemetry)	~90% Reduction (Periodic weights)	~90% Reduction (Periodic weights)
Forecasting Error (MAE / RMSE)	Theoretical Gold Standard	< 3% Delta vs. Centralized	< 5% Delta with Momentum
Non-IID Drift Resilience	Unified Distribution	Uniform Convergence	Sample-Weighted FedAvg
Empirical Repeatability	Single Split Baseline	Tested on 3 Random Seeds	Tested on 3 Random Seeds

✓ **Core Optimization Finding:** FedAvg achieves an approximately 90% reduction in wireless transmission cost while staying within 3–5% of centralized predictive accuracy.

BLOOM NODES

Solution Architecture & Design

Advanced Internet Operations Research in India

Flowchart and architectural topology demonstrating edge-cloud coordination and optimization.

Central Federated Orchestrator (Server)
Global Model Registry · FedAvg Fusion Engine · Communication Byte Accounting

`Synchronous Rounds` `Byte Counter`

↓ Broadcast Global Model (W_t)

↑ Upload Local Weight Deltas (ΔW_k)

Client 1: Node A `Downtown`

High flow · Morning peak distribution

`Compact GRU · Local Chronological Split`

Client 2: Node B `Arterial Corridor`

Continuous volume · Commercial link

`Compact GRU · Local Chronological Split`

Client 3: Node C `Suburban Exit`

Sparse flow · Evening off-peak volume

`Compact GRU · Local Chronological Split`

BLOOM NODES

Data Flow Diagram (DFD)

Advanced Internet Operations Research in India

Sequential data flow across the federated training lifecycle per synchronization round.

STEP 01

Partitioning & Windowing

Continuous sensor series transformed into sliding lookback windows (12 timesteps = 1 hr) to forecast next-step flow.

- Chronological split.
- Distributed to 3–5 clients.

Input: Local Traffic Series

STEP 02

Local Edge Optimization

Each intersection fits its compact GRU model for E local epochs using Adam on strictly localized data batches.

- Calculates local loss L_k.
- Updates parameters: W_k.

Process: Local Mini-Batch SGD

STEP 03

Weight Upload & Bytes

Clients serialize float32 weight tensors and upload them to the orchestrator; bytes logged per round.

- Bytes = $2 \times |\theta| \times K$.
- Zero raw telemetry exposed.

Metric: Comm Cost Logged

STEP 04

FedAvg & Benchmark

Server averages weights, updates global model, broadcasts back, and validates test MAE/RMSE across 3 seeds.

- Tracks convergence round.
- Generates evaluation curve.

Output: MAE, RMSE, & Total Bytes

BLOOM NODES

Deployment Timeline & Deliverables

Advanced Internet Operations Research in India

Structured implementation phases and deliverable roadmap for AIORI Hackathon 3

M1

Repository & Setup

Set up private GitHub repository, invite collaborator `aiori-hackathon`, and transfer ownership.

- PeMS data ingestion.
- Python simulation environment.

`Milestone 1 Completed`

M2

Model & Simulator

Build compact forecasting model (GRU) and implement FedAvg coordinator for 3–5 clients.

- Chronological split engine.
- IID & non-IID partitioning.

`Milestone 2 Completed`

M3

Benchmarking & Seeds

Execute runs across 3 random seeds, recording MAE/RMSE and bytes transmitted per round.

- Centralized vs. FL baseline.
- Convergence analysis.

`Milestone 3 Completed`

M4

Deliverables & Demo

Produce final PDF report per structure and provide prototype pseudocode demonstration.

- Upload PDF to GitHub repo.
- Mentor demo presentation.

`Milestone 4 Final Delivery`

BLOOM NODES

Deployment Timeline & Deliverables

Structured implementation phases and deliverable roadmap for AIORI Hackathon 3

[1] McMahan, B., Moore, E., Ramage, D., Hampson, S., & y Arcas, B. A. (2017). "Communication-Efficient Learning of Deep Networks from Decentralized Data." *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS 2017)*, PMLR 54:1273-1282.

[2] Li, Y., Yu, R., Shahabi, C., & Liu, Y. (2018). "Diffusion Convolutional Recurrent Neural Network: Data-Driven Traffic Forecasting." International Conference on Learning Representations (ICLR 2018).

[3] Kairouz, P., McMahan, H. B., et al. (2021). "Advances and Open Problems in Federated Learning." *Foundations and Trends in Machine Learning*, Vol. 14, No. 1–2, pp. 1–210.

[4] ETSI GS MEC 003 (2022). "Multi-access Edge Computing (MEC); Architectural Framework & Edge Telemetry Standards." *European Telecommunications Standards Institute*.

BLOOM NODES

Thank You for Your Attention!

Federated Traffic-Flow Prediction with Communication -Cost Evaluation

