

Overview

這是一個作品集網站，功能是呈現我的個人特色以及作品，網站有幾個頁面，首先是首頁，首頁有分幾個部分，section1是hero,會放我畫的插圖以及介紹自己，歡迎觀者進入，往下滑是section2,也是插畫，插畫中間會輪播我的作品動畫，再往下滑中間的作品動畫會慢慢變大，變成接近全螢幕繼續輪播動畫，再往下滑是section4作品gallery,會有卡片滑動，呈現所有作品，再來是頁腳，會放幾個連結讓使用者可以個別點到他們要的介面。所有動畫或是插畫都會隨著使用者滑鼠往下滑而暫停或消失，不畫逼迫使用者看完才能滑到下一個，最上面的導覽列在section1是固定在最上方，隨著滑鼠往下滑會消失，但使用者往上滑會出現在畫面上。

畫面風格：

簡潔、只在呈現作品、會有動效畫面讓畫面不呆板。

可以餐靠gsap的動畫指令。

以下是網頁動畫的指令：

首先是首頁

再來是loading頁接到首頁hero部分，我希望像影片那樣從loading頁慢慢放大成首頁，我的loading頁是圖一，hero頁是圖二。首先我希望數字部分會是慢慢推倒100%但我不想要像影片那樣跳數字，我想要像數數一樣推進，不是像影片一那樣翻頁式時鐘的推進。再來畫面出現順序是先出現兩張紅色板凳在出現中間的logo然後再開始推進數字，然後跑完之後圖一loading的板凳會像影片一樣往前推進成圖二的板凳。到了首頁的順序是剛剛說的從loading頁的小板凳推進到首頁板凳的位置，然後同時也會出現圖二的敘述（mihumisang! I'm Maida, a product and industrial designer, and a maker.）我希望先出現的是mihumisang! I'm Maida跟兩張板凳->職位敘述（a product designer-> a industrial designer,-> a maker）（a product designer, a industrial designer, a maker這三組字希望輪流替換並落在同個位子->板凳旁邊的對話筐->對話匡的敘述，請幫我生成相關的提示敘述要詳述，有問題問我

Build a cinematic loading screen that transitions seamlessly into the homepage hero for a designer's portfolio site. The two screens are not separate pages — they are one continuous camera move. The loading screen's elements physically become the hero's elements.

Brand palette: background #FDFBF6 (warm off-white), accent red #C0281C, ink #1A1A1A.

PHASE 1 — Loading Screen Assembly (0 → 1.4s)

Everything is centered on a full-viewport #FDFBF6 canvas. Elements arrive in a strict order — nothing appears simultaneously.

Step 1.1 — The two stools arrive (0 → 700ms)

Two small red stool illustrations (SVG) appear side by side at the exact center of the viewport, separated by a narrow gap where the logo will later sit. At this stage they are small — roughly 90px wide each.

- **Left stool:** enters from translateY(30px) + opacity 0 + scale(0.9) → resting state. Duration 600ms, easing cubic-bezier(0.22, 1, 0.36, 1).
- **Right stool:** identical, delayed by 120ms.
- Give each stool a barely-perceptible settle: it overshoots its final Y by 4px then eases back over the last 180ms. This should read as physical weight, not as a bounce.
- No rotation, no spin. These are handcrafted objects being set down on a floor.

Step 1.2 — The GOMO logo appears (700 → 1150ms)

The wordmark logo (interlocking circular letterforms, ink black) fades in *between* the two stools, which gently part to make room:

- Logo: scale(0.85) opacity 0 → scale(1) opacity 1, 450ms.
- Simultaneously the two stools slide outward horizontally by ~24px each to open the gap. Same 450ms, same easing. The parting motion and the logo's arrival must be one gesture.

Step 1.3 — The counter appears (1150 → 1400ms)

The percentage text fades in directly beneath the logo, starting at 0%. Fade + 8px rise, 250ms. It does not start counting yet — it holds at 0% for a beat.

PHASE 2 — The Counter (1.4s → until load complete, minimum 2.5s)

This is the detail that matters most. Read it carefully.

The number must **count**, not flip. Every single integer from 0 to 100 is rendered in sequence — 0, 1, 2, 3 ... 98, 99, 100. It should look like a tally being counted upward.

Explicitly do NOT build:

- a flip-clock / split-flap / odometer effect
- digits that slide vertically in a masked column
- a rolling-drum number picker
- numbers that skip values (e.g. 0 → 7 → 19 → 34)

The digits simply **replace themselves in place** with no transition on the glyphs at all. The only animation is the changing value.

Pacing. Do not increment on a linear timer — that reads mechanical. Ease the count:

- 0 → 60: relatively brisk
- 60 → 90: noticeably slowing
- 90 → 100: slowest, each number holding a little longer, so the final approach feels like effort

Implement with requestAnimationFrame driving an eased progress value, then Math.floor() to the displayed integer. Never let the displayed number decrease, and never let it skip an integer even if a frame is dropped — if progress jumps, step through the intermediate values on subsequent frames.

Progress source. Track real asset loading (hero images, fonts, the stool SVGs) but enforce a **minimum duration of 2.5 seconds**. If assets finish early, the counter continues at its eased pace to 100%. If assets are slow, the counter eases toward but never reaches 100% until loading actually completes — hold it around 95–97% rather than stalling at a lower number, which reads as broken.

Typography. Use font-variant-numeric: tabular-nums so the digits have fixed width. Without this, the text will visibly jitter as it goes 9 → 10 → 100. The % sign stays perfectly still. Center-align the whole string as a unit.

Ambient life. While counting, the two stools drift up and down by 2px on a slow, offset sine loop (~3s period, the right stool phase-shifted). Almost subliminal — it just stops the screen from feeling frozen.

Playback rule: the loading screen plays on **every page load / refresh**. Do not gate it behind sessionStorage or localStorage.

PHASE 3 — The Transition: Loading Becomes Hero (100% → +1.6s)

This is a **single continuous camera dolly forward**, not a page change. There must be no fade to blank, no white flash, no route transition — the viewer's eye never loses the stools.

3.1 — Exit the loading UI (0 → 400ms)

At the instant the counter hits 100%:

- The counter and the GOMO logo (the large centered one) fade out and scale to 0.92 over 350ms. They dissolve *away from the camera* — as if the camera passed through them.
- The stools do **not** react to this. They are already beginning their move.

3.2 — The stools dolly forward (0 → 1300ms) — the hero moment

The **exact same SVG elements** from the loading screen travel to their hero positions. Do not unmount and remount them. Do not crossfade between a small copy and a large copy.

Use a FLIP technique: measure the loading position/size, measure the hero target position/size, then animate the delta with transform only.

The move combines three things happening at once:

- **Scale up:** from ~90px wide to their full hero size (roughly 3× larger). The growth curve is front-loaded — it accelerates out of the loading state, then decelerates into place, exactly like a camera pushing in and settling.
- **Spread apart:** the two stools separate horizontally to their wider hero spacing.
- **Descend:** they move down from viewport center to the hero's lower-middle position.

Duration 1300ms, easing cubic-bezier(0.22, 1, 0.36, 1). The left stool leads; the right stool trails by 80ms, so they don't move as one rigid block.

Critically: at no point should the stools appear to *cut* to a new size. The scale must be continuous across the entire 1300ms. Keep the SVGs vector so they stay crisp at 3× — do not use raster images for these.

3.3 — The header arrives (400 → 900ms)

While the stools are still travelling:

- The small GOMO logo fades in at the **top-left** corner. It should feel like it is the same mark that just dissolved from center — give it a 12px rise as it appears.
- The nav links (Works, About Me, Contact Me) fade in at top-right with a 60ms stagger between them, each rising 10px.

PHASE 4 — Hero Content (starts at 900ms, overlapping the stool travel)

4.1 — Greeting (900 → 1500ms)

Mihumisang! and I'm Maida, appear as two separate lines, using a **masked line reveal**: each line sits inside an overflow: hidden wrapper, starting at translateY(100%) and rising to 0 over 700ms with cubic-bezier(0.22, 1, 0.36, 1). The second line is delayed 130ms.

This must overlap with the stools still arriving — the greeting and the stools land at roughly the same moment. That simultaneity is the whole point.

4.2 — The rotating role (starts 1700ms, then loops forever)

To the right of I'm Maida, on the same line, a role phrase appears and then cycles indefinitely through three values, **always landing in the same position**:

1. A Product Designer
2. An Industrial Designer
3. A Maker

Layout rule — solve this first. The three phrases have very different widths.

Decide on one behaviour and hold it consistently:

- **Recommended:** the role sits in a container whose left edge is fixed (flush against I'm Maida,) and whose width animates smoothly to fit each incoming phrase over 400ms. The text is left-aligned within it, so the first character never moves. The line's overall centering must not cause the whole sentence to jitter left and right on every swap — anchor the layout so only the right edge breathes.
- Reserve the container's min-height for one line so nothing below ever shifts.

Swap animation. Inside an overflow: hidden wrapper:

- Outgoing phrase: translateY(0 → -100%), opacity 1 → 0, 450ms
- Incoming phrase: translateY(100% → 0), opacity 0 → 1, 450ms, starting 80ms after the outgoing begins
- Easing cubic-bezier(0.22, 1, 0.36, 1)

Timing. Each phrase holds for **2000ms** before swapping. The cycle loops infinitely: Product → Industrial → Maker → Product → ...

Pause the rotation when the browser tab is hidden (document.visibilityState), and resume on return.

4.3 — Speech bubbles (starts 2200ms)

Two hand-drawn-style red outlined speech bubbles appear beside the stools — lāi-té-tsē on the left, Grab a seat! on the right. Both are red, italic.

The bubble outline pops first, then the text types in.

- **Bubble:** scales up from scale(0.7) with transform-origin set at the bubble's tail — i.e. it grows *out of* the stool, as if the stool is speaking. 400ms, cubic-bezier(0.34, 1.4, 0.64, 1) — this is the one place a slight overshoot is welcome, because it gives the bubble a cartoon pop. Keep the overshoot small (max 6%).
- **Text:** after the bubble finishes, the text types in character by character, ~45ms per character. lāi-té-tsē types first; Grab a seat! begins 350ms later. A thin caret is visible during typing and fades out 200ms after the last character.
- Ensure the bubble is sized to its final text from the start so it does not grow while typing.
- The lāi-té-tsē diacritics (ā, é, ē) must render correctly — verify the chosen font supports them, otherwise fall back to a font that does.

Accessibility note: the bubble text must exist in the DOM as complete strings with the typed characters revealed via CSS or index slicing — screen readers should get the full phrase, not a stream of partial words. Mark the typing container `aria-live="off"` and expose a complete, visually-hidden copy.

4.4 — Idle state (after 3500ms)

Once everything has landed:

- The stools resume the same subtle 2px sine drift from the loading screen, at a slower period (~4s). This connects the two screens — the same objects, still breathing.
- The role text continues cycling forever.
- Everything else is at rest.

Full Timeline Summary

+2200ms	Speech bubbles pop, then type
+3500ms	Idle state — stools drift, roles cycle

Technical Requirements

- **Single page, no route change.** Loading and hero are two states of one component tree. The stool SVG elements are never unmounted between them.
- Animate transform and opacity only. Never animate width, height, top, left, or margin — the one exception is the role container's width, which should use a measured transform or a ResizeObserver-driven approach rather than animating layout directly.
- Stools must be inline SVG (not) so they stay sharp through the 3× scale and can be styled.
- Preload the display font before the counter starts, so no FOUT occurs mid-count.
- Apply will-change: transform to the stools only during the dolly phase; remove it afterward.
- Recommended stack: GSAP timeline for the master sequence (its timeline() makes this ordering trivial to tune), or Framer Motion with orchestrated variants. Do not mix both.
- Target 60fps throughout. The dolly phase is the highest-risk moment — verify in Chrome Performance that no layout or paint occurs during it, only composite.

Responsive

- **Desktop:** as specified.
- **Tablet:** stool hero size ~75%, bubbles remain beside the stools.
- **Mobile:** stools scale to fit within 88vw and sit closer together. Speech bubbles move to sit *above* each stool rather than beside, to avoid clipping at the viewport edge. Reduce the dolly duration to 1000ms — long transitions feel slower on small screens. Role rotation hold time stays at 2000ms.

Reduced Motion

Under @media (prefers-reduced-motion: reduce):

- Skip the loading assembly and the dolly entirely. Show a static loading state with the counter still counting (counting is informational, not decorative — keep it, but at a fixed linear pace).
- On completion, crossfade directly to the hero final state over 300ms.
- The role text still rotates, but as a plain 200ms opacity crossfade with no vertical movement, and with a longer 3500ms hold.
- Speech bubbles appear fully formed with no typing and no pop.

Acceptance Criteria

1. The counter displays **every integer** 0–100 with no skipped values and no flip/slide effect on the digits.
2. The number does not jitter horizontally as digit count changes (tabular-nums verified).

3. The counter never reaches 100% before assets are actually loaded, and never finishes in under 2.5s.
4. During the dolly, the stools scale continuously — pausing the animation at any frame shows them mid-size, never snapped to either endpoint.
5. There is no white flash, blank frame, or visible page change between loading and hero.
6. The three role phrases all land with their first character in the identical X position, and the surrounding layout never shifts vertically.
7. The role rotation loops indefinitely and pauses when the tab is backgrounded.
8. Speech bubbles grow from their tails (from the stools), not from their centers.
9. lāi-té-tsē renders with correct diacritics.
10. The full sequence replays on every refresh.

/

開始 Scroll 後。

請為我的作品集網站實作 **Section 2 : All Work**，重點是 Hero → All Work 的「鏡頭推進式」轉場，以及一支作品集影片隨滾動由小放大到全螢幕。

Section 2 — Practice → All Work | 整合版 Prompt

這份取代先前的「Section 2」與「Section 1.5」兩份文件。因為影片是同一支、放大是同一個連續動作，實作成一個連續的 **sticky** 區塊，就完全不需要交接淡入，也不會有接縫。原本的兩區塊交叉淡入方案不再需要。

一、整體概念

Hero 結束後，畫面不是切換，而是一台攝影機持續往前推軌：先推進一片插畫拼貼，再穿過拼貼中央的作品影片，影片一路長成滿版，最後落在 All Work 的作品列表。

全程是一個 **DOM** 結構、一支影片元素。影片從插畫中央到全螢幕之間，尺寸永遠連續，沒有任何一刻是重新掛載或交叉淡入。

色票：底色 #FDFBF6、accent 紅 #C0281C、墨黑 #1A1A1A。點綴色塊為柔和的綠、橘、粉、黃、天藍。

二、結構與技術

- 外層 #practice-to-work 容器，height: 420vh
- 內層 stage : position: sticky; top: 0; height: 100vh; overflow: hidden

- 用 GSAP ScrollTrigger `scrub: 1` 取得 progress $p \in [0, 1]$ (或原生 IntersectionObserver + rAF，對 progress 做 lerp，factor $\approx 0.08-0.12$ ，製造慣性重量感而非 1:1 生硬跟隨)
- 只操作 `transform / opacity / clip-path`，絕不動 `width / height / top / left / margin`
- 全程 `scrubbed`：往上滾必須完整反向，不能有任何只觸發一次的狀態

三、Stage A — 進場動畫（非滾動驅動，進入視窗時播一次）

在 p 開始推進之前，這段是時間驅動的，`once: true`，永不重播。觸發點：區塊越過視窗高度 70%。

A1 — 插畫拼貼整組淡入 (0 → 900ms)

五個紅色描邊人形 + 所有彩色與紅色塊 全部一起出現，當作單一群組動畫：

- `opacity 0 → 1`、`scale(0.94) → 1`、`translateY(20px) → 0`
- 900ms，`cubic-bezier(0.22, 1, 0.36, 1)`
- 動整個 wrapper，不要逐一動每個元素 —— 既像一整張手作拼貼被放下，也省下大量 frame budget
- 中央的影片框屬於這個群組，一起淡入

層次很重要。拼貼不是平的，每個元素指定三層之一：

- 後層：位於影片框後方，會被影片框遮住一部分
- 中層：影片框本身
- 前層：疊在影片框邊緣上方

這個互相交疊才會讀成實體紙拼貼，而不是一堆貼紙並排。

A2 — 標題跟進 (600 → 1400ms)

拼貼快落定時文字才進場，300ms 的重疊是刻意的，讓它像是餘勢而非另一個事件。

- 第一行 `I Design Across Health And The Environment`，`: masked line reveal` —— 包在 `overflow: hidden` 內，`translateY(100%) → 0`，750ms
- 第二行 `Taking Products From Sketch To Prototype, Physical And Digital Alike.`：同上，延遲 130ms
- 文字本身不做淡入，只靠遮罩。比柔和的 `fade` 更俐落、更 editorial

A3 — Idle 微幅呼吸 (1500ms 之後)

- 每個人形與色塊各自跑慢速 `sine`：`translateY ±3px`、`rotate ±0.8°`，週期 4–7 秒不等，彼此錯開相位
- 幅度要小到「只有刻意盯著看才會發現」。一旦讓人覺得「這在動」就是太多了
- 用 CSS keyframes + 錯開的 `animation-delay`，不要走 JS/rAF

四、Stage B — 滾動時間軸（以 progress **p** 為軸）

p = 0 → 0.30：拼貼散開、標題離場

影片開始變大時，插畫必須主動讓路。如果只是被蓋住，看起來會像 bug。

- 每個人形 / 色塊沿著離拼貼中心的方向向外放射位移，位移量與它原本離中心的距離成正比（本來就靠邊的跑最遠 —— 這才像鏡頭往前穿過去）
- 同時 `opacity 1 → 0`、`scale 1 → 1.15`
- 前層元素跑得比後層快、也更早淡出。這個視差差異就是景深的關鍵
- 標題：`translateY(0 → -140px)`、`opacity 1 → 0`、`scale(1 → 0.95)`，`p = 0.28` 前完全消失
- 背景色：從 Hero / Practice 底色 lerp 到 All Work 底色（CSS 變數插值，不是瞬間換色）

p = 0.08 → 0.85：影片放大（主角，佔最長區間）

注意起點是 0.08 —— 拼貼還在畫面上時影片就已經開始長大，兩段刻意重疊，避免中間出現空白停頓。

實作方式：容器固定 `100vw × 100vh`，視覺尺寸完全靠 `clip-path: inset()` 控制，內層影片另外走 `transform: scale()`。

- `clip-path: inset(32% 30% 32% 30% round 20px) → inset(0% 0% 0% 0% round 0px)`
- 圓角與 inset 同步收斂
- 內層 `<video>`：`scale(1.12 → 1.0)`，反向推近的視差感
- 陰影：`0 24px 60px rgba(0,0,0,0.18) → 完全消失`
- 放大曲線要慢、穩、有份量：前段加速、後段長長地減速。是推軌，不是 zoom

p = 0.70 → 1.0：All Work 內容浮現

- 影片上疊一層由下往上的漸層遮罩，`opacity 0 → 0.7`，確保文字可讀
- 區塊標題 All Works ↗（accent 紅、底線、右上箭頭）從 `translateY(80px)`，`opacity 0` 浮現到定位
- 作品 grid 從畫面下緣推入：每個 item `translateY(60px → 0)`、`opacity 0 → 1`，`stagger 60–80ms`
- 出現 scroll cue（細線 + Scroll to explore）

五、中央影片的輪播

影片框持續輪播多支作品影片。

- 每支播 5 秒，以 600ms opacity 交叉淡入換到下一支（兩個 <video> 疊著淡入，絕不硬切）
- 無限循環整組
- 輪播在整個放大過程中持續進行，不會因為開始變大而停住。換片與變大是兩件獨立的事，可以重疊發生
- 屬性：muted loop playsinline preload="metadata"、object-fit: cover
- 進入視窗才 play()，離開時 pause()
- 預先載入序列中的下一支，交叉淡入時不會卡住
- 任何時刻只掛載兩個 <video> 元素（current + next），不要每支影片各掛一個

六、Easing 與節奏

- 主曲線 cubic-bezier(0.22, 1, 0.36, 1) (expo-out 感)
- 影片放大刻意佔最長的 progress 區間
- 相鄰動畫區間必須重疊（拼貼還沒散完影片就開始長、影片還沒滿版 All Work 標題就開始浮現），任何一處出現空檔都會讓推軌感斷掉
- 不要彈性、不要 overshoot、不要 bounce

七、RWD

	影片起始寬度	插畫	sticky 容器高度
桌機	40vw	五個人形 + 全部色塊	420vh
平板	55vw	減為三個最主要的人形 + 色塊	360vh
手機	80vw	只留兩個人形，改放在影片上下而非環繞	260vh

- 手機關閉 idle 漂移（省電）
- 手機若效能吃緊，輪播改為單一 poster 圖 + 淡入
- 標題在任何斷點都不得超過三行

八、可存取性

@media (prefers-reduced-motion: reduce) :

- 跳過 Stage A 進場，直接顯示最終狀態
- 關閉 idle 漂移
- 關閉滾動放大 —— 影片固定在中等尺寸，All Work 內容直接可見
- 輪播改為單純 opacity 交叉淡入，且不自動播放，顯示 poster + 播放控制

其他：

- 插畫為裝飾性，`aria-hidden="true"`、`alt=""`
- 標題必須是可選取的真實文字，不能是圖片
- 每支影片提供 `poster`
- 作品標題必須以真實文字存在於 DOM，不能只存在於影片畫面內

九、效能

- 只動 `transform/opacity/clip-path`
- 插畫用 inline SVG（放大時清晰、可整組 transform）。若必須用點陣圖，PNG 帶 alpha、2 倍解析、明確標註尺寸避免 layout shift
- 影片上限 1080p，H.264 / WebM，移除音軌，積極壓縮 —— 這些是進頁就自動播的
- `will-change: transform` 只在放大階段掛上，結束後移除
- 目標鎖 60fps。用 Chrome Performance 確認放大階段只有 composite，沒有 layout、沒有 paint

十、技術棧

React + Next.js (App Router) · GSAP ScrollTrigger (`scrub: 1`) · Lenis (與全站共用同一個 smooth-scroll instance) · inline SVG。

不要加 **Framer Motion** —— GSAP 與 Lenis 已經涵蓋，第三個動畫迴圈會造成 RAF 互搶。

十一、驗收標準

1. 拼貼整組一起淡入，標題在其之後才進場，兩者不同時
2. Idle 漂移只有刻意盯著看才會發現
3. 影片變大時，插畫是向外放射散開並淡出，不是被蓋住
4. 前層與後層插畫的移動速度肉眼可辨地不同
5. 輪播在整個放大過程持續換片，不卡頓
6. 影片從插畫中央到滿版全程尺寸連續 —— 在任一幀暫停都看得到中間尺寸，不會跳格
7. Hero → 拼貼 → All Work 之間沒有任何硬切換、閃白、或背景色階梯
8. 往上滾完整反向，沒有卡住的狀態
9. 放大全程影片不變形、不出現黑邊
10. 中階筆電上放大階段維持 60fps
11. 手機上不會因為 sticky 導致滾動卡頓或高度計算錯誤

/

再來往下滑是 'UI/UX / product Design / APP Design / CAD / Craft / reflective Design + more' 那部分，我稱之為作品 gallery

灰色格子之後會放我自己的作品照片，Design a premium horizontal gallery for a multidisciplinary designer's portfolio. It should feel like an Awwwards-winning exhibition archive, not a conventional carousel.

Overall Experience

Slow, elegant, cinematic, luxurious. Every movement has weight and momentum. Nothing playful, bouncy, or elastic. The feeling is browsing artwork inside a modern design museum — motion exists only to enhance the perception of craftsmanship, never to draw attention to itself.

Layout

- Gallery occupies nearly the full viewport.
- Projects arranged in one continuous horizontal track.
- Each card $\approx 40\text{vw}$ wide, $70\text{--}80\text{vh}$ tall, generous gaps ($\approx 6\text{vw}$) between cards.
- The user always sees: one focused project centered, plus partial slivers of the previous and next projects.
- No borders. Very subtle shadows only when necessary. Lots of breathing room.

Motion System — three layers, clearly prioritized

There are three independent sources of motion. Implement them in this exact order of precedence:

Layer 1 — Ambient auto-scroll (baseline)

- The track drifts continuously to the left at a very slow constant speed ($\approx 18\text{--}25\text{px}$ per second). It should read as "alive," not as a slideshow.
- Infinite seamless loop: duplicate the track and wrap `translateX` by the track width so there is no visible jump or end state.
- **Pause conditions:** auto-scroll eases to a stop (over $\sim 600\text{ms}$) when (a) the pointer enters the gallery, or (b) the user scrolls manually. It eases back in after 2.5s of inactivity.

Layer 2 — Scroll-driven control (user override)

- Vertical mouse wheel / trackpad scroll translates the track horizontally.
- Use `Lenis` for smooth scroll with heavy inertia. It should feel like pushing a heavy gallery wall across the room.
- Support click-and-drag on desktop and native swipe on touch.
- **Settling behaviour (important, do not misread):** there is NO instant snapping. When scroll velocity drops below threshold, the track *gently glides* to align the nearest card to center over $500\text{--}700\text{ms}$ using cubic-bezier($0.22, 1, 0.36, 1$). The alignment must be indistinguishable from natural deceleration.

Layer 3 — Distance-from-center focus (always on)

Each card's base state is a continuous function of its distance from viewport center $d \in [0, 1]$:

- scale: 1.0 at center $\rightarrow 0.90$ at $d = 1$
- opacity: $1.0 \rightarrow 0.65$
- saturate: $100\% \rightarrow 75\%$

- The inner image gets a subtle parallax: `translateX` up to $\pm 16\text{px}$, opposite the track direction.
- **Do NOT use CSS filter: blur() for depth** — it is too expensive across multiple large images and will break the 60fps target. Achieve depth through scale, opacity, and saturation only.

Hover Interaction (desktop only)

When the pointer hovers any card:

- **Hovered card:** its scale multiplies its Layer-3 base scale by **1.04**, opacity goes to 1.0, saturation to 100% — regardless of its distance from center. The hovered card always wins over the focus layer.
- **All other cards:** multiply base scale by **0.96**, drop opacity to 0.45, and animate filter: `grayscale(100%)`.
- Transition duration 400ms, easing cubic-bezier(0.22, 1, 0.36, 1). Grayscale fades in over 500ms — slightly slower than the scale, so it reads as atmosphere rather than a state toggle.
- Overlay fades in on the hovered card revealing, staggered upward by 40ms each: **Project Title / Category / Year / one-line description**.
- Performance guard: apply will-change: transform, filter, opacity only while a hover is active, and remove it on hover end. Cards outside the viewport are excluded from the grayscale pass.

Click / Navigation

- Each card is a real `<a href="/work/[slug]">` — keyboard focusable, right-click-openable, crawlable. Not a div with an `onClick`.
- On click, run a shared-element transition into the project detail page: the clicked image expands toward the detail page's hero position while the rest of the gallery fades and scales down slightly (0.98). Duration 700–900ms.
- Focus-visible state: a thin 1px outline offset 8px in the accent color. Tab and Arrow keys move between cards, and the track scrolls the focused card to center.

Typography & Visual Style

Large editorial typography, Swiss-inspired, modern sans-serif, strong hierarchy, minimal text. Soft neutral palette. Ultra minimal museum aesthetic. Images remain the primary focus. Only one large hero image per project in the gallery — supporting images appear on the detail page only.

Responsive

- **Desktop:** as described above.
- **Tablet:** cards 55vw, hover effects retained but reduced (hovered 1.02, others no grayscale).
- **Mobile:** cards 78vw. **No hover layer at all.** Instead, the card nearest to center automatically receives the "focused" treatment (full opacity, full saturation), and all others sit at 0.85 opacity with 60% saturation. Swipe to browse, tap to navigate. Auto-scroll is disabled on mobile to preserve battery and avoid fighting touch input.

Accessibility

- @media (prefers-reduced-motion: reduce): disable auto-scroll, disable parallax, disable scale transitions. Render a static horizontally scrollable track with native scroll-snap. Hover reduces to a simple opacity change.
- All images require meaningful alt text.
- Card metadata (title, category, year) must exist in the DOM at all times — visually hidden until hover, never injected on hover.

Performance

- Animate transform and opacity only. Never animate layout properties (width, height, left, top, margin).
- filter is used only for the hover grayscale pass and the saturation ramp — never blur.
- Lazy load all images; preload the next two off-screen images.
- Serve responsive srcset with AVIF/WebP; cap decoded image size at 1600px wide.
- Target a locked 60fps. Verify with Chrome Performance: no layout thrashing, no long tasks over 50ms during scroll.

Technical Stack

React + Next.js (App Router) · GSAP (all animation and ScrollTrigger) · Lenis (smooth scroll) · CSS Grid · IntersectionObserver. **Do not add Framer Motion** — GSAP and Lenis together already cover this and adding a third animation loop causes RAF contention.

Reference Feel

Bürocratik, Locomotive, Studio Freight, Dogstudio, Active Theory, MakeMePulse. A luxury print editorial brought to life. Cinematic pacing over fast UI interactions. Elegance over novelty. Each project should feel like a curated exhibition piece rather than a portfolio thumbnail.

Acceptance Criteria

1. The track drifts on its own on load, and stops gracefully the instant the pointer enters.
2. Hovering any card greys and shrinks every other card, with no flicker or frame drops.
3. Hover state overrides distance-based state cleanly — no visible "fighting" between the two scale systems.
4. Scrolling never hard-snaps, yet always ends aligned to a card.
5. The loop has no visible seam.
6. Clicking a card navigates via a real URL, with a continuous shared-element transition.
7. 60fps sustained on a mid-tier laptop with 12+ projects loaded.

/

最後是頁腳，文字也希望有簡單出現的動效。

Let's Talk!點下去會引導到Email可以傳郵件給我 (a898499@gmail.com)，文字有底線的都會對應到該去的分支網頁 (playground還在進行中所以目前沒有)，Linkedin 頁會導到我的linkedin網址 (www.linkedin.com/in/lin-wei-ting-h-8a9732343)

然後CV Dowlaod我想讓使用者可以直接下載我的cv

Build the site footer for a designer's portfolio. Layout matches the attached design: an oversized headline, a red underlined CTA, a horizontal rule, then a three-part lower row.

Structure

Upper block

- Headline: Get An Idea? — very large editorial sans-serif, near-black (#1A1A1A), tight tracking, sitting hard against the left margin.
- Below it: Let's Talk! ↗ — accent red (#C8402F), underlined, with a trailing up-right arrow glyph.
- Top-right corner: a circular outlined "back to top" button (thin 1px stroke, ~64px diameter) containing an upward arrow.
- A full-width 1px horizontal rule beneath.

Lower block — three columns

- **Left:** an italic grey label (Brief), then a short bio paragraph, then the red underlined CV Download link.
- **Right group:** three stacked link columns with red uppercase headings — SITEMAPS / SOCIALS / CONTACTS.
- SITEMAPS: Home, Works, Playground, Contact (all underlined)
- SOCIALS: LinkedIn (underlined)
- CONTACTS: London, UK and the email address — plain, not underlined

Frame: a thin red 1px border insetting the entire footer from the viewport edge, as shown.

Links & Behaviour

Element	Behaviour
Let's Talk! ↗	mailto:a898499@gmail.com — opens the user's mail client. Add a subject prefill: ?subject=Let's%20talk
Home / Works / Contact	Internal routes /, /work, /contact
Playground	Work-in-progress. Render at 40% opacity, cursor: not-allowed, non-clickable. On hover show a small tooltip: Coming soon. Keep it in the DOM so the layout is final, but mark it aria-disabled="true"
LinkedIn	https://www.linkedin.com/in/lin-wei-ting-h-8a9732343 — target="_blank" with rel="noopener noreferrer"
CV Download	 — file lives in /public/cv/, so the download attribute is honoured (it only works same-origin)

Email in CONTACTS	Also a mailto: link. Displayed with text-transform: capitalize for the editorial look, but the actual href must be lowercase: mailto:a898499@gmail.com
Back-to-top circle	Smooth scrolls to page top over ~900ms with cubic-bezier(0.22, 1, 0.36, 1). If Lenis is in use, call lenis.scrollTo(0) rather than native scrollTo so it doesn't fight the smooth-scroll instance

Entrance Animation

Trigger once when the footer crosses 80% of viewport height (IntersectionObserver, once: true — never replay on scroll back up).

Headline Get An Idea? — masked line reveal. Wrap the line in a container with overflow: hidden; the text starts at translateY(100%) and rises to 0 over 900ms with cubic-bezier(0.22, 1, 0.36, 1). It should look like the words are being lifted up from behind a solid edge, not fading in.

Everything else — a simple staggered rise: translateY(24px) + opacity 0 → translateY(0) + opacity 1, 600ms each, cubic-bezier(0.22, 1, 0.36, 1).

Stagger order and delays (relative to trigger):

Element	Delay
Headline (mask reveal)	0ms
Let's Talk!	200ms
Horizontal rule — scales in from left, scaleX 0 → 1, transform-origin left,	320ms
(Brief) + bio paragraph	420ms
CV Download	520ms
SITEMAPS column (its own 60ms internal stagger per link)	560ms
SOCIALS column	620ms
CONTACTS column	680ms
Back-to-top circle — fades in and rotates from -90deg to 0	760ms

Total sequence ≈ 1.6s. It should feel like the footer is composing itself, calmly — no bounce, no overshoot.

Hover Interactions

Underlined links (all of them) — animated underline wipe. Do not use text-decoration. Draw the underline as a pseudo-element (::after, 1px, positioned at the text baseline). On hover, the line wipes out to the right (transform-origin: right; scaleX 1 → 0), then immediately wipes back in from the left (transform-origin: left; scaleX 0 → 1). 300ms each half, cubic-bezier(0.22, 1, 0.36, 1). The text itself simultaneously shifts translateX(4px).

Let's Talk! ↗ — same underline wipe, plus the arrow glyph translates 4px right and 4px up, and the whole element brightens slightly. 350ms.

CV Download — on hover, the label crossfades to Download PDF (1.2MB) via a vertical mask swap: the current text slides up and out while the new text slides up into place, both inside an overflow: hidden wrapper. 300ms. A small downward-arrow icon fades in on the right and gently bobs 3px down. On :active, the whole link scales to 0.98.

Back-to-top circle — the circle's border thickens subtly, the background fills with the accent red, the arrow turns white and translates 4px upward, and the circle scales to 1.06. 400ms ease-out. On click, the arrow shoots upward out of the circle and a new one enters from below.

Playground (disabled) — no underline animation. Only the Coming soon tooltip fades in above it after a 150ms delay.

All hover states must reverse cleanly on mouse-out at the same duration.

Accessibility & Responsive

- Every interactive element needs a visible :focus-visible state: 1px accent-red outline, 4px offset. Hover animations should also fire on keyboard focus.
- mailto: and external links get descriptive aria-labels. External LinkedIn link announces that it opens in a new tab.
- @media (prefers-reduced-motion: reduce): skip the entrance sequence entirely (render final state), and reduce all hover effects to a simple 150ms colour change.
- **Tablet:** the three link columns stay in a row; bio drops to full width above them.
- **Mobile:** headline scales down but stays dominant; the three link columns stack vertically with the red headings retained; the back-to-top circle shrinks to 48px and moves below the CTA. All hover states are replaced with :active press states (scale 0.97).

Technical Notes

- Animate transform and opacity only.
- Add will-change: transform only while an animation is running; remove it after.
- Use a real semantic <footer> element, and <nav> for the SITEMAPS column.
- Underline pseudo-elements must not affect layout — position them absolutely.

Acceptance Criteria

1. The headline reveal reads as a mask lift, not a fade.
2. The entrance sequence runs exactly once per page load.
3. CV Download triggers an actual file save on desktop Chrome, Safari, and Firefox — not a PDF preview tab.
4. Every underline hover wipes out-then-in without flicker, and reverses correctly if the pointer leaves mid-animation.
5. Playground is visibly present but genuinely non-clickable, and is skipped by keyboard tabbing.

6. Back-to-top uses the same smooth-scroll instance as the rest of the site.

字體都是用popping