BILLET-F2: Four-Channel Fixed-Point FIR RTL IP

Technical Design and Verification Report

16 October 2026 (UTC+8)


Abstract

BILLET-F2 implements four independently configured FIR channels around one shared, configurable parallel multiply-accumulate engine. It provides independent sample histories, per-channel double-buffered coefficients and atomic bank swaps, while preserving BILLET-F1 channel-zero numerical and cycle behavior with one MAC lane.

The mandatory behavioral matrix covered all 15 legal parameter combinations at seeds 17, 89 and 233: 102,339 retired samples matched an independent integer convolution model with zero output-code error. Fifteen additional F1 compatibility runs compared 8,472 retirements with zero differences. Reset canceled 90 and 30 transactions respectively; these were accounted separately from compared outputs. Three semantic mutants were detected, and all 15 configurations passed generic synthesis and latch checks. These results establish simulated digital behavior and generic synthesizability, not physical performance. [E019–E022]

1 Architecture and design rationale

The design uses one globally shared computation engine, no input queue and one output register. Separate histories and coefficient banks isolate channel state without duplicating the entire datapath. Each computation captures its channel and active-bank identity; global commit exclusion preserves that ownership through output retirement. This conservative policy retains F1 control semantics but prevents unrelated channels from committing while the engine or output is occupied. Parallel lanes process consecutive taps, with a balanced full-width reduction tree and combinational final rounding. The five synthesizable modules total 13,997 bytes and 368 source lines. [E001, E003–E007, E022]



Functional block map, not a gate-level netlist. Edge identifiers match the directed relationships below. Crossings do not denote junctions; separate attachment points preserve arrow directions.

Block	Responsibility
B1: Handshake control	Control logic in billet_f2_top determines sample, configuration and commit acceptance, enforces commit priority and excludes swaps during computation or valid output.

Block	Responsibility
B2: Coefficient banks	billet_f2_coeff_bank, instance u_coeff_bank, owns four independent bank pairs, active selectors and fresh-write masks. Parallel reads select the captured channel and bank.
B3: Channel histories	billet_f2_history, instance u_history, owns four delay lines. Only the accepted sample's channel shifts; tap zero becomes the newest sample.
B4: Parallel MAC	billet_f2_mac, instance u_mac, captures ownership and tracks tap groups. Signed 16-by-16 products are extended before balanced reduction and exact accumulation.
B5: Round and saturate	billet_f2_round_sat, instance u_round_sat, combinationally converts the exact final sum to signed Q1.15 using nearest-even rounding and saturation.
B6: Output register	Registers in billet_f2_top capture the final result and channel, hold them under backpressure and permit retirement alongside a replacement input.

Directed relationship	Meaning
E1: B1 to B2	Accepted coefficient writes and commits
E2: B1 to B3	Accepted sample, channel and history push
E3: B1 to B4	Start and accepted transaction identity
E4: B2 to B4	Active-bank identity and coefficient operands
E5: B4 to B2	Captured channel, bank and tap-group address
E6: B4 to B3	Captured channel and tap-group address
E7: B3 to B4	Parallel history operands
E8: B4 to B5	Exact final accumulator sum
E9: B5 to B6	Rounded, saturated result
E10: B4 to B6	Final capture enable and channel
E11: B4 to B1	Computation busy
E12: B6 to B1	Output occupancy

2 Interfaces and configuration

Signal / group	Direction	Width	Contract
clk, rst_n	Input	1 bit each	Rising-edge clock and active-low asynchronous reset. Transactions use pre-edge valid/ready values.
s_data, s_channel, s_valid; s_ready	Input; output	Signed 16, 2, 1; 1 bits	Input sample stream. Channel encodings 0–3 are legal. Producers hold valid, data and channel while stalled.
m_data, m_channel, m_valid; m_ready	Output; input	Signed 16, 2, 1; 1 bits	Ordered result stream. Valid data and channel remain stable until retirement or reset. Data and channel are zero whenever m_valid is low.
cfg_valid, cfg_channel, cfg_addr, cfg_data; cfg_ready	Input; output	1, 2, ADDR_W, signed 16; 1 bits	Writes the addressed channel's inactive coefficient bank. Acceptance requires a legal address and no commit request. Address one is rejected even at TAP_COUNT= 1.
commit_valid, commit_channel; commit_ready	Input; output	1, 2; 1 bits	Requests an atomic bank swap for one channel. Acceptance requires fresh complete staging, an idle MAC and no valid output. There is no pending-request queue.

Parameter	Default	Meaning / supported values
TAP_COUNT	32	Exactly 1, 8, 16, 32 or 64 taps per channel. All values were simulated and synthesized.
MAC_LANES	1	Exactly 1, 2 or 4 parallel multiplication paths. Every legal tap/lane combination is supported, including singleton filters with unused tail lanes.
ADDR_W, ACC_W	5, 37 at default TAP_COUNT	Derived local parameters: ADDR_W=max(1,ceil(log2(TAP_COUNT))); ACC_W=32+ceil(log2(TAP_COUNT)). The singleton logarithm is zero. Channel count is fixed at four.

3 Behavior and corner cases

3.1 Exact convolution and quantization

For channel c and its accepted sample n, A[c,n]=sum over k of h[c,k]*x[c,n-k], using signed 16-bit sample and coefficient codes and zero unavailable history. Tap zero multiplies the newest sample. Exact signed 32-bit products are sign-extended to ACC_W before reduction; intermediate rounding, truncation and saturation are absent. Let q=floor(A/32768), r=A−32768q. Increment q when r>16384 or when r=16384 and q is odd, then clamp to [−32768,32767]. This implements nearest-even rounding for both signs. Tail lanes contribute zero. [E002, E005, E007]

3.2 Independent state and atomic updates

Each channel has two banks, its own active selector and a TAP_COUNT-bit written mask. Repeated writes overwrite a tap without satisfying other missing addresses. Every tap needs a fresh accepted write after reset or that channel's preceding commit. A final missing write changes completeness only after its edge. Commit flips only the selected channel's bank, clears only its written mask and preserves all histories. Reusing old bank contents never substitutes for a fresh complete update. [E002, E003]

3.3 Priority and ownership

Exact readiness is s_ready=rst_n && !busy && (!output_valid || m_ready) && !commit_valid; cfg_ready=rst_n && !commit_valid && (cfg_addr<TAP_COUNT); commit_ready=rst_n && staging_complete[commit_channel] && !busy && !output_valid. Thus any commit request blocks sample and configuration acceptance, even if incomplete. No channel can commit during computation or on an output-retirement edge. Without a commit request, configuration may coincide with sample acceptance or continue during computation and output stalls; it always targets inactive storage. [E002, E007]

3.4 Cycle boundaries

Define G=ceil(TAP_COUNT/MAC_LANES). Acceptance at E0 shifts the selected history and captures ownership. Edges E1 through EG compute the groups; immediately after EG the result is valid and busy is clear. Earliest retirement and replacement acceptance occur at EG+1, giving an unstalled initiation interval of G+1 cycles. A commit cannot share that retirement edge; without replacement work it can occur at EG+2. After commit at C, the first new-bank sample can be accepted at C+1 when commit_valid is deasserted. Backpressure changes retirement and acceptance spacing, not computation latency. [E001, E002]

3.5 Reset and parameter rejection

Asynchronous reset clears both coefficient banks, histories, masks, selectors, arithmetic/control state and output state. All public outputs are zero during reset. Accepted but unretired work is canceled without ghost results; subsequent samples initially use zero coefficients. Unsupported parameters elaborate an isolated diagnostic branch and terminate simulation nonzero with PARAMETER ERROR rather than elaborating an invalid datapath. [E002–E007]

4 Verification methods and measured results

4.1 Numerical accuracy and four-channel protocol coverage

Method. Icarus Verilog 12.0 compiled and simulated all 15 configurations at three seeds. Python 3.12.3 independently computed per-channel arbitrary-precision convolution and quotient/remainder rounding from accepted public transactions, checking pre-edge and post-edge observations and rejecting X/Z.

Result. 45/45 runs passed: 102,339 retirements, 90 cancellations and zero numerical, channel, ordering or protocol mismatches. Every run met at least 256 retirements, four distinct committed generations and 16 output-stall cycles per channel, plus computation, stalled-output and blocked-commit reset coverage and final all-channel refill. Complete denominators, counts and witnesses are retained in evidence/behavior/results.json and its per-cell files.

Evidence: E008, E009, E010, E011, E019

4.2 Directed arithmetic and control interactions

Method. Observed numerical cases and public transitions covered impulses, signed ties and near-ties, full-scale products, saturation, channel isolation, repeated writes, completeness timing, commit exclusion and overlapping output retirement/input acceptance.

Result. For 8 taps/4 lanes/seed 17, 1,755 outputs matched, with 12 commits per channel and stall counts 80/81/117/105 cycles. Coverage included 83 simultaneous configuration/sample events, 127 writes during computation, 83 during output stalls, and both same-channel and other-channel blocked commits. Negative saturation and multi-product cancellation apply to multi-tap configurations; inter-lane cancellation applies where multiple lanes are useful.

Evidence: E009, E011, E019

4.3 Measured latency and throughput

Method. Public handshake traces measured acceptance-to-valid latency, acceptance-to-retirement latency and initiation intervals for every cell. Dedicated unstalled phases asserted G-cycle latency and G+1-cycle spacing.

Result. Measured valid latency/unstalled interval in cycles, ordered by lanes 1/2/4: taps 1: 1/2, 1/2, 1/2; taps 8: 8/9, 4/5, 2/3; taps 16: 16/17, 8/9, 4/5; taps 32: 32/33, 16/17, 8/9; taps 64: 64/65, 32/33, 16/17. These are cycle measurements, not frequency or lane-count speedup claims. All per-seed ranges are in evidence/behavior/results.json.

Evidence: E019

4.4 Backpressured cycle ranges

Method. The seed-17 traces provide a comparable measured example for every parameter setting. Extended intervals include backpressure, control traffic and stimulus gaps; they are not attributed solely to output stalls.

Result. Acceptance-to-retirement ranges, ordered by lanes 1/2/4, were: taps 1: 2–24 for all lanes; taps 8: 9–31, 5–27, 3–25; taps 16: 17–39, 9–31, 5–27; taps 32: 33–55, 17–39, 9–31; taps 64: 65–87, 33–55, 17–39 cycles. Corresponding extended initiation ranges were 3–26 for all singleton settings; 10–33/6–29/4–27; 18–53/10–45/6–41; 34–101/18–85/10–77; and 66–197/34–165/18–149 cycles.

Evidence: E019

4.5 Atomic bank boundaries

Method. Generation-tagged transactions were checked against complete mathematical coefficient vectors. Each commit retained surrounding public traces and identified the last old-generation and first new-generation samples where present.

Result. No mixed-generation result or premature commit was observed. One 8/4/17 channel-zero boundary committed at cycle 173: the last old-generation sample was accepted at 142 and retired at 145 with result zero; the first new-generation sample was accepted at 175, became valid at 177 and retired at 178 with expected and observed result 45. Full boundaries are in each cell's bank_boundaries.json.

Evidence: E009, E019

4.6 F1 compatibility

Method. Unchanged F1 RTL and F2 ran identical channel-zero traffic with one lane for all five tap counts and three seeds, comparing readiness and outputs as well as the independent numerical oracle.

Result. 15/15 runs passed with 8,472 compared retirements, 30 cancellations and zero output-code differences. Initial zero banks, complete/incomplete updates, rounding, saturation, busy-time writes, stalls, retirement/replacement overlap and reset cancellation were exercised. Other F2 channels remained inactive.

Evidence: E008, E009, E010, E020

4.7 Sensitivity to semantic defects

Method. A passing 8/4/17 baseline and three disposable mutant copies used the same independent checker. Compilation failures and tool failures did not qualify as detection.

Result. All three mutants were killed by behavioral mismatches: crossed history produced 81 instead of −1441; reduction-tree corruption produced −1522 instead of −1441; relaxed bank ownership incorrectly asserted commit readiness during computation. Patches, source identities and triggering transactions are retained under evidence/defects/mutations/.

Evidence: E010, E021

4.8 Synthesizability, state and parallel structure

Method. Yosys 0.33 executed synth -noabc and check -assert for all 15 settings. Pre-flatten checks inspected named connected children, bank/history state and distinct signed operand lanes; final netlists were checked for latches and substantive outputs.

Result. 15/15 configurations passed with zero latches. Generic cell counts/sequential bits, ordered by lanes 1/2/4: taps 1: 3400/256, 3173/255, 3270/255; taps 8: 9081/1633, 14396/1633, 24744/1632; taps 16: 15555/3203, 23955/3203, 40736/3202; taps 32: 28492/6341, 43240/6341, 72913/6340; taps 64: 54539/12615,

81814/12615, 136963/12614. Useful multiplier counts were 1/2/4 for multi-tap settings and one for singleton settings. Detailed structures and netlists accompany evidence/synthesis/results.json.

Evidence: E013, E022

4.9 Illegal-parameter diagnostics

Method. Icarus elaborated taps 0/3/65 with one lane and lanes 0/3/8 with eight taps, then executed each diagnostic branch.

Result. All six cases compiled successfully and terminated with simulation exit 1 and PARAMETER ERROR.

Evidence: E014, E022

4.10 Harness reliability and portable reproduction

Method. Retained preparation failures informed harness-only repairs: explicit $finish(0) removed extra finish metadata without relaxing completion checks; singleton structure checking distinguished useful wired lanes from unused tail paths. A fresh source-only tree subsequently executed complete behavior 8/4/17, compatibility 1/1/17 and synthesis 8/4 cells.

Result. The repaired full matrices passed, and all three fresh-tree cells passed with matching source identities. Runtime metadata, prior evidence and generated binaries were excluded from copied inputs. Preparation failures remain retained separately; they are not acceptance substitutes or product RTL defects.

Evidence: E018, E019, E022, E023

5 Integration and use

Compile all five rtl/*.sv files with SystemVerilog enabled and select billet_f2_top. Use design/SPEC.md for the normative interface and edge contract and design/ARCHITECTURE.md for internal connectivity. Packed operand lane l occupies bits [16*l +: 16].

Assert reset low before operation. To update channel c, keep commit_valid low and handshake every tap into staging, then hold commit_valid and commit_channel until acceptance. Deassert the request before further writes or samples. An incomplete held commit intentionally blocks the writes needed to complete it; withdraw it or reset to resume.

Keep the output consumer responsive when awaiting commit. Backpressure preserves output and bank ownership indefinitely; the design does not force retirement. Clock-domain crossing and asynchronous-reset release discipline belong to the surrounding integration.

External prerequisites are Python 3, iverilog, vvp and Yosys. From the project root, reproduce the full behavior suite with python3 tests/verify.py --suite behavior --output evidence/behavior.

Run compatibility with python3 tests/verify.py --suite compatibility --output evidence/compatibility and semantic mutations with python3 tests/verify.py --suite defects --output evidence/defects.

Run synthesis and diagnostics with python3 tests/verify.py --suite synthesis --output evidence/synthesis. Reproduce the executed bounded fresh-tree check with python3 tests/verify.py --suite portability --output evidence/portability. Existing output directories are preserved through new attempt directories. Per-tool receipts retain exact commands, versions, source identities and raw outputs.

6 Limitations and acceptance boundary

Four channels share one engine; they are not four concurrent filters. Global commit exclusion also blocks updates to otherwise idle channels while any computation or valid output exists.

Evidence covers finite seeded simulation, directed transitions, three specific semantic mutants and generic synthesis. It is not exhaustive formal proof or evidence of sensitivity to every possible defect.

Generic cells and sequential bits are tool-dependent structural counts, not physical area. No target clock frequency, timing closure, power, FPGA resource measurement or silicon result was established.

Asynchronous clearing and parallel reads do not guarantee inference of a particular RAM or DSP macro. Technology mapping and implementation constraints remain external.

Portable reproduction executed three complete selected cells, not a second full matrix. The parent intake supplied RTL but no linked source index, parent specification or admitted baseline results; compatibility is supported by the newly executed lockstep and oracle checks rather than intake provenance.

A Source inventory

Production inventory: 5 Verilog/SystemVerilog files; 342 nonblank, non-comment lines. Source size is not a correctness or quality metric.

Production file	Physical lines	Code lines
rtl/billet_f2_coeff_bank.sv	66	62
rtl/billet_f2_history.sv	42	38
rtl/billet_f2_mac.sv	79	73
rtl/billet_f2_round_sat.sv	32	28
rtl/billet_f2_top.sv	149	141

B Verification record index

Recorded check	Outcome	Execution time (s)
behavior	passed	198.410
f1_compatibility	passed	33.651
defect_sensitivity	passed	4.815
synthesis_and_parameter_diagnostics	passed	1384.432
portable_reproduction	passed	15.762

Execution times include tool and provider waiting; they are not hardware latency or model utilization.

Reference	Original project-relative record
E008	tests/bridge.py
E009	tests/model.py
E010	tests/simulation.py
E011	tests/stimulus.py
E013	tests/synthesis.py
E014	tests/verify.py

Reference	Original project-relative record
E018	.vulcan/engineering/run-0001/attempt-0002/response.json
E019	.vulcan/engineering/run-0001/attempt-0003/stdout.log
E020	.vulcan/engineering/run-0001/attempt-0004/stdout.log
E021	.vulcan/engineering/run-0001/attempt-0005/stdout.log
E022	.vulcan/engineering/run-0001/attempt-0006/stdout.log
E023	.vulcan/engineering/run-0001/attempt-0007/stdout.log

C Document provenance

Engineering was independently accepted for the recorded source and evidence identity. This is not exhaustive proof, hardware deployment or physical signoff. The companion REPORT.md records the exact report approval and source manifest, and links the English/Chinese journeys containing original failures and interventions. A report number identifies a generation attempt, not a new hardware revision.

No developer attribution was supplied; none has been inferred.