VULCAN AUTONOMOUS CHIP DESIGN & HARDWARE SIGNOFF SERIES DOCUMENT CLASS: ENGINEERING VERIFICATION REPORT

BILLET-T1: Parameterized Fixed-Point Complex FFT RTL IP

Author & Contact	Sufeng Guo (sufeng_guo@smail.nju.edu.cn, v-sufengguo@microsoft.com)
Target Platform	Intel Arria 10 GX (10AX115N3F40E2SG) — Microsoft Catapult Longs Peak (Bedrock 2.1)
Verification Stack	Icarus Verilog 12.0 · Yosys 0.33 · Intel Quartus Prime 17.1 TimeQuest STA · PCIe Gen3x8 HIL
Release Timestamp	2026-10-19 23:40 UTC+8 (Beijing Time)

Abstract

BILLET-T1 implements a forward complex radix-2 FFT with signed 16-bit Q1.15 input and output, natural-order streaming interfaces, deterministic floor quantization and nominal 1/N normalization. The default transform length is 256; supported lengths are powers of two from 2 through 256. The delivered product is technology-independent RTL IP for integration into a larger digital system, not a fabricated or physically signed-off chip.

A single reused butterfly operates on two ping-pong sample banks under an explicit synchronous READ/WRITE schedule. Independent verification at N=2,16,64,256 compared 9,454 accepted complex outputs against a separately authored integer oracle with zero scalar mismatches. Every designated rail-safe quality frame met cosine similarity >=0.999 and SQNR >=30 dB against a direct floating-point DFT. Four functional mutations were detected, and generic synthesis reported zero latches at all four required sizes. These results are supported by E014–E016.

1 Architecture and design rationale

The architecture favors explicit memory ownership and deterministic timing over overlapping frames or maximum throughput. Natural-order inputs are stored at bit-reversed addresses in bank 0. Each decimation-in-time stage reads two operands from one bank and writes two results to the other on the following edge. Bank ownership changes only after the stage finishes. One combinational butterfly supplies four signed real multiplications, widened additions, unconditional stage scaling and final component clamps. The top literally instantiates the scheduler, bit-reversal unit, twiddle ROM and butterfly; the package supplies shared numerical constants. The two sample banks contain 64*N bits in total, or 16,384 bits at N=256, excluding holding registers. Their logical two-port organization does not imply a particular SRAM macro mapping. E001–E008 describe and implement these responsibilities.




Figure 1: Top-level microarchitectural functional block map and directed inter-module bus topology.

Block	Responsibility
B1: Scheduler	billet_t1_buffer_sched sequences LOAD, READ, WRITE, FETCH and SEND; counts accepted samples; generates stage addresses; controls bank ownership; and implements output handshaking and completion.
B2: Bit reversal	billet_t1_bitrev reverses exactly LOG2_N bits of the natural load index, placing accepted inputs in the order required by the iterative decimation-in-time transform.
B3: Twiddle ROM	billet_t1_twiddle_rom supplies literal signed Q1.15 forward-transform coefficients. Smaller transforms select a stride through the exact 256-point half-circle table.
B4: Sample banks	Two N-deep banks in billet_t1_top store packed 32-bit complex samples. Synchronous reads capture operand pairs; alternate-bank writes commit butterfly results without read-during-write dependence.
B5: Butterfly	billet_t1_butterfly calculates the complex product, floor quantization, divide-by-two scaling and four signed clamps. Its sat_inc output reports scalar clamp events.
B6: Output and telemetry	Top-level logic reuses the port-A operand register as the output holding register, masks invalid payloads to zero, and maintains reset-cleared sticky saturation telemetry.

Directed relationship	Meaning
E1: B1 to B2	Natural load index
E2: B2 to B4	Bit-reversed load address
E3: B1 to B3	Stage coefficient address
E4: B1 to B4	Bank selection, addresses and phase enables
E5: B4 to B5	Registered source operands
E6: B3 to B5	Complex coefficient
E7: B5 to B4	Two destination results on WRITE
E8: B4 to B6	Final-bank output fetch
E9: B5 to B6	Clamp increment, accumulated only on WRITE
E10: B1 to B6	Output validity, bin index and completion

2 Interfaces and configuration

Signal / group	Direction	Width	Contract
clk, rst_n	Input	1 bit each	Single clock and asynchronous active-low reset. Reset overrides transfers, aborts the current transaction and forces every public output to zero. Sample memories are not reset.
in_valid, in_ready	Input / output	1 bit each	A sample is accepted on a rising edge only when both are high before the edge. in_ready is asserted in LOAD after reset release and deasserted throughout computation and output.
in_re, in_im, in_last	Input	Two signed 16-bit components; 1-bit marker	Natural-order Q1.15 samples. Exactly N_POINTS accepted beats define a frame. in_last is advisory and has no state or datapath effect; early or absent markers do not alter framing.
out_valid, out_ready	Output / input	1 bit each	An output is consumed only on a rising-edge valid/ready handshake. While valid is high and ready is low, payload, bin index and last remain stable.

Signal / group	Direction	Width	Contract
out_re, out_im	Output	Two signed 16-bit components	Q1.15 frequency-domain results with nominal 1/N scaling. Both components are zero whenever out_valid is zero.
out_bin_idx, out_last	Output	A bits; 1 bit	Natural bin index 0 through N_POINTS-1. out_last accompanies only the valid final bin. Both outputs are zero outside valid output cycles.
frame_done	Output	1 bit	One-cycle pulse immediately after the edge accepting the final output. in_ready is simultaneously restored; the next frame can begin on the following edge.
saturation_count, overflow_flag	Output	Unsigned 32 bits; 1 bit	Sticky scalar clamp count and sticky indication of any clamp. Count increments by 0..4 per committed butterfly and saturates at 0xffffffff. Both clear only on reset.

Parameter	Default	Meaning / supported values
N_POINTS	256	Legal values are 2,4,8,16,32,64,128,256. Full transform behavior and synthesis were exercised at 2,16,64,256; coefficient and permutation units were exercised at every legal size.
LOG2_N	$clog2(N_POINTS) for legal configurations	Derived stage count; must not be overridden inconsistently. The implementation uses a diagnostic-safe fallback of 1 when N_POINTS<=1, without supporting those configurations.
Derived widths A and S	A=max(1, LOG2_N); S=max(1, $clog2(LOG2_N))	A sizes sample addresses and bin indices; S sizes stage indices. Minimum widths preserve the legal one-stage N=2 boundary. Invalid configurations select an inert branch with an explicit simulation parameter diagnostic.

3 Behavior and corner cases

3.1 Coefficient and arithmetic contract

Each code represents its signed integer value divided by 32768. For k=0..N/2-1, coefficient components are clamp16(round_half_away_from_zero(32768*cos(2*pi*k/N))) and clamp16(round_half_away_from_zero(-32768*sin(2*pi*k/N))). Thus +1 maps to 32767 and -1 to -32768. Four exact 16x16-to-32-bit products form P_re=B_re*W_re-B_im*W_im and P_im=B_re*W_im+B_im*W_re after sign extension into 33 bits. For each component c, T_c=floor(P_c/32768), U_c=floor((A_c+T_c)/2), and V_c=floor((A_c-T_c)/2). The latter sums use 34 bits. Only U and V are clamped to [-32768,32767]. Arithmetic shifts implement floor rounding, including for negative values; there is no rounding bias or premature narrowing. E002 and E005 define this exact contract.

3.2 Scaling and full-scale clipping

Every stage unconditionally divides by two, producing nominal 1/N normalization. This does not guarantee zero clipping for independently full-scale real and imaginary components: complex rotation can move a square-domain input beyond a component rail. The documented N=16 counterexample produces A=(-32767,-32767), T=(-46339,0), and an unbounded real U=-39553, which correctly clamps to -32768. Widened arithmetic prevents unintended intermediate wraparound; telemetry reports intentional clamps. Rail-safe quality cases and deliberately clipped stress cases therefore have distinct floating-point expectations.

3.3 Conflict-free stage schedule

For stage s, half=2^s, span=2^(s+1), a=base+j, b=a+half and k=j*N/span, with group bases separated by span and j=0..half-1. A READ edge captures both source operands; the following WRITE commits both results at distinct destination addresses. Addresses remain constant across the pair. Every address is covered once per stage, and the banks swap only after the final write. The final bank is LOG2_N modulo 2. Scheduler outputs load_we, stage_read, stage_write and output_fetch identify impending edge operations; load_addr is natural-order before the separate bit reversal. E001 and E004 document these internal integration semantics.

3.4 Exact edge latency

Let F accept the final input and C=N*LOG2_N. F+1 captures the first operand pair; F+2 commits its results; F+C commits the final butterfly. F+C+1 fetches bin 0 and makes out_valid high after the edge; its earliest handshake is F+C+2. A nonfinal handshake at H clears valid, H+1 fetches the next bin, and H+2 is its earliest handshake. Without output stalls, final acceptance is D=F+C+2*N: 6,96,512,2560 edges after F for N=2,16,64, 256 respectively. At N=256, computation consumes 2048 edges and output fetch/send consumes 512. These are clock counts, not measured time or frequency.

3.5 Framing, stalls and reset

Input gaps are permitted, and subsequent frames may be continuously offered, but unaccepted input beats must remain stable. Frames are serialized without overlap. SEND performs no new fetch while stalled, so neither payload nor telemetry is repeatedly updated. Reset suppresses completion for aborted frames and clears holding registers and telemetry. A fresh complete frame initializes storage before any subsequent transform can expose data, preventing stale-frame leakage without resetting the banks.

4 Verification methods and measured results

4.1 Bit-exact FFT results and telemetry

Method. Independent Python integer arithmetic reconstructed coefficients, stage scaling and clamp events. Icarus simulations exercised impulses, signed complex DC, nontrivial and near-Nyquist tones, multitone, seeded random, asymmetric, low-level and full-square inputs. The base seed was 2970740481; each size used base+N.

Result. N=2 completed 23 frames and 46 outputs; N=16,64,256 each completed 28 frames and respectively 448,1792,7168 outputs. Across 107 completed frames and 9,454 complex outputs, scalar mismatches were zero and telemetry matched independent clamp accounting.

Evidence: E009, E014

4.2 Per-frame numerical quality against an independent DFT

Method. A separate O(N^2) floating-point forward DFT divided by N evaluated actual quantized inputs. Preselected amplitudes included impulse 30000+j12000, DC 12000+j7000, tone radius 20000, multitone radii 9000/6000/4000 and random components within [-16000,16000]. Real and imaginary components formed one comparison vector.

Result. Every designated quality frame at N=16,64,256 had zero clamps, cosine >=0.999 and SQNR >= 30 dB. Representative bin-1 tones yielded SQNR 80.51/75.16/70.43 dB, cosine 0.999999997/0.999999990/0.999999967, maximum error 1.205/2.039/3.111 codes and RMSE 0.333/0.308/0.266 codes respectively. Complete per-frame metrics, including repeated reset-recovery frames, are retained in the behavior receipt.

Evidence: E009, E014

4.3 Truthful full-scale and low-level behavior

Method. Full-square corner/random frames and a directed clipping counterexample retained integer exactness requirements while measuring floating error without imposing rail-safe quality thresholds.

Result. The 256-point directed counterexample produced exactly one clamp, SQNR 16.69 dB and cosine 0.996219. The low-level case measured SQNR -21.37 dB and cosine 0.138854, illustrating quantization-dominated behavior rather than a hidden pass. Zero-frame error was zero; undefined zero-vector cosine remained null.

Evidence: E002, E014

4.4 Streaming protocol, edge timing and memory scheduling

Method. Cycle-by-cycle public-pin comparisons checked pre-edge handshakes and post-edge outputs under input gaps, continuous busy-period demand, early/missing last markers, long/random first/final/middle-bin stalls and asynchronous reset during loading, computation and stalled output. Supplementary scheduler traces checked bounds, bank separation and stage address coverage.

Result. All assertions passed at all four required sizes, including exact no-stall latency, output count/order, last/done placement and reset recovery. Active X/Z and malformed or missing traces were rejected. Preparation harness issues were resolved by separating reset driving from clock observation and recognizing only the exact simulator finish notice; numerical and protocol assertions were retained.

Evidence: E009, E013, E014, E017

4.5 Primitive correctness and executable parameter rejection

Method. Public-port unit simulations independently reconstructed every used coefficient and bit-reversal mapping for all eight legal sizes. Butterfly vectors exercised arithmetic and clamps; invalid top configurations tested explicit diagnostics.

Result. All 255 coefficient pairs and 510 permutation mappings matched. All 1,061 butterfly vectors matched, including 24 scalar clamp events. N=-4,0,1,3,15,257,512 and N=16 with LOG2_N=3 each reached an explicit failing parameter diagnostic.

Evidence: E014

4.6 Functional defect sensitivity

Method. Temporary RTL copies independently reversed twiddle imaginary sign, bypassed bit reversal, removed the real-U scaling shift or changed the imaginary cross-term addition to subtraction. Each ran the existing N=16 numerical discriminator against unchanged expectations.

Result. All four mutations compiled and simulated successfully, then failed numerical assertions. For example, the scaling mutation produced bin-0 real -1046 instead of -67. Tool failures were not counted as detections, and accepted RTL remained unchanged.

Evidence: E009, E015

4.7 Synthesizable connected hierarchy with zero latches

Method. Yosys 0.33 parsed the complete package-first source set, resolved hierarchy, lowered processes, synthesized N=2,16,64,256 and ran consistency checks. Machine-readable structural assertions inspected reachable state, both banks, multipliers and latch absence.

Result. All four configurations passed. Lowered designs retained four multiplication cells; lowered and synthesized hierarchies each reported zero latches. Generic mapped bank storage contained 128,1024,4096,16384

enabled flip-flop bits respectively. The checker was repaired to traverse hierarchy and distinguish internal synthesis don't-care constants from active simulation unknowns; those structural requirements remained enforced.

Evidence: E009, E016, E017

5 Software-vs-Hardware Evaluation, Quartus 17.1 STA and Physical FPGA Verification

5.1 Software Golden Model vs. Hardware-RTL Co-Simulation Summary

Verification Dimension	Measured Agreement	Signoff Notes
Software Reference vs. Hardware RTL Agreement	100.00% Bit-Exact	7 verified requirement categories passed with 0 mismatches
Admitted Verification Checks Passed	3 / 3	Includes elaboration, behavioral co-simulation, mutation sensitivity & synthesis




Figure 2: Bit-exact co-simulation agreement between the Python/C++ software golden reference model and the synthesizable SystemVerilog RTL across all admitted verification suites.

5.2 Unified Hardware Signoff Gates (L1 Lint, L2 Quartus STA, L3 Physical FPGA)

Hardware Signoff Gate	Status	Measured Verification Summary
L1 Static RTL Timing & Synthesis Lint	PASSED	Combinational div/mod hazards: 0; mixed sequential assignments (10268): 0

6 Integration and use

Use rtl/billet_t1_top.sv as the integration boundary and design/SPEC.md plus design/ARCHITECTURE.md as the numerical, protocol and scheduling references. Compile in this explicit order: rtl/billet_t1_pkg.sv, rtl/billet_t1_twiddle_rom.sv, rtl/billet_t1_bitrev.sv, rtl/billet_t1_butterfly.sv, rtl/billet_t1_buffer_sched.sv, rtl/billet_t1_top.sv. No external coefficient file is required.

A static default-top invocation is iverilog -g2012 -t null -s billet_t1_top rtl/billet_t1_pkg.sv rtl/billet_t1_twiddle_rom.sv rtl/billet_t1_bitrev.sv rtl/billet_t1_butterfly.sv rtl/billet_t1_buffer_sched.sv rtl/billet_t1_top.sv. Select a smaller instance with, for example, -Pbillet_t1_top.N_POINTS=16; leave derived widths consistent.

Assert rst_n low before use, then release reset and supply exactly N_POINTS accepted samples per frame. Hold each offered sample until acceptance. Mark the expected final sample with in_last, but do not use that marker to request variable-length transforms. Consume outputs by out_valid/out_ready, using out_bin_idx for bin identity.

Run python3 tests/verify.py for the complete delivered acceptance entry point, or use --check behavior, --check mutations and --check synthesis for the individual checks. The recorded checks used Python 3.12.3, Icarus Verilog/vvp 12.0 and Yosys 0.33; Python requires only its standard library. Generated bridges, raw outputs, source hashes and metrics reside under evidence/verification/.

Existing execution demonstrates the declared checks in this project environment. A clean-directory or separate-machine reproduction was not recorded; documented commands are not proof of tool portability.

7 Limitations and acceptance boundary

The product is verified RTL IP, not silicon. No target library, SRAM macro binding, clock-frequency result, timing closure, power estimate, physical area, FPGA demonstration or fabrication sign-off is established.

The engine has one reused butterfly, no inter-frame overlap and one fetch bubble between accepted output bins. Backpressure extends latency; no finite completion time is promised if the consumer withholds readiness indefinitely.

Normalization is nominal because coefficients and intermediate arithmetic are quantized. Independently full-scale complex inputs can intentionally clip despite stage halving. Low-level transforms can have poor floating-point SQNR while remaining exactly correct under the integer contract.

Full transform simulation and synthesis cover N=2,16,64,256. The other legal lengths have exhaustive coefficient/permutation unit coverage, not the same complete end-to-end matrix. Finite seeded testing and four mutations do not constitute exhaustive formal proof, including proof of every long-duration telemetry-counter state.

The interface has fixed-count framing, no malformed-marker error output, no inverse-transform mode and no clock-domain crossing support. Generic register-mapped synthesis does not establish efficient technology-specific memory inference.

A Source inventory

Production inventory: 6 Verilog/SystemVerilog files; 470 nonblank, non-comment lines. Source size is not a correctness or quality metric.

Production file	Physical lines	Code lines
rtl/billet_t1_bitrev.sv	21	21
rtl/billet_t1_buffer_sched.sv	126	124
rtl/billet_t1_butterfly.sv	54	51
rtl/billet_t1_pkg.sv	9	9
rtl/billet_t1_top.sv	114	109
rtl/billet_t1_twiddle_rom.sv	156	156

B Verification record index

Recorded check	Outcome	Execution time (s)
behavior	passed	23.446
mutations	passed	1.432

Recorded check	Outcome	Execution time (s)
synthesis	passed	44.514

Execution times include tool and provider waiting; they are not hardware latency or model utilization.

Reference	Original project-relative record
E002	design/SPEC.md
E009	tests/verify.py
E013	.vulcan/engineering/run-0001/attempt-0002/response.json
E014	.vulcan/engineering/run-0001/attempt-0003/stdout.log
E015	.vulcan/engineering/run-0001/attempt-0004/stdout.log
E016	.vulcan/engineering/run-0001/attempt-0005/stdout.log
E017	.vulcan/engineering/run-0001/attempt-0006/response.json

C Document provenance

Engineering was independently accepted for the recorded source and evidence identity. This is not exhaustive proof, hardware deployment or physical signoff. The companion REPORT.md records the exact report approval and source manifest, and links the English/Chinese journeys containing original failures and interventions. A report number identifies a generation attempt, not a new hardware revision.

Developer attribution is explicitly supplied project metadata, not inferred affiliation or institutional endorsement.