

A diagram of a rectangle with a width of 300 and a height of 100. The width is labeled '300' at the bottom, and the height is labeled '100' on the right side.

A diagram of a rectangle with a horizontal side labeled 300 and a vertical side labeled 200.

Ферма стропильная ФС-1 (опалубка)

Technical drawing of a roof truss (Ферма стропильная ФС-1) showing a side elevation. The drawing includes dimensions for various components and structural details.

Key dimensions and features:

- Overall width:** 17900
- Roof slope:** Indicated by a triangle with a vertical side of 900 and a horizontal side of 2900.
- Truss members and dimensions:**
 - Top chord: 2900, 3000, 3000, 3000, 3000, 3000
 - Bottom chord: 1140, 600, 350, 475, 380, 435, 435
 - Vertical supports: 1750, 1765, 3010, 3010
 - Diagonal bracing: 2105, 3000, 3200, 4200
 - Horizontal bracing: 850, 980, 460
- Structural details:**
 - Labels M2, T1, T2, T3, T4, T5, T6, T7, T8, T9, T10, T11, T12, T13, T14, T15, T16, T17, T18, T19, T20, T21, T22, T23, T24, T25, T26, T27, T28, T29, T30, T31, T32, T33, T34, T35, T36, T37, T38, T39, T40, T41, T42, T43, T44, T45, T46, T47, T48, T49, T50, T51, T52, T53, T54, T55, T56, T57, T58, T59, T60, T61, T62, T63, T64, T65, T66, T67, T68, T69, T70, T71, T72, T73, T74, T75, T76, T77, T78, T79, T80, T81, T82, T83, T84, T85, T86, T87, T88, T89, T90, T91, T92, T93, T94, T95, T96, T97, T98, T99, T100
 - Labels "Ось симметрии" (Axis of symmetry) and "Ось симметрии" (Axis of symmetry)

Ферма стропильная ФС-1 (армирование)

Technical drawing of a square plate with the following specifications:

- Overall dimensions: 300 x 300 mm.
- Four corner holes: $\Phi 40A600$ with a distance of 70 mm from the corners.
- Four central holes: $\Phi 14A400$ with a distance of 220 mm between them.
- Plate thickness: 80 mm.
- Edge distance: 40 mm from the outer edge to the center of the corner holes.

Technical drawing of a square plate with the following dimensions and specifications:

- Overall width: 240
- Overall height: 150
- Inner square dimensions: 180 (width) and 90 (height)
- Distance from inner square corners to outer square corners: 30
- Four holes are located at the corners of the inner square.
- Each hole has a diameter of $\varnothing 8$.

Technical drawing of a reinforced concrete column cross-section. The column is square with a total width of 300 mm and a total height of 600 mm. It is divided into three vertical sections: a top section of 150 mm, a middle section of 300 mm, and a bottom section of 220 mm. The top section contains 4 top bars (2Φ10A400) and 2 side bars (2Φ8A400). The middle section contains 4 top bars (2Φ8A400) and 4 bottom bars (2Φ14A400). The bottom section contains 4 top bars (2Φ14A400) and 4 bottom bars (Φ40A600). The column is reinforced with stirrups (шарж) of 70 mm spacing. The bottom section also shows a 40 mm concrete cover and 140 mm spacing between the bottom bars.

Technical drawing of a reinforced concrete beam cross-section. The drawing shows a rectangular cross-section with a width of 100 and a height of 250. The top reinforcement consists of 9 bars of diameter 8A240. The bottom reinforcement consists of 2 bars of diameter 20A240. The beam is shown in a perspective view, with a section cut indicated by a dashed line. The drawing includes labels for the reinforcement bars and their spacing: 9φ8A240 шаг 100, φ8A240 шаг 250, φ22A400 шаг 220, φ8A400 шаг 90, and 2φ20A240. A dimension of 100 is shown for the width. A small circle with the letter 'L' is located above the beam.

Формат A1