Working of Function in C



main.c

```
#include "Destroy.h"
#include <stdio.h>
#include <stdlib.h>
#include "struct.h"

int main(){
        .
        .
        printf..
        .
        .
        Destroy()
        .
        .
        return 0;

}
```

Destroy.c

```
#include "Destroy.h"


void Destroy(){
.
.

.
}
```

Destroy.h

```
#ifndef __Card__Destroy__
#define __Card__Destroy__

#include <stdio.h>
#include <stdlib.h>
#include "struct.h"

void Destroy( );


#endif /* defined(__Card__Destroy__) */
```











Type Casting

- Implicit Type Casting
- Explicit Type Casting

Structure ⟷ Unions

```
struct Emp
{
 char X ;     // size 1 byte
 float Y ;    // size 4 byte
} e ;
```

```
union Emp
{
 char X ;
 float Y ;
} e ;
```

```c
enum WeekDays
{
    Monday,
    Tuesday,
    Wednesday,
    Thursday,
    Friday,
    Saturday,
    Sunday
}
```

Simple Data

```c
enum WeekDays
{
    Monday = 0,
    Tuesday = 1,
    Wednesday = 2,
    Thursday = 3,
    Friday = 4,
    Saturday = 5,
    Sunday = 6
}
```

Data with Index

```c
enum WeekDays
{
    Monday = 0,
    Tuesday = 5,
    Wednesday = 10,
    Thursday = 15,
    Friday = 18,
    Saturday = 21,
    Sunday = 30
}
```

Data with Random Index

i++ → Assign → increment

++i → increment → Assign

```
// code
goto label 1 ;

Statement 1
Statement 2        → Skipped

label 1 :

Statement 3
Statement 4
// code
```

sizeof()

Returns the size of

1. Variable.
2. Data type
3. Expression
4. Pointer

Volatile

Keyword in C

Register

```c
typedef int myint;
```

keyword | datatype | new name