

Introduction to changepoint detection from first principles

Arnaud Liehrmann & Guillem Rigaill

Sorbonne Université & INRAE

February 25, 2025



Introduction

- ▶ Detecting and locating changes in distribution within time series data presents a fundamental statistical challenge.
- ▶ The first studies on changepoint detection emerged in the 1940s [Wald, 1945, Page, 1954]
- ▶ A significant increase in research activity in this area has occurred in recent decades (see [Venkatraman and Olshen, 2007, Killick et al., 2012, Fryzlewicz, 2014, Maidstone et al., 2017] among many others))



Plan

A Simple Example

An archetypical model

Conclusion

A Simple Example



- ▶ Data from [Lai et al., 2005]
- ▶ Comparative Genomic Hybridization (CGH) reveals chromosomal aberrations in DNA.
- ▶ Abrupt changes in signal intensity reveal these aberrations.

Data Analysis Questions

- ▶ Are there changes in the intensity that reveal chromosomal aberrations?
- ▶ If so,
 - ▶ How many are there?
 - ▶ A marker of genomic instability?
 - ▶ Where are they located?
 - ▶ To detect fusion and splits of certain genes
 - ▶ Which chromosomal regions are amplified or deleted?
 - ▶ Potential oncogenes and tumor suppressor genes

Statistical Goals

Detection Has a change occurred?

How many If there are changes, how many are there?

No Spurious Avoid the detection of false changes.

Estimation If there is a change, what is the intensity before and after?


Localization If there are changes, where are they, and how confident are we about their locations?

Many Types of Changes


- ▶ Gaussian data: Change in mean.
- ▶ Genomics: Poisson or Negative Binomial models
- ▶ Slope (with a continuity constraint)
- ▶ Peaks
- ▶ Changes in variance
- ▶ Changes in multiple parameters.
- ▶ Multivariate settings: Regression or graphical models.
- ▶ Network structure changes.
- ▶ Variance/Covariance
- ▶ Non-parametric changes in distribution
- ▶ ...

Many Types of Changes


CGH




Chip-Seq



Neuroscience



RNA-seq



Plan

A Simple Example

An archetypical model

Conclusion

A Principled Approach

- ▶ Hope to provide a solid understanding of the core principles of changepoint detection (exercises...)
- ▶ Focus on the univariate change-in-mean model
- ▶ Key challenges and difficulties related to changepoint detection are already present in this univariate change-in-mean model
- ▶ Considering as a baseline a penalized maximum likelihood approach (with a constant per changepoint penalty)

The univariate change in mean model is not that simple!

- ▶ Despite its apparent simplicity, it remains an active area of research (see, for example, [Killick et al., 2012, Aue and Kirch, 2024, Fryzlewicz, 2014, Kovács et al., 2023, Verzelen et al., 2023, Yu et al., 2023])
- ▶ Why: Let us consider the “vanilla” approach for just one change.
 - ▶ Our data y_1, y_2, \dots, y_n
 - ▶ Assuming the $y_t = \mu_t + \varepsilon_t$
 - ▶ Assuming ε_t are Gaussian $\mathcal{N}(0, 1)$
 - ▶ $\mu_t = 0$ for $t \leq \tau^*$ and 1 otherwise

At most one change “vanilla” approach

- ▶ Compare the mean square error with a change at τ :

$$\sum_{t=1}^{\tau} (y_t - \bar{y}_{1:\tau})^2 + \sum_{t=\tau+1}^n (y_t - \bar{y}_{\tau+1:n})^2,$$

- ▶ with the mean square error without a change

$$\sum_{t=1}^n (y_t - \bar{y}_{1:n})^2$$

- ▶ A large difference between these two indicates a change

Why is it not simple?

- ▶ We need to consider $n - 1$ changepoints/models
- ▶ To decide/infer whether there is a change or not
 - ▶ Compute/Compare all $n - 1$ mean squared errors
 - ▶ Seek to control their variation
- ▶ These squared errors are dependant
- ▶ How to exploit this statistically and computationally?

Course Focus

- ▶ Not a tutorial on a package.
- ▶ Rather aim to provide an understanding of what to look for and test in changepoint detection packages
- ▶ Focus on method optimizing globally or locally a penalized likelihood

Plan

A Simple Example

An archetypical model

Conclusion

Outline

1. Basics of At Most One Change offline
2. Basics of Multiple changepoints offline
3. Overview of more advanced topics
 - ▶ Model selection
 - ▶ Pruned dynamic programming algorithm
 - ▶ Local Search and Isolation techniques
 - ▶ Maximum Likelihood for online data

Conclusion

- ▶ Changepoint detection is a fundamental statistical challenge.
- ▶ Various types of changes can be detected in different settings
- ▶ Key challenges include detection, localization, and avoiding spurious changes.
- ▶ This course aims to provide a solid understanding of changepoint detection principles



Aue, A. and Kirch, C. (2024).

The state of cumulative sum sequential changepoint testing 70 years after page.

Biometrika, 111(2):367–391.



Fryzlewicz, P. (2014).

Wild binary segmentation for multiple change-point detection.



Killick, R., Fearnhead, P., and Eckley, I. A. (2012).

Optimal detection of changepoints with a linear computational cost.

Journal of the American Statistical Association,
107(500):1590–1598.



Kovács, S., Bühlmann, P., Li, H., and Munk, A. (2023).

Seeded binary segmentation: a general methodology for fast and optimal changepoint detection.

Biometrika, 110(1):249–256.



Lai, W. R., Johnson, M. D., Kucherlapati, R., and Park, P. J. (2005).

Comparative analysis of algorithms for identifying amplifications and deletions in array cgh data.

Bioinformatics, 21(19):3763–3770.



Maidstone, R., Hocking, T., Rigai, G., and Fearnhead, P. (2017).

On optimal multiple changepoint algorithms for large data.

Statistics and computing, 27:519–533.



Page, E. S. (1954).

Continuous inspection schemes.

Biometrika, 41(1/2):100–115.



Venkatraman, E. and Olshen, A. B. (2007).

A faster circular binary segmentation algorithm for the analysis of array cgh data.

Bioinformatics, 23(6):657–663.



Verzelen, N., Fromont, M., Lerasle, M., and Reynaud-Bouret, P. (2023).

Optimal change-point detection and localization.

The Annals of Statistics, 51(4):1586–1610.



Wald, A. (1945).

Sequential tests of statistical hypotheses.

In *Ann. Math. Statist.* (June, 1945), pages 117–186.



Yu, Y., Madrid Padilla, O. H., Wang, D., and Rinaldo, A. (2023).

A note on online change point detection.

Sequential Analysis, 42(4):438–471.