

Отчёт по лабораторной работе №4

Продвинутое использование git

Чернятин Артём Андреевич

Содержание

1	Цель работы	5
2	Теоретические сведения	6
3	Выполнение лабораторной работы	8
3.1	Работа с тестовым репозиторием	8
3.2	Подготовка рабочего репозитория	19
4	Вывод	21

Список иллюстраций

3.1	Node.js	9
3.2	установка commitizen	10
3.3	установка standard-changelog	11
3.4	package.json	12
3.5	Отправка	13
3.6	Инициализация и загрузка изменений	14
3.7	Завершение релиза	15
3.8	Отправка	16
3.9	Объединение веток	17
3.10	Завершение релиза	18
3.11	package.json и коммит	19
3.12	Завершение релиза	20

Список таблиц

1 Цель работы

Получение навыков правильной работы с репозиториями git.

2 Теоретические сведения

- Gitflow Workflow опубликована и популяризована Винсентом Дриссеном.
- Gitflow Workflow предполагает выстраивание строгой модели ветвления с учётом выпуска проекта.
- Данная модель отлично подходит для организации рабочего процесса на основе релизов.
- Работа по модели Gitflow включает создание отдельной ветки для исправлений ошибок в рабочей среде.
- Последовательность действий при работе по модели Gitflow:
- Из ветки master создаётся ветка develop.
- Из ветки develop создаётся ветка release.
- Из ветки develop создаются ветки feature.
- Когда работа над веткой feature завершена, она сливается с веткой develop.
- Когда работа над веткой релиза release завершена, она сливается в ветки develop и master.
- Если в master обнаружена проблема, из master создаётся ветка hotfix.

- Когда работа над веткой исправления hotfix завершена, она сливается в ветки develop и master.

3 Выполнение лабораторной работы

3.1 Работа с тестовым репозиторием

Для работы с Node.js добавим каталог с исполняемыми файлами, устанавливаемыми yarn, в переменную PATH.


```
aachernyatin@aachernyatin:~$ pnpn setup
bash: pnpn: command not found...
aachernyatin@aachernyatin:~$ pnpm setup
Appended new lines to /home/aachernyatin/.bashrc

Next configuration changes were made:
export PNPM_HOME="/home/aachernyatin/.local/share/pnpm"
case ":$PATH:" in
  *:$PNPM_HOME:*) ;;
  *) export PATH="$PNPM_HOME:$PATH" ;;
esac

To start using pnpm, run:
source /home/aachernyatin/.bashrc
aachernyatin@aachernyatin:~$ source ~/.bashrc
aachernyatin@aachernyatin:~$
```

Рисунок 3.1: Node.js

Программа commitizen используется для помощи в форматировании коммитов. При этом устанавливается скрипт git-cz, который мы и будем использовать для коммитов.

```
aachernyatin@aachernyatin:~$  
aachernyatin@aachernyatin:~$ pnpm add -g commitizen  
  
Update available! 10.9.0 → 10.24.0.  
Changelog: https://pnpm.io/v/10.24.0  
To update, run: pnpm self-update  
  
WARN 2 deprecated subdependencies found: glob@7.2.3, inflight@1.0.6  
Packages: +151  
+++++  
Progress: resolved 151, reused 0, downloaded 151, added 151, done  
  
/home/aachernyatin/.local/share/pnpm/global/5:  
+ commitizen 4.3.1  
  
Done in 3.1s using pnpm v10.9.0  
aachernyatin@aachernyatin:~$
```

Рисунок 3.2: установка commitizen

Программа standard-changelog используется для помощи в создании логов.

```
aachernyatin@aachernyatin:~$  
aachernyatin@aachernyatin:~$ pnpm add -g standard-changelog  
WARN 2 deprecated subdependencies found: glob@7.2.3, inflight@1.0.6  
Packages: +34  
++++  
Progress: resolved 185, reused 151, downloaded 34, added 34, done  
  
/home/aachernyatin/.local/share/pnpm/global/5:  
+ standard-changelog 7.0.1  
  
Done in 1.6s using pnpm v10.9.0  
aachernyatin@aachernyatin:~$
```

Рисунок 3.3: установка standard-changelog

Делаем первый коммит и выкладываем на github.

Необходимо заполнить несколько параметров пакета.

Таким образом, файл package.json приобретает вид:

A screenshot of a code editor window. The title bar at the top shows 'package.json' and the file path '~/.git-extended'. Below the title bar, there are three buttons: 'Open', a dropdown arrow, and a plus icon. The main area of the editor displays the content of the package.json file, which is a JSON object. The lines are numbered from 1 to 14 on the left side. The JSON content includes fields for name, version, description, main, repository, author, license, and a config object containing commitizen settings.

```
1 {  
2   "name": "git-extended",  
3   "version": "1.0.0",  
4   "description": "Git repo for educational purposes",  
5   "main": "index.js",  
6   "repository": "git@github.com:aa-chertyanin/git-extended.git",  
7   "author": "aa-chertyanin",  
8   "license": "CC-BY-4.0",  
9   "config": {  
10     "commitizen": {  
11       "path": "cz-conventional-changelog"  
12     }  
13   }  
14 }
```

Рисунок 3.4: package.json

Добавим новые файлы.

Выполним коммит.

Отправим на github.

```

aachernyatin@aachernyatin:~/git-extended$ gedit package.json
aachernyatin@aachernyatin:~/git-extended$ git add .
aachernyatin@aachernyatin:~/git-extended$ git cz
cz-cli@4.3.1, cz-conventional-changelog@3.3.0

? Select the type of change that you're committing: chore:  Other changes that don't modify src or test files
? What is the scope of this change (e.g. component or file name): (press enter to skip)
? Write a short, imperative tense description of the change (max 93 chars):
  (4) test
? Provide a longer description of the change: (press enter to skip)

? Are there any breaking changes? No
? Does this change affect any open issues? No
[master a5c28e7] chore: test
1 file changed, 14 insertions(+)
create mode 100644 package.json
aachernyatin@aachernyatin:~/git-extended$ git push
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 4 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 1.12 KiB | 1.12 MiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To github.com:aa-chertyanin/git-extended.git
  49383c6..a5c28e7  master -> master
aachernyatin@aachernyatin:~/git-extended$

```

Рисунок 3.5: Отправка

Инициализируем git-flow

Проверьте, что Вы на ветке develop

Загрузите весь репозиторий в хранилище

```

aaachernyatin@aaachernyatin:~/git-extended$ git flow init

Which branch should be used for bringing forth production releases?
  - master
Branch name for production releases: [master]
Branch name for "next release" development: [develop]

How to name your supporting branch prefixes?
Feature branches? [feature/]
Bugfix branches? [bugfix/]
Release branches? [release/]
Hotfix branches? [hotfix/]
Support branches? [support/]
Version tag prefix? []
Hooks and filters directory? [/home/aaachernyatin/git-extended/.git/hooks]
aaachernyatin@aaachernyatin:~/git-extended$ git branch
* develop
  master
aaachernyatin@aaachernyatin:~/git-extended$ git push --all
Total 0 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
remote:
remote: Create a pull request for 'develop' on GitHub by visiting:
remote:   https://github.com/aa-chertyanin/git-extended/pull/new/develop
remote:
To github.com:aa-chertyanin/git-extended.git
 * [new branch]    develop -> develop
aaachernyatin@aaachernyatin:~/git-extended$

```

Рисунок 3.6: Инициализация и загрузка изменений

Установите внешнюю ветку как вышестоящую для этой ветки

Создадим релиз с версией 1.0.0

Создадим журнал изменений

Добавим журнал изменений в индекс

Зальём релизную ветку в основную ветку

```

aachernyatin@aachernyatin:~/git-extended$ git branch --set-upstream-to=origin/develop develop
branch 'develop' set up to track 'origin/develop'.
aachernyatin@aachernyatin:~/git-extended$ git flow release start 1.0.0
Switched to a new branch 'release/1.0.0'

Summary of actions:
- A new branch 'release/1.0.0' was created, based on 'develop'
- You are now on branch 'release/1.0.0'

Follow-up actions:
- Bump the version number now!
- Start committing last-minute fixes in preparing your release
- When done, run:

    git flow release finish '1.0.0'

aachernyatin@aachernyatin:~/git-extended$ standard-changelog --first-release
aachernyatin@aachernyatin:~/git-extended$ git add CHANGELOG.md
aachernyatin@aachernyatin:~/git-extended$ git commit -am 'chore(site): add changelog'
[release/1.0.0 41d43db] chore(site): add changelog
1 file changed, 4 insertions(+)
create mode 100644 CHANGELOG.md
aachernyatin@aachernyatin:~/git-extended$ git flow release finish 1.0.0
Switched to branch 'master'
Your branch is up to date with 'origin/master'.
Merge made by the 'ort' strategy.
CHANGELOG.md | 4 +++
1 file changed, 4 insertions(+)
create mode 100644 CHANGELOG.md
Already on 'master'
Your branch is ahead of 'origin/master' by 2 commits.
(use "git push" to publish your local commits)
Switched to branch 'develop'
Your branch is up to date with 'origin/develop'.
Merge made by the 'ort' strategy.
CHANGELOG.md | 4 +++

```

Рисунок 3.7: Завершение релиза

Отправим данные на github

```
aachernyatin@aachernyatin:~/git-extended$  
aachernyatin@aachernyatin:~/git-extended$ git push --all  
Enumerating objects: 6, done.  
Counting objects: 100% (6/6), done.  
Delta compression using up to 4 threads  
Compressing objects: 100% (4/4), done.  
Writing objects: 100% (5/5), 2.67 KiB | 2.67 MiB/s, done.  
Total 5 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)  
To github.com:aa-chertyanin/git-extended.git  
a5c28e7..f289cf8 develop -> develop  
a5c28e7..ccb5f83 master -> master  
aachernyatin@aachernyatin:~/git-extended$ git push --tags  
Enumerating objects: 1, done.  
Counting objects: 100% (1/1), done.  
Writing objects: 100% (1/1), 158 bytes | 158.00 KiB/s, done.  
Total 1 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)  
To github.com:aa-chertyanin/git-extended.git  
* [new tag] 1.0.0 -> 1.0.0  
aachernyatin@aachernyatin:~/git-extended$ gh release create v1.0.0 -F CHANGELOG.md  
https://github.com/aa-chertyanin/git-extended/releases/tag/v1.0.0  
aachernyatin@aachernyatin:~/git-extended$
```

Рисунок 3.8: Отправка

Создадим ветку для новой функциональности По окончании разработки новой функциональности следующим шагом следует объединить ветку `feature_branch` с `develop`:


```
aachernyatin@aachernyatin:~/git-extended$  
aachernyatin@aachernyatin:~/git-extended$ git flow feature start feature_branch  
Switched to a new branch 'feature/feature_branch'  
  
Summary of actions:  
- A new branch 'feature/feature_branch' was created, based on 'develop'  
- You are now on branch 'feature/feature_branch'  
  
Now, start committing on your feature. When done, use:  
  
    git flow feature finish feature_branch  
  
aachernyatin@aachernyatin:~/git-extended$ touch test2  
aachernyatin@aachernyatin:~/git-extended$ git flow feature finish feature_branch  
Switched to branch 'develop'  
Your branch is up to date with 'origin/develop'.  
Already up to date.  
Deleted branch feature/feature_branch (was f289cf8).  
  
Summary of actions:  
- The feature branch 'feature/feature_branch' was merged into 'develop'  
- Feature branch 'feature/feature_branch' has been locally deleted  
- You are now on branch 'develop'  
  
aachernyatin@aachernyatin:~/git-extended$
```

Рисунок 3.9: Объединение веток

Создадим релиз с версией 1.2.3

Обновите номер версии в файле package.json. Установите её в 1.2.3

Создадим журнал изменений

Добавим журнал изменений в индекс

Зальём релизную ветку в основную ветку

```

package.json | 2 +-
2 files changed, 5 insertions(+), 1 deletion(-)
Deleted branch release/1.2.3 (was 8576694).

Summary of actions:
- Release branch 'release/1.2.3' has been merged into 'master'
- The release was tagged '1.2.3'
- Release tag '1.2.3' has been back-merged into 'develop'
- Release branch 'release/1.2.3' has been locally deleted
- You are now on branch 'develop'

aachernyatin@aachernyatin:~/git-extended$ git push --all
Enumerating objects: 9, done.
Counting objects: 100% (9/9), done.
Delta compression using up to 4 threads
Compressing objects: 100% (6/6), done.
Writing objects: 100% (6/6), 2.78 KiB | 2.78 MiB/s, done.
Total 6 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
To github.com:aa-chertyanin/git-extended.git
   f289cf8..3f930df  develop -> develop
   ccb5f83..d8efb88  master -> master

aachernyatin@aachernyatin:~/git-extended$ git push --tags
Enumerating objects: 1, done.
Counting objects: 100% (1/1), done.
Writing objects: 100% (1/1), 157 bytes | 157.00 KiB/s, done.
Total 1 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To github.com:aa-chertyanin/git-extended.git
   * [new tag]         1.2.3 -> 1.2.3

aachernyatin@aachernyatin:~/git-extended$ gh release create v1.2.3 -F CHANGELOG.md
https://github.com/aa-chertyanin/git-extended/releases/tag/v1.2.3

aachernyatin@aachernyatin:~/git-extended$

```

Рисунок 3.10: Завершение релиза

3.2 Подготовка рабочего репозитория

```
aachernyatin@aachernyatin:~/work/study/2025-2026/Операционные системы/os-intro$ gedit package.json
aachernyatin@aachernyatin:~/work/study/2025-2026/Операционные системы/os-intro$ git add .
aachernyatin@aachernyatin:~/work/study/2025-2026/Операционные системы/os-intro$ git cz
cz-cli@4.3.1, cz-conventional-changelog@3.3.0

? Select the type of change that you're committing: chore: Other changes that don't modify src or test files
? What is the scope of this change (e.g. component or file name): (press enter to skip)
? Write a short, imperative tense description of the change (max 93 chars):
(4) test
? Provide a longer description of the change: (press enter to skip)

? Are there any breaking changes? No
? Does this change affect any open issues? No
[master dbc5136] chore: test
1 file changed, 11 insertions(+), 11 deletions(-)
aachernyatin@aachernyatin:~/work/study/2025-2026/Операционные системы/os-intro$ git push
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 4 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 1.10 KiB | 1.10 MiB/s, done.
Total 3 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
To github.com:aa-chertyanin/os-intro.git
281fdf2..dbc5136 master -> master
aachernyatin@aachernyatin:~/work/study/2025-2026/Операционные системы/os-intro$
```

Рисунок 3.11: package.json и коммит

```

Already on 'master'
Your branch is ahead of 'origin/master' by 2 commits.
  (use "git push" to publish your local commits)
Switched to branch 'develop'
Your branch is up to date with 'origin/develop'.
Merge made by the 'ort' strategy.
  CHANGELOG.md | 10 ++++++++
  1 file changed, 10 insertions(+)
  create mode 100644 CHANGELOG.md
Deleted branch release/1.0.0 (was 33aec2e).

Summary of actions:
- Release branch 'release/1.0.0' has been merged into 'master'
- The release was tagged 'v1.0.0'
- Release tag 'v1.0.0' has been back-merged into 'develop'
- Release branch 'release/1.0.0' has been locally deleted
- You are now on branch 'develop'

aachernyatin@aachernyatin:~/work/study/2025-2026/Операционные системы/os-intro$ git push --all
Enumerating objects: 6, done.
Counting objects: 100% (6/6), done.
Delta compression using up to 4 threads
Compressing objects: 100% (5/5), done.
Writing objects: 100% (5/5), 2.79 KiB | 2.79 MiB/s, done.
Total 5 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
To github.com:aa-chertyanin/os-intro.git
   dbc5136..f3682ba  develop -> develop
   dbc5136..539e89d  master -> master
aachernyatin@aachernyatin:~/work/study/2025-2026/Операционные системы/os-intro$ git push --tags
Enumerating objects: 1, done.
Counting objects: 100% (1/1), done.
Writing objects: 100% (1/1), 159 bytes | 159.00 KiB/s, done.
Total 1 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To github.com:aa-chertyanin/os-intro.git
 * [new tag]          v1.0.0 -> v1.0.0
aachernyatin@aachernyatin:~/work/study/2025-2026/Операционные системы/os-intro$

```

Рисунок 3.12: Завершение релиза

4 Вывод

Мы приобрели практические навыки взаимодействия с дополнительными функциями гитхаб.