



# Integrating InterSystems IRIS with Source Control Systems

Version 2024.2  
2024-09-05

*Integrating InterSystems IRIS with Source Control Systems*

PDF generated on 2024-09-05

InterSystems IRIS® Version 2024.2

Copyright © 2024 InterSystems Corporation

All rights reserved.

InterSystems®, HealthShare Care Community®, HealthShare Unified Care Record®, IntegratedML®, InterSystems Caché®, InterSystems Ensemble®, InterSystems HealthShare®, InterSystems IRIS®, and TrakCare are registered trademarks of InterSystems Corporation. HealthShare® CMS Solution Pack™, HealthShare® Health Connect Cloud™, InterSystems® Data Fabric Studio™, InterSystems IRIS for Health™, InterSystems Supply Chain Orchestrator™, and InterSystems TotalView™ For Asset Management are trademarks of InterSystems Corporation. TrakCare is a registered trademark in Australia and the European Union.

All other brand or product names used herein are trademarks or registered trademarks of their respective companies or organizations.

This document contains trade secret and confidential information which is the property of InterSystems Corporation, One Memorial Drive, Cambridge, MA 02142, or its affiliates, and is furnished for the sole purpose of the operation and maintenance of the products of InterSystems Corporation. No part of this publication is to be used for any other purpose, and this publication is not to be reproduced, copied, disclosed, transmitted, stored in a retrieval system or translated into any human or computer language, in any form, by any means, in whole or in part, without the express prior written consent of InterSystems Corporation.

The copying, use and disposition of this document and the software programs described herein is prohibited except to the limited extent set forth in the standard software license agreement(s) of InterSystems Corporation covering such programs and related documentation. InterSystems Corporation makes no representations and warranties concerning such software programs other than those set forth in such standard software license agreement(s). In addition, the liability of InterSystems Corporation for any losses or damages relating to or arising out of the use of such software programs is limited in the manner set forth in such standard software license agreement(s).

THE FOREGOING IS A GENERAL SUMMARY OF THE RESTRICTIONS AND LIMITATIONS IMPOSED BY INTERSYSTEMS CORPORATION ON THE USE OF, AND LIABILITY ARISING FROM, ITS COMPUTER SOFTWARE. FOR COMPLETE INFORMATION REFERENCE SHOULD BE MADE TO THE STANDARD SOFTWARE LICENSE AGREEMENT(S) OF INTERSYSTEMS CORPORATION, COPIES OF WHICH WILL BE MADE AVAILABLE UPON REQUEST.

InterSystems Corporation disclaims responsibility for errors which may appear in this document, and it reserves the right, in its sole discretion and without notice, to make substitutions and modifications in the products and practices described in this document.

For Support questions about any InterSystems products, contact:

**InterSystems Worldwide Response Center (WRC)**

Tel: +1-617-621-0700

Tel: +44 (0) 844 854 2917

Email: [support@InterSystems.com](mailto:support@InterSystems.com)

# Table of Contents

<b>Integrating InterSystems IRIS with Source Control Systems.....</b>	<b>1</b>
1 Basics .....	1
1.1 InterSystems IRIS Documents .....	1
2 Creating a Source Control Class .....	1
2.1 Deciding How to Map Internal and External Names .....	2
2.2 Tools for Managing Documents and Files .....	2
2.3 Accessing Your Source Control System .....	2
3 Activating a Source Control Class .....	3
4 See Also .....	4



# Integrating InterSystems IRIS with Source Control Systems

This page explains briefly how to place InterSystems IRIS® data platform code under source control by connecting to a third-party source control system. It does not discuss how to choose an appropriate strategy or tools for your use case.

## 1 Basics

The process of placing InterSystems IRIS code under source control consists of the following steps:

- If necessary, creating a [custom source control class](#).
- [Configuring](#) the namespace or namespaces to use the source control class you have chosen.
- Also configuring the same namespaces to specify the location of the files to be loaded into the code databases. The way to perform this configuration generally depends on the source control class being used, but a common approach is to contain the relevant information in a global.

### 1.1 InterSystems IRIS Documents

On this page, the term *document* refers to any discrete item that you place within a source control system; this includes class definitions, routines, and data transformations. InterSystems IRIS records information such as whether a document has changed since the last compilation. Your source control system treats each document as a separate unit.

Each document has two names:

- An internal name.
- An external name, which is the fully qualified path to the file in the file system.

## 2 Creating a Source Control Class

To create a source control class, do the following:

1. Create a subclass of `%Studio.Extension.Base` or `%Studio.SourceControl.Base`.
2. If you started with `%Studio.Extension.Base`, create an XDATA block named `Menu` in your subclass. (Copy and paste from `%Studio.SourceControl.Base` to start this.)
3. Implement the methods of this class as needed: **AddToSourceControl()**, **CheckIn()**, **CheckOut()**, and so on. These methods would typically do the following, at a minimum:
  - If appropriate, import or export the InterSystems IRIS document to a file.
  - Call the appropriate function or method of your source control software, to act on the file.
  - Update internal information in InterSystems IRIS about the status of the given file.

- Control whether the InterSystems IRIS document is editable.

The details depend upon the source control system.

4. Implement the **GetStatus()** method of your source control class. This is required. You might also need to implement the **IsInSourceControl()** method, if the default implementation is not suitable.

## 2.1 Deciding How to Map Internal and External Names

Creating a bidirectional mapping between internal and external names may be one of the most challenging parts of implementing a source control system. Your code will need to define this mapping, which means that it must do the following:

- Given the name of an internal item, determine the corresponding filename.
- Given a changed file, determine the corresponding internal item and update it by importing the changed file.

For example, you could use a directory structure like this:

- Class files are in the `cls` subdirectory, which contains subdirectories corresponding to the package hierarchy of the classes.
- `.INT` routines are in the `int` subdirectory.
- `.MAC` routines are in the `mac` subdirectory.

So that multiple developers in different environments can use your custom source control class, your code must also provide a way to configure the basic location of the files (rather than simply hardcoding the mapping completely).

## 2.2 Tools for Managing Documents and Files

InterSystems IRIS provides the following tools for managing documents and external files:

- To export InterSystems IRIS documents, use one of the following, depending on the file format you want to use:
  - For UDL files, use **\$system.OBJ.ExportUDL()**.
  - For XML files, use **\$system.OBJ.Export()**.

UDL files more closely resemble the code as seen in an IDE.

- To import files (of either format), use **\$system.OBJ.Load()**.
- To obtain the timestamp and compile time for an InterSystems IRIS document, use the **%RoutineMgr.TS** class method.

## 2.3 Accessing Your Source Control System

The API for your source control system provides methods or functions to perform source control activities such as checking files out. Your source control class will need to make the appropriate calls to this API, and the InterSystems IRIS server will need to be able to locate the shared library or other file that defines the API itself.

Also, it is important to remember that InterSystems IRIS will execute the source control commands on the InterSystems IRIS server. This means that your XML files will be on the InterSystems IRIS server, and your file mapping must work on the operating system used on that server.

### 2.3.1 Example 1

For the following fragment, we have created wrapper methods for the API for VSS. Then we can include code like the following within the source control methods:

```
do ..VSSFile.CheckIn(..VSSFile.LocalSpec,Description)
```

The details depend on the source control software, its API, and your needs.

### 2.3.2 Example 2

The following fragment uses a Windows command-line interface to check out a file. In this example, the source control system is Perforce:

```
/// Check this routine/class out of source control.
Method CheckOut(IntName As %String, Description As %String) As %Status
{
  Set file=..ExternalName(IntName)
  If file="" Quit $$$OK
  ///...
  Set cmd="p4 edit ""_IntName_""

  #; execute the actual command
  Set sc=..RunCmd(cmd)
  If $$$ISERR(sc) Quit sc

  #; If the file still does not exist or
  #; if it is not writable then checkout failed
  If '##class(%File).Exists(file)||(#class(%File).ReadOnly(file)) {
    Quit $$$ERROR($$$GeneralError,
      "Failure: '_IntName_' not writeable in file sys")
  }

  #; make sure we have latest version
  Set sc=..OnBeforeLoad(IntName)
  If $$$ISERR(sc) Quit sc

  ///...
  Quit sc
}
```

In this example, **RunCmd()** is another method, which executes the given command and does some generic error checking. (**RunCmd()** issues the OS command via the callout interface.)

Also, this **CheckOut()** method calls the **OnBeforeLoad()** method, which ensures that the InterSystems IRIS document and the external XML file are synchronized.

## 3 Activating a Source Control Class

To activate a source control class for a given namespace, do the following in the Management Portal:

1. Select **System Administration > Configuration > Additional Settings > Source Control**.
2. On the left, select the namespace to which this setting should apply.
3. Select the name of the extension class to use and select **OK**.

This list includes all compiled subclasses of %Studio.Extension.Base in the selected namespace.

In your IDE, you may need to reopen your workspace in order to see the new menu options.

The Management Portal Production Configuration Page also supports source control, see [Configuring Source Control Settings](#).

## 4 See Also

- [Configuring Source Control Settings \(options related to interoperability productions\)](#)
- [Introduction to Visual Studio Code](#)
- [Video: Visual Studio Code for ObjectScript: Choosing an IDE/Source Code Combination](#) on the Developer Community
- [Using Studio](#)