

Working with English characters:

$$(-1.328\,65 \pm 0.502\,73) \cdot 10^{-6}$$

$$(1.3_{-0.3}^{+1.2}) \cdot 10^3 \text{ erg cm}^{-2} \text{ s}^{-1}$$

$$1,123'8 \cdot 10^{-2} - 3,086'8 \cdot 10^5$$

$$(1 \text{ to } 2) \cdot 10^3 \frac{\text{m}}{\text{s}^2}$$

$$55.36 \$$$

Adding your own prefix and unit:

preunit

Работа пакета с русскими символами:

$$(-1.328\,65 \pm 0.502\,73) \cdot 10^{-6}$$

$$(1.3_{-0.3}^{+1.2}) \cdot 10^3 \text{ эрг см}^{-2} \text{ с}^{-1}$$

$$1,123'8 \cdot 10^{-2} - 3,086'8 \cdot 10^5$$

$$(1 \text{ до } 2) \cdot 10^3 \frac{\text{м}}{\text{с}^2}$$

Other languages fall back to English units:

$$(-1.328\,65 \pm 0.502\,73) \cdot 10^{-6}$$

$$(1.3_{-0.3}^{+1.2}) \cdot 10^3 \text{ erg cm}^{-2} \text{ s}^{-1}$$

$$1,123'8 \cdot 10^{-2} - 3,086'8 \cdot 10^5$$

$$(1 \text{ to } 2) \cdot 10^3 \frac{\text{m}}{\text{s}^2}$$

Property	Value
Input noise voltage	$2 \frac{\text{nV}}{\sqrt{\text{Hz}}} > 10 \text{ Hz}$ ($2.5 \frac{\text{nV}}{\sqrt{\text{Hz}}}$ @ 1 Hz !!)
Input noise current	$5 \frac{\text{fA}}{\sqrt{\text{Hz}}}$
Input bias current	$< 5 \text{ pA}$
Temp drift	$< 2 \mu\text{V}^{-1}$
Bandwidth	200 kHz..10 kHz (gain=100..10)
Gain	$100 \text{ V V}^{-1}/1 \text{ kV V}^{-1}/10 \text{ kV V}^{-1}$ (on ac, 100/1/10 dc-gain=100 fixed)

specs: Input noise voltage: 2nV/sqrt Hz >10Hz (2.5nV/sqrtHz @1Hz !!) Input noise current: 5fA/sqrtHz
 Input bias current : <5pA Temp drift : <2uV/c Bandwidth : 200kHz..10kHz (gain=100..10K)
 Gain : 100/1k/10k V/V (on ac, 100/1k/10k dc-gain=100 fixed)