

VOLLEY Gen5 | Final-Year Project Report

Computational design, evidence review, and engineering disposition

Adityavardhan Mishra

Pratham Chawla

10 October 2026

Contents

Abstract	1
Document control and evidence convention	2
Executive summary	2
New decisive findings: finite force, feeder route and matched mission	3
1. Introduction	5
2. Literature review	6
3. Research gap	7
4. Objectives and outcome	7
5. Research methodology	7
6. Timeline	8
7. Work progress	9
8. Results	9
9. Conclusion	12
10. Future work	14
11. References and project records	14
Appendix A. Numerical and CAD audit trail	14
Appendix B. Submission and freeze status	15

Guide: Vikas Gulia **Student PRNs:** Adityavardhan Mishra — 23070125054; Pratham Chawla — 23070125029 **Department:** Mechanical Engineering, Symbiosis Institute of Technology **Document type:** Final-year project report prepared for academic review

Scope of this report. VOLLEY is a system-level engineering design and computational research project. The Gen5 evaluated configuration and adverse numerical findings are documented; decisive force and mission closure remain open. The results are predictions, with numerical cross-checks where identified. Physical prototype testing, CubeSat qualification and provider accommodation belong to a later development phase. Gen6 is presented separately as future work.

Abstract

This final-year project report evaluates a magazine-fed electromagnetic CubeSat deployer as a *computational design study*. For a twelve-payload 3U configuration, the historical periodic-force model predicts a 16.029 m/s rated release at 10.068 g and 2.782 kJ gross shot draw. A finite-array/stator 3-D analytic integral challenges that speed prediction, giving 12.448 m/s only under ideal phase with circuit and friction losses omitted. An independent Cartesian two-body calculation reproduces a 28.800775 km immediate semi-major-axis rise for the rated 450 km case. A native FreeCAD 1.0 review document and STEP exports expose an 11 mm transverse shortfall in the specified side-fed layout, with 32,915 mm³ of exact-solid overlap per cassette. The estimated 126.6 kg dry mass gives 10.547 kg of deployer per carried 3U, failing both the 2 kg economic screen and an approximately 6 kg spring-canister parity comparison. Atmospheric lifetime, exact payload interfaces and full mission delivery remain conditional or open. There is no physical prototype or VOLLEY test data. The completed result is a documented model-based decision against this Gen5 3U configuration, with Gen6 scale-up treated as future research.




Figure 1: Analysed Gen5 electromagnetic deployer configuration. CAD render; no physical article exists.

Keywords: CubeSat deployment; electromagnetic launcher; systems engineering; numerical verification; CAD interference; orbital mechanics; model credibility.

Document control and evidence convention

Item	Review baseline
Configuration	Gen5 twelve-3U side-fed reference; 1.5 m release station on 1.8 m structural longerons, 1.3 m powered stroke
Report status	Academic review draft; negative criteria retained
Evidence	Model outputs, selected independent numerical checks, native CAD import/export and prior literature
Exclusions	Hardware measurements, payload qualification, provider ICD approval, lifetime cross-check at the exact rated point
Build record	Reproduce PDF from this Markdown with Pandoc and XeLaTeX; inspect local source and run sheets

The supplied college documents define final-review criteria and a slide example. They do not supply a mandatory report template. This report therefore uses a conventional chapter structure; title/signature pages and institution-specific declarations should be added only from the official template. No unperformed test, approval or authorship certification is implied.

Executive summary

VOLLEY investigates a last-mile problem in rideshare launches: a secondary CubeSat reaches orbit but ordinarily receives the orbit selected for the primary payload. A spring deployer separates

it safely, often at roughly 1–2 m/s; that relative impulse, later drag differences, or host maneuvering can change its in-track phase. Deployment time by itself does not create persistent phase separation from an otherwise unchanged co-orbital host. A larger, deliberately commanded release velocity can also change orbital energy. The thesis evaluates whether that added capability justifies a complete deployer system. The mission model splits responsibilities between a maneuvering host, which performs coarse repositioning, and a deployer, which supplies each satellite's commanded release condition.

This report analyses one Gen5 solution: a magazine-fed, linear synchronous motor driving a reusable magnetic sled. The historical periodic-force 3U model predicts **16.0 m/s** exit speed at **10.07 g**. Its modeled dry-mass rollup is **126.6 kg**, and the power model predicts **2.782 kJ** gross electrical draw per shot. A closed-loop simulation predicts **0.0274 m/s (3σ)** exit-speed dispersion at a 15.8 m/s setpoint. In a stated orbital case, a maximum-speed release raises semi-major axis by **28.8 km**, with a **1.60×** modelled lifetime multiplier at mean solar activity. The lifetime result is atmosphere-sensitive and has not been independently rerun at the exact current operating point.

Gen5 also produced a decisive negative result. With twelve 3U satellites, its deployer mass is **10.55 kg per customer**, versus about **6 kg** for the spring canister comparator used in the thesis. This is **1.76×** as much hardware per 3U payload and fails the preset 15% mass-parity band. The study therefore reaches a decision: the conditional modelled orbital benefit does not make this Gen5 configuration a defensible 3U selection. The result completes the analytical comparison; it does not require a prototype to know that the modelled mass criterion failed. Physical payload loads, magnetic cleanliness, cycle life, and provider interfaces remain questions for a different evidence phase.

The later Gen6 programme retains the hosted sequential-deployment mission while reopening mechanism choice. It investigates an approximately **1–2 m/s to 1 km/s** release-speed envelope across electromagnetic, mechanical, stored-energy, gas/fluid, hybrid, BOLLEY and conventional options. The high end is a requirement to examine and may prove infeasible. The near-term goal is one named, reproducible, independently reviewable test-article configuration with a corresponding build/test release decision.

New decisive findings: finite force, feeder route and matched mission

The 16.029 m/s shot result assumes periodic thrust throughout a 1.3 m powered stroke. A new 3-D analytic integration of the exact cuboid field over the CAD's finite 162-belt stator finds **1.042 kJ ideal work**, corresponding to **12.448 m/s only under optimal phase with switching, voltage and friction losses omitted**. The modeled mover array and stator stop directly overlapping after 1.066 m travel. The 336 mm magnetic model and 340 mm CAD envelope also disagree. Cross-section quadrature refinement changes the three checked station forces by at most 0.369%; halving station spacing changes work by 0.096%. The magnetic field law is shared with the earlier model, so this is an adverse analytic screen, **not an independent 3-D FEM or a hardware test**. The historical 16.029 m/s remains in older tables for traceability and must not be called demonstrated performance. See [P118](#).

An **unselected R1 geometry candidate** uses a 570 mm wide enclosure. Its native FreeCAD document and STEP parts pass exact-solid static fit and twelve scripted 3U envelope transfer paths with conservative fixed-part swept boxes. It lacks the actual lift/carriage, launch restraint, actuation, tolerances, fault recovery and revised installed mass. Its increased envelope has no approved host. This candidate does not alter the evaluated Gen5 configuration or repair the performance discrepancy. See [R1 CAD record](#).

A **matched reference comparison** uses twelve identical 4 kg payloads at 450 km, the same 300 kg base host with 10 kg assumed fuel and 220 s specific impulse, and installed device masses of 72 kg for a spring class versus 126.562 kg modeled Gen5. To meet one common +16.029 m/s inertial payload target at the same epoch, ideal host preburn takes 2.693 kg of propellant with 2.5 m/s spring release and 0.827 kg with the 12.448 m/s finite Gen5 estimate. The subsequent common-input, assumed-100 N twelve-shot optimizer accepts prefixes of **4/12 spring, 1/12 finite Gen5, 1/12 historical Gen5**. None closes. These are bounded numerical cases,




Figure 2: Finite-array/stator model force versus position; no physical measurement.




Figure 3: R1 candidate section; geometry drawing, not a qualified mechanism.

not a supplier quote, proof of infeasibility or product advantage. Onboard propulsion, transport services and long-horizon drag remain unmodeled. See [matched mission inputs](#).




Figure 4: Matched reference results; assumed host and device classes.

1. Introduction

The deployment problem

The primary mission determines the launch vehicle's delivered orbit. Secondary CubeSats may have limited onboard propulsion, mass, power, or programmatic freedom to correct that orbit. Standard canisterised spring systems are mature and effective at clearance and separation. Their release conditions, however, are governed by spring energy, payload mass, and the device rather than a separately commanded velocity profile for every satellite.

The distinction between **release timing** and **relative-state change** is central. Waiting alone between zero-relative-impulse releases from an unchanged host does not produce persistent in-track phase spacing. Spring impulse, differential drag or a host maneuver can produce a relative state; a commanded velocity along or against orbital motion can change the satellite's orbital energy and semi-major axis. VOLLEY studies the latter capability while retaining a clear comparison with spring release and other alternatives. It does not claim that all constellation phasing requires a motor.

The host is an active participant in the mission model. After its primary mission, a suitable hosted platform would need attitude control, available resources and permission to operate. It could perform coarse orbital repositioning; VOLLEY would assign each secondary payload a local release state. No specific upper stage has been selected or approved for that role.

Buyer and spacecraft fit

The [audited market and customer-fit report](#) checks the relevant Drive market thesis and independent business-case review against current primary sources. [Planet's FY2026 filing](#) and [Spire's 2025 filing](#) show repeatable, configurable smallsat production. [NASA's 2026 launch review](#) confirms that a primary mission can constrain the orbit available to rideshare payloads. Together, these support a *mission hypothesis*, not customer demand.

The likely party that could pay for individualized release states is a carrier, rideshare integrator or constellation operator responsible for a delivered manifest. A standardized satellite-bus maker may specify interfaces but need not buy the system. Replenishment batches and mixed-payload rideshare are candidate jobs. A one-satellite mission already in a suitable orbit is a poor fit and should favor a qualified conventional dispenser. The analyzed Gen5 system carries twelve 3U spacecraft but fails its own 3U mass screen; a PocketQube batch is a **future interface redesign**, not an accommodated or qualified Gen5 payload class. Payloads sensitive to magnetic fields

need an explicit exclusion or design remedy. No buyer, payload or provider has confirmed these requirements.

For an economic result, price and simulate the same manifest delivered with ordinary spring impulse, spring plus host manoeuvres, onboard propulsion, an orbital-transport service and VOLLEY. The published [SpaceX rideshare starting price](#) cannot stand in for an installed VOLLEY cost or savings quote. A three-to-five-year replacement cycle and a 5–50 m/s release range are research hypotheses from the Drive market report, not Gen5 operating requirements or established market demand. The Gen6 1 km/s upper objective is a different, unvalidated regime.




Figure 5: Gen5 layout and mission hardware elements. Diagram from the thesis analysis.

2. Literature review

Approach	Established capability	Relevance and limit
Spring deployers	Flight heritage and simple separation near the low-m/s range [1]	Strong benchmark for reliability and installed mass; release energy is largely built into the device.
Spring release and differential drag	In-track spacing and gradual orbital adjustment [3]	A relative impulse or drag difference creates the separation; waiting alone from an unchanged co-orbital host does not.
Orbital transfer vehicles	Coarse orbital repositioning through a propulsive carrier	Valuable comparator for whole-mission delivery; greater spacecraft and integration burden must be counted.
Electromagnetic CubeSat studies	Magazine transport and electromagnetic launch have already been studied [4–6]	Some configurations impose conductive armatures, high acceleration or different maturity; novelty cannot be claimed for electromagnetic deployment alone.

The most relevant high-speed electromagnetic comparison in the manuscript is Feng *et al.* [4],

which models a 321.56 m/s launch of a 20 kg CubeSat but at acceleration on the order of thousands of g and with an armature/interface issue. Zhao *et al.* [5,6] study stacked CubeSat transfer and storage, including measured transport behavior in a related mechanism. These works establish that electromagnetic delivery and magazine transport are prior art. VOLLEY's more limited question is whether a **commandable** release can be delivered to an **unmodified** satellite at a much lower acceleration while accounting for the whole installed system. No universal CubeSat quasi-static acceleration qualification is assumed; the launch provider and payload-specific limits must govern a real design [2,8].

3. Research gap

The analytical gap is not “no one has considered electromagnetic deployment.” It is the coupled trade between: (i) commanded release, (ii) payload-side interface and acceleration, (iii) a reusable feed/release architecture, (iv) host reaction and mission utility, and (v) installed system mass and faults. A speed-only comparison can make a concept appear attractive while omitting its sled, power bank, brake, magazine, enclosure, control, and retained mass after each shot.

The thesis addresses that gap by constructing a complete Gen5 computational configuration and testing its own claims against explicit comparisons. It also records when those tests weaken the concept. Physical viability remains a separate research gap: numerical model agreement cannot establish manufactured tolerances, actual force, payload cleanliness, cycle reliability or provider compatibility.

4. Objectives and outcome

Analytical research objective	Completed outcome	Interpretation
Model a commandable 3U system	Gen5 CAD, magazine, sled, motor, arrest and power architecture	System-level design record, not manufactured hardware
Quantify the release	Rated shot, circuit and closed-loop simulations	Predicted performance under stated assumptions
Evaluate orbital value	Orbit model and selected independent numerical cross-checks	Conditional energy and lifetime benefit
Test whole-system competitiveness	Mass rollup, spring/alternatives comparison and preset criteria	Gen5 fails the 3U mass target
Challenge model credibility	Numerical verification, defect corrections and provenance record	Scope and remaining physical uncertainties made explicit

These objectives summarize the completed analytical research for this final-review presentation. They are a presentation synthesis, not a claim that the university approved this exact list in advance. The physical development tasks are shown later under future work.

5. Research methodology

The project follows an engineering evidence chain:

1. **Mission/use-case framing:** specify the payload, host responsibilities, target orbital change, safety limits and competent conventional comparators.
2. **Architecture trade:** examine force production, loading, restraint, guidance, arrest, reset and fault behavior, rather than only ideal acceleration.
3. **Geometry and installed mass:** build CAD geometry and count the sled, arrays, enclosure, feed, power, controls and other installed parts.

4. **Coupled models:** compute magnetic field and thrust, shot dynamics, power/circuit behavior, control dispersion, structural/flow responses and orbital consequences.
5. **Challenge the claims:** use alternate numerical methods and acceptance bands, preserve misses and update the baseline only with a recorded reason.
6. **Decision:** compare orbital benefit against mass, reliability, payload/host compatibility and the available alternatives.




Figure 6: Modelled shot: velocity, bank voltage and current at the rated point.

Numerical checks and their limits

The magnetic field was compared across an analytical representation, magpylib, and 2-D/3-D finite-element calculations. A 3-D midgap solve supports the field model at its tested location but does not independently measure the depth-integrated thrust constant. Shot and circuit predictions were compared with ngspice at stated assumptions. Structural calculations use CalculiX; airflow calculations use OpenFOAM. Orbital calculations include Cowell and GMAT cases. The independent orbit work rejected an earlier assertion that lifetime benefit was invariant across solar activity. Each check applies to its declared case and boundary conditions; none is a hardware test.




Figure 7: Representative magnetic-field model output. Source: thesis figure A02.

6. Timeline

Documented evolution

Period	Milestone	Confidence in date
2023	Free-flyer idea reframed around a host platform	Documented design decision
Mid-2025	Coilgun concept shifted toward a linear synchronous motor	Approximate historical milestone
2025-July 2026	CAD generations and mass model developed	Some dates reconstructed/approximate
July-September 2026	Gen5 analysis, numerical checks, defects and thesis record	Dated repository/analysis records
October 2026	Gen5 findings and design decision presented for final review	Review package dated 10 October 2026

The thesis repository's reconstructed history expressly marks several early milestone dates as approximate. The analytical baseline was revised as evidence improved: a CAD-derived sled mass displaced a lighter parametric estimate; a depth-resolved thrust calculation lowered the rated speed; an enclosure buildup exposed the 3U mass penalty; and an independent orbit check rejected an overbroad solar-invariance claim. These revisions are part of the completed study, not signs that the final numbers are placeholders. Gen6 research gates are described only in §10, Future work.

7. Work progress

The thesis deliverables are in hand: an authored manuscript, CAD renders and model geometry, analysis scripts/results, numerical verification run sheets, figures, a baseline record, a defect register, and a provenance statement. Numerical investigations cover the motor field, shot dynamics, bank/circuit, mass, orbit propagation, separation and selected structural, airflow and reliability issues. The study closes by retaining failed criteria and superseded results rather than silently replacing them.

The deliverable here is a completed computational thesis, not a flight article. The later long gas-guide and independent spring-cell studies are historical comparators. Gen6 has a mission direction and investigation envelope but is not a result of the Gen5 thesis. Its mechanism and exact payload/provider cases remain future choices.

8. Results

Gen5 configuration

The analysed system uses a double-sided Halbach-array linear synchronous motor to propel a reusable permanent-magnet sled to a release station 1.5 m from the breech on 1.8 m structural longerons. Two transverse cassettes are intended to feed twelve 3U satellites, but the present side-fed placement fails the fit check. A capacitor-based bank supplies the modeled pulse, and a brake is intended to arrest the sled after payload release. The **9.45 kg** sled input comes from historical Gen3 CAD solid volumes; this value reduced the exit speed relative to an earlier optimistic parametric estimate. The CAD render conveys a concept, not manufactured or assembled hardware.

Rated 3U shot

Model output	Rated result	Interpretation
Exit velocity	16.029 m/s	Modelled 3U reference shot
Payload acceleration	10.07 g	Not a payload qualification claim

Model output	Rated result	Interpretation
Pulse duration	162.3 ms	Modelled motor actuation
Peak current	320 A	Component implementation unverified
Electrical energy drawn, gross	2,782 J	Bank/circuit model
Recovered after release	47 J	39 mm available recovery zone
Sled energy to brake	1,162 J	Major loss and arrest burden
Electrical-to-payload efficiency, net	18.8%	514 J payload kinetic energy / net draw

The energy flow matters more than the velocity headline. The sled and its arrest hardware are part of the modeled price of avoiding a payload-side drive armature. Regeneration returns only a small fraction of sled energy within the available length. [P117](#) separately checks the reported mass and energy identities and finds **124.488 J (4.47%) of gross draw unitemized** after the reported kinetic, copper and bank-ESR terms. That is an accounting gap, not proof of a specific additional loss. Full electrical closure and an installed bank are still open.

Command precision

The closed-loop Monte Carlo model predicts **0.0274 m/s (3σ)** exit-velocity dispersion around a **15.8 m/s** fleet setpoint. It uses assumed sensing and plant tolerances, with headroom below the open-loop ceiling. This is a simulated distribution, not a measured release repeatability.




Figure 8: Closed-loop simulation distribution at the fleet setpoint.

Orbital utility

For the stated orbit and mean-solar-activity case, one maximum-speed release predicts a **28.8 km** semi-major-axis increase and a **1.60×** lifetime multiplier for a propulsionless satellite. A separate Cartesian two-body integration of the current rated state returns **28.800775 km**, agreeing within the declared numerical band. This checks only the immediate orbital-energy result. The atmospheric lifetime multiplier has not been independently reproduced at the exact current point.

Timing alone, with zero relative impulse and no host or drag difference, produces neither persistent phasing nor this semi-major-axis change.




Figure 9: Independent rated-state two-body orbit check. The lifetime claim is outside its scope.




Figure 10: Modelled orbital-lifetime response. Absolute values depend on atmosphere.

Installed mass changes the decision

The modeled Gen5 dry rollup is **126.6 kg** and loaded mass **174.6 kg**; these include assumed hardware and historical Gen3 sled volume, not a mass extraction from a complete installed Gen5 assembly. At twelve 3U customers, the deployer weighs **10.55 kg per customer**, compared with approximately **6 kg** for the spring canister comparator used in the analysis. The ratio is **1.758**; the preset acceptance band required parity within 15%. That band fails by a large margin. Replacing an **8 kg enclosure placeholder** with a **50.04 kg** geometry-derived buildup exposed much of the penalty. Even changing structure alone does not recover parity in the studied options. The result is a reason to reopen the architecture, not to conceal the comparison.




Figure 11: Constraint and mass-attribution analysis; mass is a model rollup.

Native CAD and packaging review

The geometry package now includes a FreeCAD 1.0 native document, eight re-exported STEP parts, and a 20-instance STEP assembly. Each imported solid passed FreeCAD validity and nonzero-volume checks. The source solids were produced in CadQuery; importing them into FreeCAD does not create parametric feature history or prove that the assembly can be manufactured. The [CAD review report](#) identifies source revisions and checks, while [P116](#) records the numerical intersection result.

The side-fed reference assembly has **526 mm** clear enclosure width. Its **205 mm** track plus two **166 mm** cassettes require **537 mm**, an **11 mm** shortfall even before running clearance. The exact solids overlap by **32,915 mm³ per side** in this placement. This fails that packaging arrangement. A different feed architecture, enclosure or dimension set requires a new configuration and reassessment; the current render must not be presented as an assembled flight article.

Decision and evidence boundary

The analytical result has four parts. The model supports a commandable release and conditional orbital-energy benefit; the full-system 3U mass criterion fails; the stated side-fed layout fails its CAD width check; and physical behavior remains unverified. The latter includes release-cycle reliability, shock and arrest loads transmitted to stowed satellites, field exposure near a customer payload, host attitude/control authority and provider approval. The known-problems register ranks several as potentially design-fatal. These findings limit product claims and define the research conclusion.

9. Conclusion

The Gen5 computational thesis reaches a research conclusion within its stated scope. Its model predicts a commandable moderate-acceleration release and a conditional orbital-energy benefit, with a separate check of the immediate two-body orbital change. Installed-mass accounting misses its preset 3U benchmark, and the side-fed reference CAD assembly fails its width check. The current configuration is therefore not a selected flight baseline. Hardware behavior and interfaces remain outside the tested evidence.

The thesis's strongest engineering contribution is the transparent decision record: the full machine was modelled, independent numerical checks corrected several claims, and an unfavourable mass result was retained. That closes the Gen5 study and provides a defensible input to a separate future architecture trade.




Figure 12: Dimensioned side-fed reference cross-section; this configuration fails the width check.

10. Future work

Gen6’s controlling objective is a reusable launch path that sequentially accepts different supported CubeSat sizes and commands each departure condition. The approximately 1–2 m/s to 1 km/s span is an investigation envelope; the upper end may force acceleration, energy, travel, payload or provider constraints that reject candidates. Electromagnetic systems are preferred for comparison but are not preselected. Competent springs, electromechanical/stored-energy, gas/fluid, hybrid, BOLLEY and conventional mission substitutes belong in the same comparison boundary.

The near-term milestone is one named test-article configuration that can be independently reviewed. Its package needs controlled geometry and drawings, a bill of materials, host and payload interfaces, full installed mass/energy/thermal accounting, assembly and inspection instructions, instrumented procedures, predetermined pass/fail and stop criteria, uncertainty and model-credibility evidence, retained failures, and an explicit build/test release decision. A rejected candidate is a valid research outcome; it must not be presented as a build-ready survivor.

11. References and project records

1. JAXA, *JEM Payload Accommodation Handbook*, Vol. 8, small-satellite deployment interface control document, cited in the VOLLEY thesis.
2. California Polytechnic State University, *CubeSat Design Specification*, Rev. 14, 2020.
3. C. Foster et al., “Constellation phasing with differential drag on Planet Labs satellites,” *Journal of Spacecraft and Rockets*, 55(2), 2018.
4. H. Feng, Y. Yang and Y. Wu, “Design and reachable domain analysis of on-orbit electromagnetic launcher for CubeSats,” *International Journal of Aerospace Engineering*, art. 3000765, 2025.
5. Y. Zhao et al., “Design and analysis of a new deployer for the in-orbit release of multiple stacked CubeSats,” *Remote Sensing*, 14(17), 4205, 2022.
6. Y. Zhao et al., “Simulation analysis and experimental verification of the transport characteristics of a high-volume CubeSat storage device,” *Aerospace*, 12(6), 466, 2025.
7. K. Halbach, “Design of permanent multipole magnets with oriented rare earth cobalt material,” *Nuclear Instruments and Methods*, 169, 1980.
8. NASA, *General Environmental Verification Standard*, GSFC-STD-7000A, 2013.
9. D. A. Vallado, *Fundamentals of Astrodynamics and Applications*, 4th ed., 2013.
10. A. Mishra, *VOLLEY-thesis*: authored manuscript, baseline, provenance, figures and validation records, repository head b30ffdc, 28 September 2026. Project record, not independent experimental evidence.
11. VOLLEY/BOLLEY, *Current Plan and Status — PLAN-R2*, controlled working baseline, 29 September 2026. Project plan, not achieved performance.

Appendix A. Numerical and CAD audit trail

Result	Reproducible record	What remains outside the check
Rated shot and energy	analysis/results/motor_results.json , analysis/motor_model.py	Unmeasured force and actual circuit parasitics
Rated immediate orbital change	P115, rated_orbit_independent.py	Atmospheric lifetime and controlled host mission
3U mass decision	mass_properties.json , BASELINE	Hardware weighing, complete installed host burden
Native geometry and collision	Gen5_Review.FCStd , FREECAD_EXPORT.json , P116	Tolerance, feed motion, payload accommodation and provider fit
Wider model and open gates	computational review , CAD review , open problems	Final verification closure and physical development

The run sheets report software, inputs, declared comparison bands and files. Figures are generated model or CAD visualizations. A screenshot of a solver interface would not by itself establish a correct result; the editable model, data and case boundary are the audit trail.

Appendix B. Submission and freeze status

The project is ready to present as a computational study with recorded adverse findings. It is **not ready** to be described as a fully validated design or released product. Before an academic freeze, close or explicitly disposition the decisive electromagnetic, feed/release, brake, host, structural and installed-system questions in the local evidence register; choose the exact college report template; record the final authorship, guide approval and submitted PDF checksum. Physical bench and qualification tests remain future work and must stay marked unrun.