

Chapter 16: Greedy Algorithm

About this lecture

- Introduce Greedy Algorithm
- Look at some problems solvable by Greedy Algorithm

Coin Changing

- Suppose that in a certain country, the coin denominations consist of:

\$1, \$2, \$5, \$10

- You want to design an algorithm such that you can make change of any x dollars using the fewest number of coins

Coin Changing

- An idea is as follows:
 1. Create an empty bag
 2. while ($x > 0$) {
 Find the largest coin c at most x ;
 Put c in the bag;
 Set $x = x - c$;
}
 3. Return coins in the bag

Coin Changing

- It is easy to check that the algorithm always return coins whose sum is x
- At each step, the algorithm makes a **greedy choice** (by including the largest coin) which looks best to come up with an optimal solution (a change with fewest #coins)
- This is an example of **Greedy Algorithm**

Coin Changing

- Is Greedy Algorithm always working?
- No!
- Consider a new set of coin denominations:
\$1, \$4, \$5, \$10
- Suppose we want a change of \$8
- Greedy algorithm: 4 coins (5,1,1,1)
- Optimal solution: 2 coins (4,4)

Greedy Algorithm

- We will look at some **non-trivial** examples where **greedy algorithm** works correctly
- Usually, to show a greedy algorithm works:
 - ✓ We show that **some** optimal solution includes the **greedy choice**
 - ➔ **selecting greedy choice is correct**
 - ✓ We show optimal substructure property
 - ➔ **solve the subproblem recursively**

Activity Selection

- Suppose you are a freshman in a school, and there are many welcoming activities
- There are n activities A_1, A_2, \dots, A_n
- For each activity A_k , it has
 - a start time s_k , and
 - a finish time f_k

Target: Join as many as possible!

Activity Selection

- To join the activity A_k ,
 - you must join at s_k ;
 - you must also stay until f_k
- Since we want as many activities as possible, should we choose the one with
 - (1) Shortest duration time?
 - (2) Earliest start time?
 - (3) Earliest finish time?
 - (4) Last start time? Last finish time?

Activity Selection

- Shortest duration time may not be good:
 $A_1 : [4:50, 5:10),$
 $A_2 : [3:00, 5:00),$ $A_3 : [5:05, 7:00),$
- Though not optimal, #activities in this solution R (shortest duration first) is at least half #activities in an optimal solution O
 - ✓ One activity in R clashes with at most 2 in O
 - ✓ If $|O| > 2|R|$, R should have one more activity

Activity Selection

- Earliest start time may even be worse:

$A_1 : [3:00, 10:00),$

$A_2 : [3:10, 3:20), A_3 : [3:20, 3:30),$

$A_4 : [3:30, 3:40), A_5 : [3:40, 3:50) \dots$

- In the worst-case, the solution contains **1** activity, while optimal has **$n-1$** activities

Greedy Choice Property

- To our surprise, **earliest finish time** works!
- We actually have the following lemma:
- Lemma: For the activity selection problem, **some** optimal solution includes an activity with earliest finish time

How to prove?

Proof: (By "Cut-and-Paste" argument)

- Let OPT = an optimal solution
 - Let A_j = activity with earliest finish time
 - If OPT contains A_j , done!
 - Else, let A' = earliest finish activity in OPT
 - ✓ Since A_j finishes no later than A' , we can replace A' by A_j in OPT without conflicting other activities in OPT
- an optimal solution containing A_j
(since it has same #activities as OPT)

Optimal Substructure

- Let A_j = activity with earliest finish time
- Let S = the subset of original activities that do not conflict with A_j
- Let OPT = optimal solution containing A_j
- Lemma:
 $OPT - \{A_j\}$ must be an optimal solution for the subproblem with input activities S

Proof: (By contradiction)

- First, $OPT - \{A_j\}$ can contain only activities in S
- If it is not an optimal solution for input activities in S , let C be some optimal solution for input S
 - C has more activities than $OPT - \{A_j\}$
 - $C \cup \{A_j\}$ has more activities than OPT
 - Contradiction occurs


Greedy Algorithm

- The previous two lemmas implies the following **correct** greedy algorithm:
 S = input set of activities ;
while (**S** is not empty) {
 A = activity in **S** with earliest finish time;
 Select **A** and update **S** by removing activities having conflicts with **A** ;
}
 If finish times are sorted in input,
 running time = $O(n)$

Example

S sorted by finish time: [Leave on board]

i	1	2	3	4	5	6	7	8	9
s_i	1	2	4	1	5	8	9	11	13
f_i	3	5	7	8	9	10	11	14	16



Maximum-size mutually compatible set: $\{a_1, a_3, a_6, a_8\}$.

Not unique: also $\{a_2, a_5, a_7, a_9\}$.

Pseudo code

Greedy-Activity-Selector(s, f)

1. $n = s.length$
2. $A = \{a_1\}$
3. $k = 1$
4. For $m = 2$ to n
5. if $s[m] \geq f[k]$
6. $A = A \cup \{a_m\}$
7. $k = m$
8. Return A

Designing a greedy algorithm

- **Greedy-choice property:** A global optimal solution can be achieved by making a local optimal (**greedy**) choice.
- **Optimal substructure:** An optimal solution to the problem contains its optimal solution to subproblem.

0-1 Knapsack Problem

- Suppose you are a thief, and you are now in a jewelry shop (nobody is around !)
- You have a big knapsack that you have "borrowed" from some shop before
 - ✓ Weight limit of knapsack: W
- There are n items, I_1, I_2, \dots, I_n
 - ✓ I_k has value v_k , weight w_k

Target: Get items with total value as large as possible without exceeding weight limit

0-1 Knapsack Problem

- We may think of some strategies like:
 - (1) Take the most valuable item first
 - (2) Take the **densest** item (with v_k/w_k is maximized) first
- Unfortunately, someone shows that this problem is **very hard** (NP-complete), so that it is **unlikely** to have a good strategy
- Let's change the problem a bit...

Fractional Knapsack Problem

- In the previous problem, for each item, we either take it all, or leave it there
 - ✓ Cannot take a fraction of an item
- Suppose we can allow taking fractions of the items; precisely, for a fraction c
 - ✓ c part of I_k has value cv_k , weight cw_k

Target: Get as valuable a load as possible, without exceeding weight limit

Fractional Knapsack Problem

- Suddenly, the following strategy works:
 - Take as much of the densest item (with v_k/w_k is maximized) as possible
 - ✓ The correctness of the above greedy-choice property can be shown by cut-and-paste argument
- Also, it is easy to see that this problem has optimal substructure property
 - implies a correct greedy algorithm

Fractional Knapsack Problem

- However, the previous greedy algorithm (pick densest) **does not work** for 0-1 knapsack
- To see why, consider **$W = 50$** and:
 - $I_1 : v_1 = \$60, w_1 = 10$ (density: 6)
 - $I_2 : v_2 = \$100, w_2 = 20$ (density: 5)
 - $I_3 : v_3 = \$120, w_3 = 30$ (density: 4)
- Greedy algorithm: \$160 (I_1, I_2)
- Optimal solution: \$220 (I_2, I_3)

Encoding Characters

- In ASCII, each character is encoded using the same number of bits (8 bits)
 - called **fixed-length** encoding
- However, in real-life English texts, not every character has the same frequency
- One way to encode the texts is:
 - ✓ Encode frequent chars with few bits
 - ✓ Encode infrequent chars with more bits
- ➔ called **variable-length** encoding

Encoding Characters

- **Variable-length** encoding may gain a lot in storage requirement
- Example:
 - ✓ Suppose we have a 100K-char file consisted of only chars **a, b, c, d, e, f**
 - ✓ Suppose we know **a** occurs 45K times, and other chars each 11K times
- ➔ Fixed-length encoding: 300K bits

Encoding Characters

- Example (cont.):

Suppose we encode the chars as follows:

$a \rightarrow 0, \quad b \rightarrow 100, \quad c \rightarrow 101,$

$d \rightarrow 110, \quad e \rightarrow 1110, \quad f \rightarrow 1111$

- Storage with the above encoding:

$$(45 \times 1 + 33 \times 3 + 22 \times 4) \times 1K$$

$$= 232K \text{ bits (reduced by 25\% !!)}$$

Encoding Characters

- Thinking a step ahead, you may consider an even "better" encoding scheme:
 $a \rightarrow 0, \quad b \rightarrow 1, \quad c \rightarrow 00,$
 $d \rightarrow 01, \quad e \rightarrow 10, \quad f \rightarrow 11$
- This encoding requires less storage since each char is encoded in fewer bits ...
- What's wrong with this encoding?

Prefix Code


- Suppose the encoded texts is: 0101
- We cannot tell if the original text is
abab, dd, abd, aeb, or ...
- The problem comes from:
one codeword is a prefix of another one

Prefix Code

- To avoid the problem, we generally want each codeword **not** a prefix of another
 - ✓ called **prefix** code, or **prefix-free** code
- Let **T** = text encoded by prefix code
- We can easily decode **T** back to original:
 - ✓ Scan **T** from the beginning
 - ✓ Once we see a codeword, output the corresponding char
 - ✓ Then, recursively decode remaining

Prefix Code Tree

- Naturally, a prefix code scheme corresponds to a **prefix code tree**
 - ✓ Each char \rightarrow a leaf
 - ✓ Root-to-leaf path \rightarrow codeword
- E.g., $a \rightarrow 0$, $b \rightarrow 100$,
 $c \rightarrow 101$, $d \rightarrow 110$,
 $e \rightarrow 1110$, $f \rightarrow 1111$



Optimal Prefix Code

- **Question:** Given frequencies of each char, how to find the **optimal** prefix code scheme (or **optimal** prefix code tree)?
- **Precisely:**
Input: S = a set n chars, c_1, c_2, \dots, c_n
with c_k occurs f_{c_k} times
- **Target:** Find codeword w_k for each c_k such that $\sum_k |w_k| f_{c_k}$ is minimized

Huffman Code


- In 1952, David Huffman (then an MIT PhD student) thinks of a greedy algorithm to obtain the optimal prefix code tree
- Let c and c' be chars with least frequencies. He observed that:
- Lemma: There is some optimal prefix code tree with c and c' sharing the same parent, and the two leaves are farthest from root

Proof: (By "Cut-and-Paste")

- Let **OPT** = some optimal solution
- If **c** and **c'** as required, done!
- Else, let **a** and **b** be two bottom-most leaves sharing same parent (such leaves must exist... **why??**)
 - swap **a** with **c**, swap **b** with **c'**
 - an **optimal** solution as required
(since it at most the same $\sum_k |w_k| f_k$ as **OPT** ... **why??**)


Graphically:

If this is optimal



Bottom-most
leaves →

then this is optimal



Optimal Substructure

- Let OPT be an optimal prefix code tree with c and c' as required
- Let T' be a tree formed by merging c, c' , and their parent into one node
- Consider $S' =$ set formed by removing c and c' from S , but adding X with $f_X = f_c + f_{c'}$
- Lemma: If T' is an optimal prefix code tree for S' , then T obtained from T' by replacing the leaf node X with an internal node having c and c' is an optimal prefix code tree for S .


Proof

- If T is not optimal tree for S then there exists an optimal tree T'' for S and $\text{cost}(T'') < \text{cost}(T)$.
- Let T''' be the tree T'' with the common parent of c and c' replaced by a leaf with X
- Then $\text{cost}(T''') = \text{cost}(T'') - f_c - f_{c'} < \text{cost}(T) - f_c - f_{c'} = \text{cost}(T')$
- Yielding a contradiction to the assumption that T' represent an optimal prefix code for S'

Graphically, the lemma says:


If this is optimal for S'

then this is optimal for S




contradiction to the assumption that T' represent an optimal prefix code for S'

If this is optimal for S



Then this is optimal for S' and better than T'



Here, $f_X = f_c + f_{c'}$

Huffman Code

- Questions:
- Based on the previous lemmas, can you obtain Huffman's coding scheme?
- What is the running time?
 $O(n \log n)$ time, using heap (how??)




Huffman(S) { // build Huffman code tree

1. Find least frequent chars c and c'
2. $S' =$ remove c and c' from S ,
but add char X with $f_X = f_c + f_{c'}$
3. $T' = \text{Huffman}(S')$
4. Make leaf X of T' an internal node by connecting two leaves c and c' to it
5. Return resulting tree

}

The steps of Huffman's algorithm


(a) f:5 e:9 c:12 b:13 d:16 a:45




The steps of Huffman's algorithm

(e)

a:45



(f)



Constructing a Huffman code

HUFFMAN(C)

```
1   $n \leftarrow |C|$ 
2   $Q \leftarrow C$  /* initialize the min-priority queue with the
   character in  $C$  */
3  for  $i \leftarrow 1$  to  $n - 1$ 
4      do allocate a new node  $z$ 
5           $z.left = x = \text{EXTRACT-MIN}(Q)$ 
6           $z.right = y = \text{EXTRACT-MIN}(Q)$ 
7           $z.freq = x.freq + y.freq$ 
8          INSERT( $Q, z$ )
9  return EXTRACT-MIN( $Q$ ) // return the root of the tree
```

Complexity: $O(n \log n)$

Practice at home

- Exercises: 16.1-2, 16.1-5, 16.2-2, 16.2-3, 16.2-5, 16.3-2, 16.3-8

-
- What is an optimal Huffman code tree for the following set of frequencies?
A:1 B:1 C:2 d:3 e:5