

EXPERIMENT No.4

Aim: To install Kubectl and execute Kubectl commands to manage the Kubernetes cluster and deploy Your First Kubernetes Application.

STEPS:

1. Select Amazon linux as OS image (You can use any but then modify commands accordingly)

[Add additional tags](#)

▼ Application and OS Images (Amazon Machine Image) [Info](#)

An AMI is a template that contains the software configuration (operating system, application server, and applications) required to launch your instance. Search or Browse for AMIs if you don't see what you are looking for below

Recents

Quick Start

Amazon Linux
aws


macOS
Mac

Ubuntu
ubuntu®

Windows
Microsoft

Red Hat
Red Hat

SUSE LI
SUS


[Browse more AMIs](#)
Including AMIs from
AWS, Marketplace and
the Community

Amazon Machine Image (AMI)

2. Make ssh connection in terminal

Note: If you have directly made connection through browser then skip this part

```
quantumvm@machine ~$ ssh -i "/Downloads/ec2-ubuntu.pem" ec2-user@ec2-54-162-208-25.compute-1.amazonaws.com
The authenticity of host 'ec2-54-162-208-25.compute-1.amazonaws.com (54.162.208.25)' can't be established.
ED25519 key fingerprint is SHA256:lBrxdG+9hnKfW0YzWmzhIwg/R4s-e7QDAMBZJpvF/E.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added 'ec2-54-162-208-25.compute-1.amazonaws.com' (ED25519) to the list of known hosts.
```

```
      _#_
     _###_
    _####_
   _#####_
  _#####_
 _#####_
#####_

Amazon Linux 2

AL2 End of Life is 2025-06-30.

V--+->

A newer version of Amazon Linux is available!

#####_
 _#####_
_#####_
#####_

Amazon Linux 2023, GA and supported until 2028-03-15.
https://aws.amazon.com/linux/amazon-linux-2023/

[ec2-user@ip-172-31-31-63 ~]$ sudo yum update
Loaded plugins: extras_suggestions, langpacks, priorities, update-motd
No packages marked for update
[ec2-user@ip-172-31-31-63 ~]$ sudo yum upgrade
Loaded plugins: extras_suggestions, langpacks, priorities, update-motd
No packages marked for update
[ec2-user@ip-172-31-31-63 ~]$
```

3. Install Docker

```
sudo dnf update
```

```
sudo dnf install docker
```

sudo systemctl enable docker

```
sudo systemctl start docker
```

To test whether docker is successfully running, use command **sudo docker run hello-world**

```
[ec2-user@ip-172-31-24-190 ~]$ sudo docker run hello-world
Unable to find image 'hello-world:latest' locally
latest: Pulling from library/hello-world
c1ec31eb5944: Pull complete
Digest: sha256:91fb4b041da273d5a3273b6d587d62d518300a6ad268b28628f74997b93171b2
Status: Downloaded newer image for hello-world:latest

Hello from Docker!
This message shows that your installation appears to be working correctly.
```

Then, configure cgroup in a daemon.json file. This allows kubernetes to manage host more efficiently

```
cd /etc/docker
```

```
cat <<EOF | sudo tee /etc/docker/daemon.json
{
  "exec-opts": ["native.cgroupdriver=systemd"]
}
EOF
sudo systemctl daemon-reload
sudo systemctl restart docker
```

4. Install Kubernetes

Note: I'm directly installing binary package you may install from package repository of your distribution

Install CNI plugins (required for most pod network):

```
CNI_PLUGINS_VERSION="v1.3.0"
ARCH="amd64"
DEST="/opt/cni/bin"
sudo mkdir -p "$DEST"
curl -L
"https://github.com/containernetworking/plugins/releases/download/${CNI_PLUGINS_V
ERSION}/cni-plugins-linux-${ARCH}-${CNI_PLUGINS_VERSION}.tgz" | sudo tar -C
"$DEST" -xz
```

Define the directory to download command files:

```
DOWNLOAD_DIR="/usr/local/bin"
sudo mkdir -p "$DOWNLOAD_DIR"
```

Optionally install crictl (required for interaction with the Container Runtime Interface (CRI), optional for kubeadm):

```
CRICTL_VERSION="v1.31.0"
ARCH="amd64"
```

```
curl -L
"https://github.com/kubernetes-sigs/cri-tools/releases/download/${CRICTL_VERSION}/c
rictl-${CRICTL_VERSION}-linux-${ARCH}.tar.gz" | sudo tar -C $DOWNLOAD_DIR -xz
```

Install kubeadm, kubelet and add a kubelet systemd service:

```
RELEASE="$(curl -sSL https://dl.k8s.io/release/stable.txt)"
ARCH="amd64"
cd $DOWNLOAD_DIR
sudo curl -L --remote-name-all
https://dl.k8s.io/release/${RELEASE}/bin/linux/${ARCH}/{kubeadm,kubelet}
sudo chmod +x {kubeadm,kubelet}
```

```
RELEASE_VERSION="v0.16.2"
curl -sSL
"https://raw.githubusercontent.com/kubernetes/release/${RELEASE_VERSION}/cmd/kre
l/templates/latest/kubelet/kubelet.service" | sed "s:/usr/bin:${DOWNLOAD_DIR}:g" |
sudo tee /usr/lib/systemd/system/kubelet.service
sudo mkdir -p /usr/lib/systemd/system/kubelet.service.d
curl -sSL
"https://raw.githubusercontent.com/kubernetes/release/${RELEASE_VERSION}/cmd/kre
l/templates/latest/kubeadm/10-kubeadm.conf" | sed "s:/usr/bin:${DOWNLOAD_DIR}:g"
| sudo tee /usr/lib/systemd/system/kubelet.service.d/10-kubeadm.conf
```

Now we need to install kubectl

Set up repository:

```
cat <<EOF | sudo tee /etc/yum.repos.d/kubernetes.repo
[kubernetes]
name=Kubernetes
baseurl=https://pkgs.k8s.io/core:/stable:/v1.31/rpm/
enabled=1
gpgcheck=1
gpgkey=https://pkgs.k8s.io/core:/stable:/v1.31/rpm/repodata/repod
md.xml.key
EOF
```

```
sudo yum install -y kubectl
```

```
ec2-user@ip-172-31-24-190 ~ $ kubectl version
Client Version: v1.31.1
Kustomize Version: v5.4.2
```

We have installed successfully installed kubernetes

After installing Kubernetes, we need to configure internet options to allow bridging.

```
sudo swapoff -a
echo "net.bridge.bridge-nf-call-iptables=1" | sudo tee -a
/etc/sysctl.conf
sudo sysctl -p
```

```
[root@ip-172-31-24-190 bin]# sudo swapoff -a
echo "net.bridge.bridge-nf-call-iptables=1" | sudo tee -a /etc/sysctl.conf
sudo sysctl -p
net.bridge.bridge-nf-call-iptables=1
net.bridge.bridge-nf-call-iptables = 1
[root@ip-172-31-24-190 bin]#
```

Disable SELINUX

Type **sudo nano /etc/selinux/config** and set the value of **SELINUX=disabled** instead of **SELINUX=permissive**

Save the file by pressing ctrl+o then press enter then press ctrl+x

```
# This file controls the state of SELinux on the system.
# SELINUX= can take one of these three values:
#   enforcing - SELinux security policy is enforced.
#   permissive - SELinux prints warnings instead of enforcing.
#   disabled - No SELinux policy is loaded.
# See also:
# https://docs.fedoraproject.org/en-US/quick-docs/getting-started-with-selinux/#getting-started-with-selinux-selinux-states-and-modes
#
# NOTE: In earlier Fedora kernel builds, SELINUX=disabled would also
# fully disable SELinux during boot. If you need a system with SELinux
# fully disabled instead of SELinux running with no policy loaded, you
# need to pass selinux=0 to the kernel command line. You can use grubby
# to persistently set the bootloader to boot with selinux=0:
#
#   grubby --update-kernel ALL --args selinux=0
#
# To revert back to SELinux enabled:
#
#   grubby --update-kernel ALL --remove-args selinux
#
SELINUX=disabled
# SELINUXTYPE= can take one of these three values:
#   targeted - Targeted processes are protected,
#   minimum - Modification of targeted policy. Only selected processes are protected.
#   mls - Multi Level Security protection.
SELINUXTYPE=targeted
```

Then reboot the system using **sudo reboot**

After rebooting we need to make ssh connection with machine after it gets disconnected

Now if we type command **sestatus**, then it show disabled

```
ec2-user@ip-172-31-24-190 ~ $ sestatus
SELinux status:                disabled
```

5. Initialize the Kubecluster

Install packages socat and iproute-tc and conntrack to avoid prelight errors

sudo dnf install socat iproute-tc conntrack-tools -y

sudo kubeadm init --pod-network-cidr=10.244.0.0/16

```

Your Kubernetes control-plane has initialized successfully!

To start using your cluster, you need to run the following as a regular user:

  mkdir -p $HOME/.kube
  sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
  sudo chown $(id -u):$(id -g) $HOME/.kube/config

Alternatively, if you are the root user, you can run:

  export KUBECONFIG=/etc/kubernetes/admin.conf

You should now deploy a pod network to the cluster.
Run "kubectl apply -f [podnetwork].yaml" with one of the options listed at:
  https://kubernetes.io/docs/concepts/cluster-administration/addons/

Then you can join any number of worker nodes by running the following on each as root:

kubeadm join 172.31.24.190:6443 --token xsbsq1.6ro11sawnvttbsvu \
  --discovery-token-ca-cert-hash sha256:10d2b67f4f4749b51854065a554c74e6a956e4782d9ab4bb79b8591648b3edef
ec2-user@ip-172-31-24-190 ~ $ kubectl get nodes

```

Copy the mkdir and chown commands from the top and execute them

```
mkdir -p $HOME/.kube
```

```
sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
```

```
sudo chown $(id -u):$(id -g) $HOME/.kube/config
```

```
sudo systemctl restart kubelet
```

Then, add a common networking plugin called flannel as mentioned in the code.

```
kubectl apply -f
```

```
https://raw.githubusercontent.com/coreos/flannel/master/Documentation/kube-flannel.yml
```

```

ec2-user@ip-172-31-24-190 ~ $ kubectl apply -f https://raw.githubusercontent.com/coreos/flannel/master/Documentation/kube-flannel.yml
namespace/kube-flannel created
clusterrole.rbac.authorization.k8s.io/flannel created
clusterrolebinding.rbac.authorization.k8s.io/flannel created
serviceaccount/flannel created
configmap/kube-flannel-cfg created
daemonset.apps/kube-flannel-ds created

```

Now type kubectl get nodes

```

The connection to the server 172.31.24.190:6443 was refused - did you specify the right host or port?
ec2-user@ip-172-31-24-190 ~ $ kubectl get nodes
The connection to the server 172.31.24.190:6443 was refused - did you specify the right host or port?
ec2-user@ip-172-31-24-190 ~ $ kubectl get nodes
^[[AError from server (Forbidden): nodes is forbidden: User "kubernetes-admin" cannot list resource "nodes" in
ec2-user@ip-172-31-24-190 ~ $ kubectl get nodes
NAME                                STATUS    ROLES    AGE   VERSION
ip-172-31-24-190.ec2.internal      Ready    control-plane   34m   v1.31.0
ec2-user@ip-172-31-24-190 ~ $ kubectl get nodes
NAME                                STATUS    ROLES    AGE   VERSION
ip-172-31-24-190.ec2.internal      Ready    control-plane   34m   v1.31.0
ec2-user@ip-172-31-24-190 ~ $

```

Note: If any time of get error of connection refused just restart the kubelet service (sudo systemctl restart kubelet)

Now that the cluster is up and running, we can deploy our nginx server on this cluster. Apply this deployment file using this command to create a deployment

```
ec2-user@ip-172-31-24-190 ~ $ kubectl apply -f https://k8s.io/examples/application/deployment.yaml
deployment.apps/nginx-deployment created
```

Use 'kubectl get pods' to verify if the deployment was properly created and the pod is working correctly.

```
ec2-user@ip-172-31-24-190 ~ $ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-mwd8p    0/1     Pending   0           7s
nginx-deployment-d556bf558-zc25s    0/1     Pending   0           7s
```

As we can see our pods are in pending state

On checking logs to we came to know the pods are in tainted state (using command **kubectl describe pod nginx-deployment-d556bf558-mwd8p**)

```
Events:
  Type    Reason            Age   From                  Message
  ----    -
Warning  FailedScheduling  56s   default-scheduler    0/1 nodes are available: 1 node(s) had untolerated taint {node-role.kubernetes.io/control-plane: }. preemption: 0/1 nodes are available:
1 node(s) had untolerated taint {node-role.kubernetes.io/control-plane: }.
```

To make pods untainted

Type kubectl get nodes to see name of node

```
ec2-user@ip-172-31-24-190 ~ $ kubectl get nodes
NAME                                STATUS   ROLES    AGE   VERSION
ip-172-31-24-190.ec2.internal      Ready    control-plane  43m   v1.31.0
ec2-user@ip-172-31-24-190 ~ $
```

Copy the name of the node (ip-172-31-24-190.ec2.internal)

Then type command **kubectl taint nodes <NODE_NAME> - -all**

In my case **kubecttl taint nodes ip-172-31-24-190.ec2.internal node-role.kubernetes.io/control-plane-**

```
ec2-user@ip-172-31-24-190 ~ $ kubecttl taint nodes ip-172-31-24-190.ec2.internal node-role.kubernetes.io/control-plane-  
node/ip-172-31-24-190.ec2.internal untainted
```

After executing above command, check again status of pods if still pending then restart kubelet wait for 1-2 minutes and check again

```
ec2-user@ip-172-31-24-190 ~ $ kubecttl get pods  
NAME                                READY   STATUS    RESTARTS   AGE  
nginx-deployment-d556bf558-mwd8p    1/1     Running   2 (73s ago) 12m  
nginx-deployment-d556bf558-zc25s    1/1     Running   2 (73s ago) 12m
```

As we can see our pods are running

Lastly, port forward the deployment to your localhost so that you can view it.

kubecttl port-forward <POD_NAME> 8080:80

In my case : **kubecttl port-forward nginx-deployment-d556bf558-mwd8p 8080:80**

Note: if you are getting connection refused error then restart kubelet

```
ec2-user@ip-172-31-24-190 ~ $ kubecttl port-forward nginx-deployment-d556bf558-mwd8p 8080:80  
Forwarding from 127.0.0.1:8080 -> 80  
Forwarding from [::1]:8080 -> 80
```

As port forwarding is active so we cannot type other commands.

Open new terminal window and make ssh connection to same machine

And type command **curl --head http://127.0.0.1:8080**

```
ec2-user@ip-172-31-24-190 ~ $ curl --head http://127.0.0.1:8080
HTTP/1.1 200 OK
Server: nginx/1.14.2
Date: Sat, 14 Sep 2024 06:54:21 GMT
Content-Type: text/html
Content-Length: 612
Last-Modified: Tue, 04 Dec 2018 14:44:49 GMT
Connection: keep-alive
ETag: "5c0692e1-264"
Accept-Ranges: bytes

ec2-user@ip-172-31-24-190 ~ $ █
3 1:ec2-user@ip-172-31-24-190:~#- 2:ec2-user@ip-172-31-24-190:~* 3:~/Downloads
```

Response status 200 (OK) indicates that our nginx server is running successfully on kubernetes

Conclusion: We began with installation and setup of docker and kubernetes. The kubernetes api server had some issues but were resolved after restarting kubelet service. The pods created were not running because nodes were tainted so we had to make them untainted. After solving all errors the nginx server pods were deployed successfully and can be accessed with the forwarded port. The nginx server can be accessed on different terminal or by making port forward process as background process by appending & after the command.