

MATLAB R2026a

HOME PLOTS APPS EDITOR PUBLISH VIEW Search (Ctrl+Shift+Space)

Save Section Section with Title Bold Italic Monospaced Hyperlink Inline LaTeX

FILE INSERT SECTION INSERT INLINE MARKUP Bulleted List Numbered List Image Preformatted Text Code Display LaTeX Publish Publish as HTML Publish as PDF

C:\Users\aabdu\OneDrive\Desktop\IT WORKBOOK\10

Files

Name

- 1.m
- 1.pdf
- 1a.png
- 1b.png
- 1c.png
- 2.m
- 2.pdf
- 2.png
- 3.m

Workspace

Name	Value	Size	Class
A	25	1×1	double
ans	3	1×1	double
condition	'High Therm...	1×19	char
HLI	28.1200	1×1	double
Q	25	1×1	double

Editor

```
8 condition='Low Thermal Stress';
9 elseif HLI>=18 && HLI <= 25
10 condition='Normal Operation';
11 elseif HLI>25&&HLI<=29
12 condition='High Thermal Stress';
13 else
14 condition='Critical Operation';
15 end
16
17 % Display result
18 fprintf('The Heat Load Index of the system is %.2f, which corresponds to %s.\n', HLI, condition);
```

Command Window

Enter heat input Q (Btu/hr): 25
Enter effective heat transfer area A (in^2): 25
The Heat Load Index of the system is 28.12, which corresponds to High Thermal Stress.

ans =
3

>> |

Editor: 100% UTF-8 CRLF Script Ln 19 Col 1