

SR-SEISMIC: RESCUE SOFTWARE AND AUTOMATED WIRELESS BEACON FOR SMARTWATCHES IN SEISMIC CATASTROPHES

Official Repository: Global Architecture, Hardware Feasibility, and Multi-Layer Contingency Flow v3.0

Autor Intelectual y Titular de Derechos de Autor / Intellectual Property & Copyright Owner:

- Nombre / Name: Angel Bravo
- Documento / ID: 32.091.864
- Ubicación / Location: Buenos Aires, Argentina
- Contacto / Contact: +54 9 11 5383-7394 (011-15-5383-7394)
- Todos los derechos reservados. Queda autorizada la revisión técnica para su potencial implementación corporativa o de seguridad pública.

Part I: Development Flowchart (The What)

The core software operates under a strict chronological protocol designed for large-scale structural collapse earthquake scenarios, optimizing every physical and electromagnetic phase of the smartwatch:

- 1. Earthquake Alert Reception:** The smart device captures the system's official real-time notification (e.g., *Google Earthquake Alerts System*). The event functions as a hardware trigger that initializes the software in a high-priority latent mode.
- 2. Black Box Mode (Impact Recording):** During and immediately after the mechanical vibrations of the earthquake, the software stores continuous vector data from axial accelerometers, gyroscopes, barometers, and optical pulse sensors into a high-speed embedded local database (SQLite/Room). This records with biomedical precision the impact trauma suffered by the victim during the collapse.
- 3. Battery Survival Transition:** Following a reasonable window defined by seismic emergency management specialists (to allow conscious civilians time to use conventional cellular networks and Wi-Fi), the operating system selectively terminates all redundant threads, screens, and transceivers. An exclusive environment is configured for the extended support of the beacon.
- 4. Beacon System Initialization:** The watch begins broadcasting open wireless pulses using the Bluetooth Low Energy (BLE) spectrum, packaging user identifiers, vital signs, and barometric data, in perfect harmony with overclocked AMOLED flashes and standardized audible acoustic frequencies.
- 5. Intermittent Maintenance:** The device automatically cycles between hardware deep sleep and active emission burst windows. This interval is balanced to provide a minimum emergency rescue window of 72 to 96 continuous hours.
- 6. Rescuer Arrival and BLE Beacon Capture:** Upon deploying to ground zero, the rescuer application passively and massively intercepts open BLE packets without requiring interaction or pairing with the entombed device, structuring a map of potential victims within the quadrant.

7. **Automated Triage via Medical Parameters:** Advanced algorithms process the vital status of received data packets within seconds and classify them chromatically: Fatal Victims (absence of cardiac and motor dynamics), Stable Trapped, and Critical Trapped (bradycardia, tachycardia, or severe oxygen desaturation due to crushing), mathematically sorting the excavation priorities of the squads.
8. **Receiver-Emitter "I See You" Signal:** The rescuer interface sends a targeted confirmation command (**ACK_TE_VI**). When received within the smartwatch's radio opening micro-window, the software instantly alters its internal clock and increases the frequency of beeps and light emissions (e.g., every 15 seconds) to consolidate micro-spatial tracking.
9. **Directional Proximity Tracking:** The Received Signal Strength Indicator (RSSI) acts under the analog principle of biological telemetry, guiding the rescuer auditively and visually through the horizontal surface coordinates X and Y.
10. **Active Radar (Z-Depth and Debris Characterization):** At the point of maximum electromagnetic gain, the rescuer's smartphone executes a calibrated pulse. The watch returns its physical timestamp and reception power, enabling the algorithm to deduce through Time of Flight (ToF) and power degradation the exact Z-axis and structural density (dense reinforced concrete slab vs. habitable cavity).
11. **Passive Psychological Containment:** Upon validating rescue viability, the rescuer app injects a high-priority audio command into the smartwatch speaker, playing a pre-recorded containment message at maximum power: "We have located you. The rescue team is working on the surface to pull you out. Stay calm."

Part II: Technical Foundations and Feasibility Analysis (The How)

1. Hardware Overclocking Module and Thermal Management

The core feasibility of this system lies in the alteration of the Duty Cycle. By applying Ultra-Short Pulses, standard thermal restrictions are bypassed under the thermodynamic laws of semiconductors.

A. AMOLED Screen and Luminous Overdriving

Panels restrict their continuous brightness to about 3,000 nits from the factory. The immediate molecular destruction threshold of organic diodes is near 5,000 nits. By forcing an overvoltage in the panel's microcontroller for a duration of $T_{\text{on}} = 50 \text{ ms}$, the generated heat follows the equation: $E_{\text{th}} = I^2 \times R \times T_{\text{on}}$. With a cooling time of $T_{\text{off}} = 600,000 \text{ ms}$ (10 minutes), the accumulated heat in the organic materials and adjacent lithium cells is negligible. This allows complete conduction dissipation and a stroboscopic flash of maximum real useful lumen intensity in seismic darkness.

B. Speaker and Acoustic Saturation

To mitigate overheating due to the Joule effect in the coil of piezoelectric or dynamic transducers, the software injects pure square or sine waves in transient millisecond bursts. The diaphragm shifts to its maximum mechanical excursion at 100% of its acoustic pressure capacity without danger of fusion from thermal or electrical fatigue.

2. Acoustic Module: Standardized Frequency and Propagation in Seismic Structures

The beep frequency is invariably fixed in the range of 3.5 kHz to 4 kHz (3500 to 4000 Hertz) based on a Triple Optimal Coincidence design:

- **Digital Noise Isolation (Software):** Heavy noise from rescue machinery and structural collapses operates below 1 kHz. A pure 3.5 kHz beep is isolated using a digital narrow-band filter (Band-pass Filter) on the rescuer's phone, mechanically suppressing 95% of the zone's ambient noise.
- **Canine Sensitivity (K9):** The auditory apparatus of search canines is highly sensitive to sharp stimuli in the mid-high spectrum (1 kHz to 8 kHz), accelerating organic marking on seismic terrain.
- **Anatomical Resonance of the Rescuer:** The human external auditory canal possesses a physical length that naturally resonates with waves from 3.5 kHz to 4 kHz. This causes passive mechanical amplification at the eardrum of between 10 and 15 decibels, exponentially increasing the hearing range of human squads without requiring more electrical power from the watch clock.

3. Radio Frequency Module (BLE): Telemetry System and RSSI Tracking

The software converts the wireless microchip into a pure transmitter of open, omnidirectional BLE Advertising Packets. The rescuer application calculates propagation loss through the RSSI measured in dBm, transforming it into an iterative acoustic indicator (Tic-Tic-Tic). Given the high absorption of masonry and reinforced concrete over the 2.4 GHz band, the signal experiences drastic drops. However, this physical attenuation is used as a precision filter: radio frequency will only escape clearly through structural air micro-fissures. By tracing a cross sweep on the surface, the exact point that registers a vertical power peak (e.g., from -95 dBm to -65 dBm) and triggers the Tic-Tic into a continuous hum will mark with millimetric precision the coordinates (X, Y) of the trapped individual.

4. Active Radar Module: Z-Depth Detection and Structural Density

Integrates a bidirectional transmedia electromagnetic echolocation logic based on two concurrent analytical variables:

1. **Distance Calculation and Physical Depth (Time of Flight - ToF):** From a beam emitted with a known power by the software ($P_{\text{emitted}} = +20 \text{ dBm}$) from the rescuer's cell phone, the watch captures the pulse and computes the exact microsecond of arrival via a Hardware Timestamp along with the reception power (P_{received}). By responding with these embedded metrics, the rescuer app deduces the net travel time discarding internal processor latency (T_{proc}): $\text{Travel Time} = T_{\text{total}} - T_{\text{proc}}$. Applying the speed of light (c), the microelectronic delay calculates real linear distance or absolute depth in meters (Z-Axis).
2. **Structure Density Calculation (Propagation Loss):** The software analyzes the net power drop ($\Delta P = P_{\text{emitted}} - P_{\text{received}}$). If Time of Flight dictates that the victim is located 3 meters away in a straight line, but the electromagnetic loss (ΔP) is massive (e.g., a 60 dB drop), the algorithm processes the discrepancy and infers that the obstructive medium is composed of solid and compact blocks of reinforced concrete and metallurgy. If the drop fits the inverse square law exactly, it dictates the existence of a hollow space or vital air bubble.

5. Reactive Module by Light Interruption (Flashlight Effect)

The ambient light sensor (ALS) of the smart watch monitors the confinement environment in a low-power passive analog mode. The software discriminates slow solar light variations, but implements a dynamic slope filter that detects fast luminosity deltas ($\Delta L/\Delta t$) of less than 200 ms. When a rescue squad sweeps surface cracks with high-power tactical spotlights in an environment of total darkness (<5 lux), the sensor generates a hardware interrupt (Hardware Interrupt). This signal instantly wakes up the main processor, aborting the 10-minute delay to initialize continuous audio alerts and maximum radio data bursts for 60 seconds.