

---

**Solutions to Practice Questions for Final (Set I)**

---

1. A

```
% actions are exogenous
{lift(E,T)} :- end(E), T=0..m-1.
```

---

2. A

```
% File 'monkey-postdiction.lp'
:- not walk(l3,0).
:- not 1{pushBox(LL,1):location(LL)}.
:- loc(box,l3,0).
```

---

3. C

```
clingo version 5.5.0
Reading from stdin
Solving...
Answer: 1
p(t,0) p(f,1)
Answer: 2
p(f,1) p(f,0)
Answer: 3
p(t,1) p(t,0)
Answer: 4
p(t,1) p(t,0)
Answer: 5
p(t,1) p(f,0)
Answer: 6
p(t,1) p(f,0)
SATISFIABLE
```

---

4. A

The formulae represent Penalty-based weight.

---

5. A

$$\begin{aligned} &P(A = 0|B = 1, C = 1) \\ &= P(A = 0, B = 1, C = 1)/P(B = 1, C = 1) \\ &= (0.15)/(0.15 + 0.05) \\ &= 0.15/0.20 \\ &= 0.75 \end{aligned}$$

---

6. B

The set  $\{MB(birb)\}$  satisfies the following rules:

$\alpha: B(x) \leftarrow RB(x)$

$\alpha: \leftarrow RB(x), MB(x)$

$\alpha: MB(birb)$

Hence,

$$W_{\Pi}(\{MB(birb)\}) = e^{3\alpha}$$

---

7. A, C, D

CycL is an extension of First-Order Logic.

---

8. D

The basic ideas of RDF are Resources, Properties, and Statements.

---

9. A, B, C, D

Disjointness of Concepts, Coverings, Domain Restrictions, and Range Restrictions are all examples of Concept Inclusions.

---

10. A

A. Correct Statement

B.  $\exists$  is incorrect,  $\equiv$  is used to capture knowledge

C.  $\sqsubseteq$  is incorrect,  $\equiv$  is used to capture knowledge

D.  $\forall$  is incorrect when referring to multiple ingredients

---