



Effective From 29th April, 2026

Product Image	Product Model	Product Description	DPP	MRP
Video Door Phone				
	DS-KH6320-WTE1 (Video Intercom) (Indoor Monitor)	7-inch Colorful TFT LCD, 1024 × 600 Max to 32 GB, SD 2.0or lower version,Built-in Omnidirectional Microphone, Noise Suppression and EchoCancellation	Rs. 13,155	Rs. 16,445
	DS-KV8413-WME1 (4 Buttons Metal Villa Door Station)	2 MP camera with IR supplement, Built-in card reader module,IK08 & IP65, Digital WDR, omnidirectional microphone, access control function, upto 2000 users capacity	Rs. 16,550	Rs. 20,688
	DS-KIS605-P (IP Intercom Kit)	2 MP HD Camera 1920 × 1080p@ 720p, Noise suppression and echo cancellation, Tamper- proof,True WDR, Access Control Function, Built-in omnidirectional microphone	Rs. 18,638	Rs. 23,300
	DS-KIS602 (Video Doorphone) (IP Network)	7-inch Colorful IPS LCD, 7.9" × 5.5" × 0.6" 10/100 Mbps Self-Adaptive Ethernet Noise suppression and Echo Cancellation Low Illumination 2 MP HD IR Camera, Main Stream:1920 × 1080 Sub Stream: 720 × 480	Rs. 28,490	Rs. 35,615
	DS-K4H258S (Magnetic Lock)	238 mm × 45 mm × 25 mm (9.4" × 1.8" × 1.0") dimension lock body (L × W × H), 182 mm × 38 mm × 12.5 mm (7.2" × 1.5" × 0.5") Dimension of armature plate (L × W × H), 12 VDC, 340 mA, Green (work status) LED indicator	Rs. 3,355	Rs. 4,195
	DS-K4H255-LZ (Bracket From Magnetic Lock)	L-bracket: 250 mm × 46 mm × 30 mm (9.8" × 1.8" × 1.2"),Z-bracket: 180 mm × 47 mm × 47 mm (7.1 × 1.9" × 1.9"), Wooden Door, Glass Door, Metal Door,High strength aluminum alloy surface sandblasting oxidation,0.5 kg (1.1	Rs.1225	Rs.1530
	DS-K4H255S (Magnetic Lock)	12 VDC to 24 VDC, 470 mA to 235 mA,-10 °C to55 °C (14 °F to 131 °F),180 mm × 47 mm × 47mm (7.1 × 1.9" × 1.9"), Wooden Door, Glass Door, Metal Door,High strength aluminum alloy surface sandblasting oxidation,0.5 kg (1.1 lb),Lock Body: 250 mm × 28 mm × 48 mm (9.8" × 1.1" × 1.9"),Armature Plate: 180 mm × 38	Rs.2,508	Rs. 3,135
	DS-K4E100 (Electric lock)	Works cooperatively with video intercom system and access control system, Lock status detection, Life	Rs. 4,815	Rs. 6,019
MinMoe Product				
	DS-K1A8503EF-B (Battery in-built)	2.4-inch LCD Display -10° C to 55° C (14° F to 131° F) 140mm × 155mm × 30mm (5.51" × 6.01" × 1.18")1,000 users 1,000 cards 100,000 records	Rs. 8,000	Rs. 10,000
	DS-K1T320EFX (Face Access Terminal)	2.4-inch LCD screen, 2 MP lens Multiple authentication methods, including face, fingerprint, card, and PIN, etc., Supports EM card Max. 500 faces, 1,000 cards, 1,000 fingerprints and 100,000 events	Rs.11,200	Rs.15,000
	DS-K1T320EFWX-B (Face Access Terminal)(With Battery Back Up)	2.4-inch LCD screen, 2 MP lens Multiple authentication methods, including face, fingerprint, card, and PIN, etc., Supports EM card Max. 500 faces, 1,000 cards, 1,000 fingerprints and 100,000 events, with built-in	Rs. 13,800	Rs. 18,000
	DS-K1T343MFWX-B (Face Access Terminal)(With Battery Back Up)	Face Recognition Terminal, 4.3-inch LCD touch screen,2 Mega pixel wide-angle lens, Built-in MI fare card reading module, Two-way audio with client software, Supports TCP/IP, Wi-Fi, Max.1500 faces capacity, Max.3000 fingerprints capacity, and Max.3000 cards, with built-in battery	Rs. 18,000	Rs. 23,500
	DS-K1T808MFWXPro Fingerprint Terminals	2.4-inch LCD screen,Max. 3000 cards, 3000 fingerprints and 100,000 events,Supports ISAPI and ISUP 5.0 protocols, ISAPI and ISUP 5.0 protocols,Supports access control and local time and attendance function,M1 cardOptical fingerprint module 1:1 and 1:N	Rs.10,420	Rs.13,025
	K1T342MFX-E1 Face Recognition Terminal	4.3-inch LCD screen,Card capacity 3,000,Face capacity 1,500, Fingerprint capacity 3,000 Event capacity 150,000 Supports Working Temperature,Working Humidity-30 °Cto 60 ° (-22 °F to 140 °F)0 to 90% (No condensing) Humidity,IP65	Rs.20,093	Rs.25,116
Access Control				
	DS-K1T802E (Access control)	EM Card, 32-bit processor, TCP/IP, Storage for 3,000 Legal Card Information, 126.5mm × 94.5mm × 24mm (4.98" × 3.72" × 0.94")	Rs. 6,855	Rs. 8,569



Effective From 29th April, 2026

Product Image	Product Model	Product Description	DPP	MRP
	DS-KAS261 (Access Control Kit)	2.5-Inch Colorful TFT LCD Display, upto 3000 fingerprints and cards, built-in card reader, upto 1,50,000 records	Rs. 15,625	Rs. 19,535
	DS-K4SL500MKW (Pro Smart Locks)	Support door opening information, alarm message upload. In-line lock cylinder to reduce maintenance costs. Low battery reminder, timely reminder to replace the battery. After the battery is completely dead, it can be started by an external micro USB emergency power supply.	Rs. 21,600	Rs. 27,000
Exit & Emergency Button				
	DS-K7P01 Exit & Emergency Button	Max. 36 VDC, 3 A, -10 °C to 55 °C (14 °F to 131 °F), 0 to 95% (relative humidity), 86 mm × 86 mm × 28.9 mm (3.39" × 3.39" × 1.14"), Aluminum alloy panel with sandblast, metal button, NO/NC/COM contact, Hollow doorframe and embedded electric	Rs. 1100	Rs. 1380
Door Station				
	DS-KD8103-E6 (3.5 Inch Plastic IP Door Station)	H.264 video compression, 2 MP HD camera, 120° wide angle view, 3.5-inch colorful LCD screen with 480 × 320 resolution, 4GB ROM, 512MB RAM, 3.5-inch screen size, WDR, outdoor application	Rs. 23,164	Rs. 28,955
	DS-KD8003-IME1 (Modular Door Station)	2MP fisheye Camera with IR Supplement, Two-lock control, Directly provide 12 V, 500 mA power output for one electronic lock without additional power supply	Rs. 15,500	Rs. 19,375